

Rāma AGI

User Guide — every feature, and how to use it

Prepared for Krishna Prasad
Generated 2026-10-10

This document is generated from the source that implements each feature: the page registry, the capability matrix, the glossary and the components themselves. It describes 18 pages, 77 capabilities and 141 glossary terms.

1. What Rāma is

Rāma is a desktop application: an Electron shell around a React interface, an Express service and a Python analysis engine. It runs on your machine. Your data, your credentials and your conversations live in encrypted files in your own user directory.

It has 18 pages, reachable from the left rail or by keyboard. Each one is listed in section 3 with what it does, what it can be asked to do, and the lowest access tier allowed to open it.

2. Starting up, and the two passwords

1. **Launch.** `npm run dev` during development, or the installed application. `node start.cjs --diagnose` reports anything the environment is missing, and `--repair` lets Rāma fix what it can.
2. **The passcode gate.** Your passcode opens the encrypted store that holds everything Rāma remembers. Enter it wrong and nothing opens — there is no partial unlock.
3. **The credential vault.** Separate, and this surprises people.

Why you are asked for a password twice. There are two encrypted stores, with two independent keys. The **passcode** at startup opens Rāma's own memory. The **vault master password**, entered on the Models page, opens the credential vault that holds your provider API keys. Neither unlocks the other, by design: one stolen secret should not open both. You may choose the same text for both if you prefer — that is your decision, not a requirement.

3. The pages

Route	Page	What it is for	Min tier
/	Chat	AGI conversation — full capability	GUEST
/home	Home	Dashboard & system overview	VIEWER
/system	System	OS metrics, process manager, cleaner	OPERATOR
/terminal	Terminal	Real embedded PTY shell	SUPERADMIN
/git	Git Sync	Repository sync & version control	OPERATOR
/agents	Agents	Multi-agent orchestration & control	OPERATOR
/models	Models	AI model router & API keys	SUPERADMIN
/intel	Intelligence	Universal prediction — multi-source truth	OPERATOR
/ide	Rāma IDE	AGI code editor — Monaco + AI + research	OPERATOR
/evolution	Evolution	Self-evolve from public repos	MASTER
/resources	Resources	Dynamic resource orchestration	OPERATOR
/mind	Rāma Mind	10 capability axes · AGI dashboard	MASTER

Route	Page	What it is for	Min tier
/genome	Genome	Capability genome · instance lattice	MASTER
/introspect	Introspect	Self-audit · experience · timeline	MASTER
/stockmind	StockMind	Stock market AI — 10 algorithms	VIEWER
/knowledge	Knowledge	Rāma persistent memory store	VIEWER
/users	Users	User management & access control	ADMIN
/settings	Settings	App config, AI providers, security	ADMIN

4. Each page in detail

Chat /

AGI conversation — full capability

What it can do: conversation · reasoning · research · code-gen

Say: "open chat" · "new chat" · "go to chat" · "open conversation"

Lowest tier that may open it: GUEST

Home /home

Dashboard & system overview

What it can do: overview · quick-nav

Say: "open home" · "go home" · "dashboard"

Lowest tier that may open it: VIEWER

System /system

OS metrics, process manager, cleaner

What it can do: os-metrics · process-kill · temp-clean · disk-analysis

Say: "open system" · "system stats" · "system monitor" · "open monitor"

Lowest tier that may open it: OPERATOR

Terminal /terminal

Real embedded PTY shell

What it can do: shell-exec · pty

Say: "open terminal" · "open shell" · "terminal"

Lowest tier that may open it: SUPERADMIN

Git Sync /git

Repository sync & version control

What it can do: git-ops · version-control · multi-machine-sync

Say: "open git" · "git sync" · "open sync"

Lowest tier that may open it: OPERATOR

Agents /agents

Multi-agent orchestration & control

What it can do: agent-spawn · parallel-execution · delegation

Say: "open agents" · "show agents" · "agent control"

Lowest tier that may open it: OPERATOR

Models /models

AI model router & API keys

What it can do: model-routing · credential-mgmt · local-models

Say: "open models" · "show models" · "model router"

Lowest tier that may open it: SUPERADMIN

Intelligence /intel

Universal prediction — multi-source truth

What it can do: multi-source-research · source-vetting · truth-extraction · calibrated-prediction

Say: "open intelligence" · "intelligence engine" · "analyze" · "predict"

Lowest tier that may open it: OPERATOR

Rāma IDE /ide

AGI code editor — Monaco + AI + research

What it can do: code-edit · ast-analysis · ai-pair-programming · sandbox-exec · online-research

Say: "open ide" · "code editor" · "open editor" · "rama ide"

Lowest tier that may open it: OPERATOR

Evolution /evolution

Self-evolve from public repos

What it can do: self-evolution · repo-scouting · license-vetting · capability-gap-analysis

Say: "open evolution" · "self improve" · "evolve"

Lowest tier that may open it: MASTER

Resources /resources

Dynamic resource orchestration

What it can do: task-scheduling · resource-governance · rate-limit-mgmt · resource-research

Say: "open resources" · "resource monitor" · "show workers"

Lowest tier that may open it: OPERATOR

Rāma Mind /mind

10 capability axes · AGI dashboard

What it can do: self-awareness · capability-tracking · memory-inspection · world-model

Say: "open mind" · "rama mind" · "show capabilities"

Lowest tier that may open it: MASTER

Genome /genome

Capability genome · instance lattice

What it can do: genome-inspection · instance-lifecycle · gene-expression · failover-analysis

Say: "open genome" · "show genome" · "show instances" · "instance lattice"

Lowest tier that may open it: MASTER

Introspect /introspect

Self-audit · experience · timeline

What it can do: self-audit · experiential-learning · regression-detection · timeline-replay

Say: "open introspection" · "self audit" · "show timeline" · "run audit"

Lowest tier that may open it: MASTER

StockMind /stockmind

Stock market AI — 10 algorithms

What it can do: market-analysis · signal-generation

Say: "open stockmind" · "stock mind" · "stock market"

Lowest tier that may open it: VIEWER

Knowledge /knowledge

Rāma persistent memory store

What it can do: knowledge-storage · semantic-search · memory-recall

Say: "open knowledge" · "knowledge base"

Lowest tier that may open it: VIEWER

Users /users

User management & access control

What it can do: user-crud · access-control · tier-mgmt

Say: "open users" · "user management" · "manage users"

Lowest tier that may open it: ADMIN

Settings /settings

App config, AI providers, security

What it can do: configuration · passcode-change · auto-start

Say: "open settings" · "settings" · "preferences"

Lowest tier that may open it: ADMIN

5. Access tiers

A lower number means more privilege. Every capability names the lowest-privileged tier still permitted to use it, and an unknown capability is denied rather than allowed. Matrix version 1.

Tier	Name	Label	Capabilities held
0	MASTER	Master	77 of 77
1	SUPERADMIN	SuperAdmin	48 of 77
2	ADMIN	Admin	34 of 77
3	OPERATOR	Operator	16 of 77
4	VIEWER	Viewer	3 of 77
5	GUEST	Guest	1 of 77

6. Keyboard

Keys	Action	Where
Ctrl/Cmd + Shift + M	Mute or unmute the microphone	Anywhere
Ctrl/Cmd + Shift + S	Mute or unmute Rāma's voice	Anywhere
1 2 3 4 5 6 7 8 9 0	Chart type: Candles, Bars, Line, Area, Baseline, Heikin-Ashi, Renko, Line Break, Kagi, Point & Figure	StockMind chart
?	Fullscreen the chart	StockMind chart
?	Toggle logarithmic price scale	StockMind chart
?	Reset the zoom	StockMind chart
?	Show or hide the volume pane	StockMind chart
[and]	Narrow or widen the candles	StockMind chart
Escape	Cancel the active drawing tool	StockMind chart

Click the chart before using its keys — they are scoped to it rather than registered on the whole document, so they cannot interfere with typing a symbol.

7. Talking to Rāma

Rāma can **speak** out of the box: speech synthesis uses the voices your operating system already has, needs no model and no network. That is why the mute chord exists.

Listening is different, and needs something installed. The Electron shell cannot use the browser's built-in speech recognition — Chromium here is built without the keys Chrome ships with, so every attempt fails.

Rāma therefore uses a ladder, local before cloud:

Level	What it is	What it needs
0	Text only	Nothing
1	Capture only — it can record, not transcribe	Microphone permission
2	Local transcription, private and free	A Whisper binary on your PATH: <code>whisper-cli</code> , <code>whisper</code> , <code>faster-whisper</code> , <code>whisper-cpp</code> . An explicit path in <code>RAMA_WHISPER_BIN</code> also works.
3	Cloud transcription	A <code>OPENAI_API_KEY</code> entry in the credential vault

If voice input does nothing, this is why. The chip beside the microphone shows your level — L0 to L4 — and clicking it re-checks. At level 0 or 1 nothing can be transcribed, and Rāma will now say so where you released the talk button instead of leaving “Transcribing...” on screen. Install a Whisper binary for level 2, which is the private and free option, or add a provider key to the vault for level 3.

Hold to talk, release to transcribe. A clip too short to be speech is discarded rather than sent. While Rāma is speaking there is a cool-down so it does not transcribe its own voice back as a command.

How Rāma replies. Short first: the answer, then a shorter explanation. Ask for more and it expands the same answer rather than starting again. The exchange is treated as one continuing conversation, so a follow-up is answered as a follow-up — you should not have to restate what you already said.

8. Your credentials

Provider API keys live in an AES-256-GCM encrypted vault in your user directory, keyed from your vault master password through Argon2id. Add them on the `/models` page.

- Nothing is stored in plaintext, and no key is written into a log or a prompt.
- A wrong vault password is **refused** — it will not open an empty vault that then overwrites the real one.
- If the vault cannot be decrypted, Rāma refuses to write over it rather than replacing it.
- Vault access is master-only. Other tiers cannot read, write or unlock it.

9. StockMind

Charts, indicators and analysis over market data stored on your own disk. 10 chart types (Candles, Bars, Line, Area, Baseline, Heikin-Ashi, Renko, Line Break, Kagi, Point & Figure), with studies, drawing tools and a volatility projection.

Two honest limits worth knowing. Heikin-Ashi opens and closes are *averages*, so they are prices that never traded — read direction from them, never levels. Renko, Line Break, Kagi and Point & Figure advance on *price*, not time, so their horizontal axis is an ordering rather than a clock: overlays, volume, session shading, your fill markers and the projection are all withheld on them, because every one of those is keyed to real bar times. Rāma says so on the chart rather than drawing them somewhere plausible.

Rāma **never places an order**. There is no order-placement channel anywhere in the application, and broker connections, where configured, are data-only.

10. Glossary

141 terms, the same definitions the interface shows when you click a ?.

The ideas behind it

Signal

One reading of one instrument, right now, with the levels to act on it.

Strategy

A rule, tested over history, that says when to enter and exit.

Backtest

Running a rule over past bars to see what it would have done.

Edge

A real, repeatable advantage — as opposed to a lucky run.

Mock data

Simulated bars. Anything computed from them is illustrative only.

Claim class

What kind of statement a number is: grounded, reflex or prose. Never a percentage.

Instrument and data

Instrument

What you are looking at — a stock, index, ETF, currency, commodity or crypto.

Exchange

Which market the instrument trades on. Set automatically when you pick one.

Interval

How much time one bar covers — one minute through one month.

Window

How far back to look. Only the depths the data provider can actually serve are offered.

Provider limit

The deepest history free data gives for this interval. Rāma is not the limit.

Bars

One bar is one interval of trading: its open, high, low, close and volume.

Candle width

How many pixels wide one candle is. Your setting, and the header shows what it measured.

Bars (override)

The exact bar count to request. The window buttons set it; you can type over them.

Stored locally

Rāma already holds these bars on this machine. No network needed.

From disk

Re-read what is already stored. Touches no network.

Fetch from provider

Ask the data providers for anything missing and store it.

Market state

Whether the exchange is inside its scheduled hours, and how old the newest stored bar is.

The chart

Candlesticks

Each bar as a body (open to close) with wicks to the high and low.

Note on the chart

A sentence pinned at a point on the chart — why you did something.

Session band

A faint band per trading day on intraday bars, so the overnight gap is visible.

Bars (OHLC)

A vertical line per bar with ticks left for open and right for close.

Line

Closing prices joined up. The right choice for multi-year views.

Area

A line with the space beneath it filled.

Baseline

Coloured above and below a reference price — your average cost when you hold it.

Price-indexed charts

Renko, Line Break, Kagi and Point & Figure: a mark appears when price MOVES, not when time passes.

Linear scale

Equal price moves get equal height.

Log scale

Equal PERCENTAGE moves get equal height. The honest scale for long views.

Percent scale

Everything measured from the first visible bar, in percent.

Volume

How much traded in each bar, in its own pane below price.

Oscillator pane

A separate pane for indicators on their own scale, like RSI and MACD.

Legend

The values of the bar under your cursor, shown top-left over the chart.

Reset zoom

Fit every bar in the window back into view.

Projection cone

The range this instrument's own volatility calls ordinary over the horizon.

Tilted cone

A cone whose centre a validated model was allowed to move off flat.

Projected candle

A future bar drawn as a range — the body is the middle half of outcomes, the wicks the wide bounds.

Projection horizon

How many bars ahead the cone reaches. Forty is the engine's ceiling.

Your fills

Arrows on the bars where you actually bought or sold.

Levels

Horizontal price lines: a signal's entry, stop and targets, and your own stop and target.

Indicators

Indicator

Arithmetic on the bars already on screen. Never a forecast.

Indicator period

How many bars a study averages over. Yours to set, and the label follows it.

SMA

Simple moving average — the mean close over N bars.

EMA

Exponential moving average — weighted toward recent bars, so it turns sooner.

Bollinger Bands

A moving average with a volatility band either side.

RSI

Relative Strength Index, 0 to 100. Above 70 is called overbought, below 30 oversold.

MACD

The gap between a fast and a slow EMA, plus a signal line and a histogram.

VWAP

The volume-weighted average price so far TODAY. Intraday only.

Signals**Setup**

Which risk geometry this row represents.

Direction (LONG / SHORT)

Whether the setup is to buy first or to sell first.

Entry

The price the setup assumes you get in at.

Stop loss (SL)

The price at which the setup is wrong and the position should be closed.

Targets (T1, T2, T3)

Three progressively further prices where the setup suggests taking profit.

R:R

Reward divided by risk — the distance to the target over the distance to the stop.

Probability

The modelled chance of reaching T1 before the stop.

Grade

The engine's own confidence band for the setup, A+ down to D.

Suppressed

A setup Rāma computed and is deliberately not recommending.

Directional probability

The ensemble's view on direction alone, before any stop or target is placed.

SL risk

The modelled chance of hitting the stop before any target.

Regime

What kind of market the engine thinks this currently is — trending, ranging, volatile.

Agreement

The share of models that landed within 0.15 of the blended probability. 0 to 1.

Uncertainty

How much the models' outputs were spread out. Lower is more confident.

Max risk

The largest loss this setup would take if the stop is honoured, in currency.

Valid for

How many bars the setup is considered live for.

Probability basis

Where the probability came from — which models, fitted on what.

Why

The features that drove this reading, in the engine's own words.

Capital and risk

Direction filter

Whether to return long setups, short setups, or both.

Base price

The last stored close. Read-only on purpose.

Capital

The amount you are sizing positions against.

Risk per trade

The share of capital you accept losing if the stop is hit.

Amount at risk

Capital times risk percent — the money on the line per trade.

Position size

Amount at risk divided by the distance to the stop.

Your book

Position

Something you hold, built from the fills you recorded.

Fill

One buy or sell that happened — quantity, price, date, fees.

Quantity

Units currently open. Negative means short.

Average cost

What you paid on average per unit, across every fill.

Last price

The newest stored close for the symbol. Amber when it is behind.

Stale price

The stored price is older than it should be, so profit figures are behind.

Unrealised P&L

Profit or loss on positions still open, at the last stored price.

Realised P&L

Profit or loss actually locked in by closed positions.

Net of fees

Everything, after the charges you recorded.

Invested

What your open positions cost you.

Market value

What your open positions are worth at the last stored prices.

Unpriced symbols

Positions with no stored price, so they are excluded from the totals.

Days held

Calendar days since your first fill in this position.

Trade style

How you intended to hold it: intraday, swing, positional or long term.

Style (assumed)

Rāma guessed the style because the position predates the field.

Style vs thesis

A note when how you are holding it contradicts what you said you would do.

Thesis

What you expected when you took the trade — stop, target, horizon and reason.

Your stop

The exit price you committed to when you opened the position.

Why you took it

Your own reason, in your own words.

Partial exit

Closing some of a position and leaving the rest open.

Needs your attention

A warning Rāma is prepared to stand behind and act on.

Readings not acted on

Things Rāma noticed but will not recommend acting on, with the reason.

Strategy builder

Block

One condition you can put into a strategy.

Combiner

How your blocks combine: all, any, or at least k of them.

Higher highs and higher lows

An uptrend defined by structure rather than by an indicator.

Lower lows and lower highs

A downtrend by structure — the mirror of the above.

Trendline break

Close crossing a line fitted over the previous N bars.

N-bar break

Close beyond the highest high or lowest low of the previous N bars.

Volume surge

Volume a multiple of its own recent average.

ATR expansion

True range running above its own longer average — a volatility filter.

Price vs SMA

A regime filter: only act while price is above, or below, a long average.

RSI band

RSI beyond a level, as a condition.

MACD signal cross

The MACD line crossing its own signal line.

Session filters

Day of week, or a time-of-day window on intraday bars.

Stop %

How far below entry (above, for a short) the strategy gives up.

Target %

How far in your favour the strategy takes profit.

Max bars

Give up after this many bars whatever the price. 0 means no time limit.

Sweep

Several values for one parameter, so Rāma tries each.

Variants

How many configurations the search will try. The most important number on the screen.

Not backtestable

A block that can run live but cannot honestly be tested on history.

Look-ahead

Using information a rule could not have had at the time.

Generated Python

A standalone script implementing your strategy. It prints signals; it places no orders.

No order placement

Rāma never places, modifies or cancels a trade. By design, permanently.

How a strategy is judged

Holdout

A final slice of history the search is never allowed to see.

Net Sharpe

Return per unit of risk, after costs. Higher is better.

Gross Sharpe

The same measure before trading costs.

Noise benchmark

The Sharpe a search of this many variants would produce from pure luck.

Chance it is real

The probability the result is a genuine edge rather than the best of many tries.

Win rate

The share of trades that made money, after costs.

Expectancy

The average net result per trade, in percent.

Max drawdown

The worst peak-to-trough fall along the way.

Cost drag

The assumed round-trip cost of one trade — commission, slippage and spread.

Confidence

none, provisional or measured — how much evidence stands behind the verdict.

ROI

Return on capital over the holdout. Reported, never requested.

Engine and models

Status

What the last request did: idle, requesting, done, or error.

Absorbed engine

StockMind's prediction maths was taken into Rāma rather than called as a separate app.

Models trained

How many models have been fitted and stored.

Feature contract

Whether the inputs a model was trained on still match what the engine computes today.

Acceptance gate

The bar a model must clear on live data before Rāma will act on its output.

Horizon

How far ahead a question looks: intraday, swing or positional.

Derivatives

PCR (OI)

Put open interest divided by call open interest for the nearest expiry.

Max pain

The strike at which option writers would pay out least.

OI support and resistance

The strikes carrying the most put and call open interest.

Futures basis

How far the future trades from spot, as a percentage.

Rollover

The share of expiring positions carried into the next series.

Expected move

The at-the-money straddle as a fraction of spot — the market's own priced move to expiry.

Days to expiry

Sessions left in the current derivatives series.

News

Sentiment

The scored tone of recent headlines, negative through positive.

Dominant event

The event type most present in the headlines — results, rating, deal, legal.

Why news is NOT BACKTESTABLE

No free feed carries enough history to measure whether tone predicts anything.

11. When something is wrong

Symptom	What to do
Voice input does nothing	Check the level chip. Below 2 means nothing can transcribe — install a Whisper binary or add a provider key.
“Vault locked” will not clear	The vault password is not the startup passcode. If it is refused, it is the wrong password; the error now says which.
A page is missing from the rail	Pages are filtered by access tier. Check section 5.
Something in the environment is broken	<code>node start.cjs --diagnose</code> , then <code>--repair</code> .
A chart study draws nothing	It will say why — usually too few bars for the period, or a study withheld on that interval or chart type.

12. What this guide does not cover

Stated plainly rather than left to be discovered:

- **The Python analysis engine has not run on this machine.** Its pinned numpy needs CPython 3.12 and a newer Python is installed, so engine-backed features — backtests, the projection's numbers, the advanced analytics — are present in the interface but unexercised here.
- **Voice input is unavailable until a transcriber is installed**, as section 7 explains.
- Features behind an access tier you do not hold are not described in operational detail.

Generated 2026-10-10 from the Rāma AGI source tree. Regenerate with `npm run guide` after any change to pages, capabilities, shortcuts or the glossary.