Exp No:19

Experiment to understand Logistic Regression for a given data set.

AIM:

Understand the Logistic Regression algorithm for the dataset given.

In [1]:
```
import numpy as np
import pandas as pd
df=pd.read_csv('Social_Network_Ads.csv')
df
```

Out[1]:

	User ID	Gender	Age	EstimatedSalary	Purchased
0	15624510	Male	19	19000	0
1	15810944	Male	35	20000	0
2	15668575	Female	26	43000	0
3	15603246	Female	27	57000	0
4	15804002	Male	19	76000	0
...	...	...	...	...	...
395	15691863	Female	46	41000	1
396	15706071	Male	51	23000	1
397	15654296	Female	50	20000	1
398	15755018	Male	36	33000	0
399	15594041	Female	49	36000	1

400 rows × 5 columns

In [2]:
```
df.head()
```

In [2]:
```
df.head()
```

Out[2]:

	User ID	Gender	Age	EstimatedSalary	Purchased
0	15624510	Male	19	19000	0
1	15810944	Male	35	20000	0
2	15668575	Female	26	43000	0
3	15603246	Female	27	57000	0
4	15804002	Male	19	76000	0

In [4]:
```
features=df.iloc[:,[2,3]].values
label=df.iloc[:,4].values
features
```

Out[4]:
```
array([[    19,  19000],
       [    35,  20000],
       [    26,  43000],
       [    27,  57000],
       [    19,  76000],
       [    27,  58000],
       [    27,  84000],
       [    32, 150000],
       [    25,  33000],
       [    35,  65000],
       [    26,  80000],
       [    26,  52000],
       [    20,  86000],
       [    32,  18000],
       [    18,  82000],
       [    29,  80000],
       [    47,  25000],
       [    45,  26000],
       [    46,  28000],
```

In [5]:
```
label
```

In [5]:
```
label
```

Out[5]:
```
array([0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 1, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 1, 0, 1, 0, 1, 0, 1, 0, 1, 1, 0, 0, 0, 1, 0, 0, 0, 1,
       0, 1, 1, 1, 0, 0, 1, 1, 0, 1, 1, 0, 1, 1, 0, 1, 0, 0, 0, 1, 1, 0,
       1, 1, 0, 1, 0, 1, 0, 1, 0, 0, 1, 1, 0, 1, 0, 0, 1, 1, 0, 1, 1, 0,
       1, 1, 0, 0, 1, 0, 0, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1, 0, 1, 1, 0, 1,
       0, 1, 0, 1, 1, 1, 1, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 0, 0, 0, 1,
       1, 0, 0, 1, 0, 1, 0, 1, 1, 0, 1, 0, 1, 1, 0, 1, 1, 0, 0, 0, 1, 1,
       0, 1, 0, 0, 1, 0, 1, 0, 0, 1, 1, 0, 0, 1, 1, 0, 1, 1, 0, 0, 1, 0,
       1, 0, 1, 1, 1, 0, 1, 0, 1, 1, 1, 0, 1, 1, 1, 1, 0, 1, 1, 1, 0, 1,
       0, 1, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1, 1, 1, 1, 1, 1, 0, 1,
       1, 1, 0, 1], dtype=int64)
```

In [6]:
```
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
```

In [7]:
```
for i in range(1,401):
  x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.
  model=LogisticRegression()
  model.fit(x_train,y_train)
  train_score=model.score(x_train,y_train)
  test_score=model.score(x_test,y_test)
  if test_score>train_score:
    print("Test {} Train{} Random State {}".format(test_score,train_score,i)
```

```
Test 0.6875 Train0.63125 Random State 3
Test 0.7375 Train0.61875 Random State 4
Test 0.6625 Train0.6375 Random State 5
Test 0.65 Train0.640625 Random State 6
Test 0.675 Train0.634375 Random State 7
Test 0.675 Train0.634375 Random State 8
Test 0.65 Train0.640625 Random State 10
Test 0.6625 Train0.6375 Random State 11
Test 0.7125 Train0.625 Random State 13
Test 0.675 Train0.634375 Random State 16
Test 0.7 Train0.628125 Random State 17
Test 0.7 Train0.628125 Random State 21
Test 0.65 Train0.640625 Random State 24
Test 0.6625 Train0.6375 Random State 25
Test 0.75 Train0.615625 Random State 26
Test 0.675 Train0.634375 Random State 27
Test 0.7 Train0.628125 Random State 28
Test 0.6875 Train0.63125 Random State 29
Test 0.6875 Train0.63125 Random State 31
```

In [8]:
```
x_train,x_test,y_train,y_test=train_test_split(features,label,test_size=0.2,
finalModel=LogisticRegression()
finalModel.fit(x_train,y_train)
```

Out[8]:
```
LogisticRegression()
```

Out[8]:
```
LogisticRegression()
```
In a Jupyter environment, please rerun this cell to show the HTML representation or trust the notebook.
On GitHub, the HTML representation is unable to render, please try loading this page with nbviewer.org.

In [9]:
```
print(finalModel.score(x_train,y_train))
print(finalModel.score(x_test,y_test))
```

```
0.834375
0.9125
```

In [10]:
```
from sklearn.metrics import classification_report
print(classification_report(label,finalModel.predict(features)))
```

```
              precision    recall  f1-score   support

           0       0.85      0.93      0.89       257
           1       0.84      0.71      0.77       143

    accuracy                           0.85       400
   macro avg       0.85      0.82      0.83       400
weighted avg       0.85      0.85      0.85       400
```

RESULT:

Experiment to understand Logistic Regression for a given data set is done.