```
krishnasree08@krishnasree08:~/ossp_session9_10$ mkdir -p ~/ossp_session9_10
cd ~/ossp_session9_10
krishnasree08@krishnasree08:~/ossp_session9_10$ nano directory_navigation.c
krishnasree08@krishnasree08:~/ossp_session9_10$ gcc -Wall -Wextra directory_navigation.c -o directory_navigation
./directory_navigation

Current directory: /home/krishnasree08/ossp_session9_10
Enter directory path (or 'back' or 'exit'): exit
krishnasree08@krishnasree08:~/ossp_session9_10$ nano builtin_dispatch.c
krishnasree08@krishnasree08:~/ossp_session9_10$ gcc -Wall -Wextra builtin_dispatch.c -o builtin_dispatch
./builtin_dispatch

OSSP> exit
Exiting program.
krishnasree08@krishnasree08:~/ossp_session9_10$ nano shell_exit.c
krishnasree08@krishnasree08:~/ossp_session9_10$ gcc -Wall -Wextra shell_exit.c -o shell_exit
./shell_exit
Simple OSSP Shell

Directory: /home/krishnasree08/ossp_session9_10
Enter 'pwd' to show path or 'exit' to quit: exit
Cleaning up resources...
Shell terminated successfully.
krishnasree08@krishnasree08:~/ossp_session9_10$ nano export_variables.c
krishnasree08@krishnasree08:~/ossp_session9_10$ gcc -Wall -Wextra export_variables.c -o export_variables
./export_variables
Enter an export command (example: export CITY=Hyderabad):
export CITY=Hyderabad
Variable exported successfully.
CITY=Hyderabad
Child process received CITY=Hyderabad
Parent process completed.
```

```
krishnasree08@krishnasree08:~/ossp_session9_10$ cd ~/ossp_session9_10

gcc -Wall -Wextra directory_navigation.c -o directory_navigation
gcc -Wall -Wextra builtin_dispatch.c -o builtin_dispatch
gcc -Wall -Wextra shell_exit.c -o shell_exit
gcc -Wall -Wextra export_variables.c -o export_variables
krishnasree08@krishnasree08:~/ossp_session9_10$ ./directory_navigation

Current directory: /home/krishnasree08/ossp_session9_10
Enter directory path (or 'back' or 'exit'): exit
```

Final result for the session

The programs demonstrate directory navigation using chdir(), built-in command dispatch, current-directory retrieval using getcwd(), process termination, and environment-variable export using setenv(). The child-process example also demonstrates fork() and waitpid().