

# CSS Selectors

---

 [w3schools.com/css/css\\_selectors.asp](https://www.w3schools.com/css/css_selectors.asp)

---

A CSS selector selects the HTML element(s) you want to style.

---

CSS selectors are used to "find" (or select) the HTML elements you want to style.

We can divide CSS selectors into five categories:

- Simple selectors (select elements based on name, id, class)
- Combinator selectors (select elements based on a specific relationship between them)
- Pseudo-class selectors (select elements based on a certain state)
- Pseudo-elements selectors (select and style a part of an element)
- Attribute selectors (select elements based on an attribute or attribute value)

This page will explain the most basic CSS selectors.

---

## The CSS element Selector

---

The element selector selects HTML elements based on the element name.

### Example

---

Here, all <p> elements on the page will be center-aligned, with a red text color:

```
p {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

---

## The CSS id Selector

---

The id selector uses the id attribute of an HTML element to select a specific element.

The id of an element is unique within a page, so the id selector is used to select one unique element!

To select an element with a specific id, write a hash (#) character, followed by the id of the element.

## Example

---

The CSS rule below will be applied to the HTML element with id="para1":

```
#para1 {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

**Note:** An id name cannot start with a number!

---

## The CSS class Selector

---

The class selector selects HTML elements with a specific class attribute.

To select elements with a specific class, write a period (.) character, followed by the class name.

## Example

---

In this example all HTML elements with class="center" will be red and center-aligned:

```
.center {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

You can also specify that only specific HTML elements should be affected by a class.

## Example

---

In this example only <p> elements with class="center" will be red and center-aligned:

```
p.center {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

HTML elements can also refer to more than one class.

## Example

---

In this example the <p> element will be styled according to class="center" and to class="large":

<p class="center large">This paragraph refers to two classes.</p>

[Try it Yourself »](#)

**Note:** A class name cannot start with a number!

---

## The CSS Universal Selector

---

The universal selector (\*) selects all HTML elements on the page.

### Example

---

The CSS rule below will affect every HTML element on the page:

```
* {  
  text-align: center;  
  color: blue;  
}
```

[Try it Yourself »](#)

---

## The CSS Grouping Selector

---

The grouping selector selects all the HTML elements with the same style definitions.

Look at the following CSS code (the h1, h2, and p elements have the same style definitions):

```
h1 {  
  text-align: center;  
  color: red;  
}
```

```
h2 {  
  text-align: center;  
  color: red;  
}
```

```
p {  
  text-align: center;  
  color: red;  
}
```

It will be better to group the selectors, to minimize the code.

To group selectors, separate each selector with a comma.

### Example

---

In this example we have grouped the selectors from the code above:

```
h1, h2, p {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

---

## Test Yourself With Exercises

---

### Exercise:

---

Set the color of all <p> elements to red.

```
<style>  
{  
  red;  
}  
</style>
```

[Start the Exercise](#)

---

## All CSS Simple Selectors

---

Selector	Example	Example description
<u>#id</u>	#firstname	Selects the element with id="firstname"
<u>.class</u>	.intro	Selects all elements with class="intro"
<u>element.class</u>	p.intro	Selects only <p> elements with class="intro"
<u>*</u>	*	Selects all elements
<u>element</u>	p	Selects all <p> elements
<u>element,element,..</u>	div, p	Selects all <div> elements and all <p> elements