WBHS

Beneficiary Authentication API

Mobile Number Based Beneficiary Verification for Empanelled Hospitals

Version	Format	Auth
1.0	JSON	API Key

Department: Finance Department | Audience: WBHS Empanelled Hospitals, TPA Operators

1. Overview

The WBHS Beneficiary Authentication API enables empanelled hospitals to securely verify whether a patient is an active beneficiary under the West Bengal Health Scheme (WBHS) using the registered mobile number.

1.1 Key Capabilities

- Real-time beneficiary lookup by mobile number
- Employee (SELF) and family member (FAMILY) verification
- Photo path retrieval for identity verification
- Beneficiary registration status validation

1.2 Intended Users

- WBHS Empanelled Hospitals
- Hospital Admission Desk / TPA Operators
- WBHS Integration Team

1.3 Source Tables

Table	Purpose
`wbhs_empBasicInfo_ONLINE`	Employee (SELF) data — filtered by MOBILE_NO
`wbhs_familyDetails_inservice_ONLINE`	Family member data — filtered by MEM_MOB_NO
`wbhs_familyDetails_inservice_ONLINE_PHOTO_SIGNATURE`	Photo path — LEFT JOIN on APP_ID + idno

2. API Endpoint

2.1 Endpoint

Method	GET

Path	`/api/v1/beneficiary-auth/mobile/{mobileNumber}`

2.2 Purpose

Verifies whether the provided mobile number belongs to an active WBHS employee (SELF) or a family member (FAMILY). Returns both SELF and FAMILY records if found for the same mobile number.

3. Authentication & Security

3.1 Required Headers

Header	Type	Required	Description
X-API-KEY	String	Yes	Hospital integration API key
Content-Type	String	Yes	application/json

3.2 Header Validation Rules

- No header validation is currently enforced in the controller
- Missing X-API-KEY is tracked as ANONYMOUS for rate limiting purposes

4. Request Parameters

4.1 Path Parameter

Parameter	Type	Required	Description
mobileNumber	String (10 digits)	Yes	Registered WBHS beneficiary mobile number

4.2 Validation Rules (enforced in service layer)

- Mobile number must be exactly 10 digits
- Only numeric values allowed
- Empty or whitespace: 400 Bad Request with message "Mobile number is required"
- Invalid format: 400 Bad Request with message "Invalid mobile number"

5. Request Example

```shell
curl -X GET
"https://api.wbhealthscheme.gov.in/api/v1/beneficiary-auth/mobile
/9876543210" \
  -H "X-API-KEY: HOSPITAL_API_KEY" \
  -H "Content-Type: application/json"
```

6. Response Structure

Sample response when both SELF and FAMILY records are found for the same mobile number:

```json
{
  "success": true,
  "message": "Beneficiary fetched successfully",
  "data": [
    {
      "applicationId": "WB/EMP/000000001",
```

```
      "employeeId": "NONGPF/WB/20260409152332377",
      "beneficiaryId": "NONGPF/WB/20260409152332377",
      "beneficiaryName": "Rajesh Kumar",
      "mobileNumber": "9876543210",
      "dateOfBirth": "1985-03-15T00:00:00",
      "memberType": "SELF",
      "relation": "Self",
      "registrationStatus": "Y",
      "validUpto": 2030-03-15,
      "bloodGroup":B+,
      "photoPath": null
    },
    {
      "applicationId": "WB/EMP/000000001",
      "employeeId": null,
      "beneficiaryId": "FAM001",
      "beneficiaryName": "Priya Kumar",
      "mobileNumber": "9876543210",
      "dateOfBirth": "1988-07-22T00:00:00",
      "memberType": "FAMILY",
      "relation": "W",
      "registrationStatus": "Y",
      "validUpto": "2026-03-31T00:00:00",
      "bloodGroup": "O+",
      "photoPath": "/ftp/photos/priya.jpg"
    }
  ]
}
```


7. Response Fields

Field	Type	Source Column	Description
`applicationId`	String	`app_id`	WBHS application ID e.g. WB/EMP/000000001
`employeeId`	String/null	`empId`	GPF/PRAN No. for SELF — null for FAMILY
`beneficiaryId`	String	`empId / idno`	Same as employeeId for SELF, idno for FAMILY
`beneficiaryName`	String	`empFirstName + empLastName / bName`	Full name — SELF concatenates first+last
`mobileNumber`	String	`MOBILE_NO / MEM_MOB_NO`	Registered mobile number
`dateOfBirth`	DateTime?	`empDob / dob`	Date of birth — nullable
`memberType`	String	`Derived`	SELF or FAMILY
`relation`	String	`mem_cd (raw)`	Raw relation code
`registrationStatus`	String	`IS_EXISTS`	Y = Active, N = Inactive — no filter applied
`validUpto`	DateTime	`Valid_UpTo`	Family validity
`bloodGroup`	String	`BEN_BLOOD_GROUP`	SELF

`photoPath`	String?	`PHOTO_FTP`	From photo signature table — null if no record

8. Business Rules (Current Implementation)

- Both SELF and FAMILY records are returned if the mobile number matches
- No IS_EXISTS = 'Y' filter applied — all records returned regardless of status
- Relation code is NOT mapped — raw mem_cd value returned (e.g. W, S, D, M)
- Photo path sourced from PHOTO_FTP column via LEFT JOIN — null if no photo record exists
- SELF bloodGroup and photoPath always return null
- SELF validUpto always returns null

9. Relation Code Reference

Raw codes returned as-is from the mem_cd column.

Code	Meaning
`W`	Wife / Spouse
`S`	Son
`D`	Daughter
`M`	Mother

`H`	Husband
`F`	Father

10. Error Responses

400 — Invalid Mobile Number

```
{ "success": false, "message": "Mobile number is required" }
```

```
{ "success": false, "message": "Invalid mobile number" }
```

404 — Beneficiary Not Found

```
{ "success": false, "message": "Beneficiary not found" }
```

429 — Rate Limit Exceeded

```
"Rate limit exceeded. Try again later."
```

500 — Internal Server Error

```
{ "success": false, "message": "An error occurred while processing your request." }
```

HTTP Status Code Summary

Code	Meaning
200	Success
400	Invalid/missing mobile number
404	Beneficiary not found
429	Rate limit exceeded
500	Internal server error

11. Rate Limiting

- 5 requests/minute per mobile number on /beneficiary-auth/mobile/{mobileNumber}
- Tracked as MOBILE:{mobileNumber} key in WBHS_API_RATE_LIMIT table
- Missing X-API-KEY is tracked as ANONYMOUS
- Window is 1 minute sliding — new row inserted per window
- Exceeding limit returns 429 plain text response

12. Audit Logging

Every request is logged to the WBHS_API_REQUEST_LOG table with the following fields:

Logged Field	Source
`ApiName`	Endpoint display name or "Beneficiary Authentication"
`Endpoint`	Request path
`HttpMethod`	GET / POST etc.
`ClientIp`	RemoteIpAddress
`UserAgent`	User-Agent header
`ApiKey`	X-API-KEY header
`RequestQuery`	Query string
`RequestBody`	Request body (GET = empty)
`ResponseStatusCode`	HTTP status code
`ResponseBody`	Truncated to 4000 chars
`ResponseTimeMs`	Elapsed milliseconds
`IsSuccess`	true if status 200–299

`ErrorMessage`	Exception message on 500
`CorrelationId`	New Guid per request

13. Privacy — Excluded Fields

The following fields are not included in the response

- Aadhaar number (EMP_ADHAR_NO / MEM_ADHAR_NO)
- HRMS ID (HRMS_ID)
- Office address (EMP_OFC_ADD)
- Salary (BASIC_SALARY, PAY_LEVEL)
- Bank details (BANK_NAME, BANK_ACCNT_NO, BANK_IFSC)
- DDO details, posting district, suspension details

13.1 Included Fields

Only minimum identity and eligibility data are required for hospital verification.

14. Operational SLA

Metric	Target
Response time	< 2 seconds
Availability	99.5%
Idempotency	Read-only, fully idempotent

Retry	Supported for timeout failures only

Final Endpoint

GET /api/v1/beneficiary-auth/mobile/{mobileNumber}