

## Bubble sort in C++

```
#include <iostream>
using namespace std;

void BubbleSort(int arr[], int n) {
    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - 1 - i; j++) {
            if (arr[j] > arr[j + 1]) {
                // Swap arr[j] and arr[j+1]
                int temp = arr[j];
                arr[j] = arr[j + 1];
                arr[j + 1] = temp;
            }
        }
    }
}

int main() {
    int arr[] = {0, 1, 5, 7, 8, 9, 4};
    int n = sizeof(arr) / sizeof(arr[0]);

    BubbleSort(arr, n);

    cout << "Sorted array: ";
    for (int i = 0; i < n; i++) {
        cout << arr[i] << " ";
    }
    cout << endl;

    return 0;
}
```

### Dry Run Table:

#### Initial:

[0, 1, 5, 7, 8, 9, 4]

#### Pass 1 (i = 0):

Compare arr[j]	Swap?	Result
0 and 1	No	[0, 1, 5, 7, 8, 9, 4]
1 and 5	No	[0, 1, 5, 7, 8, 9, 4]
5 and 7	No	[0, 1, 5, 7, 8, 9, 4]
7 and 8	No	[0, 1, 5, 7, 8, 9, 4]
8 and 9	No	[0, 1, 5, 7, 8, 9, 4]
9 and 4	Yes	[0, 1, 5, 7, 8, 4, 9]

✓ Largest element 9 moved to the end.

#### Pass 2 (i = 1):

Compare arr[j]	Swap?	Result
0 and 1	No	[0, 1, 5, 7, 8, 4, 9]
1 and 5	No	[0, 1, 5, 7, 8, 4, 9]
5 and 7	No	[0, 1, 5, 7, 8, 4, 9]
7 and 8	No	[0, 1, 5, 7, 8, 4, 9]
8 and 4	Yes	[0, 1, 5, 7, 4, 8, 9]

✓ Second-largest 8 in place.

#### Pass 3 (i = 2):

Compare arr[j]	Swap?	Result
0 and 1	No	[0, 1, 5, 7, 4, 8, 9]
1 and 5	No	[0, 1, 5, 7, 4, 8, 9]
5 and 7	No	[0, 1, 5, 7, 4, 8, 9]
7 and 4	Yes	[0, 1, 5, 4, 7, 8, 9]

#### Pass 4 (i = 3):

Compare arr[j]	Swap?	Result
0 and 1	No	[0, 1, 5, 4, 7, 8, 9]
1 and 5	No	[0, 1, 5, 4, 7, 8, 9]
5 and 4	Yes	[0, 1, 4, 5, 7, 8, 9]

#### Pass 5 (i = 4):

Compare arr[j]	Swap?	Result
0 and 1	No	[0, 1, 4, 5, 7, 8, 9]

	<table><tr><th>Compare arr[j]</th><th>Swap?</th><th>Result</th></tr><tr><td>1 and 4</td><td>No</td><td>[0, 1, 4, 5, 7, 8, 9]</td></tr></table>	Compare arr[j]	Swap?	Result	1 and 4	No	[0, 1, 4, 5, 7, 8, 9]
	Compare arr[j]	Swap?	Result				
	1 and 4	No	[0, 1, 4, 5, 7, 8, 9]				
	<p>Pass 6 (i = 5):</p>						
	<table><tr><th>Compare arr[j]</th><th>Swap?</th><th>Result</th></tr><tr><td>0 and 1</td><td>No</td><td>[0, 1, 4, 5, 7, 8, 9]</td></tr></table>	Compare arr[j]	Swap?	Result	0 and 1	No	[0, 1, 4, 5, 7, 8, 9]
	Compare arr[j]	Swap?	Result				
	0 and 1	No	[0, 1, 4, 5, 7, 8, 9]				
	<p>🚩 Final Sorted Array:</p>						
	<p>Sorted array: 0 1 4 5 7 8 9</p>						
Sorted array: 0 1 4 5 7 8 9							

Count Inversions in C++																
<pre>#include &lt;iostream&gt; #include &lt;vector&gt;  using namespace std;  long long ans;  void merge(vector&lt;long long&gt;&amp; arr, int l, int m, int r) {     int n1 = m - l + 1;     int n2 = r - m;      vector&lt;long long&gt; L(n1), R(n2);      for (int i = 0; i &lt; n1; i++)         L[i] = arr[l + i];     for (int j = 0; j &lt; n2; j++)         R[j] = arr[m + 1 + j];      int i = 0, j = 0, k = l;      while (i &lt; n1 &amp;&amp; j &lt; n2) {         if (L[i] &lt;= R[j]) {             arr[k++] = L[i++];         } else {             arr[k++] = R[j++];             ans += (m - l + 1 - i);         }     }      while (i &lt; n1) {         arr[k++] = L[i++];     }      while (j &lt; n2) {         arr[k++] = R[j++];     } }  void mergeSort(vector&lt;long long&gt;&amp; arr, int l, int r) {     if (l &lt; r) {         int m = l + (r - l) / 2;         mergeSort(arr, l, m);         mergeSort(arr, m + 1, r);         merge(arr, l, m, r);     } }  long long inversionCount(vector&lt;long long&gt;&amp; arr) {     ans = 0;     mergeSort(arr, 0, arr.size() - 1);     return ans; }  void printArray(const vector&lt;long long&gt;&amp; arr) {     for (long long num : arr) {         cout &lt;&lt; num &lt;&lt; " ";     }     cout &lt;&lt; endl; }</pre>	Step-by-Step Merge and Inversion Tracking															
	Step	Subarrays (Left - Right)	Comparison	Inversion Count	Merged Result											
	1	[2] and [3]	$2 \leq 3$	0	[2, 3]											
	2	[2, 3] and [8]	All in order	0	[2, 3, 8]											
	3	[6] and [1]	$6 > 1$	1	[1, 6]											
	4	[2, 3, 8] and [1, 6]	$2 > 1$	3 (2,3,8 > 1)												
			$2 < 6$	0												
			$3 < 6$	0												
			$8 > 6$	1	[1, 2, 3, 6, 8]											
	<div>✔ Summary</div> <table><tr><th>Merge Step</th><th>Inversions Found</th></tr><tr><td>[2] and [3]</td><td>0</td></tr><tr><td>[2, 3] and [8]</td><td>0</td></tr><tr><td>[6] and [1]</td><td>1</td></tr><tr><td>[2, 3, 8] and [1, 6]</td><td>3 + 1 = 4</td></tr><tr><td>Total Inversions</td><td>5</td></tr></table>					Merge Step	Inversions Found	[2] and [3]	0	[2, 3] and [8]	0	[6] and [1]	1	[2, 3, 8] and [1, 6]	3 + 1 = 4	Total Inversions
Merge Step	Inversions Found															
[2] and [3]	0															
[2, 3] and [8]	0															
[6] and [1]	1															
[2, 3, 8] and [1, 6]	3 + 1 = 4															
Total Inversions	5															

```
int main() {  
    vector<long long> arr = {2, 3, 8, 6, 1};  
  
    cout << "Given Array:" << endl;  
    printArray(arr);  
  
    long long inversionCountValue =  
inversionCount(arr);  
  
    cout << "Number of inversions: " <<  
inversionCountValue << endl;  
  
    return 0;  
}
```

Given Array:

2 3 8 6 1

Number of inversions: 5

## Count Sort in C++

```
#include <iostream>
#include <cstring>
using namespace std;

string countSort(string s) {
    char arr[s.length()];
    strcpy(arr, s.c_str());

    char maxch = 'a';
    for (int i = 0; i < strlen(arr); i++) {
        if (arr[i] > maxch) {
            maxch = arr[i];
        }
    }
    int max = maxch - 'a';
    int count[max + 1] = {0};

    for (int i = 0; i < strlen(arr); i++) {
        int val = arr[i] - 'a';
        count[val]++;
    }

    int k = 0;
    for (int i = 0; i <= max; i++) {
        int c = count[i];
        for (int j = 0; j < c; j++) {
            arr[k] = i + 'a';
            k++;
        }
    }

    string sortedString(arr);
    return sortedString;
}

int main() {
    string input = "countingsortexample";

    string sortedString = countSort(input);

    cout << "Original String: " << input << endl;
    cout << "Sorted String: " << sortedString << endl;

    return 0;
}
```

### Step-by-Step Dry Run:

#### Step 1: Copy string to character array

```
strcpy(arr, s.c_str());
```

Now arr = "countingsortexample"

#### Step 2: Find max character (in terms of ASCII)

```
char maxch = 'x'; // max character = 'x'
int max = maxch - 'a'; // max = 23
```

#### Step 3: Count frequency of each character

Character	Count
a	1
c	1
e	2
g	1
i	1
l	1
m	1
n	2
o	2
p	1
r	1
s	1
t	2
u	1
x	1

#### Step 4: Reconstruct the sorted array

Characters are added in order of 'a' to 'x' based on count.

Sorted string becomes:

	<div>"aceegilmnnooprsttux"</div> <div>✔ <b>Output:</b></div> <div>Original String: countingsortexample Sorted String: aceegilmnnooprsttux</div>
<div>Original String: countingsortexample Sorted String: aceegilmnnooprsttux</div>	

## Good Integers distinct in C++

```
#include <iostream>
#include <vector>
#include <algorithm>

using namespace std;

int GoodIntegers(vector<int>& arr) {
    sort(arr.begin(), arr.end()); // Sort the array

    int ans = 0;

    for (int i = 0; i < arr.size(); ++i) {
        if (arr[i] == i) { // Check if the value at index i
            matches i
            ++ans;
        }
    }

    return ans; // Return the count of good integers
}

int main() {
    vector<int> arr = {0, 1, 5, 7, 8, 9, 4};

    cout << GoodIntegers(arr) << endl;

    return 0;
}
```

### Input:

vector<int> arr = {0, 1, 5, 7, 8, 9, 4};

### Step 1: Sort the array

Sorted arr = {0, 1, 4, 5, 7, 8, 9}

↑ ↑ ↑ ↑ ↑ ↑  
 Index    0 1 2 3 4 5 6

### Step 2: Compare each element with its index

Index i	arr[i]	arr[i] == i	Count (ans)
0	0	✓ Yes	1
1	1	✓ Yes	2
2	4	✗ No	2
3	5	✗ No	2
4	7	✗ No	2
5	8	✗ No	2
6	9	✗ No	2

### Final Output:

cout << GoodIntegers(arr); // Output: 2

✓ Because arr[0] = 0 and arr[1] = 1 match their indices.

## Good Integers duplicate in C++

```
#include <iostream>
#include <vector>
#include <algorithm>

using namespace std;

int GoodIntegers(int arr[], int n) {
    sort(arr, arr + n); // Sort the array

    int ans = 0;
    int lessCount = 0;

    if (arr[0] == 0) {
        ans++;
    }

    for (int i = 1; i < n; ++i) {
        if (arr[i] != arr[i - 1]) {
            lessCount = i;
        }

        if (arr[i] == lessCount) {
            ans++;
        }
    }

    return ans;
}

int main() {
    int arr[] = {0, 1, 5, 7, 8, 9, 4};
    int n = sizeof(arr) / sizeof(arr[0]);

    cout << GoodIntegers(arr, n) << endl;

    return 0;
}
```

### Goal of the Function:

Count how many elements in the array are **equal to the number of elements less than it**.

### 🔗 Step-by-step Dry Run

#### ► Step 1: Sort the array

Initial array: {0, 1, 5, 7, 8, 9, 4}

Sorted array: {0, 1, 4, 5, 7, 8, 9}

n = 7

Variables: ans = 0, lessCount = 0

Index (i)	arr[i]	arr[i-1]	arr[i] != arr[i-1]	lessCount	arr[i] == lessCount	ans
0	0	-	-	0	✓ (0 == 0)	1
1	1	0	✓	1	✓ (1 == 1)	2
2	4	1	✓	2	✗ (4 != 2)	2
3	5	4	✓	3	✗ (5 != 3)	2
4	7	5	✓	4	✗ (7 != 4)	2
5	8	7	✓	5	✗ (8 != 5)	2
6	9	8	✓	6	✗ (9 != 6)	2

### ✓ Final Answer: 2

The two good integers are:

- 0: there are 0 elements less than it → good
- 1: there is 1 element less than it → good



## Insertion Sort in C++

```
#include <iostream>
using namespace std;

class InsertionSort {
public:
    // Function to perform insertion sort on array arr of
    size n
    void insertionSort(int arr[], int n) {
        for (int i = 1; i < n; i++) {
            insert(arr, i);
        }
    }

private:
    // Helper function to insert arr[i] into the sorted
    sub-array arr[0...i-1]
    void insert(int arr[], int i) {
        int key = arr[i]; // Element to be inserted
        int j = i - 1; // Start comparing with the
        previous element

        // Move elements of arr[0..i-1], that are greater
        than key, to one position ahead of their current
        position
        while (j >= 0 && arr[j] > key) {
            arr[j + 1] = arr[j];
            j--;
        }
        arr[j + 1] = key; // Place key at its correct position
    }
};

int main() {
    InsertionSort solution;

    // Hardcoded input array
    int arr[] = {5, 2, 9, 1, 5, 6};
    int n = sizeof(arr) / sizeof(arr[0]);

    // Sorting the array using insertion sort
    solution.insertionSort(arr, n);

    // Printing the sorted array
    for (int i = 0; i < n; i++) {
        cout << arr[i] << " ";
    }
    cout << endl;

    return 0;
}
```

Let's dry run your **Insertion Sort** code step by step with the input:

int arr[] = {5, 2, 9, 1, 5, 6};

### 🔗 Insertion Sort Dry Run Table

i	Key	Initial Array State	Comparison Index (j)	Action Taken	Updated Array
1	2	[5, 2, 9, 1, 5, 6]	j = 0 (5 > 2)	Shift 5 to index 1	[5, 5, 9, 1, 5, 6]
			j = -1	Insert 2 at index 0	[2, 5, 9, 1, 5, 6]
2	9	[2, 5, 9, 1, 5, 6]	j = 1 (5 < 9)	No shifting, insert 9 at index 2	[2, 5, 9, 1, 5, 6]
3	1	[2, 5, 9, 1, 5, 6]	j = 2 (9 > 1)	Shift 9 to index 3	[2, 5, 9, 9, 5, 6]
			j = 1 (5 > 1)	Shift 5 to index 2	[2, 5, 5, 9, 5, 6]
			j = 0 (2 > 1)	Shift 2 to index 1	[2, 2, 5, 9, 5, 6]
			j = -1	Insert 1 at index 0	[1, 2, 5, 9, 5, 6]
4	5	[1, 2, 5, 9, 5, 6]	j = 3 (9 > 5)	Shift 9 to index 4	[1, 2, 5, 9, 9, 6]
			j = 2 (5 == 5)	No shifting (stable), insert 5 at index 3	[1, 2, 5, 5, 9, 6]
5	6	[1, 2, 5, 5, 9, 6]	j = 4 (9 > 6)	Shift 9 to index 5	[1, 2, 5, 5, 9, 9]
			j = 3 (5 < 6)	Insert 6 at index 4	[1, 2, 5, 5, 6, 9]

✔ **Final Sorted Array:**

	[1, 2, 5, 5, 6, 9]
1 2 5 5 6 9	

## Merge 2 sorted subarrays in C++

```
#include <iostream>
#include <vector>
using namespace std;

// Function to merge two sorted subarrays within
// array 'a'
vector<int> mergeTwoSortedSubArray(vector<int>&
a, int s, int m, int e) {
    vector<int> temp(e - s + 1);
    int p1 = s;
    int p2 = m + 1;
    int p3 = 0;

    // Merge elements from two subarrays into temp
    array
    while (p1 <= m && p2 <= e) {
        if (a[p1] < a[p2]) {
            temp[p3] = a[p1];
            p3++;
            p1++;
        } else {
            temp[p3] = a[p2];
            p3++;
            p2++;
        }
    }

    // Copy remaining elements of the first subarray, if
    any
    while (p1 <= m) {
        temp[p3] = a[p1];
        p3++;
        p1++;
    }

    // Copy remaining elements of the second subarray,
    if any
    while (p2 <= e) {
        temp[p3] = a[p2];
        p3++;
        p2++;
    }

    // Copy sorted elements from temp back to original
    array 'a'
    for (int i = 0; i < temp.size(); i++) {
        a[s + i] = temp[i];
    }

    return a;
}

int main() {
    // Hard-coded input
    vector<int> A = {1, 3, 5, 7, 2, 4, 6, 8};
    int s = 0;
    int m = 3; // Middle index of the first sorted
    subarray
    int e = 7; // End index of the second sorted subarray

    // Merging the two sorted subarrays
```

using the input:

A = {1, 3, 5, 7, 2, 4, 6, 8}  
s = 0, m = 3, e = 7

This means:

- First sorted subarray = A[0..3] = {1, 3, 5, 7}
- Second sorted subarray = A[4..7] = {2, 4, 6, 8}

### 🔗 Dry Run Table:

Step	p1	p2	temp[] (after step)	Comment
1	0	4	{1}	1 < 2, so copy 1 from left
2	1	4	{1, 2}	2 < 3, so copy 2 from right
3	1	5	{1, 2, 3}	3 < 4, so copy 3 from left
4	2	5	{1, 2, 3, 4}	4 < 5, so copy 4 from right
5	2	6	{1, 2, 3, 4, 5}	5 < 6, so copy 5 from left
6	3	6	{1, 2, 3, 4, 5, 6}	6 < 7, so copy 6 from right
7	3	7	{1, 2, 3, 4, 5, 6, 7}	7 < 8, so copy 7 from left
8	4	7	{1, 2, 3, 4, 5, 6, 7, 8}	only 8 left, copy from right

Now the merged array looks like:

A = {1, 2, 3, 4, 5, 6, 7, 8}

### ✔ Final Output:

Merged array: 1 2 3 4 5 6 7 8

```
vector<int> result = mergeTwoSortedSubArray(A,  
s, m, e);  
  
// Print the result  
cout << "Merged array: ";  
for (int num : result) {  
    cout << num << " ";  
}  
cout << endl;  
  
return 0;  
}
```

Merged array: 1 2 3 4 5 6 7 8

## Merge Sort in C++

```
#include <iostream>
#include <vector>
using namespace std;

class MergeSort {
public:
    void merge(vector<int>& arr, int l, int m, int r) {
        int n1 = m - l + 1;
        int n2 = r - m;

        // Create temporary arrays
        vector<int> L(n1), R(n2);

        // Copy data to temporary arrays L[] and R[]
        for (int i = 0; i < n1; i++)
            L[i] = arr[l + i];
        for (int j = 0; j < n2; j++)
            R[j] = arr[m + 1 + j];

        // Merge the temporary arrays back into arr[l..r]
        int i = 0; // Initial index of first subarray
        int j = 0; // Initial index of second subarray
        int k = l; // Initial index of merged subarray

        while (i < n1 && j < n2) {
            if (L[i] <= R[j]) {
                arr[k] = L[i];
                i++;
            } else {
                arr[k] = R[j];
                j++;
            }
            k++;
        }

        // Copy the remaining elements of L[], if any
        while (i < n1) {
            arr[k] = L[i];
            i++;
            k++;
        }

        // Copy the remaining elements of R[], if any
        while (j < n2) {
            arr[k] = R[j];
            j++;
            k++;
        }
    }

    void mergeSort(vector<int>& arr, int l, int r) {
        if (l >= r) {
            return; // Base case: array size is 0 or 1
        }
        int m = l + (r - l) / 2;
        mergeSort(arr, l, m); // Sort first half
        mergeSort(arr, m + 1, r); // Sort second half
        merge(arr, l, m, r); // Merge sorted halves
    }
};
```

Let's walk through a **dry run** of your **Merge Sort implementation** with the input:

arr = {12, 11, 13, 5, 6, 7}

### 📌 Step-by-step Breakdown:

We'll visualize the recursive division and merging process.

### 🌿 Recursive Division (mergeSort)

Level	Call	Subarray
1	mergeSort(arr, 0, 5)	[12, 11, 13, 5, 6, 7]
2	mergeSort(arr, 0, 2)	[12, 11, 13]
3	mergeSort(arr, 0, 1)	[12, 11]
4	mergeSort(arr, 0, 0)	[12]
4	mergeSort(arr, 1, 1)	[11]
3	merge(arr, 0, 0, 1)	merge [12] and [11] ⇒ [11, 12]
3	mergeSort(arr, 2, 2)	[13]
2	merge(arr, 0, 1, 2)	merge [11, 12] and [13] ⇒ [11, 12, 13]
2	mergeSort(arr, 3, 5)	[5, 6, 7]
3	mergeSort(arr, 3, 4)	[5, 6]
4	mergeSort(arr, 3, 3)	[5]
4	mergeSort(arr, 4, 4)	[6]
3	merge(arr, 3, 3, 4)	merge [5] and [6] ⇒ [5, 6]
3	mergeSort(arr, 5, 5)	[7]
2	merge(arr, 3, 4, 5)	merge [5, 6] and [7] ⇒ [5, 6, 7]

<pre>int main() {     MergeSort solution;      // Hardcoded input array     vector&lt;int&gt; arr = {12, 11, 13, 5, 6, 7};     int n = arr.size();      cout &lt;&lt; "Given Array:" &lt;&lt; endl;     for (int num : arr) {         cout &lt;&lt; num &lt;&lt; " ";     }     cout &lt;&lt; endl;      solution.mergeSort(arr, 0, n - 1);      cout &lt;&lt; "\nSorted array:" &lt;&lt; endl;     for (int num : arr) {         cout &lt;&lt; num &lt;&lt; " ";     }     cout &lt;&lt; endl;      return 0; }</pre>	<table><tr><td>1</td><td>merge(arr, 0, 2, 5)</td><td>merge [11, 12, 13] and [5, 6, 7] ⇒ [5, 6, 7, 11, 12, 13]</td></tr></table> <p>✔ <b>Final Sorted Array:</b></p> <p>[5, 6, 7, 11, 12, 13]</p> <p>■ <b>Visual of Merges</b></p> <p>Initial: [12, 11, 13, 5, 6, 7] Split1: [12, 11, 13]   [5, 6, 7] Split2: [12, 11] [13]   [5, 6] [7] Merge1: [11, 12] + [13] = [11, 12, 13] Merge2: [5, 6] + [7] = [5, 6, 7] Final Merge: [11, 12, 13] + [5, 6, 7] = [5, 6, 7, 11, 12, 13]</p>	1	merge(arr, 0, 2, 5)	merge [11, 12, 13] and [5, 6, 7] ⇒ [5, 6, 7, 11, 12, 13]
1	merge(arr, 0, 2, 5)	merge [11, 12, 13] and [5, 6, 7] ⇒ [5, 6, 7, 11, 12, 13]		
<p>Given Array: 12 11 13 5 6 7</p> <p>Sorted array: 5 6 7 11 12 13</p>				

## Order of removal in C++

```
#include <iostream>
#include <algorithm>
#include <vector>
using namespace std;

class OrderOfRemoval {
public:
    static int orderOfRemoval(vector<int>& arr) {
        int n = arr.size();
        sort(arr.begin(), arr.end()); // Sorting the array

        int ans = 0;
        for (int i = 0; i < n; i++) {
            int temp = arr[i] * (n - i);
            ans += temp;
        }

        return ans;
    }
};

int main() {
    // Hardcoded input array
    vector<int> arr = {1, 2, 3, 4, 5};
    int n = arr.size();

    // Calling orderOfRemoval function to calculate the
    // order of removal
    int result = OrderOfRemoval::orderOfRemoval(arr);

    // Printing the result
    cout << "Order of removal: " << result << endl;

    return 0;
}
```

Let's perform a **detailed dry run** of your orderOfRemoval function using the input array:

arr = {1, 2, 3, 4, 5}

### Step-by-step Dry Run:

1. **Sort the array:** The input array {1, 2, 3, 4, 5} is already sorted, so no changes are made.

Sorted array: {1, 2, 3, 4, 5}

2. **Initialize Variables:**
  - o n = arr.size() = 5
  - o ans = 0 (This will hold the final result)
3. **Iterate and calculate the result:** For each element arr[i] in the array, the contribution of that element to the ans is calculated by multiplying arr[i] with the remaining elements (i.e., arr[i] \* (n - i)).

### Dry Run Table:

i	arr[i]	n - i	arr[i] * (n - i)	Cumulative ans
0	1	5	1 * 5 = 5	0 + 5 = 5
1	2	4	2 * 4 = 8	5 + 8 = 13
2	3	3	3 * 3 = 9	13 + 9 = 22
3	4	2	4 * 2 = 8	22 + 8 = 30
4	5	1	5 * 1 = 5	30 + 5 = 35

### Final Result:

After the loop finishes, the value of ans is 35.

So, the output of the program is:

Order of removal: 35

Order of removal: 35

## Subsets in C++

```
#include <iostream>
#include <vector>
using namespace std;

class Subsets {
public:
    vector<vector<int>> subsets(vector<int>& nums) {
        int n = nums.size();
        int totalno = (1 << n);
        vector<vector<int>> ans;

        for (int i = 0; i < totalno; i++) {
            vector<int> temp;
            for (int j = 0; j < n; j++) {
                if (checkBit(i, j)) {
                    temp.push_back(nums[j]);
                }
            }
            ans.push_back(temp);
        }

        return ans;
    }

private:
    // Helper function to check if the i-th bit in n is set
    bool checkBit(int n, int i) {
        return (n & (1 << i)) != 0;
    }
};

int main() {
    // Create an instance of the Subsets class
    Subsets solution;

    // Hardcoded input array
    vector<int> nums = {1, 2, 3}; // Example input

    // Calling subsets to generate all subsets of the array
    vector<vector<int>> subsets =
solution.subsets(nums);

    // Printing all subsets
    for (auto& subset : subsets) {
        cout << "[";
        for (size_t i = 0; i < subset.size(); i++) {
            cout << subset[i];
            if (i < subset.size() - 1) {
                cout << ", ";
            }
        }
        cout << "]" << endl;
    }

    return 0;
}
```

### Detailed Table:

i (Binary)	Subset Indexes	Subset Elements	Subset
0 (000)	None	None	[]
1 (001)	0	{1}	[1]
2 (010)	1	{2}	[2]
3 (011)	0, 1	{1, 2}	[1, 2]
4 (100)	2	{3}	[3]
5 (101)	0, 2	{1, 3}	[1, 3]
6 (110)	1, 2	{2, 3}	[2, 3]
7 (111)	0, 1, 2	{1, 2, 3}	[1, 2, 3]

### Explanation of Each Iteration:

- Iteration 1 (i = 0 / Binary 000):**
  - No bits are set, so the subset is empty: [].
- Iteration 2 (i = 1 / Binary 001):**
  - Only the least significant bit is set, so the subset includes only the element 1: [1].
- Iteration 3 (i = 2 / Binary 010):**
  - The second bit is set, so the subset includes only the element 2: [2].
- Iteration 4 (i = 3 / Binary 011):**
  - The first and second bits are set, so the subset includes the elements 1 and 2: [1, 2].
- Iteration 5 (i = 4 / Binary 100):**
  - The third bit is set, so the subset includes only the element 3: [3].
- Iteration 6 (i = 5 / Binary 101):**
  - The first and third bits are set, so the subset includes the elements 1 and 3: [1, 3].
- Iteration 7 (i = 6 / Binary 110):**
  - The second and third bits are set, so the subset includes the elements 2 and 3: [2, 3].
- Iteration 8 (i = 7 / Binary 111):**
  - All bits are set, so the subset includes all elements: [1, 2, 3].

### Final Output:

The final list of subsets is:

```
[]
[1]
[2]
[1, 2]
[3]
```



	<div>[1, 3] [2, 3] [1, 2, 3]</div>
<div>[] [1] [2] [1, 2] [3] [1, 3] [2, 3] [1, 2, 3]</div>	

## Heapsort in C++

```
#include <iostream>
using namespace std;

void heapify(int arr[], int n, int i) {
    int largest = i;
    int left = 2 * i + 1;
    int right = 2 * i + 2;

    if(left < n && arr[left] > arr[largest])
        largest = left;

    if(right < n && arr[right] > arr[largest])
        largest = right;

    if(largest != i) {
        swap(arr[i], arr[largest]);
        heapify(arr, n, largest);
    }
}

void heapSort(int arr[], int n) {
    for(int i = n / 2 - 1; i >= 0; i--)
        heapify(arr, n, i);

    for(int i = n - 1; i > 0; i--) {
        swap(arr[0], arr[i]);
        heapify(arr, i, 0);
    }
}

int main() {
    int arr[] = {12, 11, 13, 5, 6, 7};
    int n = sizeof(arr)/sizeof(arr[0]);

    heapSort(arr, n);

    cout << "Sorted array is \n";
    for(int i = 0; i < n; i++) {
        cout << arr[i] << " ";
    }
    return 0;
}
```

Step-by-Step Dry Run

### ✔ Step 1: Build Max Heap

Indices:

0: 12   1: 11   2: 13   3: 5   4: 6   5: 7

Start from i = 2 (last non-leaf node)

i	Heapify Subtree	Max-Heap after heapify
2	[13, 7]	No change
1	[11, 5, 6]	No change
0	[12, 11, 13, 5, 6, 7]	swap 12 with 13 → heapify(2) swaps 12 with 7 → Done

✦ Max Heap Built:

[13, 11, 7, 5, 6, 12]

### ✔ Step 2: Extract Elements & Heapify

We now swap root with last element and reduce heap size (n--) after each step:

i	Swap arr[0] & arr[i]	Array after swap	Heapify to max heap
5	swap(13, 12)	[12, 11, 7, 5, 6, 13]	→ heapify → [11, 12, 7...] → [11, 6, 7, 5, 12, 13]
4	swap(11, 6)	[6, 5, 7, 11, 12, 13]	→ heapify → [7, 5, 6...]
3	swap(7, 5)	[5, 6, 7, 11, 12, 13]	→ heapify → [6, 5, ...]
2	swap(6, 5)	[5, 6, 7, 11, 12, 13]	→ heapify → [5, 6, ...] (already heap)
1	swap(5, 5)	Done	

✔ Final Output  
Sorted array is  
5 6 7 11 12 13

Sorted array is

5 6 7 11 12 13

Insertion Sort in C++

```
#include <iostream>
using namespace std;

// void insertionSort(int arr[], int n) {
//   for (int i = 1; i < n; i++)
//   {
//     int key=arr[i];
//     int j=i-1;
//     while(j>=0 && arr[j]>key){
//       arr[j+1]=arr[j];
//       j=j-1;
//     }
//     arr[j + 1] = key;
//   }
// }

void insertionSort(int arr[], int n) {
  for (int i = 1; i < n; i++)
  {
    int j=i;
    while(j>0 && arr[j-1]>arr[j]){
      swap(arr[j],arr[j-1]);
      j--;
    }
  }
}

int main() {
  int arr[] = {12, 11, 13, 5, 6};
  int n = sizeof(arr)/sizeof(arr[0]);
  insertionSort(arr, n);
  cout << "Sorted array: \n";
  for(int i = 0; i < n; i++) {
    cout << arr[i] << " ";
  }
  return 0;
}
```

Input:  
arr[] = {12, 11, 13, 5, 6}

Step-by-Step Dry Run (Tabular Form)

i (loop index)	j (inner loop)	Comparison	Action	Array State
1	1	11 < 12	swap(11, 12)	[11, 12, 13, 5, 6]
2	2	13 < 12? ✗	no swap	[11, 12, 13, 5, 6]
3	3	5 < 13 → swap		[11, 12, 5, 13, 6]
	2	5 < 12 → swap		[11, 5, 12, 13, 6]
	1	5 < 11 → swap		[5, 11, 12, 13, 6]
4	4	6 < 13 → swap		[5, 11, 12, 6, 13]
	3	6 < 12 → swap		[5, 11, 6, 12, 13]
	2	6 < 11 → swap		[5, 6, 11, 12, 13]

✔ Final Output:  
Sorted array:  
5 6 11 12 13

5 6 11 12 13

## MergeSort in C++

```
#include<bits/stdc++.h>
using namespace std;

void merge(int arr[], int l, int m, int r) {
    int n1=m-l+1;
    int n2=r-m;
    int left[n1];
    int right[n2];

    for(int i=0;i<n1;i++){
        left[i]=arr[l+i];
    }

    for(int j=0;j<n2;j++){
        right[j]=arr[m+1+j];
    }
    int i = 0, j = 0, k = l;

    while(i<n1 && j<n2){
        if(left[i]<=right[j]){
            arr[k]=left[i];
            i++;
        }else{
            arr[k]=right[j];
            j++;
        }
        k++;
    }

    while (i < n1) {
        arr[k]=left[i];
        i++;
        k++;
    }

    while(j<n2){
        arr[k]=right[j];
        j++;
        k++;
    }
}

void mergeSort(int arr[], int l, int r) {
    if (l >= r) {
        return;
    }
    int m = l + (r - l) / 2;
    mergeSort(arr, l, m);
    mergeSort(arr, m + 1, r);
    merge(arr, l, m, r);
}


int main() {
    /* Enter your code here. Read input from STDIN.
    Print output to STDOUT */

    int n;
    cin >> n;
    int arr[n];
    for (int i = 0; i < n; i++)
    {
```

Example Input:

n = 6

arr = {38, 27, 43, 3, 9, 82}

 Merge Sort Recursive Dry Run (Call Stack Overview)

Call Level	Function Call	Action	Array State
1	mergeSort(0, 5)	Split at 2	
2	mergeSort(0, 2)	Split at 1	
3	mergeSort(0, 1)	Split at 0	
4	mergeSort(0, 0)	Base case	[38]
4	mergeSort(1, 1)	Base case	[27]
3	merge(0, 0, 1)	Merge [38] & [27] → [27, 38]	[27, 38, 43, 3, 9, 82]
2	mergeSort(2, 2)	Base case	[43]
2	merge(0, 1, 2)	Merge [27, 38] & [43]	[27, 38, 43, 3, 9, 82]
1	mergeSort(3, 5)	Split at 4	
2	mergeSort(3, 4)	Split at 3	
3	mergeSort(3, 3)	Base case	[3]
3	mergeSort(4, 4)	Base case	[9]
2	merge(3, 3, 4)	Merge [3] & [9] → [3, 9]	[27, 38, 43, 3, 9, 82]
1	mergeSort(5, 5)	Base case	[82]
1	merge(3, 4, 5)	Merge [3, 9] & [82]	[27, 38, 43, 3, 9, 82]
0	merge(0, 2, 5)	Merge [27, 38, 43] & [3, 9, 82] →	

<pre>        cin &gt;&gt; arr[i];     }      mergeSort(arr,0,n-1);      for (int i = 0; i &lt; n; i++)     {         cout &lt;&lt; arr[i] &lt;&lt; " ";     }     cout &lt;&lt; endl;     return 0; }</pre>	<table><tr><td></td><td></td><td>[3, 9, 27, 38, 43, 82]</td><td></td></tr></table> <p>✔ Final Output: 3 9 27 38 43 82</p>			[3, 9, 27, 38, 43, 82]	
		[3, 9, 27, 38, 43, 82]			
3 9 27 38 43 82					

## Quick Sort in C++

```
#include <iostream>
using namespace std;

int medianOfThree(int arr[],
int l, int h) {
    int mid = l + (h - l) / 2;
    if (arr[l] > arr[mid])
        swap(arr[l], arr[mid]);
    if (arr[l] > arr[h])
        swap(arr[l], arr[h]);
    if (arr[mid] > arr[h])
        swap(arr[mid], arr[h]);
    return mid;
}
```

```
int partition(int arr[], int l,
int h) {
    int medianIndex =
medianOfThree(arr, l, h);
    swap(arr[l],
arr[medianIndex]); // Move
median to start as pivot
```

```
    int pivot = arr[l];
    int left = l + 1;
    int right = h;

    while (left <= right) {
        while (left <= right &&
arr[left] < pivot) left++;
        while (left <= right &&
arr[right] > pivot) right--;
```

```
        if (left <= right) {
            swap(arr[left],
arr[right]);
            left++;
            right--;
        }
    }
}
```

```
    swap(arr[l], arr[right]); //
Put pivot in correct place
    return right;
}
```

```
void rquicksort(int arr[], int
l, int h) {
    if (l < h) {
        int pivot = partition(arr,
l, h);
        rquicksort(arr, l, pivot -
1);
        rquicksort(arr, pivot + 1,
h);
    }
}
```

```
int main() {
    int arr[] = {24, 97, 40, 67,
88, 85, 15};
```

Here's a **dry run** of your Quicksort code in **tabular form** for the input:


```
int arr[] = {24, 97, 40, 67, 88, 85, 15};
```

We'll trace:

- Recursive calls
- Chosen pivot (via median-of-three)
- Partitioning process
- Array state after each step

### 🔄 Step-by-Step Dry Run Table:

Step	Subarray (l to h)	Median-of-Three	Pivot	Final Pivot Index	Array After Partition
1	arr[0..6] = {24,97,40,67,88,85,15}	40 (mid=2)	40	2	{24,15,40,67,88,85,97}
2	arr[0..1] = {24,15}	15 (mid=0)	15	0	{15,24,40,...}
3	arr[1..1] = {24}	-	-	-	(Base case, already sorted)
4	arr[3..6] = {67,88,85,97}	85 (mid=4)	85	4	{...,67,85,88,97}
5	arr[3..3] = {67}	-	-	-	(Base case)
6	arr[5..6] = {88,97}	88 (mid=5)	88	5	{...,67,85,88,97} (already sorted)

<pre>int n = sizeof(arr) / sizeof(arr[0]);  rquicksort(arr, 0, n - 1);  cout &lt;&lt; "Sorted array: "; for (int i = 0; i &lt; n; i++) {     cout &lt;&lt; arr[i] &lt;&lt; " "; } cout &lt;&lt; endl;  return 0; }</pre>	<p> <b>Final Sorted Array:</b></p> <p>{15, 24, 40, 67, 85, 88, 97}</p>
15, 24, 40, 67, 85, 88, 97	

---

**Input:**

11 12 22 25 64

### Selection Sort Dry Run Table

✓ **Final Output:**

Sorted array:  
11 12 22 25 64