

SINCE 1935

VARUNA[®]
ELECTRIC

AGRICULTURE

BOREWELL SUBMERSIBLE
PUMP SERIES



H A R B O O N D M E I N JOSH



Our Certifications & USP's



5" BOREWELL SUBMERSIBLE PUMP SETS



125 mm (5")
Submersible Pump Sets

125mm (5") with Water Filled Motor

DESCRIPTION

Varuna brand makes reliable, efficient and durable Submersible pump sets with best quality as per IS 9283:2024
Following are the salient features of Submersible pump sets with Water filled Motor.

SALIENT FEATURES

- › Dynamically balanced rotating parts to ensure minimum noise and vibration-free operation.
- › Accurately machined on CNC machine to get reliable performance and long life.
- › Pump sets perform in wide voltage band.
- › Starts easily at low voltage.
- › Metal inserted with sand guard to improve life in sandy bore.
- › Manufactured using a much sophisticated process hence ensuring more reliability in performance.
- › Heavy Duty Carbon thrust bearing with German Technology.
- › Products are available with NRV which reduces the thrust load of back pressure.
- › Motors are designed using multi layer PVC insulated wire for better reliability and easy repairing at remote location.

Material Of Construction

MOTOR DETAILS

Stator	: Insulated varnish using vacuum impregnation method
Rotor	: Copper Rotor
Motor Body	: Stainless Steel
Thrust Bearing	: Self aligned carbon Vs. Stainless steel thrust bearing that withstands high axial thrust load in water lubrication
Winding	: Multi Layer PVC insulated wire
Cable Sealing Arrangement	: Protecting device to prevent foreign particles from entering into the motor arrangement.
Journal Bearings	: Gun Metal Bush with 2% nickel and additional centrifugal molding process to avoid chance of warm out
Pressure Diaphragm	: Sufficient size to contain expansion of water inside the Diaphragm motor and avoid the defeat of cooling water

PUMP DETAILS

Bowl	: Cast iron / Stainless Steel
Impeller	: Stainless Steel Cast / SSSM
Shaft	: Stainless Steel
Wearing Rings	: High Quality Abrasion resistant Stainless Steel
Suction Casing	: Heavy Duty casting material to get proper grip on motor as well as to provide path for suction of water.
Non Return Valve	: To reduce the thrust generated due to back pressure of the long pipe line when pump set is switched off hence leading to increase in the life of the pump

Applications



SPRINKLER
IRRIGATION



DRIP IRRIGATION
SYSTEM



AGRICULTURE
WATER SUPPLY



INDUSTRIAL
APPLICATION



CIVIL & DOMESTIC
WATER SUPPLY



FIRE FIGHTING
SYSTEM

V5

SUITABLE FOR 131 mm BOREWELL OR ABOVE (Min.Bore Dia. 131mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 200-240 VOLTS SINGLE PHASE / 380-415 VOLTS THREE PHASE,
50 Hz. A.C. SUPPLY. Maximum Motor OD :- 122 mm & Pump O.D. :- 127 mm

OUTLET SIZE :- 75mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM					
	kW	H.P.			0	225	275	475	570	650
VS 51	2.2	3.0	3		28	25	23	20	17	13
VS 51	3.0	4.0	3		28	25	23	20	17	13
VS 51	3.7	5.0	4		38	34	31	27	22	18
VS 51	4.5	6.0	5		47	42	38	33	27	22
VS 51	5.5	7.5	6		56	50	46	40	33	27
VS 51	7.5	10.0	8		75	67	61	53	44	35

Note : Single Phase Motors are available up to 7.5 HP

6" BOREWELL SUBMERSIBLE PUMP SETS



150 mm (6")
Submersible Pump Sets

150 mm (6") with Water Filled Motor

DESCRIPTION

Varuna brand makes reliable, efficient and durable Submersible pump sets of best quality as per IS 8034: 2018. Following are the salient features of Submersible pump sets with Water filled Motor.

SALIENT FEATURES

- Motor and Pump come in a single unit for easy installation.
- Pump sets perform in wider voltage band.
- Pump sets also available in single phase and phase to phase.
- Heavy Duty Carbon thrust bearing with German Technology.
- Superior performance as compared to competitors.
- CI bowl makes design strong and easy to repair.
- Metal Inserted with sand guard to increase life in sandy bore.
- Product available up to 30 HP.

Material Of Construction

MOTOR DETAILS

Stator	: Insulated varnish using vacuum impregnation method.
Rotor	: Copper Rotor.
Moto Body	: Stainless Steel.
Thrust Bearing	: Self aligned Carbon Vs. Stainless steel thrust bearing that withstands high axial thrust load in water lubrication.
Winding	: Multi Layer PVC insulated wire.
Cable Sealing Arrangement	: Protecting device to prevent foreign particles from entering into the motor arrangement.
Journal Bearings	: Gun Metal Bush with 2% nickel and additional centrifugal molding process to avoid chance of warm out.
Pressure Diaphragm	: Sufficient size to contain expansion of water inside the motor and avoid the defeat of cooling water.

PUMP DETAILS

Bowl	: Cast iron / Stainless Steel.
Impeller	: Stainless Steel Cast / SSSM.
Shaft	: Stainless Steel.
Wearing Rings	: High Quality Abrasion resistant stainless Steel.
Suction Casing	: Heavy Dusty casting material to get proper grip on motor as well as Provide path for suction of water. SS strainer is also provided to protect against foreign particles.
Non Return Valve	: To reduce the thrust generated due to back pressure of the long pipe line when pump set is switched off hence leading to increase in the life of the pump.

Applications



SPRINKLER
IRRIGATION



DRIP IRRIGATION
SYSTEM



AGRICULTURE
WATER SUPPLY



INDUSTRIAL
APPLICATION



CIVIL & DOMESTIC
WATER SUPPLY



FIRE FIGHTING
SYSTEM

V6 Slim

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 200-240 VOLTS SINGLE PHASE / 380-415 VOLTS THREE PHASE, 50 Hz. A.C. Maximum Motor OD :- 122mm & Pump OD :- 142mm

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM					
	kW	H.P.			0	50	90	110	120	140
VSH:61BN (RSS)	2.2	3.0	8		85	73	68	62	56	50

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	95	112	120	135	150	170	190
VSH:62N (RSS)	2.2	3.0	6		65	58	52	50	47	41	35	25

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	140	165	185	200	230	250	270
VSH:64N (RSS)	2.2	3.0	5		59	53	50	47	44	37	33	28
VSH:64N (RSS)	3.7	5.0	8		94	85	80	75	70	59	53	45

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	130	175	215	220	245	280	325
VSH:64BN (RSS)	3.7	5.0	6		73	64	60	55	54	50	42	30

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	235	290	300	320	350	370	390
VSH:65N (RSS)	3.0	4.0	4		52	44	40	38	36	32	28	25
VSH:65N (RSS)	3.7	5.0	5		65	55	50	48	45	40	35	31
VSH:65N (RSS)	5.5	7.5	8		104	88	80	77	72	64	56	50

Note : Single Phase Motors are available up to 7.5 HP

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY. Maximum Motor OD :- 142 mm & Pump OD. :- 142 mm

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM					
	kW	H.P.			0	50	90	110	120	140
VSH:61N	2.2	3.0	8		85	73	68	62	56	50
VSH:61N	3.0	4.0	10		106	93	85	80	74	65
VSH:61N	3.7	5.0	13		138	108	96	88	78	71
VSH:61N	3.7	5.0	14		148	116	103	95	84	76
VSH:61N	4.5	6.0	16		170	150	140	128	120	104
VSH:61N	5.5	7.5	18		191	169	158	144	135	117
VSH:61N	5.5	7.5	20		212	190	175	162	152	134
VSH:61N	7.5	10.0	24		254	228	210	195	183	162
VSH:61N	9.3	12.5	30		318	285	263	243	228	201

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	95	112	120	135	150	170	190
VSH:62N	2.2	3.0	6		65	58	52	50	47	41	35	25
VSH:62N	3.0	4.0	8		87	77	69	67	63	55	47	33
VSH:62N	3.7	5.0	10		108	96	87	83	78	68	58	42
VSH:62N	3.7	5.0	12		130	115	105	100	94	83	70	50
VSH:62N	4.5	6.0	12		130	115	105	100	94	83	70	50
VSH:62N	4.5	6.0	14		152	134	123	117	110	97	82	58
VSH:62N	5.5	7.5	14		152	134	123	117	110	97	82	58
VSH:62N	5.5	7.5	16		173	153	140	133	125	111	93	67
VSH:62N	7.5	10.0	18		195	173	158	150	141	125	105	75
VSH:62N	7.5	10.0	20		217	192	175	167	157	138	117	83
VSH:62N	9.3	12.5	24		260	230	210	200	188	166	140	100
VSH:62N	9.3	12.5	28		303	268	245	233	219	194	163	117
VSH:62N	11.0	15.0	30		325	288	263	250	235	208	175	125

Note : Single Phase Motors are available up to 7.5 HP

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	140	165	185	200	230	250	270
VSH:64N	2.2	3.0	4		47	42	40	38	35	30	26	22
VSH:64N	2.2	3.0	5		59	53	50	47	44	37	33	28
VSH:64N	3.0	4.0	6		71	64	60	56	53	44	40	34
VSH:64N	3.7	5.0	8		94	85	80	75	70	59	53	45
VSH:64N	4.5	6.0	10		118	106	100	94	88	74	66	56
VSH:64N	5.5	7.5	12		142	127	120	113	106	89	79	67
VSH:64N	7.5	10.0	14		165	148	140	132	123	104	92	78
VSH:64N	7.5	10.0	16		189	170	160	150	141	118	106	90
VSH:64N	9.3	12.5	18		213	191	190	169	159	133	119	101
VSH:64N	9.3	12.5	20		236	212	200	188	176	148	132	112
VSH:64N	11.0	15.0	24		283	254	240	226	211	178	158	134

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	130	175	215	220	245	280	325
VSH:64BN	2.2	3.0	4		48	43	40	37	36	33	28	20
VSH:64BN	3.7	5.0	6		73	64	60	55	54	50	42	30
VSH:64BN	4.5	6.0	8		97	85	80	73	72	67	56	40
VSH:64BN	5.5	7.5	10		122	107	100	92	90	83	70	50
VSH:64BN	7.5	10.0	12		146	128	120	110	108	100	84	60
VSH:64BN	7.5	10.0	13		158	139	130	119	117	108	91	65
VSH:64BN	9.3	12.5	15		183	160	150	138	135	125	105	75
VSH:64BN	9.3	12.5	16		195	171	160	147	144	133	112	80
VSH:64BN	11.0	15.0	20		243	213	200	183	180	167	140	100
VSH:64BN	15.0	20.0	25		304	267	250	229	225	208	175	125

Note : Single Phase Motors are available up to 7.5 HP

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	235	290	300	320	350	370	390
VSH:65N	3.7	5.0	5		65	55	50	48	45	40	35	31
VSH:65N	4.5	6.0	6		78	66	60	58	54	48	42	37
VSH:65N	5.5	7.5	8		104	88	80	77	72	64	56	50
VSH:65N	7.5	10.0	10		130	110	100	96	90	80	70	62
VSH:65N	9.3	12.5	11		143	121	110	106	99	88	77	68
VSH:65N	9.3	12.5	12		156	132	120	115	108	96	84	74
VSH:65N	9.3	12.5	13		169	143	130	125	117	104	91	81
VSH:65N	11.0	15.0	14		182	154	140	134	126	112	98	87
VSH:65N	11.0	15.0	15		195	165	150	144	135	120	105	93
VSH:65N	13.0	17.5	16		208	176	160	154	144	128	112	99
VSH:65N	13.0	17.5	17		221	187	170	163	153	136	119	105
VSH:65N	15.0	20.0	20		260	220	200	192	180	160	140	124
VSH:65N	18.5	25.0	25		325	275	250	240	225	200	175	155
VSH:65N	22.5	30.0	30		390	330	300	288	270	240	210	186

Note : Single Phase Motors are available up to 7.5 HP

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 142 mm & Pump OD. :- 142 mm

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	kW	H.P.			100	105	111	118	126	142	158	179	200
VSH:61N HF	2.20	3.00	8		86	80	77	69	67	63	55	47	33
VSH:61N HF	3.00	4.00	10		108	100	96	87	83	78	68	58	42
VSH:61N HF	3.70	5.00	12		130	120	115	105	100	94	83	70	50
VSH:61N HF	3.70	5.00	14		151	140	134	123	117	110	97	82	58
VSH:61N HF	4.50	6.00	16		173	160	153	140	133	125	111	93	67
VSH:61N HF	5.50	7.50	18		194	180	173	158	150	141	125	105	75
VSH:61N HF	5.50	7.50	20		216	200	192	175	167	157	138	117	83
VSH:61N HF	7.50	10.00	24		259	240	230	210	200	188	166	140	100
VSH:61N HF	9.30	12.50	30		324	300	288	263	250	235	208	175	125

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	kW	H.P.			107	132	137	160	180	195	225	245	264
VSH:62N HF	2.20	3.00	6		73	65	63	59	56	53	44	40	34
VSH:62N HF	3.00	4.00	8		97	87	84	78	75	70	59	53	45
VSH:62N HF	3.70	5.00	10		122	109	105	98	94	88	74	66	56
VSH:62N HF	4.00	6.00	12		146	131	126	117	113	106	89	79	67
VSH:62N HF	5.50	7.50	14		171	153	148	137	132	123	104	92	78
VSH:62N HF	5.50	7.50	16		195	174	169	157	150	141	118	106	90
VSH:62N HF	7.50	10.00	18		219	196	190	176	169	158	133	119	101
VSH:62N HF	7.50	10.00	20		244	218	211	196	188	176	148	132	112
VSH:62N HF	9.30	12.50	24		292	262	253	235	226	211	178	158	134
VSH:62N HF	11.00	15.00	28		341	305	295	274	263	246	207	185	157
VSH:62N HF	13.00	17.50	30		365	327	316	294	282	264	222	198	168
VSH:62N HF	13.00	17.50	32		390	349	337	313	301	282	237	211	179

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	KW	H.P.			147	179	189	210	226	231	257	294	341
VSH:64N HF	2.20	3.00	4		49	48	43	40	37	36	33	28	20
VSH:64N HF	3.00	4.00	6		73	72	64	60	55	54	50	42	30
VSH:64N HF	3.70	5.00	8		98	96	85	80	73	72	67	56	40
VSH:64N HF	4.00	6.00	10		122	120	107	96	92	90	83	70	50
VSH:64N HF	5.50	7.50	12		146	144	128	120	110	108	100	84	60
VSH:64N HF	7.50	10.00	15		183	180	160	150	138	135	125	105	75
VSH:64N HF	7.50	10.00	16		195	192	171	160	147	144	133	112	80
VSH:64N HF	9.30	12.50	20		244	240	213	200	183	180	167	140	100
VSH:64N HF	11.00	15.00	22		268	264	235	220	202	198	183	154	110
VSH:64N HF	13.00	17.50	25		305	300	267	250	229	225	208	175	125
VSH:64N HF	15.00	20.00	32		390	384	341	320	294	288	267	224	160

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			119	223	276	285	304	333	352	371
VSH:64BN HF	3.00	4.00	5		60	55	50	48	45	40	35	31
VSH:64BN HF	3.70	5.00	6		72	66	60	58	54	48	42	37
VSH:64BN HF	4.00	6.00	8		96	88	80	77	72	64	56	50
VSH:64BN HF	5.50	7.50	10		120	110	100	96	90	80	70	62
VSH:64BN HF	7.50	10.00	12		144	132	120	115	108	96	84	74
VSH:64BN HF	7.50	10.00	13		156	143	130	125	117	104	91	81
VSH:64BN HF	9.30	12.50	15		180	165	150	144	135	120	105	93
VSH:64BN HF	11.00	15.00	16		192	176	160	154	144	128	112	99
VSH:64BN HF	13.00	17.50	20		240	220	200	192	180	160	140	124
VSH:64BN HF	15.00	20.00	25		300	275	250	240	225	200	175	155

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	KW	H.P.			232	254	287	320	333	355	389	410	433
VSH:65N HF	3.7	5.0	5		62	58	54	50	46	43	38	34	30
VSH:65N HF	4.5	6.0	6		74	70	65	60	55	52	46	41	36
VSH:65N HF	5.5	7.5	8		99	93	86	80	74	69	61	54	48
VSH:65N HF	7.5	10.0	10		124	116	108	100	92	86	76	68	60
VSH:65N HF	9.30	12.50	11		136	128	119	110	101	95	84	75	66
VSH:65N HF	9.30	12.50	12		149	139	130	120	110	103	91	82	72
VSH:65N HF	9.30	12.50	13		161	151	140	130	120	112	99	88	78
VSH:65N HF	11.0	15.0	14		174	162	151	140	129	120	106	95	84
VSH:65N HF	11.0	15.0	15		186	174	162	150	138	129	114	102	90
VSH:65N HF	13.0	17.5	16		198	186	173	160	147	138	122	109	96
VSH:65N HF	13.0	17.5	17		211	197	184	170	156	146	129	116	102
VSH:65N HF	15.0	20.0	20		248	232	216	200	184	172	152	136	120
VSH:65N HF	18.5	25.0	25		310	290	270	250	230	215	190	170	150
VSH:65N HF	22.5	30.0	30		372	348	324	300	276	258	228	204	180

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)
 APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
 Maximum Motor OD :- 142 mm & Pump OD. :- 147 mm

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	50	75	96	121	145	165	178	195	206
VSS 50H	2.2	3.0	6		94	90	84	78	66	60	48	36	24	12
VSS 50H	3.0	4.0	8		125	120	112	104	88	80	64	48	32	16
VSS 50H	3.7	5.0	10		156	150	140	130	110	100	80	60	40	20
VSS 50H	4.5	6.0	12		187	180	168	156	132	120	96	72	48	24
VSS 50H	5.5	7.5	15		234	225	210	195	165	150	120	90	60	30
VSS 50H	7.5	10.0	20		312	300	280	260	220	200	160	120	80	40
VSS 50H	9.3	12.5	24		374	360	336	312	264	240	192	144	96	48

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	90	115	135	150	180	200	230	240	250
VSS 60H	2.2	3.0	5		78	75	68	64	58	51	41	30	21	15
VSS 60H	3.0	4.0	7		109	105	95	90	81	71	57	42	29	21
VSS 60H	3.7	5.0	8		125	120	109	102	93	82	66	48	34	24
VSS 60H	4.5	6.0	10		156	150	136	128	116	102	82	60	42	30
VSS 60H	5.5	7.5	12		187	180	163	153	139	123	99	72	51	36
VSS 60H	5.5	7.5	13		203	195	177	166	151	133	107	78	55	39
VSS 60H	7.5	10.0	16		250	240	218	205	186	163	131	96	67	48
VSS 60H	9.3	12.5	20		312	300	272	256	232	204	164	120	84	60
VSS 60H	11.0	15.0	23		359	345	313	294	267	235	189	138	97	69
VSS 60H	11.0	15.0	24		374	360	326	307	278	245	197	144	101	72
VSS 60H	13.0	17.5	27		421	405	367	346	313	275	221	162	113	81
VSS 60H	15.0	20.0	30		468	450	408	384	348	306	246	180	126	90

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 142 mm & Pump OD. :- 147 mm

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	130	145	175	195	210	240	265	290	300
VSS 80H	2.2	3.0	4		62	58	55	52	48	45	38	32	24	18
VSS 80H	3.0	4.0	5		78	72	69	65	60	56	48	40	30	22
VSS 80H	3.7	5.0	6		93	87	82	78	72	68	57	48	36	27
VSS 80H	4.5	6.0	7		109	102	97	91	84	78	67	56	42	32
VSS 80H	4.5	6.0	8		124	116	110	104	96	90	76	64	48	36
VSS 80H	5.5	7.5	10		155	145	138	130	120	112	95	80	60	45
VSS 80H	7.5	10.0	12		186	173	166	156	144	135	114	96	72	53
VSS 80H	7.5	10.0	13		202	188	179	169	156	146	124	104	78	58
VSS 80H	9.3	12.5	15		232	218	206	195	180	169	142	120	90	68
VSS 80H	11.0	15.0	18		279	261	248	234	216	202	171	144	108	81
VSS 80H	11.0	15.0	19		294	276	261	247	228	214	180	152	114	86
VSS 80H	13.0	17.5	21		326	305	290	273	252	235	200	168	126	95
VSS 80H	13.0	17.5	22		341	319	302	286	264	248	209	176	132	99
VSS 80H	15.0	20.0	24		372	348	331	312	288	269	228	192	144	108
VSS 80H	15.0	20.0	25		388	362	344	325	300	281	238	200	150	112
VSS 80H	18.5	25.0	30		465	435	412	390	360	338	285	240	180	135

Note : Single Phase Motors are available up to 7.5 HP

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	KW	H.P.			0	150	200	250	270	310	360	380	400
VSS 100H	2.2	3.0	3		50	46	41	37	35	29	23	19	16
VSS 100H	3.0	4.0	4		67	61	55	49	47	39	31	25	21
VSS 100H	3.7	5.0	5		83	77	68	62	58	48	38	32	27
VSS 100H	4.5	6.0	6		100	92	82	74	70	58	46	38	32
VSS 100H	5.5	7.5	8		133	123	109	99	93	77	61	51	43
VSS 100H	7.5	10.0	10		167	153	137	123	117	97	77	63	53
VSS 100H	9.3	12.5	12		200	184	164	148	140	116	92	76	64
VSS 100H	11.0	15.0	15		250	230	205	185	175	145	115	95	80
VSS 100H	13.0	17.5	17		284	260	233	209	199	165	131	107	90
VSS 100H	13.0	17.5	18		300	276	246	222	210	174	138	114	96
VSS 100H	15.0	20.0	20		333	307	273	247	233	193	153	127	107
VSS 100H	18.5	25.0	25		417	383	342	308	292	242	192	158	133
VSS 100H	22.5	30.0	30		500	460	410	370	350	290	230	190	160

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	KW	H.P.			0	210	250	300	350	375	415	430	465
VSS 125H	3.0	4.0	3		48	45	42	38	34	30	24	20	18
VSS 125H	3.7	5.0	4		64	60	56	51	45	40	32	27	24
VSS 125H	4.5	6.0	5		80	75	70	63	57	50	40	33	30
VSS 125H	5.5	7.5	6		96	90	84	76	68	60	48	40	36
VSS 125H	7.5	10.0	8		128	120	112	101	91	80	64	53	48
VSS 125H	9.3	12.5	10		160	150	140	127	113	100	80	67	60
VSS 125H	11.0	15.0	12		192	180	168	152	136	120	96	80	72
VSS 125H	13.0	17.5	14		224	210	196	177	159	140	112	93	84
VSS 125H	15.0	20.0	16		256	240	224	203	181	160	128	107	96
VSS 125H	18.5	25.0	20		320	300	280	253	227	200	160	133	120
VSS 125H	22.5	30.0	24		384	360	336	304	272	240	192	160	144

Note : Single Phase Motors are available up to 7.5 HP

OUTLET SIZE :- 65mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	215	290	360	410	470	535	580	640	650
VSS 150H	2.2	3.0	2		32	30	28	26	24	20	16	12	8	5
VSS 150H	3.7	5.0	3		48	45	42	39	36	31	25	19	13	7
VSS 150H	4.5	6.0	4		64	60	56	52	48	41	33	25	17	10
VSS 150H	5.5	7.5	5		80	75	70	65	60	51	41	31	21	12
VSS 150H	7.5	10.0	7		112	105	98	91	84	71	57	43	29	17
VSS 150H	9.3	12.5	8		128	120	112	104	96	82	66	50	34	19
VSS 150H	11.0	15.0	10		160	150	140	130	120	102	82	62	42	24
VSS 150H	13.0	17.5	12		192	180	168	156	144	122	98	74	50	29
VSS 150H	15.0	20.0	13		208	195	182	169	156	133	107	81	55	31
VSS 150H	18.5	25.0	17		272	255	238	221	204	173	139	105	71	41
VSS 150H	22.5	30.0	20		320	300	280	260	240	204	164	124	84	48

OUTLET SIZE :- 65mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	135	245	395	530	585	690	770	835	880
VSS 200H	3.0	4.0	2		32	30	28	26	22	21	15	11	8	4
VSS 200H	4.5	6.0	3		48	45	42	39	33	32	23	17	12	6
VSS 200H	5.5	7.5	4		64	60	56	52	44	42	30	22	16	8
VSS 200H	7.5	10.0	5		80	75	70	65	55	53	38	28	20	10
VSS 200H	9.3	12.5	6		96	90	84	78	66	63	45	33	24	12
VSS 200H	11.0	15.0	8		128	120	112	104	88	84	60	44	32	16
VSS 200H	13.0	17.5	9		144	135	126	117	99	95	68	50	36	18
VSS 200H	15.0	20.0	10		160	150	140	130	110	105	75	55	40	20
VSS 200H	18.5	25.0	13		208	195	182	169	143	137	98	72	52	26
VSS 200H	22.5	30.0	15		240	225	210	195	165	158	113	83	60	30

Note : Single Phase Motors are available up to 7.5 HP

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 142 mm & Pump OD. :- 142 mm

OUTLET SIZE :- 65mm (ON DEMAND CAN PROVIDE 75mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	335	410	420	475	550	620	652
VS 60N	2.2	3.0	3		29	24	22	21	20	18	15	14
VS 60N	3.0	4.0	4		39	32	30	29	27	24	21	19
VS 60N	3.7	5.0	5		49	39	37	36	34	30	26	23
VS 60N	4.5	6.0	6		59	47	44	44	41	36	31	28
VS 60N	5.5	7.5	7		68	55	52	51	47	42	36	32
VS 60N	5.5	7.5	8		78	63	59	58	54	48	41	37
VS 60N	7.5	10.0	10		98	79	74	73	68	60	51	46
VS 60N	9.3	12.5	12		117	95	89	87	81	72	62	56
VS 60N	11.0	15.0	15		146	118	111	109	101	90	77	69
VS 60N	15.0	20.0	20		195	158	148	145	135	120	103	93

OUTLET SIZE :- 75mm (ON DEMAND CAN PROVIDE 65mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	350	420	480	505	550	600	680	770	860
VS 61N	3.0	4.0	3		34	29	28	26	25	24	22	19	15	10
VS 61N	3.7	5.0	4		45	39	37	35	34	32	29	25	20	13
VS 61N	4.5	6.0	5		56	48	47	44	43	40	36	31	25	16
VS 61N	5.5	7.5	6		68	58	56	53	51	48	44	38	30	20
VS 61N	7.5	10.0	7		79	68	65	61	60	56	51	44	35	23
VS 61N	7.5	10.0	8		90	77	75	70	68	64	58	50	40	26
VS 61N	9.3	12.5	9		101	87	84	79	77	72	65	56	45	29
VS 61N	9.3	12.5	10		113	97	93	88	85	80	73	63	50	33
VS 61N	11.0	15.0	11		124	106	103	96	94	88	80	69	55	36
VS 61N	11.0	15.0	12		135	116	112	105	102	96	87	75	60	39
VS 61N	13.0	17.5	14		158	135	131	123	119	112	102	88	70	46
VS 61N	15.0	20.0	16		180	155	149	140	136	128	116	100	80	52
VS 61N	18.5	25.0	20		225	193	187	175	170	160	145	125	100	65

Note : Single Phase Motors are available up to 7.5 HP

OUTLET SIZE :- 75mm (ON DEMAND CAN PROVIDE 65mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.			0	430	450	480	580	650	750	820	880	950
VS 63N	3.7	5.0	3		36	32	29	27	26	24	20	17	13	11
VS 63N	4.5	6.0	4		48	43	38	36	34	32	26	22	18	14
VS 63N	5.5	7.5	5		60	54	48	45	43	40	33	28	22	18
VS 63N	7.5	10.0	6		72	65	58	54	52	48	40	34	26	22
VS 63N	9.3	12.5	7		84	76	67	63	60	56	46	39	31	25
VS 63N	9.3	12.5	8		96	86	77	72	69	64	53	45	35	29
VS 63N	11.0	15.0	10		120	108	96	90	86	80	66	56	44	36
VS 63N	13.0	17.5	11		132	119	106	99	95	88	73	62	48	40
VS 63N	15.0	20.0	12		144	130	115	108	103	96	79	67	53	43

OUTLET SIZE :- 75 mm (ON DEMAND CAN PROVIDE 100mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	530	660	710	850	930	1090	1255
VS 64N	3.7	5.0	2		24	20	19	18	17	16	14	10
VS 64N	4.5	6.0	3		36	30	27	26	25	24	21	15
VS 64N	5.5	7.5	4		48	40	37	35	33	32	27	21
VS 64N	7.5	10.0	5		60	50	46	44	41	40	34	26
VS 64N	9.3	12.5	6		72	60	56	53	50	48	41	32
VS 64N	9.3	12.5	7		84	70	65	61	58	56	47	37
VS 64N	11.0	15.0	8		96	80	74	70	66	64	54	42
VS 64N	13.0	17.5	9		108	90	83	79	74	72	61	47
VS 64N	15.0	20.0	10		120	100	93	88	83	80	68	53

Note : Single Phase Motors are available up to 7.5 HP

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 142 mm & Pump OD. :- 144 mm

OUTLET SIZE :- 75 mm (ON DEMAND CAN PROVIDE 100mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	720	790	840	890	930	1050	1210
VS 65N	4.5	6.0	2		26	19	18	17	16	15	14	10
VS 65N	5.5	7.5	3		39	28	27	26	25	24	21	15
VS 65N	7.5	10.0	4		52	37	36	35	33	32	28	20
VS 65N	9.3	12.5	5		65	47	45	43	42	40	35	25
VS 65N	11.0	15.0	6		78	56	54	52	50	48	42	30
VS 65N	11.0	15.0	7		91	65	63	61	58	56	49	35
VS 65N	13.0	17.5	7		91	65	63	61	58	56	49	35
VS 65N	15.0	20.0	8		104	75	72	69	67	64	56	40

V7

SUITABLE FOR 175mm BOREWELL OR ABOVE (Min. Bore Dia. 175mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 142 mm & Pump OD. :- 160 mm

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	1120	1580	1730	1890	2100	2280	2460
VJN:7JT 30 (THH)	5.5	7.5	2		34	24	22	20	18	17	14	9
VJN:7JT 25 (THHH)	5.5	7.5	3		48	36	33	30	27	25	21	14
VJN:7JT 50 (THH)	7.5	10.0	2		34	24	22	20	18	17	14	9
VJN:7JT 30 (THHH)	7.5	10.0	3		48	36	33	30	27	25	21	14
VJN:7JT 30 (THH)	9.3	12.5	3		48	36	33	30	27	25	21	14
VJN:7JT 30 (THH)	11.0	15.0	4		65	49	44	41	36	33	28	19
VJN:7JT 50 (T)	15.0	20.0	4		70	54	48	45	41	37	33	25
VJN:7JT 50 (T)	18.5	25.0	5		88	68	60	56	51	46	41	31

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	550	750	950	1150	1500	1900	2400
VJN: 7JT 30 (THHH)E	7.5	10.0	3		45	39	36	33	30	27	22	16

VJ

SUITABLE FOR 175mm BOREWELL OR ABOVE (Min. Bore Dia. 175mm)
 APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
 Maximum Motor OD :- 142 mm & Pump OD. :-165 mm

OUTLET SIZE :- 75mm (ON DEMAND CAN PROVIDE 100mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE		DISCHARGE IN LPM									
	kW	H.P.			0	460	600	950	1200	1300	1450	1550	1660	1750
VJH 7A: 25	7.50	10.00	3	HEAD IN METERS	52	42	39	34.5	29	25	21	17.5	15	
VJH 7A: 30	4.5	6.0	2		35		31	27	22	20	19	15	14	
VJH 7A: 35	5.50	7.50	2		35	30	29	25	20	18	14	12	11	
VJH 7A: 35	9.30	12.50	3		52	45	44	38	30	27	21	19	16	
VJH 7A: 50	7.50	10.00	2		40	34	32	28	26	23	20	18	16	
VJH 7A: 50	11.00	15.00	3		60	51	48	42	39	34	30	27	24	
VJH 7A: 60	9.30	12.50	2		44	39	36	32	28	27	25	23	20	
VJHH 7A:25	5.50	7.50	3		46	40	39	33	28	25	21	19	15	
VJHH 7A:25	7.50	10.00	3		55	44	41	35	29	27	24	21	18	
VJHH 7A:25	7.50	10.00	4		66			48	45	40	35		30	
VJHH 7A:25	15.00	20.00	6		110	88	82	70	58	54	48	42	36	25
VJHH 7A:35	5.50	7.50	2		37	32	31	26	22	20	17	15	12	
VJHH 7A:35	9.30	12.50	3		56	48	46	39	33	30	26	22	18	
VJHH 7A:35	11.00	15.00	4		74	64	62	52	44	40	34	30	24	
VJHH 7A:35	11.00	15.00	5		84	71	67	59	52	47	40	31	24	
VJHH 7A:35	13.00	17.50	5		84	71	67	59	52	47	40	31	24	
VJHH 7A:35	15.00	20.00	5		92	81	78	65	55	50	42	38	30	
VJHH 7A:35	18.50	25.00	6		111	96	93	78	66	60	51	45	36	
VJHH 7A:35	22.50	30.00	8		148	128	124	104	88	80	68	60	48	
VJHH 7A:50	7.50	10.00	2		42	38	35	31	27	25	23	21	19	16
VJHH 7A:50	11.00	15.00	3		63	56	53	48	40	38	34	32	28	24
VJHH 7A:50	15.00	20.00	4		84	74	70	62	54	50	46	42	38	32
VJHH 7A:50	18.50	25.00	5		105	92	88	78	68	62	58	53	48	40
VJHH 7A:50	22.50	30.00	6		126	110	105	93	81	75	69	63	57	48



SUITABLE FOR 175mm BOREWELL OR ABOVE (Min. Bore Dia. 175mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 142 mm & Pump OD. :- 160 mm

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	450	750	1050	1400	1850	2150	2400
VJN7JT - 25 (THH)	5.5	7.5	3		45	42	37	33	28	23	18	14
VJN7JT - 30 (THH)	7.5	10	3		48	45	40	35	30	26	21	16
VJN7JT - 30 (THH)E	9.3	12.5	3		49	46	41	36	31	27	22	17
VJN7JT - 30 (THH)E	11	15	4		58	55	51	43	38	33	25	20
VJN7JT - 25 (THH) E	11	15	5		73	67	60	54	47	39	30	23
VJN7JT - 30 (THH)E	13	17.5	5		75	69	64	55	48	42	32	25
VJN7JT - 25 (THH)	13	17.5	6		85	80	72	65	56	47	36	28

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	600	800	950	1150	1300	1450	1600
VJN7J - 30 (THH) E	9.3	12.5	4		60	51	48	44	39	35	32	28
VJN7J - 30 (THH)	9.3	12.5	5		75	64	60	55	49	44	40	35

8" BOREWELL SUBMERSIBLE PUMP SETS



200 mm (8")
Submersible Pump Sets

200 mm (8") with Water Filled Motor

DESCRIPTION

Varuna brand makes reliable, efficient and durable Submersible pump sets of best quality as per IS 8034: 2018. Following are the salient features of Submersible pump sets with Water filled Motor.

SALIENT FEATURES

- › Motor and Pump come in a single unit for easy installation.
- › Pump sets perform in wider voltage band.
- › Pump sets also available in single phase and phase to phase.
- › Heavy Duty Carbon thrust bearing with German Technology.
- › Superior performance as compared to competitors.
- › CI bowl makes design strong and easy to repair.
- › Metal Inserted with sand guard to increase life in sandy bore.
- › Product Available up to 85 HP in 8" & Above 85 HP in 9".

Material Of Construction

MOTOR DETAILS

Stator	: Insulated varnish using vacuum impregnation method.
Rotor	: Copper Rotor.
Moto Body	: Stainless Steel.
Thrust Bearing	: Self aligned Carbon Vs. Stainless steel thrust bearing that withstands high axial thrust load in water lubrication.
Winding	: Multi Layer PVC insulated wire.
Cable Sealing Arrangement	: Protecting device to prevent foreign particles from entering into the motor arrangement.
Journal Bearings	: Gun Metal Bush with 2% nickel and additional centrifugal molding process to avoid chance of warm out.
Pressure Diaphragm	: Sufficient size to contain expansion of water inside the motor and avoid the defeat of cooling water.

PUMP DETAILS

Bowl	: Cast iron.
Impeller	: Stainless Steel Cast / SSSM.
Shaft	: Stainless Steel.
Wearing Rings	: High Quality Abrasion resistant Stainless Steel.
Suction Casing	: Heavy Dusty casting material to get proper grip on motor as well as Provide path for suction of water. SS strainer is also provided to protect against foreign particles.
Non Return Valve	: To reduce the thrust generated due to back pressure of long pipe line at the time of switch off hence leading to increase in the life of the pump.

Applications



SPRINKLER
IRRIGATION



DRIP IRRIGATION
SYSTEM



AGRICULTURE
WATER SUPPLY



INDUSTRIAL
APPLICATION



CIVIL & DOMESTIC
WATER SUPPLY



FIRE FIGHTING
SYSTEM

VJ

SUITABLE FOR 200mm BOREWELL OR ABOVE (Minimum Bore Diameter 200mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 142 mm & Pump OD B :- 178 mm & (C & E) :- 194 mm

OUTLET SIZE :- 100 mm

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM												
	KW	H.P.			0	460	600	950	1200	1300	1450	1550	1660	1750	1800	1950	2000
VJH 8B: 25	7.5	10.0	3		54	43	40	37	32	29	23	19	17				
VJH 8B: 35	5.5	7.5	2		37	32	30	26	23	30	17	14	12				
VJH 8B: 35	9.3	12.5	3		56	48	45	39	35	33	28	23	18				
VJH 8B: 35	11.0	15.0	4		76	64	60	52	47	43	37	31	24				
VJH 8B: 35	15.0	20.0	5		95	80	75	65	59	54	48	40	30				
VJH 8B: 35	18.5	25.0	6		114	96	90	78	70	65	57	47	36				
VJH 8B: 35	22.5	30.0	8		152	128	120	104	94	86	76	63	48				
VJH 8B: 50	7.5	10.0	2		41	36	33	30	28	24	21	19	17	14			
VJH 8B: 50	11.0	15.0	3		62	54	50	45	42	38	34	30	25	20			
VJH 8B: 50	15.0	20.0	4		82	72	66	60	56	48	42	38	34	28			
VJH 8B: 50	18.5	25.0	5		103	90	83	75	70	60	53	48	43	35			
VJH 8B: 50	22.5	30.0	6		123	108	99	90	84	72	63	57	51	42			
VJH 8B: 60	9.3	12.5	2		47	42	38	34	30	28	26	24	22	19			
VJH 8C: 60	9.3	12.5	2		45	39	37	35	33	31	29	27	24	22	20	18	16
VJH 8B: 60	13.0	17.5	3		71	63	57	51	45	42	39	36	33	29			
VJH 8B: 60	18.5	25.0	4		94	84	76	68	60	56	52	48	44	38			
VJH 8C: 70	11.0	15.0	2		49	43	41	38	35	33	30	27	24	22	20	18	16
VJH 8C: 70	15.0	20.0	3		73	64	61	57	52	49	47	45	42	39	36	33	30
VJH 8E: 80	13.0	17.5	2		51	47	45	41	37	34	32	30	28	26	23	21	19
VJH 8E: 80	18.5	25.0	3		76	71	67	62	55	51	48	45	42	39	35	32	28
VJH 8E: 100	15.0	20.0	2		54	48	46	43	41	39	38	37	36	34	32	30	27
VJH 8E: 100	22.5	30.0	3		81	72	69	65	62	59	57	56	54	51	48	45	41

VJ

SUITABLE FOR 200mm BOREWELL OR ABOVE (Minimum Bore Diameter 200mm)
 APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
 Maximum Motor OD :- 142 mm & Pump OD B :- 178 mm & (C & E) :- 194 mm

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE		DISCHARGE IN LPM													
	KW	H.P.			0	460	600	950	1200	1300	1450	1550	1660	1750	1800	1950	2000	2200
VJHH 8B: 25	7.5	10.0	3		56	45	42	38	34	31	26	22	19					
VJHH 8B: 35	5.5	7.5	2		39	35	32	28	25	22	18	16	13					
VJHH 8B: 35	9.3	12.5	3		59	53	48	42	37	35	30	25	20					
VJHH 8B: 35	11.0	15.0	5		100	88	80	70	62	57	50	42	33					
VJHH 8B: 50	7.5	10.0	2		44	39	37	33	32	28	25	23	20	17	14			
VJHH 8B: 50	11.0	15.0	3		66	58	56	50	47	42	37	34	30	25	21			
VJHH 8C: 35	9.3	12.5	3		60		52		44	43	39		36		32	26	23	
VJHH 8C: 35	11.0	15.0	4		75		68		59	55	52		48		42	34	30	
VJHH 8C: 50	7.5	10.0	2		43		36	33	31	28	26	25	23	20	17	15	13	
VJHH 8C: 50	11.0	15.0	3		64		54	50	46	42	40	38	35	30	25	22	20	
VJHH 8C: 50	15.0	20.0	4		80		70		60	58	54	51	47		41	34	30	
VJHH 8C: 60	9.3	12.5	2		47					36	34	32	30	27	25	22	20	
VJHH 8C: 60	13.0	17.5	3		69					54	51	48	45	55	37	37	30	
VJHH 8C: 60	18.5	25.0	4		86				69	66		60	56		51	46	43	
VJHH 8C: 70	11.0	15.0	2		51	48	46	43	40	38	36	35	33	31	30	27	25	20
VJHH 8C: 70	15.0	20.0	3		77	72	69	65	60	57	55	53	50	47	45	41	38	30

OUTLET SIZE :- 100 mm

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM															
	KW	H.P.			0	1000	1200	1300	1350	1400	1500	1600	1700	1750	1850	2000	2150	2200	2300	2500
VJHH:8B 25(THH)	7.5	10.0	3		58	50	46	44	43	42	35	33	29	26	23	18				
VJHH:8B 30(THH)	7.5	10.0	3		59	51	47	45	44	43	36	34	30	27	24	19				
VJHH:8CT 35(THH)	9.3	12.5	3		63	51	50	48	47	46	45	43	38	34	31	24	20			
VJHH:8CT 50(THH)	7.5	10.0	2		47	42	39	36	34	33	32	30	28	26	25	23	17	14	10	
VJHH:8CT 50(THH)	11.0	15.0	3		71	62	58	54	53	51	48	45	42	40	38	35	25	20	15	
VJHH:8CT 50G(THH)	11.0	15.0	3		73	69	67	65	64	63	62	61	58	56	52	48	43	38	28	20
VJHH:8C 70(THH)	11.0	15.0	2		51	48	46	43	40	38	37	35	33	31	30	27	25	20	10	

V8

SUITABLE FOR 200mm BOREWELL OR ABOVE (Min. Bore Dia. 200mm)
 APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
 Maximum Motor OD :- 180 mm & Pump O.D . :-194 mm

OUTLET SIZE :- 75mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE		DISCHARGE IN LPM							
	kW	H.P.			0	110	250	430	550	660	710	800
VN 25 B	15.0	20.0	8	HEAD IN METERS	176	162	150	134	107	91	75	54
VN 25 B	18.5	25.0	10		220	202	187	168	134	114	94	68
VN 25 B	22.0	30.0	10		220	202	187	168	134	114	94	68
VN 25 B	22.0	30.0	12		264	242	224	202	161	137	113	82
VN 25 B	30.0	40.0	14		308	283	262	235	188	160	132	95
VN 25 B	30.0	40.0	16		352	323	299	269	214	182	150	109
VN 25 B	33.0	45.0	18		396	364	337	302	241	205	169	122

V8

SUITABLE FOR 200mm BOREWELL OR ABOVE (Min. Bore Dia. 200mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 180 mm & Pump O.D . :-194 mm

OUTLET SIZE :- 75mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	KW	H.P.			0	120	400	480	700	750	800	850
VN 30 B	11.0	15.0	5		109	104	97	93	68	60	50	41
VN 30 B	15.0	20.0	6		130	125	117	111	81	72	60	49
VN 30 B	15.0	20.0	7		156	146	136	130	95	84	70	57
VN 30 B	18.5	25.0	8		178	167	156	148	108	97	81	65
VN 30 B	22.0	30.0	10		223	209	194	185	135	121	101	81
VN 30 B	26.0	35.0	12		267	251	233	222	162	145	121	98
VN 30 B	30.0	40.0	12		267	251	233	222	162	145	121	98
VN 30 B	30.0	40.0	13		289	271	253	241	176	157	131	106
VN 30 B	33.0	45.0	15		326	313	292	278	203	181	151	122
VN 30 B	37.0	50.0	15		326	313	292	278	203	181	151	122
VN 30 B	37.0	50.0	16		348	334	311	296	216	193	161	130
VN 30 B	37.0	50.0	17		369	355	330	315	230	205	171	138
VN 30 B	40.0	55.0	18		391	376	350	333	243	217	181	146
VN 30 B	45.0	60.0	20		435	418	389	370	270	241	201	163

V8

SUITABLE FOR 200mm BOREWELL OR ABOVE (Min. Bore Dia. 200mm)
 APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
 Maximum Motor OD :- 180 mm & Pump O.D . :-194 mm

OUTLET SIZE :- 75mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	kW	H.P.			0	767	825	885	928	968	1000	1052
VN 40 RB	15.0	20.0	5		113	97	77	71	66	61	60	55
VN 40 RB	18.5	25.0	6		135	117	93	86	80	73	72	66
VN 40 RB	22.0	30.0	7		158	136	108	100	93	86	84	78
VN 40 RB	22.0	30.0	8		180	155	123	114	106	98	95	89
VN 40 RB	26.0	35.0	9		203	175	139	129	120	110	107	100
VN 40 RB	30.0	40.0	10		225	194	154	143	133	122	119	111
VN 40 RB	37.0	50.0	10		225	194	154	143	133	122	119	111
VN 40 RB	33.5	45.0	11		248	214	170	157	146	134	131	122
VN 40 RB	37.0	50.0	12		270	233	185	171	159	147	143	133
VN 40 RB	37.0	50.0	13		293	253	201	186	173	159	155	144
VN 40 RB	40.0	55.0	14		315	272	216	200	186	171	167	155
VN 40 RB	45.0	60.0	14		315	272	216	200	186	171	167	155
VN 40 RB	45.0	60.0	15		338	291	231	214	199	183	179	166
VN 40 RB	56.0	75.0	16		360	311	247	229	213	195	191	177
VN 40 RB	63.0	85.0	18		405	350	278	258	240	219	215	199

OUTLET SIZE :- 75mm

TYPE OF FLOW : RADIAL

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	kW	H.P.			0	170	290	400	500	600	650	750	850
VN 50 R	5.5	7.5	2		41	40	39	40	38	36	35	31	26
VN 50 R	9.3	12.5	3		62	60	60	58	56	53	51	45	39
VN 50 R	13.0	17.5	4		82	80	78	76	74	70	68	59	50
VN 50 R	15.0	20.0	5		103	102	100	96	92	88	85	73	63
VN 50 R	18.5	25.0	6		124	121	119	115	111	106	102	89	76
VN 50 R	22.5	30.0	7		144	140	138	133	130	122	119	104	88
VN 50 R	26.0	35.0	8		164	160	156	152	148	140	136	120	100
VN 50 R	30.0	40.0	10		205	200	196	191	185	175	170	148	127
VN 50 R	33.0	45.0	11		226	220	215	210	204	193	187	162	138
VN 50 R	37.5	50.0	12		246	240	235	230	222	210	204	176	150
VN 50 R	45.0	60.0	12		246	240	235	230	222	210	204	176	150
VN 50 R	41.0	55.0	13		266	260	255	248	240	228	221	191	162
VN 50 R	45.0	60.0	14		287	280	275	267	260	245	238	206	176
VN 50 R	56.0	75.0	14		287	280	275	267	260	245	238	206	176
VN 50 R	63.0	85.0	16		281	274	269	263	254	240	233	201	171

SUITABLE FOR 200mm BOREWELL OR ABOVE (Minimum Bore Diameter 200mm)
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.
Maximum Motor OD :- 180 mm & Pump O.D . :-194 mm

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE		DISCHARGE IN LPM									
		kW	H.P.			0	800	1000	1150	1250	1400	1500	1600	1700	1800
VQ : 25	NB	7.5	10.0	3	HEAD IN METERS	53	41	36	34	30	22	20	18		
VQ : 25	NB	11.0	15.0	5		88	68	60	56	50	36	33	30		
VQ : 25	NB	15.0	20.0	7		123	95	84	78	70	50	46	42		
VQ : 35	NB	5.5	7.5	2		38	29	26	24	21	18	17	15	14	
VQ : 35	NB	9.3	12.5	3		57	44	40	36	34	27	26	20	18	
VQ : 35	NB	11.0	15.0	4		76	59	53	48	45	35	34	30	27	
VQ : 35	NB	15.0	20.0	5		95	73	67	60	57	44	43	38	30	
VQ : 35	NB	18.5	25.0	6		114	88	80	72	68	53	51	46	36	
VQ : 35	NB	22.5	30.0	7		133	103	93	84	79	62	60	54	42	
VQ : 35	NB	26.0	35.0	8		152	118	106	96	90	71	68	62	48	
VQ : 35	NB	30.0	40.0	9		171	133	119	108	101	80	77	70	54	
VQ : 35	NB	30.0	40.0	10		190	148	132	120	112	89	85	78	60	
VQ : 35	NB	30.0	40.0	11		209	163	145	132	123	98	94	86	66	
VQ : 35	NB	33.0	45.0	11		209	163	145	132	123	98	94	86	66	
VQ : 35	NB	37.5	50.0	12		228	178	158	144	134	107	102	94	72	
VQ : 35	NB	41.0	55.0	12		228	178	158	144	134	107	102	94	72	
VQ : 35	NB	45.0	60.0	14		266	208	184	168	156	125	119	110	84	
VQ : 50	NB	7.5	10.0	2		39	32	30	28	25	21	19	17	14	13
VQ : 50	NB	11.0	15.0	3		59	47	44	42	37	31	29	25	21	19
VQ : 50	NB	15.0	20.0	4		79	64	60	56	50	42	38	34	28	26
VQ : 50	NB	18.5	25.0	5		99	80	75	70	63	53	48	43	35	33
VQ : 50	NB	22.5	30.0	6		119	96	90	84	76	64	57	52	42	40
VQ : 50	NB	26.0	35.0	7		139	112	105	98	89	75	67	61	49	47
VQ : 50	NB	30.0	40.0	8		159	128	120	112	102	86	76	70	56	54
VQ : 50	NB	33.0	45.0	9		179	144	135	126	115	97	86	79	63	61
VQ : 50	NB	37.5	50.0	10		199	160	150	140	128	108	95	88	70	68
VQ : 50	NB	41.0	55.0	11		219	176	165	154	144	119	105	97	77	75

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM									
		kW	H.P.			0	800	1000	1150	1250	1400	1500	1600	1700	1800
VQ : 50	NB	45.0	60.0	12		239	192	180	168	157	130	114	106	84	82
VQ : 60	NB	93.0	12.5	2		46	38	35	33	30	27	24	21	19	
VQ : 60	NB	13.0	17.5	3		69	57	52	50	45	41	36	32	29	
VQ : 60	NB	18.5	25.0	4		92	76	69	66	60	55	48	43	39	
VQ : 60	NB	22.5	30.0	5		115	95	86	83	75	69	60	54	49	
VQ : 60	NB	26.0	35.0	6		138	114	103	99	90	83	72	65	59	
VQ : 60	NB	33.0	45.0	7		161	133	120	116	105	97	84	76	69	
VQ : 60	NB	37.5	50.0	8		184	152	137	132	120	111	96	87	79	
VQ : 60	NB	41.0	55.0	9		207	171	154	149	135	125	108	98	89	
VQ : 60	NB	45.0	60.0	10		230	190	171	165	150	139	120	109	99	

V8

SUITABLE FOR 200mm/250mm BOREWELL OR ABOVE

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

OUTLET SIZE :- 100mm (ON DEMAND CAN PROVIDE 125mm)

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE		DISCHARGE IN LPM														
		KW	H.P.			0	800	1000	1150	1250	1400	1500	1600	1700	1800	1950	2050	2200	2300	2450
VQ : 70	NC	11.0	15.0	2	HEAD IN METERS	44			38	32	30	29	28	26	24	20	17	14	12	11
VQ : 70	NC	15.0	20.0	3		66			57	47	45	44	41	38	35	30	25	21	18	16
VQ : 70	NC	22.5	30.0	4		88			76	63	60	58	55	50	47	40	33	27	24	21
VQ : 70	NC	26.0	35.0	5		110			95	79	75	73	69	63	59	50	41	34	30	26
VQ : 80	NE	18.5	25.0	3		71	61	57	55	53	50	48	46	44	41	36	33	30	25	20
VQ : 80	NE	26.0	35.0	4		95	81	76	73	71	67	64	61	59	55	48	44	40	33	27
VQ : 80	NE	33.0	45.0	5		119	101	95	92	89	84	80	76	74	69	60	55	50	42	34
VQ : 80	NE	41.0	55.0	6		143	121	114	110	107	101	96	91	89	83	72	66	60	50	41
VQ : 80	NE	45.0	60.0	7		167	141	133	128	125	118	112	106	104	97	84	77	70	59	48
VQ : 80	NE	49.0	65.0	8		191	161	152	147	143	135	128	121	119	111	96	88	80	67	54
VQ : 80	NE	52.0	70.0	9		215	182	171	165	161	152	144	137	134	125	108	99	90	76	61
VQ : 80	NE	56.0	75.0	10		238	202	190	183	178	168	160	152	148	138	120	110	100	84	68
VQ : 80	NE	60.0	80.0	11		262	222	209	202	196	185	176	167	163	152	132	121	110	92	75
VQ : 80	NE	64.0	85.0	12		286	242	228	220	214	202	192	182	178	166	144	132	120	101	82
VQ : 80	NE	67.0	90.0	13		310	262	247	238	232	219	208	197	193	180	156	143	130	109	88
VQ : 80	NE	75.0	100.0	14		334	282	266	257	250	236	224	212	208	194	168	154	140	118	95
VQ : 100	NE	15.0	20.0	2		51	45	43	42	41	39	38	37	35	33	30	28	25	21	18
VQ : 100	NE	22.5	30.0	3		77	68	65	63	62	59	57	56	53	50	45	42	38	32	27
VQ : 100	NE	30.0	40.0	4		102	90	86	84	82	78	76	74	70	66	60	56	50	42	36
VQ : 100	NE	37.5	50.0	5		128	113	108	105	103	98	95	93	88	83	75	70	63	53	45
VQ : 100	NE	45.0	60.0	6		154	136	130	126	124	118	114	112	106	100	90	84	76	64	54
VQ : 100	NE	52.0	70.0	7		179	158	151	147	144	137	133	130	123	116	105	98	88	74	63
VQ : 100	NE	60.0	80.0	8		205	181	173	168	165	157	152	149	141	133	120	112	101	85	72
VQ : 100	NE	67.0	90.0	9		230	203	194	189	185	176	171	167	158	149	135	126	113	95	81
VQ : 100	NE	75.0	100.0	10		256	226	216	210	206	196	190	186	176	166	150	140	126	106	90
VQ : 100	NE	82.5	110.0	11		282	249	238	231	227	216	209	205	194	183	165	154	139	117	99
VQ : 100	NE	90.0	120.0	12		307	271	259	252	247	235	228	223	211	199	180	168	151	127	108
VQ : 100	NE	97.5	130.0	13		333	294	281	273	268	255	247	242	229	216	195	182	164	138	117
VQ : 100	NE	105.0	140.0	14		358	316	302	294	288	274	266	260	246	232	210	196	176	148	126
VQ : 100	NE	112.5	150.0	15		384	339	324	315	309	294	285	279	264	249	225	210	189	159	135

NOTE : Above 60 H.P motors are availablein only V9 & V10

V8

SUITABLE FOR 200mm/250mm BOREWELL OR ABOVE
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
		kW	H.P.			0	900	1150	1300	1470	1600	1750
VQ 50N (T)	HC	15.0	20.0	4		80	68	64	60	55	51	45
VQ 50N (T)	HC	30.0	40.0	8		160	136	128	120	110	102	90

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
		kW	H.P.			0	900	1150	1300	1450	1600	1800
VQ 60N (T)	HC	18.5	25.0	4		87	75	69	65	60	55	48
VQ 60N	HC	56.0	75.0	13		283	244	224	211	195	179	156
VQ 60N	HC	60.0	80.0	12		262	225	207	195	180	165	144
VQ 60N	HC	60.0	80.0	14		305	263	242	228	210	193	168
VQ 60N	HC	63.0	85.0	14		305	263	242	228	210	193	168
VQ 60N	HC	63.0	85.0	15		327	281	259	244	225	206	180

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
		kW	H.P.			0	1400	1550	1700	1850	2000	2100	2250
VQ 70N (T)	HC	45.0	60.0	8		190	141	133	121	110	101	89	77
VQ 70N	HC	45.0	60.0	9		214	159	150	136	124	114	100	87

NOTE : Above 60 H.P motors are availablein only V9 & V10

V8

SUITABLE FOR 200mm BOREWELL OR ABOVE (Min. Bore Dia. 200mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 180 mm & Pump O.D B:-178 mm & C & E :-194 mm

OUTLET SIZE :- 100mm (ON DEMAND CAN PROVIDE 125mm)

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE	DISCHARGE IN LPM														
		KW	H.P.		0	1000	1150	1260	1350	1400	1550	1700	1800	1950	2050	2150	2300	2450	2550
VQ : 25	HB	7.5	10.0	3	57	41	36	33	31	27	21	19	16						
VQ : 35	HB	5.5	7.5	2	39	29	26	24	21	20	17	13	13						
VQ : 35	HB	9.3	12.5	3	58	43	39	36	32	30	25	20	19						
VQ : 35	HB	11.0	15.0	4	77	57	52	48	43	40	33	27	25						
VQ : 35	HB	15.0	20.0	5	97	72	65	60	53	50	42	33	32						
VQ : 50	HB	7.5	10.0	2	43	32	31	29	27	25	22	17	14						
VQ : 50	HB	11.0	15.0	3	65	48	46	43	40	37	32	26	21						
VQ : 50	HB	15.0	20.0	4	87	64	62	57	53	49	44	34	28						
VQ : 50	HB	18.5	25.0	5	109	80	77	71	66	61	55	43	35						
VQ : 60	HB	9.3	12.5	2	49	37	34	33	31	29	27	21	19	15					
VQ : 60	HB	13.0	17.5	3	74	56	51	50	47	44	41	32	29	23					
VQ : 70	HC	11.0	15.0	2	45		35	33	32	31	30	27	25	22	19	17	14	12	11
VQ : 70	HC	15.0	20.0	3	68		52	50	48	47	45	40	37	33	28	25	21	18	16
VQ : 70	HC	22.5	30.0	4	91		69	67	64	63	60	53	49	44	37	31	28	24	21
VQ : 70	HC	26.0	35.0	5	113		86	83	80	78	75	67	62	55	47	42	35	30	27
VQ : 70	HC	30.0	40.0	6	135		105	99	96	93	90	81	75	66	57	51	42	36	33
VQ : 70	HC	37.5	50.0	7	158		123	116	112	109	105	95	88	77	67	60	49	42	39
VQ : 70	HC	41.0	55.0	8	180		140	132	128	124	120	108	100	88	76	68	56	48	44
VQ : 70	HC	49.0	65.0	9	203		158	149	144	140	135	122	113	99	86	77	63	54	50
VQ : 70	HC	52.0	70.0	10	225		175	165	160	155	150	135	125	110	95	85	70	60	55

V8

SUITABLE FOR 200mm BOREWELL OR ABOVE (Min. Bore Dia. 200mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 180 mm & Pump O.D B:-178 mm & C & E :-194 mm

MODEL	PUMP TYPE	MOTOR RATING		STAGE		DISCHARGE IN LPM						
		kW	H.P.			0	350	750	1050	1350	1450	1600
VQ : 35N (TPLH)	HCB E	11.0	15.0	4	HEAD IN METERS	71	64	60	56	48	44	41
VQ : 35N (TPLH)	HCB E	15.0	20.0	5		89	80	75	70	60	45	51
VQ : 35N (TPLH)	HCB E	18.0	25.0	6		106	96	90	84	72	66	61
VQ : 35N (TPLH)	HCB E	22.5	30.0	7		124	112	105	98	84	77	71
VQ : 35N (TPLH)	HCB E	22.5	30.0	8		142	129	120	113	97	89	81
VQ : 35N (TPLH)	HCB E	26.0	35.0	8		142	129	120	113	97	89	81
VQ : 35N (TPLH)	HCB E	26.0	35.0	9		160	145	135	127	109	100	91
VQ : 35N (TPLH)	HCB E	30.0	40.0	9		160	145	135	127	109	100	91
VQ : 35N (TPLH)	HCB E	30.0	40.0	10		177	161	150	141	121	111	101
VQ : 35N (TPLH)	HCB	34.0	45.0	11		195	177	165	155	133	122	111
VQ : 35N (TPLH)	HCB	37.0	50.0	12		213	193	180	169	145	133	122
VQ : 35N (TPLH)	HCB	41.0	55.0	14		248	225	210	197	169	155	142
VQ : 35N (TPLH)	HCB	45.0	60.0	14		248	225	210	197	169	155	142
VQ : 35N (TPLH)	HCB	45.0	60.0	15		266	241	225	211	181	166	152

OUTLET SIZE :- 100mm

TYPE OF FLOW : MIXED

MODEL	PUMP TYPE	MOTOR RATING		STAGE		DISCHARGE IN LPM						
		kW	H.P.			0	700	1050	1250	1450	1600	1800
VQ : 50N (TPLH)	NCB E	15.0	20.0	4	HEAD IN METERS	79	68	64	60	54	50	44
VQ : 50N (TPLH)	NCB E	18.0	25.0	5		99	85	80	75	68	63	55
VQ : 50N (TPLH)	NCB E	22.5	30.0	6		118	102	96	90	82	76	66
VQ : 50N (TPLH)	NCB E	26.0	35.0	7		138	119	112	105	95	88	77
VQ : 50N (TPLH)	NCB E	30.0	40.0	8		158	136	129	121	109	101	89
VQ : 50N (TPLH)	NCB	34.0	45.0	9		178	153	145	136	122	113	100
VQ : 50N (TPLH)	HCB	37.0	50.0	10		197	170	161	151	136	126	111
VQ : 50N (TPLH)	NCB	37.0	50.0	11		217	187	177	166	150	139	122
VQ : 50N (TPLH)	NCB	41.0	55.0	11		217	187	177	166	150	139	122
VQ : 50N (TPLH)	HCB	45.0	60.0	12		237	204	193	181	163	151	133
VQ : 50N (TPLH)	NCB	45.0	60.0	13		257	221	209	196	177	164	144
VQ : 50N (TPLH)	HCB	56.3	75.0	14		276	238	225	211	190	176	155
VQ : 50N (TPLH)	HCB	56.3	75.0	15		296	255	241	226	204	189	166

V8

SUITABLE FOR 200mm BOREWELL OR ABOVE (Min. Bore Dia. 200mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 180 mm & Pump O.D B:-178 mm & C & E :-194 mm

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
		kW	H.P.			0	850	1100	1280	1400	1600	1750	1900
VQ:60N (TPLH)	HC E	13.0	17.5	3		63	54	51	48	45	41	36	32
VQ:60N (TPLH)	HC E	18.0	25.0	4		84	72	68	64	60	54	48	42
VQ:60N (TPLH)	HC E	22.5	30.0	5		105	90	85	80	75	68	60	53
VQ:60N (TPLH)	HC	26.0	35.0	6		126	108	102	96	90	82	72	64
VQ:60N (TPLH)	NC E	30.0	40.0	7		146	126	119	113	105	95	85	74
VQ:60N (TPLH)	HC	37.0	50.0	8		167	144	136	129	120	109	97	85
VQ:60N (TPLH)	HC	41.0	55.0	9		188	162	153	145	135	123	109	96
VQ:60N (TPLH)	HC	45.0	60.0	10		209	180	170	161	150	136	121	106
VQ:60N (TPLH)	NC	45.0	60.0	11		230	198	187	177	165	150	133	117
VQ:60N (TPLH)	HC	56.3	75.0	12		251	216	204	193	180	163	145	127
VQ:60N (TPLH)	HC	56.0	75.0	13		272	234	221	209	195	177	157	138
VQ:60N (TPLH)	NC	63.7	85.0	14		293	252	238	225	210	191	169	149
VQ:60N (TPLH)	HC	63.7	85.0	15		314	270	255	241	225	204	181	159

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
		kW	H.P.			0	700	900	1100	1400	1600	1800	2100
VQ:70N (TPLH)	HC E	15.0	20.0	3		70	62	59	56	51	48	44	35
VQ:70N (TPLH)	HC E	22.5	30.0	4		93	83	79	75	68	64	59	47
VQ:70N (TPLH)	HC	26.0	35.0	5		116	103	98	93	85	80	73	58
VQ:70N (TPLH)	HC E	30.0	40.0	6		140	124	118	112	102	97	88	70
VQ:70N (TPLH)	HC	34.0	45.0	6		140	124	118	112	102	97	88	70
VQ:70N (TPLH)	HC	37.0	50.0	7		163	144	137	130	119	113	102	81
VQ:70N (TPLH)	HC	41.0	55.0	8		186	165	157	149	136	129	117	93
VQ:70N (TPLH)	HC	45.0	60.0	9		209	186	177	168	153	145	132	105
VQ:70N (TPLH)	NC	56.3	75.0	10		233	206	196	186	170	161	146	116
VQ:70N (TPLH)	HC	56.3	75.0	11		256	227	216	205	187	177	161	128
VQ:70N (TPLH)	HC	63.7	85.0	12		279	248	236	224	204	193	176	140
VQ:70N (TPLH)	HC	63.7	85.0	13		303	268	255	242	221	209	190	151

MODEL	PUMP TYPE	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
		kW	H.P.			0	700	1050	1350	1550	1650	1950	2200
VQ:80N (TPLH)	HC E	18.8	25.0	3		71	63	59	55	51	48	39	32
VQ:80N (TPLH)	HC	26.0	35.0	4		95	85	79	74	69	65	53	43
VQ:80N (TPLH)	NC E	30.0	40.0	5		119	106	98	92	86	81	66	53
VQ:80N (TPLH)	HC	37.0	50.0	6		143	127	118	110	103	97	79	64
VQ:80N (TPLH)	HC	41.0	55.0	7		166	148	137	129	120	113	92	74
VQ:80N (TPLH)	HC	45.0	60.0	8		190	169	157	147	137	129	105	85
VQ:80N (TPLH)	HC	56.3	75.0	9		214	190	177	165	154	145	118	96
VQ:80N (TPLH)	NC	45.0	75.0	10		238	211	196	184	171	161	131	106
VQ:80N (TPLH)	NC	63.7	85.0	11		262	232	216	202	188	177	144	117

HMPS

HORIZONTAL OPENWELL SUBMERSIBLE MONOBLOCK PUMPSETS



Salient Features

- Compact Design Pump set for easy handling and installation.
- High iron to get better life in heavy and contaminated water.
- Front Side Carbon bearing with Stainless Steel Thrust plate and Back side SG Iron plate with Gunmetal Bush for long life at wide head condition.
- Stamping is Electrical Grade silicon steel for lower power consumption for higher product life.
- Advance Hydraulic Design for highest energy efficiency in Pump set.
- Wide voltage band and better performance at low voltage.
- Dynamically Balanced Rotating part to ensure minimum noise and vibration free operation.
- Products are available with NRV which reduces the thrust load of back pressure.
- Also providing pin hole on drain plug, which allows motor to fill water by itself to maintain water level inside the motor.
- Hardware MOC of SS for easy Service and maintenance.

Applications



Canal & River



Fountain



High Rise
Building

HMPS

HORIZONTAL OPENWELL MONO SUBMERSIBLE MONOBLOCK PUMPSETS

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50Hz, A.C. SUPPLY

MODEL NAME	MOTOR RATING		PIPE SIZE(mm)		DISCHARGE IN LPM	HEAD IN METER						
	kW	H.P.	SUC.	DEL.		6	9	12	15	18	21	24
3 OSV 50	2.20	3.00	62	50			640	600	560	500	430	350
3 OSV 65	2.20	3.00	62	62				880	740	600	100	

MODEL NAME	MOTOR RATING		PIPE SIZE(mm)		DISCHARGE IN LPM	HEAD IN METER																				
	kW	H.P.	SUC.	DEL.		44	42	40	38	36	32	30	28	26	24	23	22	21	20	19	18	17	16	15	12	10
5 OSV 50	3.7	5.0	65	50				0	270	360	420	480	500	560	570	580	595	610	620							
HMPS 2H	3.7	5.0	65	50		0	200	300	350	440	490	550	580	600	605	610	620									
5 OSV 62	3.7	5.0	65	65								0	380	640	770	810	840	880	930	980	1020	1080	1120			
5 OSV 75	3.7	5.0	75	75									0	520	720	760	820	860	920	970	1020	1080	1120			
5 OSV 100	3.7	5.0	100	100										0	220	330	500	680	760	850	980	1100	1150	1200	1350	1500

MODEL NAME	MOTOR RATING		PIPE SIZE(mm)		DISCHARGE IN LPM	HEAD IN METER																	
	kW	H.P.	SUC.	DEL.		48	46	44	42	40	39	38	36	34	32	30	28	26	24	22	20	18	16
6 OSV 50	4.5	6.0	65	50		0	150	300	400	450	480	500	540	595	605	615	620	630	640	650			
6 OSV 62	4.5	6.0	65	65										0	200	500	650	770	900	1000	1100		

MODEL NAME	MOTOR RATING		PIPE SIZE(mm)		DISCHARGE IN LPM	HEAD IN METER																											
	kW	H.P.	SUC.	DEL.		54	52	48	46	44	40	38	36	34	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	16			
HMPS	5.5	7.5	65	50		0	220	300	400	450	560	580	600	630	660	680	700																
7.5 OSV 65	5.5	7.5	75	65										0	650	750	830	850	950	1050	1080	1150	1200	1210	1220	1250	1270	1300	1330	1400			
7.5 OSV 75	5.5	7.5	75	75										0	500	500	700	750	830	990	1030	1050	1110	1200	1230	1270							
7.5 OSV 100	5.5	7.5	100	100												0	330	540	840	900	950	1000	1090	1180	1230	1280	1300	1400	1480				

MODEL NAME	MOTOR RATING		PIPE SIZE(mm)		DISCHARGE IN LPM	HEAD IN METER																		
	KW	H.P.	SUC.	DEL.		66	64	61	60	56	54	52	48	46	40	36	34	32	30	28	25	22	20	
HMPS	7.5	10.0	65	50		0	200	350	400	450	480	520	550	590	650									
10 OSV 75	7.5	10.0	75	75													0	800	850	1000	1100	1180	1240	1300
10 OSV 100	7.5	10.0	100	100													0	380	640	840	1080	1320	1560	1620

MINI HMPS

HORIZONTAL OPENWELL SUBMERSIBLE MONOBLOCK PUMPSETS

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 200-240 VOLTS SINGLE PHASE / 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

MODEL NAME	H.P	SIZE (in mm)	DISCHARGE IN LPM	HEAD IN METER										
				6	9	12	15	18	21	24	28	30	32	34
HMPS HSS	1.5	40 X 40					285	260	215	170	80			
HMPS HSS	2.0	50 X 50						290	260	240	175	105		

MODEL NAME	MOTOR RATING		PIPE SIZE(mm)		DISCHARGE IN LPM	HEAD IN METER								
	kW	H.P.	SUC.	DEL.		6	9	12	15	18	21	24	26	28
ULTRA 05	0.37	0.5	25	25		192	147	125	107	70				
ULTRA 10	0.75	1.0	25	25			217	200	182	163	143	122	93	61
ULTRA 20	1.50	2.0	50	50		436	380	350	330	280	220	160	85	

VMPS

VERTICAL OPENWELL SUBMERSIBLE MONOBLOCK PUMPSETS



Salient Features

- Compact Design Pump set for easy handling and installation.
- High iron to get better life in heavy and contaminated water.
- Front Side Carbon bearing with Stainless Steel Thrust plate and Back side SG Iron plate with Gunmetal Bush for long life at wide head condition.
- Stamping is Electrical Grade silicon steel for lower power consumption for higher product life.
- Advance Hydraulic Design for highest energy efficiency in Pump set.
- Wide voltage band and better performance at low voltage.
- Dynamically Balanced Rotating part to ensure minimum noise and vibration free operation.
- Products are available with NRV which reduces the thrust load of back pressure.
- Also providing pin hole on drain plug, which allows motor to fill water by itself to maintain water level inside the motor.
- Hardware MOC of SS for easy Service and maintenance.

Applications



Canal & River



Fountain



High Rise
Building

VMPS

VERTICAL OPENWELL SUBMERSIBLE PUMPSETS

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

MODEL NAME	MOTOR RATING		STAGE	FRAME	PUMP TYPE	OUTLET IN mm.	HEAD IN METERS	DISCHARGE IN L.P.M.								
	kW	H.P.						0	300	360	420	480	540	600	660	720
V V: 301 / 3	2.2	3.0	3	F2/A60	M 60	65		29	25	23	22	20	17	14	12	10
V V: 401 / 4	3.0	4.0	4	F2/A60	M 60	65		39	33	31	29	27	23	19	16	13
V V: 603 / 5	4.5	6.0	5	F2/A100	M 61	80		59	53	49	44	38	33	30		

VMPS

VERTICAL OPENWELL SUBMERSIBLE PUMPSETS

MODEL NAME	MOTOR RATING		STAGE	FRAME	PUMP TYPE	OUTLET IN mm.	HEAD IN METERS	DISCHARGE IN L.P.M.						
	kW	H.P.						0	300	360	420	480	540	600
V V: 504 / 4	3.70	5.0	4	F2/A80	M 61	80		47	43	39	35	30	27	24
V V: 7503 / 6	5.50	7.50	6	F2/A125	M 61	80		71	64	59	53	45	40	36
V V: 1005/7 M61	7.50	10.0	7	FA/A125	M 61	80		82	74	68	61	53	46	42

MODEL NAME	MOTOR RATING		STAGE	FRAME	PUMP TYPE	OUTLET IN mm.	HEAD IN METERS	DISCHARGE IN L.P.M.							
	kW	H.P.						0	540	600	660	720	780	840	900
V V: 602 / 2	4.5	6.0	2	F2/A100	R 30H	80		40	35	34	33	31	29	27	24
V V: 7507/2	5.5	7.5	2	F2/A125	R 50R	80		41			35	33	31	28	24
V V: 1003/3	7.5	10.0	3	F2/A160	R 30H	80		60	53	51	49	46	44	41	36
V V : 12502/4	9.3	12.5	4	F2/A180	R 30H	80		80	70	68	66	62	58	54	48
V V : 1502/5	11.0	15.0	5	F2/210	R 30H	80		100	87	85	82	77	72	67	60
V V : 17502/6	13.0	17.5	6	F2/A250	R 30H	80		120	105	102	99	93	87	81	72
V V : 2004/5	15.0	20.0	5	F2/A290	R 50R	80		103			87	83	79	70	61

VMPS

VERTICAL OPENWELL SUBMERSIBLE PUMPSETS

APPROXIMATE PERFORMANCE CHART AT 2880 RPM,380-415 VOLTS THREE PHASE ,50Hz.A.C SUPPLY

MODEL NAME	MOTOR RATING		STAGE	FRAME	PUMP TYPE	OUTLET IN mm.	TOTAL HEAD IN METERS	DISCHARGE IN L.P.M.																
	KW	H.P.						0	1000	1150	1260	1350	1400	1550	1700	1800	1800	1950	2050	2150	2300	2450	2550	
V V : 1009/3	7.5	10.0	3	F2/A160	M 25 HB	100 / 125		57	41	36	33	31	27	21	19	16	16							
V V : 12509/4	9.3	12.5	4	F2/A160	M 25 HB	100 / 125		76	55	48	44	41	36	28	25	21	21							
V V : 1509/5	11.0	15.0	5	F2/A160	M 25 HB	100 / 125		95	68	60	55	52	45	35	32	27	27							
V V : 7508/2	5.5	7.5	2	F2/A125	M 35 HB	100 / 125		39	29	26	24	21	20	17	13	11	11							
V V : 12506/3	9.3	12.5	3	F2/A180	M 35 HB	100 / 125		58	43	39	36	32	30	25	20	19	19							
V V : 1505/4	11.0	15.0	4	F2/A210	M 35 HB	100 / 125		77	57	52	48	43	40	33	27	25	25							
V V : 2005/5	15.0	20.0	5	F2/A290	M 35 HB	100 / 125		97	72	65	60	53	50	42	33	32	32							
V V : 10010/2	7.5	10.0	2	F2/A160	M 50 HB	100 / 125		43	32	31	29	27	25	22	17	14	14							
V V : 1506/3	11.0	15.0	3	F2/A210	M 50 HB	100 / 125		65	48	46	43	40	37	32	26	21	21							
V V : 2006/4	15.0	20.0	4	F2/A290	M 50 HB	100 / 125		87	64	62	57	53	49	44	34	28	28							
V V : 10011/2	7.5	10.0	2	F2/A160	M 50 HC	100 / 125		40	31	29	27	25	24	22	19	17	17	14	12					
V V : 1507/3	11.0	15.0	3	F2/A210	M 50 HC	100 / 125		60	47	44	41	38	36	33	29	26	26	21	18					
V V : 2007/4	15.0	20.0	4	F2/A290	M 50 HC	100 / 125		89	63	59	55	51	48	44	39	35	35	28	24					
V V : 12507/2	9.3	12.5	2	F2/A180	M 60 HB	100 / 125		49	37	34	33	31	29	27	21	19	19	15						
V V : 17505/3	13.0	17.5	3	F2/A250	M 60 HB	100 / 125		74	56	51	50	47	44	41	32	29	29	23						
V V : 12508/2	9.3	12.5	2	F2/A180	M 60 HC	100 / 125		45	36	34	33	31	29	27	23	21	21	18						
V V : 17506/3	13.0	17.5	3	F2/A250	M 60 HC	100 / 125		68	53	51	50	46	44	41	35	32	32	27						
V V : 1509/2	11.0	15.0	2	F2/A210	M 70 HC	100 / 125		45		35	33	32	31	30	27	25	25	22	19	17	14	12	11	
V V : 2009/3	15.0	20.0	3	F2/A290	M 70 HC	100 / 125		68		52	50	48	47	45	40	37	37	33	28	25	21	18	16	
V V : 20010/2	15.0	20.0	2	F2/A290	M 100 HE	100 / 125		55			45	43	41	39	37	35	35	33	30	28	25	21	18	

MODEL	MOTOR RATING		STAGE	OUTLET IN mm.	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.				0	125	170	210	250	300	340	400	450	520
VVT : 25/2	2.2	3.0	2	50		41	38	37	36	35	32	29	26	21	15
VVT : 25/3	3.7	5.0	3	50		62	57	56	55	52	48	44	38	32	22
VVT : 25/4	5.5	7.5	4	50		82	76	75	73	69	64	58	51	42	29
VVT : 25/5	7.5	10.0	5	50		103	95	93	91	87	80	73	64	53	37
VVT : 25/6	7.5	10.0	6	50		124	114	112	109	104	96	87	77	63	44
VVT : 25/7	9.3	12.5	7	50		144	133	131	128	121	112	102	89	74	51

MODEL	MOTOR RATING		STAGE	OUTLET IN mm.	HEAD IN METERS	DISCHARGE IN LPM									
	kW	H.P.				0	200	250	290	340	420	480	550	600	700
VVT : 30/2	3.7	5.0	2	65		45	43	42	41	39	36	33	30	26	19
VVT : 30/3	5.5	7.5	3	65		67	64	63	61	58	54	50	44	38	28
VVT : 30/4	7.5	10.0	4	65		89	86	84	81	77	73	66	59	51	37
VVT : 30/5	9.3	12.5	5	65		112	107	105	102	97	90	83	73	63	47
VVT : 30/6	11.0	15.0	6	65		134	128	126	122	116	108	100	88	76	56
VVT : 30/7	13.0	17.5	7	65		157	150	147	143	136	126	116	102	88	66

MODEL	MOTOR RATING		STAGE	OUTLET IN mm.	HEAD IN METERS	DISCHARGE IN LPM								
	kW	H.P.				0	300	450	480	550	650	700	760	820
VVT : 35/2	5.5	7.5	2	65		45	42	41	40	37	34	29	24	21
VVT : 35/3	7.5	10.0	3	65		67	63	62	60	56	51	44	36	32
VVT : 35/4	9.3	12.5	4	65		90	84	82	80	74	68	59	48	42
VVT : 35/5	11.0	15.0	5	65		112	105	103	100	93	85	73	60	53
VVT : 35/6	13.0	17.5	6	65		134	126	124	120	112	102	88	72	64
VVT : 35/7	15.0	20.0	7	65		156	147	144	140	130	119	102	84	74

CMB

CENTRIFUGAL MONOBLOCK PUMP CLASS "B"



Salient Features

- › High operating efficiency and low power consumption
- › Long trouble-free life and easy to repair
- › Minimum noise and vibration-free
- › "B" class insulation and low temperature for smooth operation in wide voltage bands
- › Grease-lubricated anti-friction ball bearings with best quality at both ends so withstand radial and axial load.
- › Good mechanical strength and higher efficiency

Applications



Car Washing



Lawn Sprinklers



Hotel & Hospitals



Agriculture
Water Supply



CENTRIFUGAL MONOBLOCK PUMPSETS
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 200-240 VOLTS SINGLE PHASE / 380-415 VOLTS THREE PHASE,
50 Hz. A.C. SUPPLY.

MODEL	H.P.	kW	Size (in mm)		HEAD IN METERS																	
					5	6	8	9	10	12	14	16	18	20	22	24	26	28	30	32	34	38
VNA 10B	0.5	0.37	25 x 25	DISCHARGE IN LPH	-	-	7000	6800	6500	5500	4000	2500 (15ms)	-	-	-	-	-	-	-	-	-	-
VNA 10BLS	0.5	0.37	25 x 25		-	-	7000	6800	6500	5500	4000	2500 (15ms)	-	-	-	-	-	-	-	-	-	-
VNA 11B	0.5	0.37	25 x 25		-	-	7800	7680	7500	7200	6360	5000	4140	2000	0 (21ms)	-	-	-	-	-	-	-
VNA 11B H	0.75	0.55	25 x 25		-	13800	10500	7200	-	-	8500	8000	7300	6100	4000	3000 (23ms)	-	-	-	-	-	-
VNA 28B	0.50	0.37	40 x 40		-	13800	10500	7200	13200	9000		-	-	-	-	-	-	-	-	-	-	-
VNA 28B WV	0.50	0.37	40 x 40		-	16800	14400	13800	13200	9000	6000	-	-	-	-	-	-	-	-	-	-	-
VNA 28B WVR	0.5	0.37	40 x 40		-	16800	14400	13800	13200	9000	6000	-	-	-	-	-	-	-	-	-	-	-
VNA 28B WVRLS	0.5	0.37	40 x 40		-	16800	14400	13800	13200	9000	6000	-	-	-	-	-	-	-	-	-	-	-
VNA 29B	0.5	0.37	50 x 50		20000	18000	14000	12000	9000	-	-	-	-	-	-	-	-	-	-	-	-	-
VNA 29B LH	0.5	0.37	50 x 50		18000	16000	12000	9500	-	-	-	-	-	-	-	-	-	-	-	-	-	-
VNA 14B	1.0	0.75	25 x 25		-	-	-	-	-	-	-	12000	11800	10000	7500	4200	-	-	-	-	-	-
VNA 25B	1.0	0.75	32 x 25		-	-	-	-	-	-	-	8200	8100	8000	7700	5700	4000 (25ms)	-	-	-	-	-
VNA 13B	1.0	0.75	40 x 40		-	-	19200	19000	18700	18000	15600	12600	10800	7000	-	-	-	-	-	-	-	-
VNA 18B	1.0	0.75	50 x 40		-	24000	21600	19500	16800	15000	11700	6900	-	-	-	-	-	-	-	-	-	-
VNA 17B	1.0	0.75	50 x 50		-	30000	28800	26400	25500	18000	-	-	-	-	-	-	-	-	-	-	-	-
VNA 17B HH	1.0	0.75	50 x 50		-	-	30000	27000	24000	23100	18600	7500	-	-	-	-	-	-	-	-	-	-
VNA 17B LS HH	1.0	0.75	50 x 50		-		30000	27000	24000	23100	18600	7500	-	-	-	-	-	-	-	-	-	-
VNA 40B	1.0	0.75	40 x 40		48000	42000	24000	9000	-	-	-	-	-	-	-	-	-	-	-	-	-	-
VNA 19B	1.5	1.1	40 x 40		-	-	16000	15800	15700	14500	13500	13200	12000	11000	8300	4800	-	-	-	-	-	-
VNA 15B	1.5	1.1	50 x 40		-	-	24600	24000	22800	20400	18000	15600	12300	8100	2400	-	-	-	-	-	-	-
VNA 20B	1.5	1.1	50 x 50		-	-	28200	27600	26400	21900	14100	-	-	-	-	-	-	-	-	-	-	-
VNA 20B HH	1.5	1.1	50 x 50		-	-	-	-	16000	15000	13500	11400	7800	3000	-	-	-	-	-	-	-	-
VNA 26B	1.5	1.1	65 x 50		-	-	28800	27600	24000	21600	16200	11000	-	-	-	-	-	-	-	-	-	-
VNA 27B	1.5	1.1	75 x 75		5400	45000	25500	10000	-	-	-	-	-	-	-	-	-	-	-	-	-	-
VNA 27B HF	1.5	1.1	75 x75		-	57000	44400	40800	31200	10800	-	-	-	-	-	-	-	-	-	-	-	-
VNA 23B	2.0	1.5	50 x 40		-	-	25500	25000	24600	23100	20700	18900	16800	12000	6500	-	-	-	-	-	-	-
VNA 23B HD	2.0	1.5	50 x 40		-	-	21000	20600	20100	18600	18000	17400	16800	15600	14400	12600	9600	8400	5400	-	-	-
VNA 16B	2.0	1.5	50 x 50		-	-	30000	27000	26400	24900	23100	20400	18000	13000	11800	8500 (23m)	-	-	-	-	-	-
VNA 16B HD	2.0	1.5	50 x 50		-	-	23400	22920	22500	21000	20460	19800	19200	18000	16800	15000	12300	10800	-	-	-	-
VNA 24B	2.0	1.5	65 x 50		-	37500	35400	34500	32400	29400	27600	22800	19200	15000	-	-	-	-	-	-	-	-
VNA 24B HH	2.0	1.5	65 x 50		-	-	-	-	26000	23500	22000	19300	16300	13500	8000	-	-	-	-	-	-	-
VNA 21B	2.0	1.5	75 x 65		-	42000	37200	35400	33000	29800	24000	15600	-	-	-	-	-	-	-	-	-	-
VNA 30B	2.0	1.5	75 x 75		-	50000	42000	39000	35400	30000	-	-	-	-	-	-	-	-	-	-	-	-
VNA 30B MK	2.0	1.5	75 x 75		-	50000	42000	39000	35400	30000	-	-	-	-	-	-	-	-	-	-	-	-
VNA 30 30BK L (HH) K	1.5	1.1	75 x 75		-	55000	42600	36000	30000	20000	-	-	-	-	-	-	-	-	-	-	-	-
VNA 34B	2.0	1.5	100 x 100		-	72000	58500	48000	36000	-	-	-	-	-	-	-	-	-	-	-	-	-
VNA 31B	3.0	2.2	75 x 65		-	-	62500	58000	50000	46500	40000	3000(15ms)	-	-	-	-	-	-	-	-	-	-
VNA 32B	3.0	2.2	75 x 75		-	-	64000	59000	52000	47000	40500	31500(15ms)	-	-	-	-	-	-	-	-	-	-
VNA 32B HD K	3.0	2.2	75 x 75		-	61200	54000	49200	44400	37800	28500	-	-	-	-	-	-	-	-	-	-	-
VNA 33 B	3.0	2.2	65 x 50			-	-	-	46000	44500	41500	38000	34000	29500	23500	15000	-	-	-	-	-	-
VNA 35 B	3.0	2.2	100 x 100		78000	75000	61000	54000	48000	36000	-	-	-	-	-	-	-	-	-	-	-	-
VNA 35B NK	3.0	2.2	100 x 100		-	70800	57600	46800	34800	21000	-	-	-	-	-	-	-	-	-	-	-	-
VNA 36B	3.0	2.2	50 x 50		-	-	24000	23800	23600	22900	22600	22300	21900	21500	21000	20500	20000	19600	-	15800	-	-
VNA 37B	3.0	2.2	50 x 40		-	-	-	-	-	-	21300	21000	20400	19500	18000	17400	16800	16200	15000	10500	7500	-
VNA 54B	5.0	3.7	100 x 100		-	-	84000	82200	81000	75000	51000	-	-	-	-	-	-	-	-	-	-	-
VNA 51 BH	5.0	3.7	65 x 50		-	-	-	-	-	-	-	-	-	-	-	-	31800	-	27120	24000	21600	16080
VNA 53 BJ	5.0	3.7	80 x 65		-	-	-	-	-	64800	62400	60480	55200	45000	-	22800	-	-	-	-	-	-



CENTRIFUGAL MONOBLOCK PUMPSETS
APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 200-240 VOLTS SINGLE PHASE / 380-415 VOLTS THREE PHASE,
50 Hz. A.C. SUPPLY.

MODEL	MOTOR RATING		PIPE SIZE (mm)		DISCHARGE IN LPH	HEAD IN METERS							
	Kw	HP	SUC.	DEL.		6	9	12	15	18	21	24	26
VNA 10B L (LH)	0.37	0.50	25	25		7400	6400	5400	4700	2300	-	-	-
VNA 11B L (LH)	0.37	0.50	25	25		6800	6300	6000	5100	3900	3600	1000	-