

```

1 namespace CSharp;
2 class LinqJoin
3 {
4     public static void Main()
5     {
6         // Student collection
7         IList<Student> studentList = new List<Student>() {
8             new Student() { StudentID = 1, StudentName = "John", Age = 18, StandardID = 1 } ,
9             new Student() { StudentID = 2, StudentName = "Steve", Age = 21, StandardID = 1 } ,
10            new Student() { StudentID = 3, StudentName = "Bill", Age = 18, StandardID = 2 } ,
11            new Student() { StudentID = 4, StudentName = "Ram", Age = 20, StandardID = 2 } ,
12            new Student() { StudentID = 5, StudentName = "Ron", Age = 21 }
13        };
14
15        IList<Standard> standardList = new List<Standard>() {
16            new Standard(){ StandardID = 1, StandardName= "Standard 1"},
17            new Standard(){ StandardID = 2, StandardName= "Standard 2"},
18            new Standard(){ StandardID = 3, StandardName= "Standard 3"}
19        };
20
21        // Left Outer Join using query syntax
22        var innerJoinResult =
23            from student in studentList
24            join standard in standardList
25                on student.StandardID equals standard.StandardID into oj
26            from studstand in oj.DefaultIfEmpty()
27            select new
28            {
29                StudentName = student.StudentName,
30                StandardName = studstand?.StandardName ?? "Not Assigned"
31            };
32
33        foreach (var obj in innerJoinResult)
34        {
35            Console.WriteLine("{0} - {1}", obj.StudentName, obj.StandardName);
36        }
37    }
38 }
39 public class Student
40 {
41     public int StudentID { get; set; }
42     public string StudentName { get; set; }
43     public int Age { get; set; }
44     public int StandardID { get; set; }
45 }
46
47 public class Standard
48 {
49     public int StandardID { get; set; }
50     public string StandardName { get; set; }
51 }

```