Topological Void Analysis: A Mathematical Framework for Systematic Technical Innovation Discovery in Knowledge Spaces

Anonymous

Abstract. Identifying where to innovate in a dense technical domain—such as operating systems or hardware/software co-design—is fundamentally a search problem in a high-dimensional knowledge space. Existing approaches rely on keyword search, citation proximity, or human intuition, none of which formalise the notion of an *unexplored region* that is simultaneously relevant to a target goal and absent from prior art.

We present *Topological Void Analysis* (TVA), a mathematical framework that defines *topological voids* as triads (A, B, C) in a dense-sparse hybrid embedding space. A void requires three conditions: (i) both concepts A and B are semantically cohesive with domain anchor C; (ii) their pairwise similarity falls within a calibrated marginality band—avoiding both obvious combinations and unrelated noise; and (iii) they share a sparse lexical bridge while the geodesic midpoint on the embedding hypersphere is unoccupied.

Applied to ∼140k indexed documents, TVA generates 1,896 invention candidates across 96 targets; 85% pass automated quality filtering and 90 survive multi-expert adversarial review. Two case studies demonstrate the framework surfaces non-obvious connective tissue rather than merely obvious related pairs.

1 Introduction

Modern software systems, especially at the systems-software layer, evolve through incremental invention: a developer notices a gap between two subsystems, proposes an abstraction to bridge them, and the community iterates toward a patch or patent. The *noticing* step is bottlenecked by human attention and domain breadth. A single engineer cannot simultaneously hold in mind the locking semantics of the Linux scheduler, the memory-ordering guarantees of eBPF JIT output, the ELF relocation model, and the BPF verifier's type system well enough to recognise that an IFUNC-style dispatch contract could unify the latter three.

This paper asks: *can we formalise and automate the act of recognising unexplored technical gaps*?

We answer yes, and make the following contributions:

1. A formal definition of a *topological void* (Section 4): a triad (A, B, C) satisfying domain cohesion, calibrated marginality, and sparse lexical bridge conditions in a hybrid dense-sparse embedding space.
2. A *vacancy probing* mechanism (Section 5) based on spherical linear interpolation (SLERP) that rejects pseudo-voids whose midpoint is occupied by existing documents.
3. An *adaptive threshold calibration* procedure (Section 6) that derives domain-specific marginality bounds from corpus statistics, removing manual tuning.
4. A large-scale empirical evaluation (Section 8) with two detailed case studies demonstrating that TVA surfaces non-obvious yet technically grounded innovation candidates.

2 Background and Motivation

2.1 Technical Knowledge as an Embedding Space

Pre-trained embedding models map technical documents into a high-dimensional unit sphere [7]. Points close in cosine distance share semantic content; distant points are unrelated. A *knowledge corpus* $\mathcal{K}$ is a finite set of such points.

Innovation in this view is the act of bridging two concepts A, B that are not yet co-located in $\mathcal{K}$, provided their combination is relevant to a target goal C.

2.2 Limitations of Prior Art Search

Conventional patent and prior-art search is keyword-driven or citation-driven [9, 13]. These methods retrieve *known* content; they do not identify *missing* content. Knowledge-graph completion approaches [2] predict missing edges but require a pre-defined relation schema and do not model the continuous "marginality" notion central to patentable non-obviousness.

2.3 The Marginality Principle

Patent law requires that an invention be *non-obvious*: too similar to existing work fails the novelty bar; too dissimilar yields an incoherent or non-enabling disclosure. High-value inventions live in a band of *moderate dissimilarity*—far enough from prior art to be novel, close enough to the domain to be useful. This is the informal basis for our formal marginality condition.

3 Why Standard Approaches Fail

Before presenting TVA, we trace the design evolution that motivated it. Each prior approach solved part of the problem but broke down in a characteristic way.

Cosine similarity (top-k retrieval). The simplest baseline retrieves the k documents closest to the target vector v_{target}. The result is highly relevant but *redundant*: the top-k set is dominated by documents from the same well-covered subsystem, and the returned concepts are trivially related to each other. Nothing in the ranking identifies a *gap* between two concepts.

Maximum Marginal Relevance (MMR) [3]. MMR extends top-k retrieval by penalising similarity to already-selected items:

$$\text{MMR} = \arg\max_{d_i \in R \setminus S} \big[\lambda \cos(d_i, q) - (1-\lambda) \max_{d_j \in S} \cos(d_i, d_j)\big]$$

MMR improves diversity but does not identify missing regions. A high-MMR pair (A, B) may still have existing prior art at their midpoint—exactly where an inventor would look for a gap. In our experiments, ∼30% of high-MMR pairs had a nearest neighbour within cosine distance 0.08 of their linear midpoint, rendering them false voids.

MMR + latent vector arithmetic ("Queen formula"). Inspired by the additive structure of word embeddings [10], we combined MMR with concept arithmetic: after selecting a diverse pair (A, B) via MMR, we computed a bridge vector $v_{\text{bridge}} = v_{\text{target}} + (v_A - v_B)$ and retrieved candidates nearest to v_{bridge}. The intuition mirrors the classical analogy *king* − *man* + *woman* ≈ *queen* [10]: the difference vector encodes a directional concept shift that, when applied to the target, should surface the desired gap.

Why it fails in high dimensions. The analogy arithmetic of Word2Vec works in 300-dimensional skip-gram space because the training objective explicitly aligns semantic directions with linear offsets. BGE-M3 operates in 1024-dimensional contextualised representation space, which suffers from two compounding problems. First, transformer embeddings are *anisotropic* [7]: all vectors cluster in a narrow cone, so the difference $v_A - v_B$ is nearly orthogonal to the principal semantic axes. Adding such a vector to v_{target} moves the probe point toward the boundary or exterior of the semantic manifold, far from any real document. Second, in high-dimensional spaces the curse of dimensionality flattens the cosine-distance distribution [1]: nearest-neighbour dis-

tances concentrate around a single value, stripping the difference vector of directional meaning. In our experiments, ∼67% of bridge vectors produced by this method had no corpus neighbour within cosine distance 0.25, confirming that they escaped the manifold entirely.

Lesson. All three approaches fail to provide an occupancy guarantee: they rank or construct candidate points without verifying that the target region is genuinely unoccupied in the corpus. This motivates the three-condition filter and SLERP vacancy probe described in the next section.

4 The Topological Void Framework

4.1 Notation

Let $\mathcal{K} = \{k_1, \ldots, k_n\} \subset S^{d-1}$ be a corpus of ℓ_2-normalised d-dimensional embeddings. We use BGE-M3 ($d = 1024$) [4], which produces both dense vectors and sparse lexical weight vectors for each document. We write $\text{dense}(k)$ for the dense vector and $\text{sparse}(k) \subset \Sigma^*$ for the top-p weighted tokens.

Let $\cos(u, v) = u^\top v$ for unit vectors. Let $\text{Sparse}(k) = \{t \in \text{sparse}(k) : t \notin \mathcal{S}\}$ where $\mathcal{S}$ is a domain stop-word list (high-frequency, low-specificity tokens such as `int`, `define`, `linux`).

4.2 Formal Definition

Definition 1 (Topological Void)**.** *Let $A, B \in \mathcal{K}$ be two corpus documents and let $C = m(A, B)$ (Definition 2) be their synthetic* void midpoint*—the geodesic bridge concept derived from A and B. The pair (A, B) forms a* topological void *with respect to a domain query vector $v_{\text{target}} \in S^{d-1}$ if all of the following hold:*

C1 (Domain Cohesion).

$$\cos(\text{dense}(A), v_{\text{target}}) > \tau_{\text{domain}}$$
$$\cos(\text{dense}(B), v_{\text{target}}) > \tau_{\text{domain}}$$

C2 (Calibrated Marginality).

$$\tau_{\text{low}} \;\leq\; \cos(\text{dense}(A), \text{dense}(B)) \;\leq\; \tau_{\text{high}}$$

C3 (Sparse Lexical Bridge).

$$\text{Sparse}(A) \cap \text{Sparse}(B) \;\neq\; \emptyset$$

C4 (Vacancy).

$$\max_{k \in \mathcal{K} \setminus \{A,B\}} \cos(k,\, C) \;<\; \theta_v$$

where θ_v is a vacancy threshold.

Intuitively: A and B both point toward the target domain (C1); are neither trivially similar nor unrelated (C2); share at least one meaningful technical token as a conceptual bridge (C3); and the synthetic void midpoint $C = m(A, B)$ is unoccupied by any existing document (C4). The idea to be invented lives in the neighbourhood of C—the gap between two related but unexplored concepts.

4.3 Ranking Voids

Valid pairs (A, B) are ranked by a multi-objective scoring functional $\mathcal{H}(A, B; v_{\text{target}})$ that integrates (i) relevance of the synthetic void midpoint $C = m(A, B)$ to the target domain, (ii) a redundancy penalty against already-selected solutions, and (iii) a non-linear marginality reward centred at the band $[\tau_{\text{low}}, \tau_{\text{high}}]$. The precise functional form and weights are omitted per commercial confidentiality requirements, consistent with industry-track submission guidelines.

5 Vacancy Probing via SLERP

A key failure mode of purely similarity-based approaches is the *false void*: two documents that appear to span an empty region but whose midpoint is, in fact, close to an existing document. Condition C4 addresses this.

Definition 2 (Geodesic Midpoint)**.** *For unit vectors $u, v \in S^{d-1}$ with $\theta = \arccos(u^\top v)$, the geodesic midpoint on S^{d-1} is given by SLERP [12]:*

$$m(u, v) = \text{slerp}(u, v, \tfrac{1}{2}) = \frac{u + v}{\|u + v\|}, \quad \theta \notin \{0, \pi\}$$

with fallback to u for antipodal vectors ($\theta = \pi$).

We use the geodesic midpoint rather than an arbitrary interpolation because it is *equidistant* from u and v on the hypersphere: $\cos(m(u,v),u) = \cos(m(u,v),v)$, guaranteeing that the vacancy test is symmetric with respect to both anchors. For non-antipodal unit vectors this simplifies to normalised linear interpolation; the SLERP formulation handles the degenerate case and connects to the broader literature on geodesic midpoints in curved spaces [12].

Vacancy check (C4) is an $O(n)$ dot-product scan of the corpus matrix against $m(A,B)$, requiring no index rebuild.

6 Adaptive Threshold Calibration

Static thresholds fail across corpora with different density profiles. TVA employs a density-aware calibration layer that derives both τ_{domain} and $[\tau_{\text{low}}, \tau_{\text{high}}]$ on-the-fly from the empirical distribution of the current query's candidate pool.

6.1 Domain Threshold τ_{domain}

The domain cohesion threshold combines a data-driven percentile statistic over the cosine-score distribution of all candidates with a corpus-specific floor. The key property is that τ_{domain} rises in dense regions and falls in sparse ones, preventing both over-permissive selection and empty-result failures. Specific parameterisation is omitted per confidentiality requirements.

6.2 Marginality Band $[\tau_{\text{low}}, \tau_{\text{high}}]$

The marginality band is centred at the empirical mode of the pairwise-similarity distribution among domain-cohesive candidates, with width derived from the spread of that distribution. This operationalises non-obviousness: the band excludes the high-similarity tail (obvious combinations) and the low-similarity tail (unrelated noise) without hard-coded constants. Scale parameters are omitted per confidentiality requirements.

7 System Implementation

We implement TVA in a prototype that ingests a heterogeneous corpus of Linux kernel source (parsed via tree-sitter into function/struct/symbol chunks), hardware architecture manuals, academic papers (PDF-extracted), and patent texts. The corpus contains approximately 140,000 indexed documents after deduplication.

Embedding. We use BGE-M3 [4] in local offline mode for both dense ($d = 1024$) and sparse (top-p lexical weights) representations. All computation runs on CPU.

Index. Dense vectors are stored in a FAISS flat index [8] for $O(n)$ exact similarity search. Sparse tokens are stored in an SQLite FTS5 inverted index for boolean co-occurrence queries.

Candidate generation. For a given target phrase, we embed the target, retrieve the top-K domain-cohesive candidates (C1), enumerate all $\binom{K}{2}$ pairs, and filter by C2, C3, and C4 in sequence. Surviving pairs are ranked and the top-k returned as voids.

Idea generation. Each void is passed to a frontier LLM with a structured prompt instructing it to propose a technical invention disclosure (TID) that bridges the two void concepts toward the target domain. The LLM is not told the scoring details; it receives only the void description and the target.

8 Evaluation

8.1 Setup

We run TVA over a Cartesian matrix of 12 target domains (Linux scheduler, memory management, file systems, eBPF, virtualisation, networking, power management, device drivers, IRQ handling, CXL memory, PCIe, and security) crossed with 8 x86 micro-architecture feature areas (PEBS, AMX, TDX, CXL, APIC, RAPL, EPT, AVX-512), yielding 96 target specifications. For each target, TVA produces up to 10 void triads, each triggering one LLM call for idea generation.

Quality evaluation. We use a four-stage automated filtering pipeline as a proxy for expert

review:

1. *Structural check*: validates JSON completeness and absence of fictional kernel APIs.

2. *Reality check*: iterative critique-and-revise with up to 3 rounds; rejects physically impossible ideas.

3. *Adversarial review*: a four-specialist committee (kernel correctness, novelty/prior-art, strategic value, security/stability) each independently assigns APPROVE / REVISE / REJECT with an integer score.

4. *Deterministic verdict*: fatal-flaw, yellow-card, and majority rules aggregate the four specialist votes.

8.2 Quantitative Results

Table 1 summarises the filtering funnel over 1,896 candidate ideas generated across all 96 targets.

The 90 candidates reaching a REVISE verdict received substantive technical feedback from all four specialists (avg. 5.1 issues per specialist per candidate, avg. specialist score 4.0–5.0/5). Under our deterministic rules, REVISE indicates that the committee found genuine technical merit and requested elaboration—it is a *qualified positive result*, not a rejection. The two case studies below are drawn from this REVISE cohort.

The 0% APPROVE rate reflects an intentionally stringent threshold (unanimous high scores with no fatal flaws from any of four specialists), appropriate for patent-quality claims. The evaluation corpus presented here spans fewer than two days of operation with full metadata propagation. Extended results over a longer run are ongoing; updated numbers will appear in the final version.

8.3 Rejection Taxonomy

To understand *why* ideas fail, we categorise the fatal flaws in the 888 REJECT verdicts by keyword analysis of specialist feedback. Table 2 shows the distribution.

Three observations stand out. First, 90.2% of rejections are triggered by `fatal_flaw_reject` (at least one specialist identifies a blocking technical error), confirming that the committee is performing genuine domain-specific reasoning rather than surface-level critique. Second, locking and concurrency errors (35.5%) dominate, consistent with the difficulty of safe kernel synchronisation—exactly the class of error that a Linux maintainer would cite when rejecting a patch. Third, prior-art overlap (19.8%) indicates that a significant fraction of void-derived ideas, while geometrically novel in embedding space, overlap with existing techniques when viewed through a deep-domain lens. This motivates future work on tighter prior-art integration in the vacancy probe.

8.4 Case Study 1: TSX-Advisory MGLRU Rotation Capsules

Target and void. Target: *Optimize Linux memory management using x86 TSX microarchitecture features.* TVA surfaced void #2 from 8 candidate voids: concept A is a paper on *optimistic memory reclamation in lock-free programs*, concept B is a storage-technology selection study (TRaCaR Ratio). Sparse bridge tokens: `memory`, `optimistic`, `reclamation`, `access`. The geodesic midpoint $C = m(A, B)$ had no corpus neighbour within cosine distance 0.09—confirming vacancy.

Idea. The LLM proposed *TSX-advisory single-folio same-lruvec MGLRU rotation capsules*: a fail-closed mechanism that wraps the Linux MGLRU folio rotation fast-path in an RTM (Restricted Transactional Memory) speculation region. If the transaction aborts, the fallback acquires the `lru_lock` normally. The proposal introduces per-folio mutation cookies (seqcount-like odd/even) and a fail-closed locked revalidation step to preserve lruvec consistency.

Expert verdict (REVISE — 3/4 APPROVE), 3 rounds. This is the highest-approval result in our new-format cohort.

- *Kernel Hardliner* (APPROVE): "TSX advisory path is architecturally sound; RTM abort falls back correctly."
- *Prior-Art Shark* (APPROVE): "No direct prior art on TSX-advisory MGLRU rotation; non-obviousness defensible."
- *Intel Strategist* (APPROVE): "Strong x86

Table 1: Quality filtering funnel over 1,896 void-derived invention candidates.

Stage	Surviving	Rate	Notes
Void generation (Forager + LLM)	1,896	100%	96 targets, ≤10 voids each
Structural check (Professor)	1,836	96.8%	Rejects missing fields, fictional APIs
Reality check (RC, ≤3 rounds)	1,620	85.4%	Iterative critique-and-revise
Adversarial review (Debate Panel)	978	51.6%	4 specialists, ≤2 revision rounds
↪ REVISE verdict	90	4.7%	Substantive feedback; human review candidates
↪ APPROVE verdict	0	0.0%	Stringent: unanimous high scores, no fatal flaws

Table 2: Fatal flaw categories across 888 rejected candidates (new-format runs). Note: counts exceed 888 because multiple specialists may flag flaws per candidate.

Category	Count	%	Representative specialist quote
Locking / concurrency model	1,072	35.5%	"Synchronisation model violates LKMM; rq-¿lock discipline not pro
Prior art / novelty overlap	599	19.8%	"Reads as combination of existing thermal-pressure and NUMA-bal
Other technical issues	757	25.0%	Various implementation-specific correctness objections
Incomplete specification	230	7.6%	"Concurrency contract for sidecar metadata not fully specified"
Security / side-channel risk	199	6.6%	"Side-channel exposure via scheduler-observable pressure signal"
Kernel ABI / notrace violation	165	5.5%	"Target function absent from /proc/kallsyms (inlined or notrace)"

TSX differentiation story on Xeon platforms with hardware TSX support."

- *Security Guardian* (REVISE, fatal flaw): "TSX/TAA policy gating not specified concretely enough to guarantee fail-closed behavior under incomplete writer-coverage."

After Round 3 revision: mutation-cookie semantics were formalised (monotonic counter, never odd during active optimistic phase), and the TSX admissibility check was made explicit: RTM is enabled only when `X86_FEATURE_RTM` is present *and* the current kernel TAA mitigation policy permits transactional use. Three of four specialists approved the final draft, making this the strongest positive result in the evaluation cohort.

8.5 Case Study 2: Verifier-Derived Synchronization Contracts

Void. Void #5 in the same run: concept A is `ELF_MACHINE_NAME` (an ELF portability macro), concept B is `addend_may_be_ifunc` (a linker IFUNC relocation predicate). Sparse bridge tokens: `addend_may_be_ifunc`, `elf_machine_name`, `x86_64`. The pairwise cosine similarity (0.64) is at the high end of the calibrated band, indicating the pair is related but non-obvious in the target context.

Idea. Despite the weak, oblique signal, the LLM proposed *Verifier-Derived Synchronization Contract Vectors (SCVs)* for the x86 eBPF JIT: an immutable per-program sidecar table in which the eBPF verifier records each synchronisation site's primitive family, memory order, address class, context mask, and admissibility class; the JIT resolves each site exactly once at load time to an inline template or call-equivalent thunk. The idea ran through three rounds of adversarial revision, refining the SCV schema and clarifying LKMM-equivalence requirements.

Expert verdict (REVISE after 3 rounds — qualified positive). The idea underwent three rounds of adversarial revision (all REVISE, no REJECT; avg. specialist score 5.0/5). Representative feedback and responses:

- *Round 1 — Kernel Hardliner*: "Define the stable-feature admissibility rule in terms of existing `x86_cpufeature` APIs." → Added explicit stable-feature whitelist (TSO baseline, CX8, optional CX16); excluded

RTM/HLE and revocable features.

- *Round 2 — Kernel Hardliner*: "The SCV ABI requires precise versioning and endianness specification." → SCV entry schema extended with `linux_primitive_id`, `width_code`, `memory_order`, `admissibility_class`.
- *Round 3 — Prior-Art Shark*: "Claims overlap with generic verifier fact propagation." → Claims narrowed to the normative primitive-family identifier and the one-time admissibility resolution rule.

Significance. This case demonstrates a key property of TVA: the void pair (`ELF_MACHINE_NAME`, `addend_may_be_ifunc`) has no surface-level connection to BPF synchronisation semantics. A human engineer would not naturally connect these concepts; the LLM used the IFUNC dispatch mechanism as a structural analogy for per-site JIT resolution. The 3-round revision trace confirms that the idea was technically grounded enough to survive sustained adversarial critique and emerge with a stronger, more narrowly-claimed design. This is the "non-obvious connective tissue" that TVA is designed to surface.

9 Discussion

Why does a weak void signal still yield a strong idea? The void conditions define the *search region*, not the idea itself. The LLM fills the region with its own parametric knowledge. A sparse but valid bridge token (here, `addend_may_be_ifunc`) acts as a semantic trigger—analogous to how a human expert reading an unrelated paper suddenly connects it to their domain expertise. TVA formalises the triggering mechanism; the LLM supplies the reasoning.

Calibration sensitivity. The adaptive τ_{domain} calibration reduces manual tuning but introduces dependence on corpus density. For very sparse domains, the percentile-based calibration may set τ_{domain} too low, admitting noisy candidates. The vacancy probe (C4) partially compensates by rejecting occupied midpoints.

On the choice of REVISE as positive evidence. We deliberately present REVISE rather than APPROVE verdicts as case studies. Under our deterministic rules, APPROVE requires unanimous high scores with no fatal flaws from any of four independent specialists—a bar calibrated for patent-ready enabling disclosures. REVISE with 3/4 specialist approval and substantive technical feedback represents the system's *intended* output: technically grounded innovation candidates that require domain-expert completion, not autonomous patent generation. A system that routinely produces APPROVE verdicts from LLM specialists alone would be under-calibrated rather than superior—it would fail to catch the locking, prior-art, and security issues that Table 2 shows are pervasive in this domain. The 90 REVISE candidates are the value; the 0% APPROVE rate is evidence of calibration rigour, not system failure.

Evaluation limitations. Our automated adversarial review pipeline is a proxy for human expert evaluation. Human evaluation of the 90 REVISE candidates and extended benchmark data over a longer operational window are left for future work.

Reproducibility note. This paper is submitted to the Industry Research Track. Specific hyperparameter values and functional forms for $\mathcal{H}$ and the calibration layer are omitted per commercial confidentiality requirements, consistent with industry-track guidelines. The four conditions C1–C4, the vacancy probe, and the calibration strategy are described with sufficient precision to reproduce the qualitative behaviour; practitioners can derive corpus-specific values from the described procedures. Guidance on calibration ranges is available upon request from the authors.

Meta-evaluation. An early draft of this manuscript was subjected to the Debate Panel itself. The system's Writing Reviewer penalised the evaluation section for "narrative cherry-picking" and "lack of falsifiability," directly prompting the inclusion of the empirical rejection taxonomy (Table 2) and the deterministic verdict formalisation presented in Section 8. This meta-evaluation provides a concrete demonstration that the adversarial review framework produces substantive,

self-consistent critique resistant to sycophantic bias: the system identified and corrected a weakness in its own originating paper.

10 Future Work

Recursive Topological Expansion. Currently, TVA interpolates strictly within the empirical boundaries of human-authored prior art. A profound avenue for future research is *recursive innovation bootstrapping*. By vectorising and re-ingesting highly-rated, APPROVE-verdict Technical Invention Disclosures back into the active corpus as synthetic prior art, the system can dynamically alter the topology of the knowledge space. In this autoregressive loop, a synthesised TID acts as a newly established structural anchor in the embedding space, creating secondary topological voids between itself and historically distant concepts. This feedback mechanism would transition TVA from a single-step gap-discovery engine into an autonomous "technology tree" generator—iteratively mapping multi-generational frontiers of systems architecture beyond the immediate human horizon.

Downstream implementation. The structured TID format produced by TVA—comprising problem statement, architecture overview, implementation plan, and draft claims—is designed to be directly actionable. A validated TID can serve as a specification prompt for LLM-based coding agents [5], enabling a seamless path from knowledge-gap discovery to prototype implementation. Future work will evaluate end-to-end pipelines from void discovery through automated patch generation and CI-validated compilation.

Human-architect integration. Ideas that exhaust the automated revision budget without reaching APPROVE are routed to a `PENDING_HUMAN_REVIEW` queue. These candidates represent the frontier where LLM reasoning reaches its current limit—precisely the cases most worthy of expert human attention. A structured human-in-the-loop interface that presents the accumulated specialist critique alongside the draft is a natural next step.

11 Related Work

Patent and technology forecasting. [9] propose keyword-based patent maps for technology opportunity identification. [13] apply BERT to prior-art search. Neither formalises the notion of an unexplored region or provides a mathematical criterion for non-obviousness.

Knowledge graph completion. TransE [2] and its successors predict missing triples in knowledge graphs. These methods require a pre-defined relation schema and binary (present/absent) labels; TVA operates on continuous similarity and does not require a schema.

Diversity-based retrieval. Maximum Marginal Relevance [3] selects a diverse set of documents relevant to a query by penalising redundancy. TVA uses a similar relevance-novelty trade-off but applies it to the *generation* of new concepts rather than the retrieval of existing ones.

LLMs for code and creativity. Large language models have demonstrated strong performance on code generation [11, 5] and instruction-following [14]. We treat LLMs as black-box reasoners invoked after void discovery; the novelty is the void identification mechanism, not the generation step.

Topological data analysis. Persistent homology [6] identifies topological features (connected components, loops, voids) in point clouds. Our use of "topological void" is inspired by but distinct from TDA: we define voids in semantic embedding space by algebraic conditions on pairwise similarities, not by simplicial complex homology.

Embedding geometry. [7] show that contextualised representations are anisotropic—concentrated in a narrow cone. Our adaptive threshold calibration is designed to be robust to this property; SLERP avoids the geometric distortion that linear interpolation introduces in anisotropic spaces.

12 Conclusion

We have presented Topological Void Analysis, a mathematical framework for systematic techni-

cal innovation discovery. By defining topological voids as triads satisfying domain cohesion, calibrated marginality, sparse lexical bridge, and vacancy conditions in a hybrid dense-sparse embedding space, TVA converts the informal notion of "unexplored region" into a decidable predicate.

Applied to a 140k-document corpus of Linux kernel and hardware specifications, TVA generated 1,896 invention candidates, 85% of which survived automated quality filtering and 90 of which engaged four adversarial expert reviewers with substantive technical critique. Two case studies illustrate that TVA surfaces both obvious-gap ideas and non-obvious connective-tissue ideas that neither keyword search nor human browsing would naturally find.

We release the mathematical framework and threshold calibration procedure for reproducibility; implementation details are available upon request.

References

[1] Kevin Beyer, Jonathan Goldstein, Raghu Ramakrishnan, and Uri Shaft. When is "nearest neighbor" meaningful? In *International Conference on Database Theory (ICDT)*, pages 217–235, 1999.

[2] Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oktavian Yakhnenko. Translating embeddings for modeling multi-relational data. In *Advances in Neural Information Processing Systems*, pages 2787–2795, 2013.

[3] Jaime Carbonell and Jade Goldstein. The use of MMR, diversity-based reranking for reordering documents and producing summaries. In *Proceedings of the 21st Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 335–336, 1998.

[4] Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. BGE M3-Embedding: Multi-Lingual, Multi-Functionality, Multi-Granularity Text Embeddings Through Self-Knowledge Distillation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2318–2335, 2024.

[5] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde de Oliveira Pinto, Jared Kaplan, Harrison Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. In *arXiv preprint arXiv:2107.03374*, 2021.

[6] Herbert Edelsbrunner, David Letscher, and Afra Zomorodian. Topological persistence and simplification. *Discrete & Computational Geometry*, 28:511–533, 2002.

[7] Kawin Ethayarajh. How contextual are contextualized word representations? Comparing the geometry of BERT, ELMo, and GPT-2 embeddings. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, pages 55–65, 2019.

[8] Jeff Johnson, Matthijs Douze, and Hervé Jégou. Billion-scale similarity search with GPUs. *IEEE Transactions on Big Data*, 7(3):535–547, 2021.

[9] Sungjoo Lee, Byungun Yoon, and Yongtae Park. An approach to discovering new technology opportunities: Keyword-based patent map approach. In *Technovation*, volume 29, pages 481–497, 2009.

[10] Tomas Mikolov, Wen-tau Yih, and Geoffrey Zweig. Linguistic regularities in continuous space word representations. In *Proceedings of NAACL-HLT*, pages 746–751, 2013.

[11] Erik Nijkamp, Bo Pang, Hiroaki Hayashi, Lifu Tu, Huan Wang, Yingbo Zhou, Silvio Savarese, and Caiming Xiong. CodeGen: An open large language model for code with multi-turn program synthesis. In *The Eleventh International Conference on Learning Representations*, 2023.

[12] Ken Shoemake. Animating rotation with quaternion curves. In *Proceedings of the 12th*

Annual Conference on Computer Graphics and Interactive Techniques (SIGGRAPH), pages 245–254, 1985.

[13] Martin Srebrovic and Imai Yoko. Applying BERT to patent prior art search. In *arXiv preprint arXiv:2101.02105*, 2021.

[14] Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*, pages 13484–13508, 2023.