
# FORECASTING FLOOD INUNDATION IN CALGARY AND DENVER

Kristin Chang & Jenna Epstein | Land Use & Environmental Modeling (CPLN 675)

# **MOTIVATION**

According to the World Health Organization, floods are the most frequent natural disaster affecting countries across the globe. Floods have the potential to leave communities devastated not only because of the direct loss of life due to drowning and infrastructure damage, but also because of indirect impacts such as increased transmission of disease, higher risk of injury and hypothermia, disrupted or disabled infrastructure systems, and increased likelihood of causing other natural disasters. In the past ten years, climate change has exacerbated the effects of natural disasters like flooding, drought, sea level rise, and extreme precipitation and their frequency and intensity are expected to continue to rise if left unchecked.



This document outlines a machine learning algorithm that predicts which areas of a city are at the highest risk of flooding disasters. The model is created using past flood extent data from the City of Calgary in Canada to measure accuracy and then is applied to the City of Denver in the United States to measure generalizability.

## SIGNIFICANT FEATURES

#### **Mean Elevation**

Elevation generally describes the topography of the land. Areas at lower levels of elevation are at higher risk for floods than areas at higher elevations. We explored calculating the lowest degree of elevation per fishnet grid cell in Calgary, but found that using the mean helped the performance of our model.

#### **Distance to Nearest Stream**

Understanding the structure of streams helps inform the intensity of potential flooding. If the water level of the stream exceeds the stream channel, then flooding occurs. Areas that are closer to streams are more vulnerable to floods than areas that are farther away. A stream network was generated based on the Digital Elevation Model for Calgary, and distance was calculated for each fishnet grid cell to the nearest stream.

#### **Maximum Flow Accumulation**

Flooding occurs when water levels exceed the stream channel. Based on the direction of the streams calculated above, using the maximum accumulation value in each grid cell allows us to evaluate at the highest risk level. In other words, the resulting model will present a "worst-case-scenario" picture enabling planners to be over-prepared rather than under-prepared.

#### **Distance to Nearest Steep Slope**

Steep slopes in the land can contribute to both flow direction and flow accumulation. Additionally, a steeper slope likely accelerates the speed of flow and can intensify in the case of a flood. Thus, it is important to be aware of the location of steep slopes in the topography and their relative distance to past floods.


#### **Distance to Nearest Park**


Land cover or soil type can be indicative of areas prone to flooding. The more permeable the surface is, the more risky it is for floods. Initially, land cover data for Calgary (from the city's open data portal) was used to identify which fishnet grid cells were impervious based on their land cover type; however, this did not help the model perform well. Instead, distance to nearest park is incorporated into the model. Parks are generally covered in grass which is fairly permeable. Thus, the closer a fishnet grid cell is to a park, the more likely it is to become inundated.

#### **Number of Hydrological Feature Intersections**

In addition to mere distance to stream lines, the frequency of intersections with hydrological features could indicate damper soils and areas at greater risk of inundation. Hydrology data was brought in from Calgary's open data portal, and the number of intersections per fishnet grid cell was calculated.


#### **Mapping Significant Features**





#### Plotting Significant Features per Inundation Outcome

These six selected significant features are shown below in the plots to show differences in across fishnet grid cells that flooded and those that did not, according to the classification from the 2013 inundation extent.



# MODEL

inundationModel <glm(inundation ~ ., family="binomial"(link="logit"), data=(calgaryTrain) %>% as.data.frame() %>% dplyr::select(-ID FISHNET, -geometry))

# **MODEL RESULTS**

12977
inundation
Generalized linear model
binomial
logit

χ²(6)	4779.80
Pseudo-R <sup>2</sup> (Cragg-Uhler)	0.64
Pseudo-R <sup>2</sup> (McFadden)	0.56
AIC	3812.46
BIC	3864.75

	Est.	S.E.	z val.	р
(Intercept)	37.84	1.89	20.06	0.00
steepslope_dist	-0.00	0.00	-20.60	0.00
dist_parks	-0.00	0.00	-2.95	0.00
flowacc_max	0.00	0.00	5.49	0.00
dist_stream	-0.00	0.00	-2.50	0.01
elevation_mean	-0.04	0.00	-20.64	0.00
n_hydro_int	3.14	0.10	32.37	0.00
Standard errors: MLF				

Standard errors: MLE


All p-values are ≤ 0.05, indicating statistical significance for all of the features included.

The results of each scenario at the optimal threshold for accuracy (0.38) are displayed in the table below. These results support our above observation that the model predicts well for areas of no inundation than areas of inundation.

Type of Prediction	Description	Results
True Positive (TP)	Model predicts inundation and there is inundation	425
True Negative (TN)	Model predicts no inundation and there is no inundation	4873
False Positive (FP)	Model predicts inundation and there is no inundation	167
False Negative (FN)	Model predicts no inundation and there is inundation	96

The Receiver Operating Characteristic (ROC) Curve for the model is a helpful goodness of fit indicator, while depicting trade-offs between true positive and false positive metrics at each threshold. A line going "over" the curve shows a useful fit. The area under the curve (AUC) here is ~0.96, indicating a useful fit. A reasonable AUC is between 0.5 and 1.


Through cross-validation, the model performs at a mean of ~95% accuracy, defending the strength of the model for inundation in Calgary.




### MAPPING CALGARY PREDICTIONS

The first map shows the confusion matrix results for the test set to better understand spatial arrangement of the outcomes. The second and third maps show predictions for inundation across Calgary are mapped for each fishnet grid cell. We elected to display the predictions on a probabilities scale to achieve a more continuous surface. This left-most map shows the same predicted probabilities, but with the 2013 flood extent overlay. This helps to compare the predicted inundation outcomes with the actual data used to train the model in the first place.

### **Prediction Classes on Calgary Test Set**




### Predicted Probabilities for Inundation in Calgary



### **Predicted Probabilities for Inundation in Calgary**

2013 flood extent in red overlay



# MAPPING DENVER PREDICTIONS

Now that we have confirmed the model's high quality performance in Calgary, we see if it is generalizable to other cities. Denver, Colorado has a similar topography, infrastructure, and population to Calgary. We perform the same feature engineering for the selected features and run the model for Denver. A map of probability predictions is displayed to the right. It is clear that it predicts flooding in areas near streams, but less so elsewhere.

# CONCLUSION

This model as we have shown is strong, but not perfect. We could further refine its accuracy and generalizability by conducting more evaluation on the Denver results, exploring more engineered features, and looking at spatial differences within each context. We could also investigate dissimilar cities, like those on coasts, to assess the model's efficacy with coastal flood inundation. We are optimistic that the story being told through these data visualizations, coupled with democratizing access to the algorithm itself, can propel relevant decision-makers to better prepare for flood inundation.

#### Predicted Probabilities for Inundation in Denver

100

75

25

