

- Flaps are used to slow down aircraft & generate more lift at ~~low~~ lower speed. Increase ^{the} camber of the wing. Mostly used during takeoffs & landings. Controlled by ~~switch~~ switch & electrically actuated. Can only be moved down to 10°, 20°, & 30°.

Cessna 172 Landing gear

- Doesn't move ~~conver~~ drag to minimize drag. They can have fairings or aerodynamic covers.
- Front wheel controlled by pedals, connected by pushrods. They have shock absorber & ~~spring~~ for suspension & another called shimmy damper to avoid oscillation on its vertical axis at high speed on the ground.
- Back wheels have brakes by pedals.

Cessna 172 Cockpit:

- Primary flight display, & the MFD (multifunctional display). The plane has avionic system Garmin G 1000.
- 3 analog gauges: Airspeed indicator, altitude indicator, & altimeter in case of 2 screens fail.
- Airspeed found by pilot tube, hence goes to pilot tube when icy conditions, below wing location.
- Altimeter & vertical speed are taken from the static pressure port located on left side of fuselage. Switch can read the pressure inside if static pressure is clogged.
- The PFD was a INU (internal measuring unit) for altimeter.

- On the left in cockpit, bottom, there is switch for lights, auxiliary fuel pump, avionics & master electricity. Bottom is where circuit breaker is. Ignition switch on bottom left, has magnetor selector; always on both. In the center there is main throttle control of engine & next is the fuel mixture to richer or leaner, ~~for~~ changing depends on altitude for efficient combustion. Flap switch & on right of it is to control airflow inside cabin & temperature. Fuel shut off valve in case of any etc. Fuel selector switch on the bottom.

Cessna 172 Light & electrical system:

- Beacon light in front of vertical stabilizer, flashing red light.
- Strobe light also known as anti-collision lights are white flashing light & can be located on the end of wing tips & sometimes in other model on the tail.
- Navigation light or position light shows a light to give position for ex: ~~red on~~ constant red on left, green on right wing & white on top of vertical stabilizer. Landing tip & taxi lights are in middle of wing, leading edge are used to illuminate the ground when landing & taxiing off.