

4.7 Clustering [focusing on single linkage]



Clustering

Clustering. Given a set U of n points labeled p_1, \dots, p_n , classify into coherent groups.

↑
photos, documents, micro-organisms

Distance function. Numeric value specifying "closeness" of two objects.

↑
number of corresponding pixels whose
intensities differ by some threshold

Fundamental problem. Divide into clusters so that points in different clusters are far apart.

- Routing in mobile ad hoc networks.
- Identify patterns in gene expression.
- Document categorization for web search.
- Similarity searching in medical image databases
- Skycat: cluster 10^9 sky objects into stars, quasars, galaxies.

Clustering of Maximum Spacing


Goal: Divide objects into k non-empty groups (aka clusters): **k-clustering**

Distance function. Assume it satisfies several natural properties.

- $d(p_i, p_j) = 0$ iff $p_i = p_j$ (identity of indiscernibles)
- $d(p_i, p_j) \geq 0$ (nonnegativity)
- $d(p_i, p_j) = d(p_j, p_i)$ (symmetry)

Spacing. Min distance between any pair of points in different clusters.

Clustering of maximum spacing. Given an integer k , find a k -clustering of maximum spacing.



Greedy Clustering Algorithm

Single-linkage clustering algorithm.

- Form a graph on the vertex set U , corresponding to n clusters.
- Find the closest pair of objects such that each object is in a different cluster, and add an edge between them.
- Repeat $n-k$ times until there are exactly k clusters.


Key observation. This procedure is precisely Kruskal's algorithm (except we stop when there are k connected components).

Remark. Equivalent to finding an MST and deleting the $k-1$ most expensive edges.

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.


Observation: The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).



Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Observation: The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).




Cut Property $\Rightarrow d(e_1), d(e_4) \geq d(e_2)$

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. C^* is a k -clustering of max spacing.

Observation: The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).




Cut Property $\Rightarrow d(e_1) \geq d(e_3) \Rightarrow d(e_1) \geq \max\{d(e_2), d(e_3)\}$

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. C^* is a k -clustering of max spacing.

Observation: The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).




Cut Property $\Rightarrow d(e_4) \geq \max\{d(e_2), d(e_3)\}$

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. C^* is a k -clustering of max spacing.

Observation: The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).



$$\text{Spacing} = \max\{d(e_2), d(e_3)\}$$

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Proof?

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C_1^*, \dots, C_k^* formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Pf. Let C denote some other clustering C_1, \dots, C_k .


- The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).

Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Pf. Let C denote some other clustering C_1, \dots, C_k .

- The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).
- Let p_i, p_j be in the same cluster in C^* , say C^*_r , but different clusters in C , say C_s and C_t .




Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Pf. Let C denote some other clustering C_1, \dots, C_k .

- The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).
- Let p_i, p_j be in the same cluster in C^* , say C^*_r , but different clusters in C , say C_s and C_t .
- Some edge (p, q) on p_i - p_j path in C^*_r spans two different clusters in C .




Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Pf. Let C denote some other clustering C_1, \dots, C_k .

- The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).
- Let p_i, p_j be in the same cluster in C^* , say C^*_r , but different clusters in C , say C_s and C_t .
- Some edge (p, q) on p_i - p_j path in C^*_r spans two different clusters in C .
- All edges on p_i - p_j path have length $\leq d^*$ since Kruskal chose them (and we did not delete them from our MST).



Greedy Clustering Algorithm: Analysis

Theorem. Let C^* denote the clustering C^*_1, \dots, C^*_k formed by deleting the $k-1$ most expensive edges of a MST. Then C^* is a k -clustering of max spacing.

Pf. Let C denote some other clustering C_1, \dots, C_k .

- The spacing of C^* is the length d^* of the $(k-1)^{\text{st}}$ most expensive edge (in MST).
- Let p_i, p_j be in the same cluster in C^* , say C^*_r , but different clusters in C , say C_s and C_t .
- Some edge (p, q) on p_i - p_j path in C^*_r spans two different clusters in C .
- All edges on p_i - p_j path have length $\leq d^*$ since Kruskal chose them (and we did not delete them from our MST).
- Spacing of C is $\leq d^*$ since p and q are in different clusters. ■

