

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int a = 10;  
        int b = 3;  
        System.out.println(a / b);  
    }  
}
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

2. Which of the following is not a primitive data type?

**Answer**

string

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code snippet?

```
class DivisionExample {  
    public static void main(String[] args) {  
        double num1 = 10.5;  
        double num2 = 3;  
        int result = (int)(num1 / num2);  
        System.out.println(result);  
    }  
}
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

4. What is the output of the following code?

```
import java.util.*;  
  
class RelationalOperatorExample {  
    public static void main(String[] args) {  
        int x = 8, y = 4;  
        boolean result = (x != y);  
  
        System.out.println(result);  
    }  
}
```

**Answer**

true

**Status :** Correct

**Marks :** 1/1

5. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int a = 5;  
        int b = 10;  
  
        int sum = a + b;  
        int bitwiseAnd = a & b;  
        int bitwiseOr = a | b;  
  
        System.out.println(sum);  
        System.out.println(bitwiseAnd);  
        System.out.println(bitwiseOr);  
    }  
}
```

**Answer**

15015

**Status :** Correct

**Marks :** 1/1

6. What is the output of the following program?

```
class Arithmetic {  
    public static void main(String[] args) {  
        char ch = 'A';  
        System.out.println(ch);  
    }  
}
```

**Answer**

A

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following code snippet?

```
import java.util.*;

class OperatorPrecedenceExample {
    public static void main(String[] args) {
        int a = 5, b = 3, c = 2;
        int result = a + b * c;

        System.out.println(result);
    }
}
```

**Answer**

11

**Status :** Correct

**Marks :** 1/1

8. What is the output of the following program?

```
class Demo {
    public static void main(String[] args) {
        String text = "Hello, World!";
        System.out.println(text);
    }
}
```

**Answer**

Hello, World!

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
import java.util.*;

class TernaryOperatorExample {
    public static void main(String[] args) {
        int a = 5, b = 10;
```

```
int result = (a > b) ? a : b;  
System.out.println(result);  
}  
}
```

**Answer**

10

**Status : Correct**

**Marks : 1/1**

10. Which of the following data types is used to store floating-point numbers with greater precision?

**Answer**

double

**Status : Correct**

**Marks : 1/1**

11. What is the result of the following expression?

```
import java.util.*;
```

```
class ComplexExpressionExample {  
    public static void main(String[] args) {  
        int a = 5, b = 2, c = 3, d = 4;  
        int result = a + b * c / d - b;  
  
        System.out.println(result);  
    }  
}
```

**Answer**

4

**Status : Correct**

**Marks : 1/1**

12. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int count = 8;  
        count = count ^ 1;  
  
        System.out.println(count);  
    }  
}
```

**Answer**

9

**Status :** Correct

**Marks :** 1/1

13. Which of the following data types is used to store single characters?

**Answer**

char

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following program?

```
class DataTypesMCQ {  
    public static void main(String[] args) {  
        int a = 10;  
        double b = 5;  
        System.out.println(a / b);  
    }  
}
```

**Answer**

2.0

**Status :** Correct

**Marks :** 1/1

15. What is the output of the following code?

```
class TestClass {  
    public static void main(String[] args) {  
        int x = 5;  
        int X = 10;  
  
        int sum = x + X;  
        int bitwiseResult = x | X;  
  
        System.out.println(sum);  
        System.out.println(bitwiseResult);  
    }  
}
```

**Answer**

1515

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Gloria is responsible for monitoring the performance of two machines in a factory. She needs to determine which of the two machines is operating closest to the optimal temperature of 100 degrees Celsius using the relational operator.

Assist Gloria in displaying the machine's temperature, which is closer to 100, and the difference from 100.

##### ***Input Format***

The first line of input consists of an integer N, representing the temperature of the first machine.

The second line consists of an integer M, representing the temperature of the second machine.



### **Output Format**

The output prints "The integer closer to 100 is X with a difference of Y" where X is the temperature of the closer machine and Y is the difference from 100.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 90

80

Output: The integer closer to 100 is 90 with a difference of 10

### **Answer**

```
// You are using Java
import java.util.Scanner;
//import java.lang.Math;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int N=myobj.nextInt();
        int M=myobj.nextInt();

        int a=Math.abs(N-100);
        int b=Math.abs(M-100);

        if(a<b){
            System.out.println("The integer closer to 100 is "+N+" with a difference of
"+a);
        }

        else{
            System.out.println("The integer closer to 100 is "+M+" with a difference of
"+b);
        }
    }
}
```

Status : Correct

Marks : 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. PROBLEM STATEMENT:

Dave got two students who want help with their doubt. Each hands out an integer and wants to find if one integer is positive while the other is not divisible by 3. Write a program to achieve this and conclude for them.

##### ***Input Format***

The first line of input represents the first integer.

The second line of input represents the second integer.

##### ***Output Format***

The output should display as "One of the integers is positive while the other is not divisible by 3." or "Neither of the integers meets the condition."

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 4

3

Output: One of the integers is positive while the other is not divisible by 3.

**Answer**

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int a = myobj.nextInt();
        int b = myobj.nextInt();
        //boolean c1=(a>0 && a%3!=0);
        //boolean c2=(b>0 && b%3!=0);
        if((a>0 && b%3!=0)||(b>0 && a%3!=0)){
            System.out.println("One of the integers is positive while the other is not
divisible by 3.");
        }
        else{
            System.out.println("Neither of the integers meets the condition.");
        }
    }
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem statement

Manoj, a developer at MoneyMatters Inc., is working on improving the company's financial system. He needs to create a program that takes an integer input, converts it into a double, and displays both the original integer and the converted double value.

##### ***Input Format***

The input consists of a single integer representing a monetary amount.

##### ***Output Format***

The first line of the output displays the "Original Integer: ", followed by an integer representation of the input value.

The second line displays the "Converted Double: ", followed by a double value representing the input as a decimal value.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 20

Output: Original Integer: 20

Converted Double: 20.0

**Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main (String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        double b= a;
        System.out.println("Original Integer: "+a);
        System.out.println("Converted Double: "+b);

    }
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Vishal and Arun are discussing the properties of numbers. Vishal gives Arun two integers. He asks Arun to check if the sum of these two numbers is a multiple of their product.

Can you assist Arun and determine whether the sum is a multiple of the product?

##### ***Input Format***

The input consists of two space-separated integers.

##### ***Output Format***

The output prints:

1. "Sum is Multiple of Product" if the sum of the two numbers is divisible by their product.
2. "Sum is Not Multiple of Product" otherwise.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1 2

Output: Sum is Not Multiple of Product

### **Answer**

```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        String a=myobj.nextLine();

        String[] parts=a.split(" ");
        int b=Integer.parseInt(parts[0]);
        int c=Integer.parseInt(parts[1]);

        if((b+c)==(b*c)){
            System.out.println("Sum is Multiple of Product");
        }
        else{
            System.out.println("Sum is Not Multiple of Product");
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement:

Emily has a beautiful circular garden in her backyard. She's interested in calculating two important measurements for her garden: the circumference and the area. To do this, she needs a program that can take the radius of her circular garden as input and provide the calculated circumference and area as output. The formulas she should use are as follows:

To calculate the circumference (C) of a circle, you can use the formula:

$$C = 2 * \pi * r$$

$$A = \pi * r^2$$

Where:

C represents the circumference.

A represents the area.

$\pi$  (pi) is approximately 3.14159.

r is the radius of the circle.

Emily is not a programmer, and she needs your help to create a program that will make these calculations for her garden.

### ***Input Format***

The first line of input contains a single double-point number radius, representing the radius of the circle.

### ***Output Format***

The output should consist of two lines:

The first line should print the circumference of the circle rounded to 2 decimal places, followed by the unit "meters".

The second line should print the area of the circle rounded to 2 decimal places, followed by the unit "square meters".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 3.0

Output: Circumference: 18.85 meters

Area: 28.27 square meters

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        double num=myobj.nextFloat();
```

```
//System.out.println(num);  
double circum = 2*3.14159*num;  
double area = 3.14159*num*num;  
System.out.printf("Circumference: %.2f meters%n",circum);  
System.out.printf("Area: %.2f square meters",area);  
  
}  
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q6

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Joey is learning about bitwise operations and is working on a project that involves extracting specific bits from integers. He needs to write a program that takes an integer and the number of bits N as input and outputs the value of the lowest N bits of the integer.

Help Joey in his project to understand and visualize how bitwise operations work in practical scenarios.

##### ***Input Format***

The first line of input consists of an integer X, representing the given integer.

The second line consists of an integer N, representing the number of bits to extract.

### **Output Format**

The output displays "Result:" followed by an integer representing the value of the lowest N bits of the given integer.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 85

2

Output: Result: 1

### **Answer**

```
// You are us
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int X = myobj.nextInt();
        int N = myobj.nextInt();

        /*String c=Integer.toBinaryString(a);
        int d=Integer.parseInt(c);
        int len=c.length();

        for(int i=0;i<b && i<len;i++){
            int bit=c.charAt(len-1-i)-'0';// to pick bits from right to left if dont use -'0' it
            takesascii code

            sum+= bit*Math.pow(2,i);

        }*/
        int mask=(1<<N)-1;
        int result = X & mask;

        System.out.println("Result:"+result);
    }
}
```

Status : Correct

Marks : 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q7

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement:

Miles is working on a program that involves analyzing two integers. He wants to check if either one of the integers is both:

Less than or equal to zero, and Odd. Can you help him create a program that identifies whether either of the integers meets these conditions?

##### ***Input Format***

The input consists of two integers on separate lines, denoted as 'input1' and 'input2'.

##### ***Output Format***

A single line with a boolean result (either 'true' or 'false') indicating whether either 'input1' or 'input2' is both less than or equal to zero and odd.

Refer to the sample output for format specifications

**Sample Test Case**

Input: -45

10

Output: true

**Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        //boolean c;
        if((a<=0 && a%2!=0)||b<=0 && b%2!=0))
            System.out.println(true);
        else
            System.out.println(false);
    }
}
```

**Status :** Correct

**Marks : 10/10**



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q8

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In the Kingdom of Finance, the royal treasury is managed by the treasurer, Sir Cedric. Sir Cedric tracks the daily expenses of the kingdom using an expense report that lists three major categories: food, clothing, and utilities. However, the King wants to know if the average daily expense is greater than at least two of these categories to ensure the kingdom is spending wisely.

Your task is to help Sir Cedric determine if the average daily expense is greater than two of the categories. Specifically, you need to calculate the average of the three expenses and check if it is greater than any two categories.

Note: Use the ternary operator

### ***Input Format***

Three integers a, b, and c represent the daily expenses for food, clothing, and utilities. Each integer is provided on a single line.

### ***Output Format***

The average of the three expenses, rounded to two decimal places.

A message indicating whether the average is greater than at least two of the expense categories.

1. If the average is greater than the two smallest monthly expenses, print "Average is greater than both X and Y," where X and Y are the two smallest expenses.
2. Otherwise, display "Average is not greater than two smallest expenses".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 4

6

10

Output: 6.67

Average is greater than both 4 and 6

### ***Answer***

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        int c=myobj.nextInt();
        double avg=(a+b+c)/3.00;
        System.out.printf("%.2f\n",avg);
        if (avg>a && avg>b)
            System.out.println("Average is greater than both "+a+" and "+b);
        else if(avg>a && avg>c)
```

```
System.out.println("Average is greater than both "+a+" and "+c);  
else if(avg>b && avg>c)  
System.out.println("Average is greater than both "+b+" and "+c);  
else  
System.out.println("Average is not greater than two smallest expenses");
```

```
}
```

```
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q9

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Phill is a quality control manager at a manufacturing plant. He needs to verify if a sensor reading at a midpoint station (S2) falls exactly halfway between the readings of the previous station (S1) and the next station (S3). Help him by developing a program that checks if the second sensor reading is the average (midpoint) of the first and third sensor readings.

Use the relational operator to solve the program.

##### ***Input Format***

The first line of input consists of an integer S1, representing the sensor reading of the first station.

The second line consists of an integer S2, representing the sensor reading of the midpoint station.

The third line consists of an integer S3, representing the sensor reading of the next station.

### **Output Format**

The first line of output displays a boolean value representing whether the sensor reading at the midpoint station is halfway between the readings of the first and the next stations.

The second line displays one of the following:

1. If the result is true, print "The second integer is halfway between the first and third integers."
2. Otherwise, print "The second integer is not halfway between the first and third integers."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

7

10

Output: false

The second integer is not halfway between the first and third integers.

### **Answer**

```
// You are using Java
import java.util.Scanner;
import java.lang.Math;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        int c=myobj.nextInt();
        //int d=Math.floorDiv(a,c);
        int d=(a+c)/2;
        if (d==b)
```

```
System.out.printf("true\nThe second integer is halfway between the first  
and third integers.");  
    else  
        System.out.printf("false\nThe second integer is not halfway between the  
first and third integers.");  
  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_Q10

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### **Section 1 : Coding**

##### **1. Problem Statement**

Aishu is supervising a construction project that needs to be completed with the help of three workers: A, B, and C.

She knows how many days each of them would take to complete the entire project individually:

A can complete it in x days, B in y days, C in z days.

Initially, all three workers (A, B, and C) work together for d1 days.

After that, C leaves, and only A and B continue for another d2 days.

Then B also leaves, and A works alone to finish the remaining work.

Your task is to help aishu to implement this functionality using the class WorkDistribution and Method calculateWork(int x, int y, int z, int d1, int d2)

Calculate the total work completed in the first  $d_1$  days by A, B, and C. Calculate the work completed in the next  $d_2$  days by A and B. Determine the remaining work after these  $d_1 + d_2$  days.

### ***Input Format***

The first line of input contains five space-separated integers:  $x$   $y$   $z$   $d_1$   $d_2$

where:

$x$  represents the Days A takes to complete the work alone

$y$  represents the Days B takes to complete the work alone

$z$  represents the Days C takes to complete the work alone

$d_1$  represents the Days A, B, and C work together

$d_2$  represents the Days A and B work together (after C leaves)

### ***Output Format***

The first line of output prints "Work done in first  $d_1$  days (A+B+C): " followed by a double value rounded to 2 decimal places.

The second line of output prints "Work done in next  $d_2$  days (A+B): " followed by a double value rounded to 2 decimal places.

The third line prints "Remaining work: " followed by a double value rounded to 2 decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 10 20 30 2 2

Output: Work done in first  $d_1$  days (A+B+C): 0.37

Work done in next  $d_2$  days (A+B): 0.30

Remaining work: 0.33

### ***Answer***



```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        int c=myobj.nextInt();
        int d=myobj.nextInt();
        int e=myobj.nextInt();
        float d1 = ((1/(float)a)+(1/(float)b)+(1/(float)c))*d;
        float d2=(1/(float)a+1/(float)b)*e;
        float d3=1-(d1+d2);
        System.out.printf("Work done in first d1 days (A+B+C): %.2f%n",d1);
        System.out.printf("Work done in next d2 days (A+B): %.2f%n",d2);
        System.out.printf("Remaining work: %.2f",d3);

    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

In the Kingdom of Delivery Logistics, there is a giant truck used for transporting packages across the kingdom. The truck has a maximum capacity represented by an integer, and each package also has a specific weight. The truck's efficiency and safety depend on whether the weight of the package is below a certain threshold.

The kingdom's delivery service has a rule: if the weight of a package is less than one-third of the truck's total capacity, the package is eligible for quick processing and dispatch. However, if the weight is too heavy, the package will require special handling.

As a logistics manager, you need to check whether the weight of the package is less than one-third of the truck's total capacity.

Write a program using a ternary operator that helps determine whether the package weight meets the requirement for quick processing or if it needs special handling.

### ***Input Format***

The first line of input consists of an integer  $p$ , representing the weight of the package.

The second line consists of an integer  $w$ , representing the total weight capacity of the truck.

### ***Output Format***

The first line of output prints "One-third of Truck: X," where X is one-third of the truck's total weight capacity as a double value with two decimal places.

The second line of output displays one of the following:

1. If  $p$  is less than one-third of the truck's total weight capacity, print "Package weight is less than one-third of the truck's capacity".
2. Otherwise, print "Package weight is not less than one-third of the truck's capacity".

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 13  
60

Output: One-third of Truck: 20.00  
Package weight is less than one-third of truck's capacity

### ***Answer***

```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
```

```
int a=myobj.nextInt();
int b=myobj.nextInt();
double c=(double)b/3.00;
System.out.printf("One-third of Truck: %.2f\n",c);
if(c>a)
    System.out.println("Package weight is less than one-third of truck's
capacity");
else
    System.out.println("Package weight is not less than one-third of truck's
capacity");

}
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Mickey and Miney are walking through a magical forest. The forest is full of enchanted stones, each with a unique number. There is a legend that says the magic power of the stones can be revealed by using a special operation. To determine the magic power of a given stone, you need to perform a bitwise AND operation with the number 15.

Each stone's number is represented by an integer, and Mickey needs to find the magic power of each stone by applying this operation.

Your task is to help Mickey compute the result of the bitwise AND operation of the given stone number with 15, and print the result.

### ***Input Format***

The input consists of a single integer.

### ***Output Format***

The output should display a single integer, which is the result of the bitwise AND operation between input and 15.

Refer to the sample output for format specifications.

### **Sample Test Case**

Input: 25

Output: 9

### **Answer**

```
// You are using Scanner
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=a&15;
        System.out.println(b);
    }
}
```

**Status :** Correct

**Marks :** 10/10

### **3. PROBLEM STATEMENT:**

Maria, a software developer, is working on a project to create a simple program to determine which of two integers is closest to zero. The integers can be either positive or negative. The program needs to take two integer inputs and calculate which one is closer to zero. If both integers are equidistant from zero, the program should return 0.

#### **Input Format**

The input contains two lines:

The first line of the input contains an integer, which can be either a positive or a negative integer.

The second line of the input contains an integer, which can be either a positive or a negative integer.

#### **Output Format**

The output displays the integer that is closest to zero in the following format:

"The integer closest to zero is: [closest\_integer]"

Here, [closest\_integer] should be replaced with the integer that is closer to zero based on its absolute value.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

8

Output: The integer closest to zero is: 5

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        if (Math.abs(a)==Math.abs(b))
            System.out.printf("The integer closest to zero is: 0");

        else if(Math.abs(a)<Math.abs(b))
            System.out.printf("The integer closest to zero is: %d",a);

        else
            System.out.printf("The integer closest to zero is: %d",b);
    }
}
```

Status : Correct

Marks : 10/10

#### 4. PROBLEM STATEMENT:

Maria, a software developer, is working on a program to determine if two given integers which can be either positive or negative integers have the same parity (both even or both odd). She needs your help in writing this program.

Write a program that takes two integers as input and checks if both integers are either even or odd.

##### **Input Format**

The input consists of two lines:

The first line consists of an integer (input1) which can be either positive or negative.

The second line consists of an integer (input2) which can be either positive or negative.

##### **Output Format**

The output is displayed in the following format:

If both integers have the same parity (i.e., both even or both odd), print:

"Both integers are either even or odd"

Otherwise, print:

"The integers have different parities"

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 2

-4

Output: Both integers are either even or odd

**Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{  
    public static void main(String[] args){  
        Scanner myobj=new Scanner(System.in);  
        int a=myobj.nextInt();  
        int b=myobj.nextInt();  
        if((a%2==0 && b%2==0)||(a%2!=0 && b%2!=0))  
            System.out.println("Both integers are either even or odd");  
        else  
            System.out.println("The integers have different parities");  
    }  
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 1\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

In a logistics company, each delivery pack contains a specific number of items, and the priority customer receives double the amount. Write a program to determine the total number of delivery packs required for the operation, considering the number of items per pack and the number of customers given as input by the user.

##### Example

Input:

Number of items per pack = 96

Number of customers = 8

Output:

10

Explanation:

Given the number of items per pack = 96 and the number of customers = 8, the calculations are as follows:

Total number of items needed = number of items per pack \* number of customers =  $96 * 8 = 768$ . Priority customer's share = double the amount of items per pack =  $2 * 96 = 192$ . Total items with the priority customer = total items needed + priority share =  $768 + 192 = 960$ . Number of packs needed =  $(960 + 96 - 1) / 96 = 10.98$ . Since we cannot have a fraction of a pack, the output is 10.

### **Input Format**

The input consists of two space-separated integers N and C, representing the number of items per pack and the number of customers.

### **Output Format**

The output displays an integer, representing the total number of delivery packs required for the operation.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1 1

Output: 3

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        int t_=a*b;
        int p_cus=2*a;
```

```
int total=t_+p_cus;  
int pack=(total+a-1)/a;  
System.out.println(pack);  
  
}  
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Mandy is a software engineer working on a program to analyze two integers based on specific conditions using a logical operator. She needs to determine if both integers are odd or if at least one of them is divisible by 7.

Depending on the result, she wants to print different messages.

If the condition is met, the program should identify and print the first number that is divisible by 7 or indicate that both numbers are odd. If the condition is not met, the program should print a message indicating the condition was not met, along with the input numbers.

### **Input Format**

The first line of input consists of an integer representing the first input number.

The second line consists of an integer representing the second input number.

### **Output Format**

The output displays "Condition met: " followed by an integer representing the first number divisible by 7, or prints "Both numbers are odd" if the two inputs are odd.

If the condition is not met, it displays "Conditions not met: " followed by the two input integers, separated by a space.

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 7

14

Output: Condition met: 7

### Answer

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();

        if(a%7==0)
            System.out.println("Condition met: "+a);
        else if(b%7==0)
            System.out.println("Condition met: "+b);
        else if(a%2!=0 && b%2!=0)
            System.out.println("Condition met: Both numbers are odd");
        else
            System.out.printf("Conditions not met: %d %d",a,b);
    }
}
```

Status : Correct

Marks : 10/10

### 3. Problem Statement

Mandy is working on a cybersecurity project that involves basic encryption techniques. She wants to write a program that takes an integer number and performs a bitwise XOR operation to flip all the bits.

Help Mandy in this encryption using bitwise operations.

#### Input Format

The input consists of an integer N, representing the number to be flipped.

#### Output Format

The output displays "Result: " followed by an integer representing the result of the bitwise XOR operation to flip all the bits.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 0

Output: Result: 255

### **Answer**

```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        /*String b=Integer.toBinaryString(a);
        int c=Integer.parseInt(b);
        int sum=0;

        for(int i=0;i<8;i++){
            int d=c%10;
            c=c/10;
            if(d==0) //flipping bits
                sum+=Math.pow(2,i);
        }
        System.out.printf("Result: %d", sum); */
        System.out.printf("Result: %d", 255^a);
    }
}
```

**Status : Correct**

**Marks : 10/10**

### **4. Problem Statement:**

"Write a program that helps identify the type of a triangle based on the lengths of its three sides. The program prompts the user to input the lengths of sides 'a,' 'b,' and 'c,' and then it classifies the triangle as 'Equilateral' if all sides are equal, 'Isosceles' if two sides are equal, or 'Scalene' if all sides are different. Can you provide the Java code for this task?"

### ***Input Format***

The first line of the input is an integer 'a' representing the length of side 'a.'

The second line of the input is an integer 'b' representing the length of side 'b.'

The third line of the input is an integer 'c' representing the length of side 'c.'

### ***Output Format***

The program outputs a single line that specifies the type of the triangle: "Equilateral," "Isosceles," or "Scalene."

### ***Sample Test Case***

Input: 3

4

5

Output: The triangle is Scalene

### ***Answer***

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        int b=myobj.nextInt();
        int c=myobj.nextInt();
        //if(a==b&&(a!=c||b!=c)||((b==c&&())))
        //System.out.println("The triangle is Isosceles");
        if(a!=b&&b!=c&&c!=a)
            System.out.println("The triangle is Scalene");
        else if (a==b&&b==c&&c==a)
            System.out.println("The triangle is Equilateral");
    }
}
```

```
        else  
            System.out.println("The triangle is Isosceles");  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 14

#### Section 1 : MCQ

1. What will be the output of the following code?

```
class Test {  
    public static void main(String[] args) {  
        int num = 15;  
        if (num > 10)  
            if (num % 3 == 0)  
                System.out.print("Divisible");  
            else  
                System.out.print("Not Divisible");  
        }  
    }  
}
```

**Answer**

Divisible



**Status :** Correct

**Marks :** 1/1

2. What will be the output of the following code?

```
class Main {  
    public static void main(String[] args) {  
        for (int i = 5; i > 0; i--) {  
            System.out.print(i + " ");  
        }  
    }  
}
```

**Answer**

5 4 3 2 1

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        int i = 10;  
        do {  
            System.out.print(i + " ");  
            i -= 3;  
        } while(i > 0);  
    }  
}
```

**Answer**

10 7 4 1

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following code?

```
class LoopTest {  
    public static void main(String[] args) {
```

```
int i = 1;
while (i > 0) {
    System.out.print(i + " ");
    i++;
    if (i == 5) break;
}
}
```

**Answer**

1 2 3 4

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
class Test {
    public static void main(String[] args) {
        int x = 5, y = 2;
        if (x + y == 10)
            System.out.print("Ten");
        else if (x - y == 3)
            System.out.print("Three");
        else
            System.out.print("None");
    }
}
```

**Answer**

Three

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following Java code snippet?

```
public class Main {
    public static void main(String[] args) {
        int score = 75;
        if(score >= 90) {
```

```
        System.out.println("Grade: A");
    } else if(score >= 80) {
        System.out.println("Grade: B");
    } else if(score >= 70) {
        System.out.println("Grade: C");
    } else {
        System.out.println("Grade: D");
    }
}
}
```

**Answer**

Grade: C

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following Java code snippet?

```
public class Main {
    public static void main(String[] args) {
        int day = 4;
        String result = "";
        switch(day) {
            case 1:
                result = "Monday";
                break;
            case 2:
                result = "Tuesday";
                break;
            case 3:
                result = "Wednesday";
                break;
            default:
                result = "Other Day";
        }
        System.out.println(result);
    }
}
```

**Answer**

Other Day

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        int i = 1;  
        while(i < 10) {  
            i += 2;  
        }  
        System.out.println(i);  
    }  
}
```

**Answer**

11

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
class ConditionTest {  
    public static void main(String[] args) {  
        int x = 10;  
        if (x > 5)  
            System.out.print("High");  
    }  
}
```

**Answer**

High

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```

class Loop {
    public static void main(String[] args) {
        for (int i = 1; i <= 3; i++) {
            for (int j = 1; j <= 2; j++) {
                System.out.print(i + "" + j + " ");
            }
        }
    }
}

```

**Answer**

11 12 21 22 31 32

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following code?

```

public class Main {
    public static void main(String[] args) {
        for(int i = 1; i <= 20; i = i * 2) {
            System.out.print(i + " ");
        }
    }
}

```

**Answer**

1 2 4 8 16

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following code?

```

class Test {
    public static void main(String[] args) {
        int a = 4, b = 5;
        if ((a + b) % 2 == 0)
            System.out.print("Even");
        else

```

```
        System.out.print("Odd");  
    }  
}
```

**Answer**

Odd

**Status : Correct**

**Marks : 1/1**

13. What will be the output of the following code?

```
public class Main {  
    public static void main(String[] args) {  
        int sum = 0;  
        for(int i = 1; i <= 5; i++) {  
            sum += i;  
        }  
        System.out.println(sum);  
    }  
}
```

**Answer**

15

**Status : Correct**

**Marks : 1/1**

14. What will be the output of the following code?

```
class LoopTest {  
    public static void main(String[] args) {  
        int i = 1;  
        do {  
            System.out.print(i + " ");  
            i *= 2;  
        } while (i <= 8);  
    }  
}
```

**Answer**

1 2 4 8 10

**Status :** Wrong

**Marks :** 0/1

15. What will be the output of the following code?

```
class ConditionTest {  
    public static void main(String[] args) {  
        int a = 7;  
        if (a == 7)  
            System.out.print("Match");  
        else  
            System.out.print("No Match");  
    }  
}
```

**Answer**

Match

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Arun is working on a project to automate the process of determining whether a student has passed or failed based on their subject marks.

He aims to create a simple program that takes positive integers as marks for five subjects from the user. If the average of the marks is greater than or equal to 50, the student has passed the exam. Otherwise, the student has failed.

Help Arun to implement the project.

##### ***Input Format***

The input consists of five space-separated integers, representing the marks in five subjects.



### **Output Format**

The first line of output prints "Average score: " followed by an integer representing the average score.

The second line prints one of the following:

1. If the condition is satisfied, print "The student has passed".
2. Otherwise, the output prints "The student has failed".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 50 60 70 80 90

Output: Average score: 70

The student has passed

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{  
    public static void main(String[] args){  
        Scanner myobj=new Scanner(System.in);  
        int a=myobj.nextInt();  
        int b=myobj.nextInt();  
        int c=myobj.nextInt();  
        int d=myobj.nextInt();  
        int e=myobj.nextInt();  
        int avg=(a+b+c+d+e)/5;  
        System.out.println("Average score: "+ avg);  
        if (avg>=50)  
            System.out.println("The student has passed");  
        else  
            System.out.println("The student has failed");  
    }  
}
```

Status : Correct

Marks : 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Samantha is a diligent math student who is exploring the world of programming. She is learning Java and has recently studied conditional statements. One day, her teacher gives her an interesting problem to solve, which takes a number as input and checks whether it is a multiple of 5 or 7.

Help her complete the task.

##### ***Input Format***

The input consists of a single integer N, representing the number to be checked.

##### ***Output Format***

If the number is a multiple of 5 but not 7, the output prints "N is a multiple of 5"

If the number is a multiple of 7, the output prints "N is a multiple of 7".

Otherwise the output prints "N is neither multiple of 5 nor 7" where N is an entered integer.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10

Output: 10 is a multiple of 5

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int a=myobj.nextInt();
        if(a%5==0)
            System.out.println(a+" is a multiple of 5");
        else if(a%7==0)
            System.out.println(a+" is a multiple of 7");
        else if (a%5!=0 && a%7!=0)
            System.out.printf("%d is neither multiple of 5 nor 7",a);
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John is a fitness trainer, and he wants to use the BMI calculator to assess the body mass index of his clients. He has a list of clients based on their height and weight.

John plans to write a program to quickly determine the BMI and provide a classification for each client.

If BMI is less than 18.5, the program will classify it as "Underweight" If BMI is between 18.6 and 24.9, the program will classify it as "Normal Weight" If BMI is between 25.0 and 29.9, the program will classify it as "Overweight" If BMI is 30.0 or higher, the program will classify it as "Obese"

Note: Formula to calculate BMI =  $\text{weight}/(\text{height}*\text{height})$

***Input Format***

The first line of input consists of a double value, representing the height of the person in meters.

The second line consists of a double value, representing the weight of the person in kilograms.

### ***Output Format***

The first line of output prints "BMI: " followed by a double (rounded to two decimal places) representing the calculated BMI.

The second line prints "Classification: " followed by a string indicating the BMI category (Underweight, Normal Weight, Overweight, or Obese).

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1.2

45.2

Output: BMI: 31.39

Classification: Obese

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        double ht=myobj.nextDouble();
        double bt=myobj.nextDouble();
        double bmi=bt/(ht*ht);
        System.out.printf("BMI: %.2f\n",bmi);
        if(bmi<18.5)
            System.out.println("Classification: Underweight");
        else if(bmi>18.6 && bmi<24.9)
            System.out.println("Classification: NormalWeight");
        else if(bmi>25.0 && bmi<29.9)
            System.out.println("Classification: Overweight");
        else
```

```
        System.out.println("Classification: Obese");  
    }  
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Amit wants to evaluate the depreciation of his car over time to understand its current value and categorize it based on that value.

Write a program that helps him determine the current value of his car after a certain number of years of depreciation and classify it into one of three categories:

High: If the current value is greater than 10,000. Medium: If the current value is between 5,000 and 10,000, both inclusive. Low: If the current value is less than 5,000.

The depreciation rate of the car is 15% per year. The program should calculate the current value of the car after applying this depreciation over the given number of years and print the current value along with the category.



### ***Input Format***

The first line of input consists of an integer, representing the initial cost of the car.

The second line consists of an integer, representing the number of years the car has been depreciating.

### ***Output Format***

The first line of output prints a double value, representing the current value of the car, rounded off to two decimal places "Current Value: <value>".

The second line prints its category "Category: <categories>".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 20000  
5

Output: Current Value: 8874.11  
Category: Medium

### ***Answer***

```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int cost = myobj.nextInt();
        int years= myobj.nextInt();
        double Value=cost;
        for(int i=0;i<years;i++){
            Value=Value*0.85; }//15%depriciation

        System.out.printf("Current Value: %.2f",Value);
        if (Value > 10000) {
            System.out.println("\nCategory: High");
        } else if (Value >= 5000) {
```

```
        System.out.println("\nCategory: Medium");
    } else {
        System.out.println("\nCategory: Low");
    }
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ted, the computer science enthusiast, has accepted the challenge of writing a program that checks if the number of digits in an integer matches the sum of its digits.

Guide Ted in designing and writing the code to solve this problem using a 'do-while' loop.

##### ***Input Format***

The input consists of an integer N, representing the number to be checked.

##### ***Output Format***

If the sum is equal to the number of digits, print "The number of digits in N matches the sum of its digits."

Else, print "The number of digits in N does not match the sum of its digits."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 20

Output: The number of digits in 20 matches the sum of its digits.

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj= new Scanner(System.in);
        int a=myobj.nextInt();
        int count=0;
        int sum_=0;
        int c=Math.abs(a);
        do{
            int b=c%10;
            sum_+=b;
            count ++;
            c=c/10;
            //count +=1;
            //sum+=b;
        }while(c>0);

        if(sum_==count)
            System.out.printf("The number of digits in %d matches the sum of its
digits.",a);
        else
            System.out.printf("The number of digits in %d does not match the sum of its
digits.",a);
    }
}
```

Status : Correct

Marks : 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q6

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Maya, a student in an arts and crafts class, wants to create a pattern using stars (\*) in a specific format. She plans to use a program to help her construct the pattern.

Write a program that takes an integer as input and constructs the following pattern using nested for loops.

Input: 5

Output:

```
*  
* *
```

```
* * *
* * * *
* * * * *
* * * *
* * *
* *
*
*
```

### ***Input Format***

The input consists of a number (integer) representing the number of rows.

### ***Output Format***

The output displays the required pattern.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 5

Output: \*

```
* *
* * *
* * * *
* * * * *
* * * *
* * *
* *
*
*
```

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
```

```
Scanner myobj = new Scanner(System.in);
int a =myobj.nextInt();
for(int i=1;i<=a;i++){
    for(int j=1;j<=i;j++){
        System.out.print(" *");
    }
    System.out.println();
}
for(int j=a-1;j>=1;j--){
    for(int k=1;k<=j;k++){
        System.out.print(" *");
    }
    System.out.println();
}
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q7

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are taking part in a coding challenge where your task is to design a program that conjures a mesmerizing numerical pyramid pattern. The enchanting pattern is fashioned using a for loop and is customized based on user input.

Participants are prompted to unveil the pyramid's magic by specifying its height - essentially dictating the number of rows in this spellbinding creation.

Write a program that employs to weave this captivating numerical pyramid as shown below.

Example

Input:

4

Output:

### ***Input Format***

The input consists of a positive integer n representing the number of rows in the pattern.

### ***Output Format***

The output prints the required pyramid pattern, as shown in the sample output.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 4

Output: 1

123

12345

1234567

### ***Answer***

```
import java.util.Scanner;

public class Main{
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int n = scanner.nextInt();

        for (int i = 1; i <= n; i++) {
            for (int space = 1; space <= n - i; space++) {
                System.out.print(" ");
            }
            for (int num = 1; num <= (2 * i - 1); num++) {
                System.out.print(num);
            }
        }
    }
}
```

```
        System.out.println();  
    }  
    scanner.close();  
}  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_Q8

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

A bank generates secure codes using 3-digit numbers where each digit is unique, and the code must be divisible by 3. You are tasked with generating the first N such codes based on user input, ensuring the digits are unique and the number is divisible by 3.

Note: Use nested for loops to solve.

##### ***Input Format***

The first line contains an integer N representing the number of valid codes to generate.

##### ***Output Format***

The output prints N lines, each line contains a valid 3-digit code.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

Output: 102

105

108

120

123

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int n = myobj.nextInt();
        int j=100;
        while(n!=0){
            int m=j%3;
            int a=j%10;
            int b=(j%100)/10;
            int c=(j%1000)/100;
            if(m==0 && (a!=b && b!=c && c!=a))
            {
                System.out.println(j);
                n=n-1;
            }
            j++;
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

You are given a number of distribution centers (rows) and are tasked with generating a zigzag shipment route pattern. Each shipment route should alternate between left-to-right and right-to-left, as described below.

The program should print the zigzag pattern with a tab (\t) separating the columns. For each row, the shipment numbers should follow a diagonal pattern where numbers are placed in a zigzag, left to right on odd rows and right to left on even rows.

##### ***Input Format***

The input consists of an integer N, which represents the number of distribution centers (rows) for the zigzag pattern.

### Output Format

The output prints the zigzag pattern with N rows, formatted with a tab space (\t) separating the columns.

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 5

Output:       1  
          2  6  
         3  7  10  
         4  8  11  13  
         5  9  12  14  15

### Answer

```
import java.util.*;

public class Main{
    public static void main(String[] args) {
        Scanner ss = new Scanner(System.in);
        int n = ss.nextInt();
        for(int i=1;i<=n;i++){
            int j=0;
            int s=i;
            int q=1;
            for(int p=n-i;p>0;p--){
                System.out.print("\t");
            }
            while(j<i){
                System.out.printf("%d\t\t",s);
                s=s+(n-q);
                j++;
                q++;
            }
            System.out.printf("\n");
        }
    }
}
```

Status : Correct

Marks : 10/10

## 2. Problem Statement

Ravi wants to estimate the total utility bill for a household based on the consumption of electricity, water, and gas.

Write a program to calculate the total bill using the following criteria:

The cost per unit for electricity is 0.12, for water is 0.05, and for gas is 0.08. A discount is applied to the total cost based on the following conditions: If the total cost is 100 or more, a 10% discount is applied. If the total cost is between 50 and 99.99, a 5% discount is applied. No discount is applied if the total cost is less than 50.

The program should output the total bill after applying the discount with two decimal places.

### **Input Format**

The input consists of three double values, representing the number of units consumed for electricity, water, and gas respectively.

### **Output Format**

The output prints a double value, representing the total bill after applying the discount, formatted to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1000.0

200.0

100.0

Output: 124.20

### **Answer**

```
// You are using Java
import java.util.Scanner;
```



```

public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        double e=myobj.nextDouble();
        double w=myobj.nextDouble();
        double g=myobj.nextDouble();
        double e_c=e*0.12;
        double w_c=w*0.05;
        double g_c=g*0.08;
        double total=e_c + w_c + g_c;
        double tot;
        if(total>100)
            tot=(total-(total*0.10)); // total - 10%discount
        else if(total>50 && total<99.99)
            tot=total*0.95;// 5% == > rem 95%
        else
            tot=total;

        System.out.printf("%.2f",tot);

    }
}

```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

Rohit is tasked with designing a program to analyze the digits of a given integer.

Write a program to help Rohit that takes an integer as input and identifies the minimum odd digit and the maximum even digit present in the number. If no odd or even digits are present, display appropriate messages.

Implement the solution using a 'while' loop to iterate through the digits of the given number.

#### **Input Format**

The input consists of an integer n.

### **Output Format**

The first line of output prints the message "Minimum odd digit: " followed by an integer representing the smallest odd digit found in the input number.

If no odd digit exists, it prints "There are no odd digits in the number."

The second line of output prints the message "Maximum even digit: " followed by an integer representing the largest even digit found in the input number.

If no even digit exists, it prints "There are no even digits in the number."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3465

Output: Minimum odd digit: 3

Maximum even digit: 6

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int n = myobj.nextInt();
        int temp = n;
        int [] array=new int[5];
        int digit,minodd=10,maxeven=0;
        while(temp>0){
            digit = temp%10;
            if(digit%2==0){
                if(digit>maxeven)
                    maxeven=digit;
            }
            else{
                if(digit<minodd)
```

```

        minodd=digit;
    }
    temp=temp/10;
}
if(minodd==10)
    System.out.printf("There are no odd digits in the number.%n");
else
    System.out.printf("Minimum odd digit: %d%n",minodd);

if(maxeven==0)
    System.out.printf("There are no even digits in the number.%n");
else
    System.out.printf("Maximum even digit: %d",maxeven);

    }
}

```

**Status :** Correct

**Marks : 10/10**

#### 4. Problem Statement

Sampad is a high school teacher who wants to convert numeric grades into letter grades.

Write a program that accepts a numeric grade as input. The program should then convert this numeric grade into a letter grade based on specific conditions. The letter grades are A, B, C, D and F.

The conversion is determined by the following conditions:

If the numeric grade is 90 or higher, it's an "A" If the numeric grade is between 80 and 89 (inclusive), it's a "B" If the numeric grade is between 70 and 79 (inclusive), it's a "C" If the numeric grade is between 60 and 69 (inclusive), it's a "D" If the numeric grade is below 60, it's an "F"

##### **Input Format**

The input consists of an integer representing the numeric grade of the student.

### **Output Format**

The output prints the letter grade corresponding to the input numeric grade as "Letter Grade: <grade>".

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 85

Output: Letter Grade: B

### **Answer**

```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int a = myobj.nextInt();
        if(a>=90)
            System.out.println("Letter Grade: A");
        else if(a>=80 && a<=89)
            System.out.println("Letter Grade: B");
        else if(a>=70 && a<=79)
            System.out.println("Letter Grade: C");
        else if(a>=60 && a<=69)
            System.out.println("Letter Grade: D");
        else if(a<60)
            System.out.println("Letter Grade: F");

    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 2\_CY

Attempt : 2  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Samantha is a diligent math student who is exploring the world of programming. She is learning Java and has recently studied conditional statements. One day, her teacher gives her an interesting problem to solve, which takes a number as input and checks whether it is a multiple of 5 or 7.

Help her complete the task.

##### ***Input Format***

The input consists of a single integer N, representing the number to be checked.

##### ***Output Format***

If the number is a multiple of 5 but not 7, the output prints "N is a multiple of 5"

If the number is a multiple of 7, the output prints "N is a multiple of 7".

Otherwise the output prints "N is neither multiple of 5 nor 7" where N is an entered integer.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10

Output: 10 is a multiple of 5

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int a = myobj.nextInt();
        if(a%5==0)
            System.out.printf("%d is a multiple of 5",a);
        else if(a%7==0)
            System.out.printf("%d is a multiple of 7",a);
        else if(a%5!=0 && a%7!=0)
            System.out.printf("%d is neither multiple of 5 nor 7",a);

    }
}
```

**Status :** Correct

**Marks :** 10/10

## **2. Problem Statement**

Raj is solving a physics problem involving projectile motion, where he

needs to calculate the time a ball hits the ground using a quadratic equation of the form  $ax^2 + bx + c = 0$ . Depending on the coefficients, the ball may hit the ground once, twice, or not at all in real time.

Help Raj find all real roots of the equation, if any.

Note: discriminant =  $b^2 - 4ac$

### ***Input Format***

The input consists of three space-separated doubles a, b, and c, representing the coefficients of the quadratic equation.

### ***Output Format***

If there are two real roots, print:

- "Two real solutions:"
- "Root1 = <value>"
- "Root2 = <value>"

If there is one real root, print:

- "One real solution:"
- "Root = <value>"

If there are no real roots, print:

- "There are no real solutions."

Note: values are rounded to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1 6 9

Output: One real solution:

Root = -3.00

### ***Answer***

```

import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        double a = sc.nextDouble();
        double b = sc.nextDouble();
        double c = sc.nextDouble();

        double discriminant = b * b - 4 * a * c;

        if (discriminant > 0) {
            double root1 = (-b + Math.sqrt(discriminant)) / (2 * a);
            double root2 = (-b - Math.sqrt(discriminant)) / (2 * a);
            System.out.println("Two real solutions:");
            System.out.printf("Root1 = %.2f\n", root1);
            System.out.printf("Root2 = %.2f\n", root2);
        } else if (discriminant == 0) {
            double root = -b / (2 * a);
            System.out.println("One real solution:");
            System.out.printf("Root = %.2f\n", root);
        } else {
            System.out.println("There are no real solutions.");
        }

        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Noah is analyzing numbers within a given range  $[A, B]$  and wants to calculate a special sum. For each number in the range, he calculates the product of its odd digits (ignoring even digits). If the number contains no odd digits, it is skipped. The sum of these products for all numbers in the range is the result.



Write a program to compute this sum.

Example

Input:

10 12

Output:

3

Explanation:

For 10, odd digits = 1, product = 1.

For 11, odd digits = 1, 1, product =  $1 * 1 = 1$ .

For 12, odd digits = 1, product = 1.

Total sum =  $1 + 1 + 1 = 3$

### ***Input Format***

The input consists of two space-separated integers A and B, representing the inclusive range boundaries.

### ***Output Format***

The output prints a single integer representing the sum of the products of odd digits for all numbers in the range.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 10 12

Output: 3

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
```

```

public static void main(String[] args){
    Scanner myobj = new Scanner(System.in);
    int a=myobj.nextInt();
    int b=myobj.nextInt();
    int sum=0;
    int c;
    /*for(int i=a;i<=b;i++){
        if(i%2==0){
            product=1;
            sum+=product;
        }

        else{
            int temp=i;
            product=1;
            while(temp>0){
                c=temp%10;
                temp=temp/10;
                product*=c;
                //sum+=product;
            }
            sum+=product;
        }
    }*/
    for (int i = a; i <= b; i++) {
        int product = 1;
        boolean OddDigit = false;

        int temp = i;
        while (temp > 0) {
            int digit = temp % 10;
            if (digit % 2 == 1) { // odd digit
                product *= digit;
                OddDigit = true;
                temp /= 10;
            }
            //temp /= 10;
        }
        else{
            product *=1;
            temp/=10;
        }
    }
}

```

```

        if (OddDigit) {
            sum += product;
        }
    }
    System.out.println(sum);
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

John is a fitness trainer, and he wants to use the BMI calculator to assess the body mass index of his clients. He has a list of clients based on their height and weight.

John plans to write a program to quickly determine the BMI and provide a classification for each client.

If BMI is less than 18.5, the program will classify it as "Underweight" If BMI is between 18.6 and 24.9, the program will classify it as "Normal Weight" If BMI is between 25.0 and 29.9, the program will classify it as "Overweight" If BMI is 30.0 or higher, the program will classify it as "Obese"

Note: Formula to calculate BMI =  $\text{weight}/(\text{height} \times \text{height})$

##### **Input Format**

The first line of input consists of a double value, representing the height of the person in meters.

The second line consists of a double value, representing the weight of the person in kilograms.

##### **Output Format**

The first line of output prints "BMI: " followed by a double (rounded to two decimal places) representing the calculated BMI.

The second line prints "Classification: " followed by a string indicating the BMI

category (Underweight, Normal Weight, Overweight, or Obese).

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1.2

45.2

Output: BMI: 31.39

Classification: Obese

### **Answer**

// You are using Java

import java.util.Scanner;

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
  
        double height = sc.nextDouble();  
        double weight = sc.nextDouble();  
  
        double bmi = weight / (height * height);  
        System.out.printf("BMI: %.2f%n", bmi);  
  
        if (bmi < 18.5) {  
            System.out.println("Classification: Underweight");  
        } else if (bmi <= 24.9) {  
            System.out.println("Classification: Normal Weight");  
        } else if (bmi <= 29.9) {  
            System.out.println("Classification: Overweight");  
        } else {  
            System.out.println("Classification: Obese");  
        }  
  
        sc.close();  
    }  
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 3\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[][] a = {  
            {1, 2},  
            {3, 4}  
        };  
        int sum = 0;  
        for (int i = 0; i < a.length; i++)  
            for (int j = 0; j < a[0].length; j++)  
                sum += a[i][j];  
        System.out.println(sum);  
    }  
}
```

**Answer**

10

**Status :** Correct

**Marks :** 1/1

2. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] nums = {3, 6, 7, 2, 8};  
        int sum = 0;  
        for (int i = 0; i < nums.length; i++) {  
            if (nums[i] % 2 == 0)  
                sum += nums[i];  
        }  
        System.out.println(sum);  
    }  
}
```

**Answer**

16

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
class M {  
    public static void main(String[] args) {  
        int[][] arr = {  
            {1, 2},  
            {3, 4},  
            {5, 6}  
        };  
  
        for (int i = 0; i < arr.length; i++) {  
            System.out.print(arr[i][0] + " ");  
        }  
    }  
}
```

```
}
```

**Answer**

1 3 5

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following code?

```
class Sample {  
    public static void main(String[] args) {  
        int[][] data = {  
            {1, 2},  
            {3, 4}  
        };  
        int sum = 0;  
  
        for (int[] row : data) {  
            for (int val : row) {  
                sum += val;  
            }  
        }  
  
        System.out.println("Sum = " + sum);  
    }  
}
```

**Answer**

Sum = 10

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 1, 3, 1, 4};  
        int count = 0;  
        for (int i = 0; i < a.length; i++) {
```

```
        if (a[i] == 1) count++;
    }
    System.out.println(count);
}
}
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
class ReverseArray {
    public static void main(String[] args) {
        int[] a = {1, 2, 3, 4};
        for (int i = 0; i < a.length / 2; i++) {
            int temp = a[i];
            a[i] = a[a.length - 1 - i];
            a[a.length - 1 - i] = temp;
        }
        for (int i : a)
            System.out.print(i + " ");
    }
}
```

**Answer**

4 3 2 1

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following code?

```
class Q {
    public static void main(String[] args) {
        int[] a = {1, 2, 3, 4};
        for (int i = 0; i < a.length; i++) {
            if (a[i] % 2 == 0)
                a[i] = 0;
        }
    }
}
```



```
}  
    System.out.println(a[1] + " " + a[3]);  
}  
}
```

**Answer**

0 0

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
class Sample {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 3};  
        int product = 1;  
        for (int i = 0; i < a.length; i++) {  
            product *= a[i];  
        }  
        System.out.println(product);  
    }  
}
```

**Answer**

6

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[][] arr = {  
            {5, 6, 7},  
            {8, 9, 10}  
        };  
        System.out.println(arr[0][2]);  
    }  
}
```

**Answer**

7

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[][] a = {  
            {1, 2},  
            {3, 4}  
        };  
        for (int i = 0; i < a.length; i++) {  
            for (int j = 0; j < a[0].length; j++) {  
                System.out.print(a[i][j] + " ");  
            }  
        }  
    }  
}
```

**Answer**

1 2 3 4

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] a = {1, 2, 3, 4};  
        for (int i = 0; i < a.length / 2; i++) {  
            int temp = a[i];  
            a[i] = a[a.length - 1 - i];  
            a[a.length - 1 - i] = temp;  
        }  
        System.out.println(a[0]);  
    }  
}
```

```
}
```

**Answer**

4

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the given code?

```
public class Main {  
    public static void main(String[] args) {  
        int[] arr = {1, 2, 3, 4, 5};  
        int n = arr.length;  
        int temp = arr[0];  
  
        for (int i = 0; i < n - 1; i++) {  
            arr[i] = arr[i + 1];  
        }  
        arr[n - 1] = temp;  
  
        for (int num : arr) {  
            System.out.print(num + " ");  
        }  
    }  
}
```

**Answer**

2 3 4 5 1

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following code?

```
class Q {  
    public static void main(String[] args) {  
        int[] nums = {4, 2, 9, 5};  
        int max = nums[0];  
        for (int i = 1; i < nums.length; i++) {  
            if (nums[i] > max)
```

```
        max = nums[i];
    }
    System.out.println(max);
}
}
```

**Answer**

9

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following code?

```
public class Test {
    public static void main(String[] args) {
        int[] x = {4, 8, 12};
        int result = x[0] * x[2];
        System.out.println(result);
    }
}
```

**Answer**

48

**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following code?

```
class Sample {
    public static void main(String[] args) {
        int[][] matrix = {
            {1, 2, 3},
            {4, 5, 6}
        };
        System.out.println(matrix[1][2]);
    }
}
```

**Answer**

6

Status : Correct

Marks : 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 3\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Rosh is intrigued by numerical patterns. Today, she stumbled upon a puzzle while working with arrays. She wants to compute the sum of the third-largest and second-smallest elements from a list of integers. She seeks your help to implement a program that solves this for her efficiently.

##### ***Input Format***

The first line of input is an integer N, representing the size of the array.

The second line of input consists of N space-separated integers, representing the elements of the array.

##### ***Output Format***

The output displays a single integer representing the sum of the third-largest and second-smallest elements in the array.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 10

10 20 30 40 50 60 70 80 90 100

Output: 100

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String args[]){
        Scanner myobj = new Scanner(System.in);
        int size = myobj.nextInt();
        int[] arr=new int[size];
        for(int i =0;i<size;i++){
            arr[i]=myobj.nextInt();
            //System.out.println(numbers[i]);
        }
        for(int i=0;i<size-1;i++){
            for(int j=0;j<size-1-i;j++){
                if(arr[j]>arr[j+1])
                {
                    int temp=arr[j];
                    arr[j]=arr[j+1];
                    arr[j+1]=temp;
                }
            }
        }
        if(size>=3){
            int sum=arr[1]+arr[size-3];
            System.out.println(sum); }
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 3\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Monica is interested in finding a treasure but the key to opening is to get the sum of the main diagonal elements and secondary diagonal elements.

Write a program to help Monica find the diagonal sum of a square 2D array.

Note: The main diagonal of the array consists of the elements traversing from the top-left corner to the bottom-right corner. The secondary diagonal includes elements from the top-right corner to the bottom-left corner.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of rows and columns.



The following N lines consist of N space-separated integers, representing the 2D array elements.

### **Output Format**

The first line of output prints "Sum of the main diagonal: " followed by an integer, representing the sum of the main diagonal.

The second line prints "Sum of the secondary diagonal: " followed by an integer, representing the sum of the secondary diagonal.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

1 2 3

4 5 6

7 8 9

Output: Sum of the main diagonal: 15

Sum of the secondary diagonal: 15

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
```

```
    public static void main(String[] args){
```

```
        Scanner myobj = new Scanner(System.in);
```

```
        int rows=myobj.nextInt();
```

```
        int cols= rows;
```

```
        int [][] mat = new int[rows][cols];
```

```
        int main_d=0;
```

```
        int sec_d=0;
```

```
        for(int i=0;i<rows;i++){
```

```
            for(int j=0;j<cols;j++){
```

```
                mat[i][j]=myobj.nextInt();
```

```
                if(i==j){
```

```
                    main_d+=mat[i][j];
```

```
                }
```

```
                if((i+j)==(rows-1)){
```

```
                    sec_d+=mat[i][j];
```

```
    }  
  }  
  
  //int sec_d=mat[0][2]+mat[1][1]+mat[2][0];  
  System.out.println("Sum of the main diagonal: "+main_d);  
  System.out.println("Sum of the secondary diagonal: "+sec_d);  
}  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 3\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are developing a warehouse management system for a shipping company. The system uses an integer array to represent the weights of packages in a specific order. To verify that the weight capacity is not exceeded, the program needs to calculate the sum of the weights of the first and last packages in the list.

Task:

Write a code to calculate the sum of the weights of the first and last packages in the list. The program should take an integer array as input and return the total weight of the first and last packages.

##### ***Input Format***

The first line of the input is an integer N representing the size of the array.

The second line of the input is N space-separated integer values.

### **Output Format**

The output is displayed in the following format:

"Sum of the first and last elements: <<Sum>>"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

10 20 30 40 50

Output: Sum of the first and last elements: 60

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
```

```
    public static void main(String[] args){
```

```
        Scanner myobj = new Scanner(System.in);
```

```
        int size=myobj.nextInt();
```

```
        int [] arr=new int[size];
```

```
        for(int i=0;i<size;i++){
```

```
            arr[i]=myobj.nextInt();
```

```
        }
```

```
        int result = arr[0]+arr[size-1];
```

```
        System.out.println("Sum of the first and last elements: "+result);
```

```
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 3\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Sesha is developing a weather monitoring system for a region with multiple weather stations. Each weather station collects temperature data hourly and stores it in a 2D array.

Write a program that can add the temperature data from two different weather stations to create a combined temperature record for the region.

##### ***Input Format***

The first line of input consists of two space-separated integers N and M, representing the number of rows and columns of the matrices, respectively.

The next N lines consist of M space-separated integers, representing the values of the first matrix.

The following N lines consist of M space-separated integers, representing the values of the second matrix.

### **Output Format**

The output prints the addition of the two matrices in N rows and M columns, representing the combined temperature record.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3 3

1 2 3

4 5 6

7 8 9

1 1 1

2 2 2

3 3 3

Output: 2 3 4

6 7 8

10 11 12

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int rows=myobj.nextInt();
        int cols=myobj.nextInt();
        int [][]mat1=new int[rows][cols];
        int [][]mat2=new int[rows][cols];
        int [][]mat3=new int[rows][cols];
        for(int i=0;i<rows;i++){
            for(int j=0;j<cols;j++){
                mat1[i][j]=myobj.nextInt();
            }
        }
        for(int k=0;k<rows;k++){
            for(int l=0;l<cols;l++){
```

```
        mat2[k][l]=myobj.nextInt();
    }
}
for(int m=0;m<rows;m++){
    for(int n=0;n<cols;n++){
        mat3[m][n]=mat1[m][n]+mat2[m][n];
        System.out.print(mat3[m][n]+" ");
        System.out.printf("\n");
    }
}
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 3\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Sharon is creating a program that finds the first repeated element in an integer array. The program should efficiently identify the first element that appears more than once in the given array. If no such element is found, it should appropriately display a message.

Help Sharon to complete the program.

##### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of elements in the array.

The second line consists of  $n$  space-separated integers, representing the array elements.



### **Output Format**

If a repeated element is found, print the first element that appears more than once.

If no repeated element is found, print "No repeated element found in the array".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 8

12 21 13 14 21 36 47 21

Output: 21

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int size=myobj.nextInt();
        int [] arr=new int[size];
        for(int i=0;i<size;i++){
            arr[i]=myobj.nextInt();
        }
        //int []seen=new int[size];
        int seen=0;
        for(int i=0;i<size;i++){
            for(int j=i+1;j<size;j++){
                if(arr[i]==arr[j]){
                    seen=arr[i];
                    i=size;// forcing outer loop to end
                    break;
                }
            }
        }
        //break;
```

```
}  
    if(seen==0)  
        System.out.println("No repeated element found in the array");  
    else  
        System.out.println(seen);  
  
}  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 3\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Eminem is a billiard player who enjoys playing billiards and also likes solving mathematical puzzles. He notices that the billiard balls on the table are arranged in a grid, and he is curious to find the sum of the numbers written on each ball.

Write a program to find the sum of all the numbers written on each ball in the grid.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of rows.

The second line consists of an integer M, representing the number of columns.

The following lines N lines consist of M space-separated integers, representing the numbers written on each ball.

### **Output Format**

The output prints an integer representing the sum of all the numbers written on each ball.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

3

1 2 3

4 5 6

7 8 9

Output: 45

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int x=myobj.nextInt();
        int y=myobj.nextInt();
        int [][]mat=new int[x][y];
        int sum=0;
        for(int i=0;i<x;i++){
            for(int j=0;j<y;j++){
                mat[i][j]=myobj.nextInt();
                sum+=mat[i][j];
            }
        }
        System.out.println(sum);
    }
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

In a customer loyalty program, reward points are logged in a sorted array as customers make transactions. Occasionally, due to system errors, duplicate entries for the same transaction may appear. To ensure accurate reward calculations, it's crucial to remove these duplicates from the list.

Write a program to process the array of reward points, removing any duplicates while preserving the order of unique entries. The program should then display the cleaned list of unique reward points and the total count of these unique points.

### **Input Format**

The first line of input consists of an integer N, representing the number of reward points.

The second line consists of N space-separated integers, representing the reward points in sorted order.

### **Output Format**

The first line of output prints the cleaned list of unique reward points separated by a space.

The second line of output prints an integer representing the total count of unique reward points.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

100 100 200

Output: 100 200

2

### **Answer**

```
// You are using Java
import java.util.Scanner;

public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int size=myobj.nextInt();
        int []arr=new int[size];
        int count=0;
        for(int i=0;i<size;i++){
            arr[i]=myobj.nextInt();

        }
        int dup=-1;
        for(int j=0;j<size;j++){
            if(dup!=arr[j]){
                dup=arr[j];
                System.out.print(arr[j] + " ");
                count+=1;
            }
        }
        /*for(int j=0;j<size;j++){
            if(j==0 || arr[j]!=arr[j-1]){
                System.out.print(arr[j] + " ");
                count+=1;
            }
        }*/
        System.out.print("\n"+count);
    }
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Egath is participating in a coding hackathon, and one of the challenges requires him to work with an array of integers. The task is to remove exactly one element from the array such that the sum of the remaining elements is a prime number.

Help Egath find the first possible prime sum by removing one element or determining if no such prime sum can be achieved.

### ***Input Format***

The first line of input consists of an integer N, representing the number of elements in the array.

The second line consists of N space-separated integers, representing the array elements.

### ***Output Format***

If removing one element results in a prime sum, print the sum.

If no such prime sum can be achieved by removing exactly one element, print "No valid prime sum found".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 3

1 2 3

Output: 5

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
```

```
    public static int isprime(int num) {
        if (num <= 1) {
            return 0;
        }
        for (int i = 2; i * i <= num; i++) {
            if (num % i == 0) {
                return 0;
            }
        }
    }
}
```

```

    }
    return 1;
}
public static void main(String[] args){
    Scanner myobj=new Scanner(System.in);
    int size=myobj.nextInt();
    int []arr=new int[size];
    int totalsum=0;
    for(int i=0;i<size;i++){
        arr[i]=myobj.nextInt();
        totalsum+=arr[i];
    }
    for(int i=0;i<size;i++){
        int newsum=totalsum-arr[i];
        if(isprime(newsum)==1){
            System.out.println(newsum);
            return;
        }
    }
    System.out.println("No valid prime sum found");
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Priya is building a system to automate image transformations using matrix operations. To do this, she needs to multiply two matrices representing pixel data and transformation rules.

Help Priya perform matrix multiplication and print the resulting matrix if the operation is valid.

##### **Input Format**

The first line of input consists of two int values, representing the number of rows R1 and columns C1 of the first matrix.

The next R1 × C1 integers represent the elements of the first matrix.



The next line consists of two int values, representing the number of rows R2 and columns C2 of the second matrix.

The next  $R2 \times C2$  integers represent the elements of the second matrix.

### **Output Format**

If matrix multiplication is possible, print R1 lines, each containing C2 space-separated int values representing the resulting matrix.

Otherwise, print "Matrix multiplication not possible".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 2 3

1 2 3

4 5 6

3 2

7 8

9 10

11 12

Output: 58 64

139 154

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        //int r1=myobj.nextInt();
        //int c1=myobj.nextInt();
        String s1=myobj.nextLine();
        String []parts=s1.split(" ");
        int r1=Integer.parseInt(parts[0]);
        int c1=Integer.parseInt(parts[1]);
        int [][]mat1=new int[r1][c1];
        //System.out.println(c1);
```

```

        for(int i=0;i<r1;i++){
            for(int j=0;j<c1;j++){
                mat1[i][j]=myobj.nextInt();
            }
        }
        int r2=myobj.nextInt();
        int c2=myobj.nextInt();
        int [][]mat2=new int[r2][c2];
        int [][]mat3=new int[r1][c2];
        for(int i=0;i<r2;i++){
            for(int j=0;j<c2;j++){
                mat2[i][j]=myobj.nextInt();
            }
        }
        if(c1!=r2)
            System.out.println("Matrix multiplication not possible");

        else
        {
            for(int i=0;i<r1;i++){
                for(int j=0;j<c2;j++){
                    for(int k=0;k<c1;k++){
                        mat3[i][j]+=mat1[i][k]*mat2[k][j];
                        //System.out.print(mat3[i][j] +" ");
                    }
                }
            }
            for(int i=0;i<r1;i++){
                for(int j=0;j<c2;j++){
                    System.out.print(mat3[i][j] +" ");
                }
                System.out.print("\n");
            }
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 3\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Emma is a data analyst working with a grid-based system where each cell contains important numerical data. The grid represents spatial data, inventory records, or structured reports that require periodic updates.

Due to system updates and new requirements, Emma needs to modify the grid in the following ways:

She wants to insert either a new row or a new column at a given position. Later, she needs to delete either a row or a column from the modified matrix.

##### ***Input Format***

The first line contains two integers rows and cols (the dimensions of the matrix).

The next rows lines contain cols space-separated integers representing the initial matrix.

The next line contains two integers insertType and insertIndex:

- insertType = 0 for row insertion, 1 for column insertion.
- insertIndex is the position where the new row/column should be added.

If inserting a row, the next cols integers represent the new row or If inserting a column, the next rows integers represent the new column.

The next line contains two integers deleteType and deleteIndex:

- deleteType = 0 for row deletion, 1 for column deletion.
- deleteIndex is the position to be deleted.

### ***Output Format***

The first line of output prints the string "After insertion" followed by the modified matrix with the inserted row or column.

Each row of the matrix is printed on a new line with space-separated integers.

The next line prints the string "After deletion" followed by the final matrix after the specified deletion operation.

Each row of the resulting matrix is printed on a new line with space-separated integers.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 3 3

1 2 3

4 5 6

7 8 9

0 1

10 11 12

12

Output: After insertion

1 2 3  
10 11 12  
4 5 6  
7 8 9  
After deletion  
1 2  
10 11  
4 5  
7 8

**Answer**

```
import java.util.Scanner;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
  
        int rows = sc.nextInt();  
        int cols = sc.nextInt();  
        int[][] matrix = new int[rows][cols];  
  
        for (int i = 0; i < rows; i++) {  
            for (int j = 0; j < cols; j++) {  
                matrix[i][j] = sc.nextInt();  
            }  
        }  
  
        int insertType = sc.nextInt();  
        int insertIndex = sc.nextInt();  
  
        if (insertType == 0) {  
            int[][] newMatrix = new int[rows + 1][cols];  
            int[] newRow = new int[cols];  
            for (int i = 0; i < cols; i++) {  
                newRow[i] = sc.nextInt();  
            }  
            for (int i = 0; i < insertIndex; i++) {  
                newMatrix[i] = matrix[i];  
            }  
            newMatrix[insertIndex] = newRow;  
            for (int i = insertIndex; i < rows; i++) {  
                newMatrix[i + 1] = matrix[i];  
            }  
        }  
    }  
}
```

```

    }
    matrix = newMatrix;
    rows++;
} else {
    int[][] newMatrix = new int[rows][cols + 1];
    int[] newCol = new int[rows];
    for (int i = 0; i < rows; i++) {
        newCol[i] = sc.nextInt();
    }
    for (int i = 0; i < rows; i++) {
        for (int j = 0; j < insertIndex; j++) {
            newMatrix[i][j] = matrix[i][j];
        }
        newMatrix[i][insertIndex] = newCol[i];
        for (int j = insertIndex; j < cols; j++) {
            newMatrix[i][j + 1] = matrix[i][j];
        }
    }
    matrix = newMatrix;
    cols++;
}

```

```

System.out.println("After insertion");
printMatrix(matrix, rows, cols);

```

```

int deleteType = sc.nextInt();
int deleteIndex = sc.nextInt();

if (deleteType == 0) {
    int[][] newMatrix = new int[rows - 1][cols];
    int r = 0;
    for (int i = 0; i < rows; i++) {
        if (i == deleteIndex) continue;
        newMatrix[r++] = matrix[i];
    }
    matrix = newMatrix;
    rows--;
} else {
    int[][] newMatrix = new int[rows][cols - 1];
    for (int i = 0; i < rows; i++) {
        int c = 0;
        for (int j = 0; j < cols; j++) {

```

```

        if (j == deleteIndex) continue;
        newMatrix[i][c++] = matrix[i][j];
    }
}
matrix = newMatrix;
cols--;
}

System.out.println("After deletion");
printMatrix(matrix, rows, cols);
}

public static void printMatrix(int[][] matrix, int rows, int cols) {
    for (int i = 0; i < rows; i++) {
        for (int j = 0; j < cols; j++) {
            System.out.print(matrix[i][j] + " ");
        }
        System.out.println();
    }
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Nikila is working as an intern in a software firm and is practicing with a matrix where each row represents a set of numerical values. Her task is to identify the row with the highest sum of its elements and remove that row from the matrix. After removing the row with the highest sum, Nikila needs to print the updated matrix.

Your task is to help Nikila in implementing the same. If there are two or more rows that have same the highest sum, the firstly encountered row is deleted.

### **Input Format**

The first line of the input consists of two space-separated integers, R and C, representing the number of rows and columns in the matrix, respectively.

The following R lines each contain, C space-separated integers representing the matrix elements.

### **Output Format**

The output prints the matrix after removing the row with the highest sum. Each row should be printed on a new line, with elements separated by a space.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 2 2

1 2

3 4

Output: 1 2

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int r=myobj.nextInt();
        int c=myobj.nextInt();
        int [][]mat=new int[r][c];
        for(int i=0;i<r;i++){
            for(int j=0;j<c;j++){
                mat[i][j]=myobj.nextInt();
            }
        }
        int []max=new int[r];
        int [][]newmat=new int[r-1][c];
        for(int i=0;i<r;i++){
            int sum=0;
            for(int j=0;j<c;j++){
                sum+=mat[i][j];
            }
            max[i]=sum;
        }
    }
}
```



```

//for(int i=0;i<r;i++){
//System.out.print(max[i] + " ");}
int max_num=-1;
int index=0;
for(int i=0;i<r;i++){

    if(max_num<max[i]){
        max_num=max[i];
        index=i;
    }

}
//System.out.println(index);
for(int i=0;i<r;i++){
    if(i==index){
        continue;
    }
    for(int j=0;j<c;j++){
        //if(i==index){
        //continue;}
        System.out.print(mat[i][j] + " ");
    }
    System.out.println();
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Robin is a tech-savvy teenager who is diving into programming.

He is working on a project to find special elements in an array called 'leaders.' Leaders are those exceptional elements that are greater than the sum of all the elements to their right.

Assist Robin in writing this program.

Example

Input:

6

16 28 74 19 25 11

Output:

74 25 11

Explanation:

The element 16 is not greater than the sum of elements to its right ( $28 + 74 + 19 + 25 + 11 = 157$ )

The element 28 is not greater than the sum of elements to its right ( $74 + 19 + 25 + 11 = 129$ )

The element 74 is greater than the sum of elements to its right ( $19 + 25 + 11 = 55$ )

The element 19 is not greater than the sum of elements to its right ( $25 + 11 = 36$ )

The element 25 is greater than the sum of elements to its right (11)

The last element 11 is always a leader since there are no elements to its right.

So, the output is {74, 25, 11}.

### ***Input Format***

The first line of input consists of an integer N, representing the number of elements in the array.

The second line consists of N space-separated integers, representing the elements of the array.

### ***Output Format***

The output prints the special elements in the given array, that are greater than the sum of all the elements to their right.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

3 4 2 5 1

Output: 5 1

### **Answer**

```
// You are using Java
import java.util.Scanner;
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int size=myobj.nextInt();
        int []arr=new int[size];
        for(int i=0;i<size;i++){
            arr[i]=myobj.nextInt();
        }

        for(int j=0;j<size;j++){
            int sum=0;

            for(int k=j+1;k<size;k++){
                sum+=arr[k];
            }

            if(arr[j]>sum)
                System.out.print(arr[j] + " ");
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

### **4. Problem Statement:**

Mason is participating in a coding challenge where he must manipulate an

integer array. His task is to replace every element in the array with the next greatest element to its right. The last element of the array remains unchanged, as there is no element to its right.

Your job is to help Mason write a program that performs this transformation and outputs the modified array.

### ***Input Format***

The first line of input contains an integer  $n$  representing the number of elements in the array.

The second line of input contains  $n$  space-separated integers representing the elements of the array.

### ***Output Format***

The output prints the modified array of  $n$  integers, where each element (except the last one) is replaced by the maximum element to its right, and the last element remains unchanged.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 6

12 3 91 15 12 14

Output: 91 91 15 14 14 14

### ***Answer***

// You are using Java

```
import java.util.Scanner;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int size=myobj.nextInt();
        int []arr=new int[size];
        //int max=0;
        for(int j=0;j<size;j++){
            arr[j]=myobj.nextInt();
```

```
}  
for(int i=0;i<size-1;i++){  
    int max=-100;  
    for(int k=i+1;k<size;k++){  
        if(max<arr[k])  
            max=arr[k];  
    }  
    System.out.print(max + " ");  
  
}  
System.out.print(arr[size-1]);
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 4\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. What will be the output of the following program?

```
class Main {  
    public static void main(String[] args) {  
        String s = new String("5");  
        System.out.println(1 + 1111 + s + 1 + 1010);  
    }  
}
```

**Answer**

1112511010

**Status : Correct**

**Marks : 1/1**

2. Predict the output for the following code.

```
class Main {  
    public static void main(String[] fruits) {  
        String fruit1 = new String("apple");  
        String fruit2 = new String("orange");  
        String fruit3 = new String("pear");  
        fruit3 = fruit1;  
        fruit2 = fruit3;  
        fruit1 = fruit2;  
        System.out.println(fruit1);  
        System.out.println(fruit2);  
        System.out.println(fruit3);  
    }  
}
```

**Answer**

appleappleapple

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following program?

```
public class Main {  
    public static void main(String[] args) {  
        String str = "1234.34";  
        int a = Integer.parseInt(str);  
        System.out.println(a);  
    }  
}
```

**Answer**

NumberFormatException

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following program?

```
class Main {  
    public static void main(String args[]) {
```

```
StringBuffer sb = new StringBuffer("Hello");
System.out.println("buffer = " + sb);
System.out.println("length = " + sb.length());
System.out.println("capacity = " + sb.capacity());
}
}
```

**Answer**

buffer = Hello length = 5 capacity = 21

**Status :** Correct

**Marks :** 1/1

5. Predict the output for the following code:

```
public class Main {
    public static void main(String[] args) {
        float a = 10.0f;
        String temp = Float.toString(a);
        System.out.println(temp);
    }
}
```

**Answer**

10.0

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
class Main {
    public static void main(String args[]) {
        char c[] = {'j', 'a', 'v', 'a'};
        String s1 = new String(c);
        String s2 = new String(s1);
        System.out.println(s1);
        System.out.println(s2);
    }
}
```



**Answer**

javajava

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following program?

```
class Main {  
    public static void main(String[] args) {  
        String greet = "Welcome\n";  
        System.out.print("String: " + greet);  
        int length = greet.length();  
        System.out.print("Length: " + length);  
    }  
}
```

**Answer**

String: WelcomeLength: 8

**Status :** Correct

**Marks :** 1/1

8. Predict the output for the following code:

```
class Main {  
    public static void main(String args[]) {  
        StringBuffer sb = new StringBuffer("I Java!");  
        sb.insert(5, "like ");  
        System.out.println(sb);  
    }  
}
```

**Answer**

I Javlike a!

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following program?

```

class Main {
    public static void main(String[] args) {
        String s1 = "EDUCATION";
        String s2 = new String("EDUCATION");
        String s3 = "EDUCATION";
        if (s1 == s2) {
            System.out.println("s1 and s2 equal");
        }
        else {
            System.out.println("s1 and s2 not equal");
        }
        if (s1 == s3) {
            System.out.println("s1 and s3 equal");
        }
        else {
            System.out.println("s1 and s3 not equal");
        }
    }
}

```

**Answer**

s1 and s2 not equals1 and s3 equal

**Status :** Correct

**Marks :** 1/1

10. What is the output of the following code?

```

class Main
{
    public static void main(String args[])
    {
        StringBuffer c = new StringBuffer("Hello");
        c.delete(0,2);
        System.out.println(c);
    }
}

```

**Answer**

llo

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following program?

```
class Main {  
    public static void main(String args[]) {  
        String name="Work Hard";  
        name.concat("Success");  
        System.out.println(name);  
    }  
}
```

**Answer**

Work Hard

**Status :** Correct

**Marks :** 1/1

12. Predict the output for the following code.

```
public class Main {  
    public static void main(String[] args) {  
        String a = "java";  
        char temp = a.charAt(1);  
        System.out.println(temp);  
    }  
}
```

**Answer**

a

**Status :** Correct

**Marks :** 1/1

13. What will be the output for the following code?

```
class Main {  
    public static void main(String[] args) {  
        String languages[] = { "C", "C++", "Java", "Python", "Ruby"};  
        for (String sample: languages) {
```

```
        System.out.println(sample);
    }
}
}
```

**Answer**

CC++JavaPythonRuby

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following code?

```
class Main {
    public static void main(String args[]) {
        String s1 = "Hello i love java";
        String s2 = new String(s1);
        System.out.println((s1 == s2) + " " + s1.equals(s2));
    }
}
```

**Answer**

false true

**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following code?

```
class Main {
    public static void main(String args[])
    {
        StringBuffer sb = new StringBuffer("Hello");
        System.out.println("buffer before = " + sb);
        System.out.println("charAt(1) before = " + sb.charAt(1));
        sb.setCharAt(1, 'i');
        sb.setLength(2);
        System.out.println("buffer after = " + sb);
        System.out.println("charAt(1) after = " + sb.charAt(1));
    }
}
```

**Answer**

buffer before = HellocharAt(1) before = ebuffer after = HicharAt(1) after = i

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 4\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In a publishing company, editors often need to quickly analyze passages of text to check for punctuation usage. To assist them, you are asked to write a program that counts the number of specific punctuation marks in each passage.

The punctuation marks of interest are:

Commas (,) Periods (.) Question marks (?)

##### ***Input Format***

The first line of input contains an integer T, representing the number of test cases (passages).

Each of the next T lines contains a single passage of text.



```
        System.out.printf("%d %d %d\n",co,pe,qu);  
    }  
}
```

**Status :** Correct

**Marks : 10/10**



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 4\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Anu is developing a tool for a conference registration system. Participants submit keywords related to their fields of interest. The organizer wants to sort these keywords alphabetically to generate tags for session grouping.

Write a program that accepts at least five keywords as input arguments and outputs them in sorted alphabetical order.

##### ***Input Format***

The first line of input contains an integer n, representing the number of keywords.

The second line of input contains n space-separated keywords (string).

##### ***Output Format***

The output prints n space separated strings representing the sorted keyword in alphabetical order.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

Blockchain Cloud AI Data Cybersecurity

Output: AI Blockchain Cloud Cybersecurity Data

### **Answer**

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj=new Scanner(System.in);
        int num=myobj.nextInt();
        myobj.nextLine();
        String [] b = new String[num];
        for(int i=0;i<num;i++)
        {
            b[i]=myobj.next();
            //System.out.println(b[i]);
        }
        Arrays.sort(b);
        for(int j=0;j<num;j++)
        {
            System.out.print(b[j] + " ");
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 4\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Bechan Chacha is seeking help to filter out valid mobile numbers from a list provided by his crush. He can only pick his crush's number if the list contains valid mobile numbers.

A mobile number is considered valid if:

It has exactly 10 digits. It consists only of numeric values (0–9). It does not begin with zero.

Your task is to determine whether each mobile number in the list is valid or not.

##### ***Input Format***

The first line contains an integer T, representing the number of mobile numbers

to check.

The next T lines each contain a string S, representing a mobile number.

### **Output Format**

For each mobile number S, the output print "YES" if it is valid.

Otherwise, print "NO".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1  
9876543210

Output: YES

### **Answer**

// You are using Java  
import java.util.\*;

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int a=myobj.nextInt();
        myobj.nextLine();
        for(int i=0;i<a;i++)
        {
            String b=myobj.nextLine();
            if(b.charAt(0)!='0' && b.length()==10 && b.matches("[0-9]+"))
                System.out.println("YES");
            else
                System.out.println("NO");
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 4\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Arjun is learning how to filter words from a sentence based on grammar rules. He wants to identify the valid words in a sentence.

A word is considered valid if it satisfies all these conditions:

The word contains only alphabets (a–z, A–Z). The word length is at least 2 characters. The word should not contain digits or special characters.

Your task is to read a sentence and print all the valid words in it.

##### ***Input Format***

The input contains a single line containing a sentence S.

##### ***Output Format***

The output prints all the valid words separated by spaces.

If no valid word exists, print "No valid words."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Hello world1 123 ab" @#\$ Hi

Output: Hello Hi

### **Answer**

```
// You are using Java
import java.util.*;
public class Main{
    public static void main(String[] args){
        Scanner ss=new Scanner(System.in);
        String sen=ss.nextLine();
        String[] word = sen.split("\\s+");
        boolean foundvalid=false;

        for(int i=0;i<word.length;i++){

            if((word[i].matches("[a-zA-Z]+")) && (word[i].length()>=2)
            && !(word[i].matches("[^a-zA-Z0-9]+"))){
                //words==> all should be alpha and also len 2 so third condition is optional
                System.out.print(word[i] + " ");
                foundvalid=true;
            }

        }
        if(foundvalid==false)
            System.out.println("No valid words.");
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 4\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In a secure banking system, customers are required to create PIN codes for accessing their accounts. The bank wants to validate these PIN codes before accepting them.

A PIN code is considered valid if:

It consists of exactly 4 digits. All characters must be numeric (0–9). It cannot contain all identical digits (e.g., 1111 is invalid).

Your task is to determine whether each PIN code in the list is valid or not.

##### ***Input Format***

The first line of input contains an integer T, representing the number of PIN codes to check.

The next T lines each contain a string S, representing a PIN code.

### **Output Format**

For each PIN code S, the output print "YES" if it is valid.

Otherwise, the output print "NO".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1234

Output: YES

### **Answer**

// You are using Java

import java.util.\*;

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        int a=myobj.nextInt();
        myobj.nextLine();

        for(int i=0;i<a;i++)
        {
            String pin=myobj.nextLine();

            if(pin.length()==4 && pin.matches("[0-9]+")
            && !(pin.charAt(0)==pin.charAt(1) && pin.charAt(1)==pin.charAt(2)
            && pin.charAt(2)==pin.charAt(3)))
                System.out.println("YES");
            else
                System.out.println("NO");
        }
    }
}
```



Status : Correct

Marks : 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 4\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Sana is analyzing text for a secret code. She wants to find all words in a sentence that start and end with the same letter. These words are considered "special words" for her analysis.

Your task is to write a program that extracts and prints all words that start and end with the same letter (case-insensitive).

If no such word exists, print "No special words found".

##### ***Input Format***

The input contains a single line containing a sentence with multiple words.

##### ***Output Format***

The output prints all words that start and end with the same letter separated by a space.

If no word satisfies the condition, print "No special words found".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Anna went to the civic center

Output: Anna civic

### **Answer**

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        String s1=myobj.nextLine();
        String []word =s1.split(" ");
        boolean found = false;
        for(int i=0;i<word.length;i++)
        {
            int a=word[i].length();
            if(Character.toLowerCase(word[i].charAt(0))==Character.toLowerCase(word[i].charAt(a-1)))
            {
                found=true;
                System.out.print(word[i] + " ");
            }
        }
        if(found==false)
            System.out.println("No special words found");
    }
}
```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

Riya is preparing a puzzle game for her friends. She wants to include a feature that highlights special words in a sentence — specifically, palindromic words (words that read the same forward and backward).

Your task is to help Riya by writing a program that extracts all palindrome words from the given sentence. If there are no palindromes, print "No palindromes found".

### ***Input Format***

The input contains a single string S representing a sentence.

### ***Output Format***

The output prints all palindromic words separated by a space.

If no palindrome exists, print "No palindromes found".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: madam went to school

Output: madam

### ***Answer***

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String [] args){
        Scanner myobj = new Scanner(System.in);
        String s1= myobj.nextLine();
        String []word=s1.split(" ");
        boolean pal=true;
        boolean foundpali=false;
        for(int i=0;i<word.length;i++)
        {
```

```

String a=word[i];
for(int j=0;j<(a.length())/2;j++){
    pal=true;
    if(a.charAt(j)!=a.charAt(a.length()-1-j))
    {
        pal=false;
        break;
    }
}
if(pal==true)
{
    System.out.print(a + " ");
    foundpali=true;
}
}
if(!foundpali)
    System.out.print("No palindromes found");
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Ravi is analyzing text messages for his research on typing patterns. He wants to count the number of uppercase letters, lowercase letters, and digits in a sentence to understand typing trends.

Your task is to help Ravi by writing a program that takes a sentence and prints the count of uppercase letters, lowercase letters, and digits.

#### **Input Format**

The input contains a single line containing a sentence (string).

#### **Output Format**

The output prints three integers separated by spaces:

- Number of uppercase letters

- Number of lowercase letters
- Number of digits

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Hello World 123

Output: 2 8 3

### **Answer**

```
// You are using Java
import java.util.*;

public class Main{
    public static void main(String [] args){
        Scanner myobj = new Scanner(System.in);
        String sen = myobj.nextLine();
        String []words = sen.split(" ");
        int lc=0,uc=0,digi=0;
        for(int i=0;i<words.length;i++)
        {
            String s1=words[i];
            for(int j=0;j<s1.length();j++){
                char ch = s1.charAt(j);
                if(Character.isUpperCase(ch))
                    uc+=1;
                else if(Character.isLowerCase(ch))
                    lc+=1;
                else if(Character.isDigit(ch))
                    digi+=1;
            }
        }
        System.out.printf("%d %d %d",uc,lc,digi);
    }
}
```

**Status : Correct**

**Marks : 10/10**

#### 4. Problem Statement

At a digital library, the system needs to analyze passages to identify the frequency of vowels, since they are key for linguistic research. You are asked to write a program that counts the number of vowels in each passage of text.

The vowels of interest are:

a, e, i, o, u (both uppercase and lowercase).

##### ***Input Format***

The first line of input contains an integer T, representing the number of test cases (passages).

Each of the next T lines contains a single passage of text.

##### ***Output Format***

For each test case, print a single integer representing the total number of vowels in the passage.

The first line of output corresponds to the first passage, the second line to the second passage, and so on.

Refer to the sample output for formatting specifications.

##### ***Sample Test Case***

Input: 1  
Hello World

Output: 3

##### ***Answer***

```
// You are using Java
import java.util.*;

public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
```

```
int a=myobj.nextInt();
myobj.nextLine();
//int vowel=0;
for(int i=0;i<a;i++)
{
    int vowel=0;
    String s1=myobj.nextLine();
    String []word=s1.split(" ");
    for(int j=0;j<s1.length();j++)
    {
        char ch=s1.charAt(j);
        if(ch=='a' || ch=='e' || ch=='i' || ch=='u' || ch=='o'
        || ch=='A' || ch=='E' || ch=='I' || ch=='U' || ch=='O')
            vowel+=1;
    }
    System.out.println(vowel);
}
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 4\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Anjali is preparing a report on text complexity. She wants to identify all words in a sentence that contain at least one digit so she can analyze numeric mentions.

Your task is to write a program that extracts and prints all words containing at least one digit from a given sentence.

If no such word exists, print "No words with digits found".

##### ***Input Format***

The input contains a single line containing a sentence with multiple words.

##### ***Output Format***

The output prints all words containing at least one digit separated by a space.

If no word contains a digit, print "No words with digits found".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: The model X100 and Y200 are available

Output: X100 Y200

### **Answer**

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        String s1 = myobj.nextLine();
        String [] words = s1.split(" ");
        int flag=0;
        for(int i=0;i<words.length;i++)
        {
            char[]arr=words[i].toCharArray();
            for(int j=0;j<arr.length;j++){
                if(Character.isDigit(arr[j]))
                {
                    System.out.print(words[i]+" ");
                    flag=1;
                    break;
                }
            }
        }
        if(flag==0)
            System.out.println("No words with digits found");
    }
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Neha is analyzing text messages to identify words that have repeated characters. A word is considered "repetitive" if any character appears more than once in that word.

Your task is to write a program that extracts all words that contain repeated characters from a given sentence.

If no such word exists, print "No repetitive words found".

### ***Input Format***

The input contains a single line containing a sentence with multiple words.

### ***Output Format***

The output prints all words that contain repeated characters separated by a space.

If no word contains repeated characters, print "No repetitive words found".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: letter balloon apple tree

Output: letter balloon apple tree

### ***Answer***

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        String s1=myobj.nextLine();
        String []words=s1.split(" ");
        int flag=0;
        for(int i=0;i<words.length;i++){
```

```

        int localflag=0;
        String s2=words[i];
        for(int j=0;j<s2.length();j++){
            char [] ch=s2.toCharArray();
            for(int k=0;k<s2.length();k++){
                if(ch[j]==ch[k] && j!=k){
                    localflag=1;
                    flag=1;
                    break;
                }
            }
            if(localflag==1)
                break;
        }
        if(localflag==1)
            System.out.print(s2 + " ");
    }
    if(flag==0)
        System.out.print("No repetitive words found");
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

In a college, students are required to create unique usernames for accessing the digital library.

The librarian needs your help to verify whether the usernames entered by students are valid.

A username is considered valid if:

It contains only letters (a–z, A–Z) and digits (0–9). Its length is between 5 and 15 characters (inclusive). It must start with a letter (not a digit).

Your task is to determine whether each username in the list is valid or not.

### ***Input Format***

The first line of input contains an integer T, representing the number of usernames to check.

The next T lines each contain a string S, representing a username.

### ***Output Format***

For each username S, the output print "YES" if it is valid.

Otherwise, the output print "NO".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

Alice123

Output: YES

### ***Answer***

// You are using Java

import java.util.\*;

```
public class Main{
    public static void main (String[] args){
        Scanner myobj=new Scanner(System.in);
        int num=myobj.nextInt();
        myobj.nextLine();

        int flag=1;
        for(int i=0;i<num;i++)
        {
            String s1=myobj.nextLine();
            char []arr=s1.toCharArray();
            flag=1;

            if (arr.length < 5 || arr.length > 15) {
                flag = 0;
            }
        }
    }
}
```

```

else if (!(Character.isLetter(arr[0]))) {
    flag = 0; }
else{
    for(int j=0;j<arr.length;j++)
    {
        if(!Character.isLetterOrDigit(arr[j]))
        {
            flag=0;
            break;
        }
    }
    if(flag==1)
    System.out.println("YES");
    else
    System.out.println("NO");
}
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A bookstore wants to analyze the titles of books to determine their longest word in each title. This helps in designing banners and covers.

Your task is to write a program that, given a sentence (book title), finds and prints the longest word. If multiple words have the same maximum length, print the first one.

##### **Input Format**

The input contains a single line containing a sentence representing the book title.

##### **Output Format**

The output prints a string representing the longest word in the sentence (book title).

Refer to the sample output for formatting specifications.

**Sample Test Case**

Input: The Chronicles of Narnia

Output: Chronicles

**Answer**

// You are using Java

import java.util.\*;

```
public class Main{
    public static void main(String[] args){
        Scanner myobj = new Scanner(System.in);
        String s1=myobj.nextLine();
        String [] words = s1.split(" ");
        int longestw=0;
        int index=0;
        for(int i=0;i<words.length;i++)
        {
            int longw=words[i].length();
            if(longestw<longw)
            {
                longestw=longw;
                index=i;
            }
        }
        System.out.println(words[index]);
    }
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. What will be the output of the following code?

```
class Test {  
    private int value;  
    Test(int value) {  
        this.value = value;  
    }  
    public int getValue() {  
        return value;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Test obj = new Test(10);  
        System.out.println(obj.value);  
    }  
}
```



```
}
```

**Answer**

Compile-time error

**Status :** Correct

**Marks :** 1/1

2. What is the output of the following code?

```
class Box {  
    int height;  
    Box(int height) {  
        this.height = height;  
    }  
    void modifyHeight(Box b) {  
        b.height += 10;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Box b1 = new Box(20);  
        b1.modifyHeight(b1);  
        System.out.println(b1.height);  
    }  
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
class Person {  
    int age = 18;  
}  
  
public class Main {  
    public static void main(String[] args) {
```

```
Person p = new Person();  
p.age += 2;  
System.out.println("Age: " + p.age);  
}  
}
```

**Answer**

Age: 20

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following code?

```
class A {  
    int y = 30;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        A a1 = new A();  
        A a2 = new A();  
        a1.y = 50;  
        System.out.println(a2.y);  
    }  
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
class Box {  
    int volume(int l, int b, int h) {  
        return l * b * h;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Box b = new Box();  
        System.out.println(b.volume(2, 3, 4));  
    }  
}
```

**Answer**

24

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
class Ball {  
    int size = 11;  
}  
  
class Game {  
    public static void main(String[] args) {  
        Ball b1 = new Ball();  
        Ball b2 = new Ball();  
        b2.size = 10;  
        System.out.println(b1.size);  
    }  
}
```

**Answer**

11

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following code?

```
class A {  
    int x = 50;  
}  
  
public class Main {
```

```
public static void main(String[] args) {  
    A obj1 = new A();  
    A obj2 = obj1;  
    obj2.x = 100;  
    System.out.println(obj1.x);  
}  
}
```

**Answer**

100

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
class MathUtils {  
    int add(int x) {  
        return x + x;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        MathUtils m = new MathUtils();  
        System.out.println(m.add(5));  
    }  
}
```

**Answer**

10

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
class Person {  
    String name;  
    void setName(String n){  
        name = n;  
    }  
}
```

```
    }  
    void printName() {  
        System.out.println(name);  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        Person p = new Person();  
        p.printName();  
    }  
}
```

**Answer**

null

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
class Alpha {  
    void greet(String name) {  
        System.out.println("Hello " + name);  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Alpha obj = new Alpha();  
        obj.greet("Anu");  
    }  
}
```

**Answer**

Hello Anu

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following code?

```
class Sample {  
    int x = 10;  
  
    void display() {  
        System.out.println("x = " + x);  
    }  
  
    public static void main(String[] args) {  
        Sample s = new Sample();  
        s.display();  
    }  
}
```

**Answer**

x = 10

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following code?

```
class Box {  
    int length = 5;  
    int width = 4;  
  
    int area() {  
        return length * width;  
    }  
  
    public static void main(String[] args) {  
        Box b = new Box();  
        System.out.println("Area = " + b.area());  
    }  
}
```

**Answer**

Area = 20

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following code?

```
class A {  
    int p = 5;  
    int q = 2;  
}  
  
class Main {  
    public static void main(String[] args) {  
        A obj = new A();  
        System.out.println(obj.p + obj.q);  
    }  
}
```

**Answer**

7

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following code?

```
class Demo {  
    void printMessage() {  
        System.out.println("Hello from Demo");  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Demo d = new Demo();  
        d.printMessage();  
    }  
}
```

**Answer**

Hello from Demo

**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following code?

```
class A {  
    int val = 20;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        A obj1 = new A();  
        A obj2 = obj1;  
        obj2.val += 5;  
        System.out.println(obj1.val);  
    }  
}
```

**Answer**

25

**Status :** Correct

**Marks :** 1/1



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are working as a developer for CityBank, which wants to build a basic account management system.

Each customer at the bank has:

An Account Number (integer) A Customer Name (string) An Initial Balance (double)

The bank allows two types of transactions:

Deposit – increases the balance. Withdrawal – decreases the balance only if enough funds are available.

If the withdrawal amount is greater than the balance, the withdrawal should not happen, and the balance should remain the same.

You are required to implement this system using:

A class with attributes for account details. A constructor to initialize account details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's account details after all transactions.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

### ***Output Format***

For each customer, print the details in the following format:

1. Account Number: <account\_number>
2. Customer Name: <customer\_name>
3. Final Balance: <final\_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma

Final Balance: 4000.0

**Answer**

```
import java.util.*;

class Customer{
    private int accno;
    private String name;
    private double initial;
    private double balance;

    public Customer(int accno,String name,double initial){//construcor
        this.accno = accno;
        this.name = name;
        this.initial = initial;
    }
    public int getAccnum(){//to access or get values
        return accno;
    }
    public String getCusname(){
        return name;
    }
    //setAccnum and setCusname are optional
    public double getBalance(){
        return balance;
    }

    public void setbalance(double balance,double withdrawal){//set to update
        balance value
        if(balance>=withdrawal){
            this.balance =balance -withdrawal;
        }
        else
            this.balance=balance;
    }
}

public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int N=sc.nextInt();
        Customer []cus = new Customer[N];
    }
}
```

```
//array creation "Customer" userdefined dtype created by class
for(int i=0;i<N;i++){
```

```
    int accno=sc.nextInt();
    sc.nextLine();
    String name=sc.nextLine();
    double initial=sc.nextDouble();
    double deposit=sc.nextDouble();
    double withdrawal=sc.nextDouble();
    double balance = initial + deposit;
```

```
    cus[i] = new Customer(accno, name, initial);
```

```
//cus[i] is already of type Customer because the array was declared
```

```
//When you have an array of objects, like Customer[] cus, you don't repeat the
type every time.
```

```
//so only we here ignoring the syntax classname here.
```

```
    cus[i].setbalance(balance,withdrawal);
    System.out.println("Account Number: "+cus[i].getAccnum());
    System.out.println("Customer Name: "+cus[i].getCusname());
    System.out.println("Final Balance: "+cus[i].getBalance());
```

```
    }
}
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Neha is working as a developer for CityElectricity Board, which wants to build a household electricity billing system.

Each customer's electricity account has:

A Customer ID (integer) A Customer Name (string) Units Consumed (double)

The electricity bill is calculated based on these rules:

For the first 100 units 5 units charge per unit For the next 100 units (101–200) 7 units charge per unit For units above 200 10 units charge per unit If the total bill exceeds 2000 units, a 5% discount is applied on the final bill.

Neha has been asked to implement this system using:

A class with attributes for customer details. A constructor to initialize customer details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Units Consumed (double).

### ***Output Format***

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Bill: <final\_bill> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

80

Output: Customer ID: 1001

Customer Name: Ravi Kumar

Final Bill: 400.0

### ***Answer***

// You are using Java

```
import java.util.*;
```

```
class Customer{  
    private int customerid;  
    private String name;  
    private double units;  
    private double final_bill;  
  
    public Customer(int customerid,String name, double units){  
        this.customerid=customerid;  
        this.name=name;  
        this.units=units;  
    }  
  
    public int getID(){  
        return customerid;  
    }  
    public String getName(){  
        return name;  
    }  
    public double getBill(){  
        return final_bill;  
    }  
    public void setBill(double units){  
        if(units>200)  
            final_bill=500.00 + 700.00 + (units-200)*10;  
        else if(units>100 && units<=200)  
            final_bill=500.00 + (units-100)*7;  
        else  
            final_bill=units*5;  
  
        if(final_bill>2000)  
            this.final_bill=final_bill * 0.95;  
    }  
}
```

```
public class Main{  
    public static void main(String[] args){  
        Scanner sc = new Scanner(System.in);  
        int N=sc.nextInt();
```

```
Customer []cus=new Customer[N];
for(int i=0;i<N;i++){
    int customerid=sc.nextInt();
    sc.nextLine();
    String name=sc.nextLine();
    double units=sc.nextDouble();
    cus[i] = new Customer(customerid,name,units);

    System.out.println("Customer ID: "+cus[i].getID());
    System.out.println("Customer name: "+cus[i].getName());
    cus[i].setBill(units);
    System.out.println("Final Bill: "+cus[i].getBill());

}
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are working as a developer for CityCab, a taxi service company that wants to build a ride fare management system.

Each customer booking has:

A Booking ID (integer) A Customer Name (string) A Distance Travelled in km (double)

The fare calculation rules are:

Base Fare = 50 units (flat charge for every ride). Per km charge = 10 units/km. If the distance is greater than 20 km, a 10% discount is applied on the total fare.

You are required to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customer rides.

Finally, display each booking's details and final fare.

### ***Input Format***

The first line of input contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the booking ID (integer).
- The following line contains the customer's name (string).
- The next line contains the distance travelled (double).

### ***Output Format***

For each booking, print the details in the following format:

1. Booking ID: <booking\_id>
2. Customer Name: <customer\_name>
3. Final Fare: <final\_fare> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1  
1234  
Rahul Sharma  
15

Output: Booking ID: 1234  
Customer Name: Rahul Sharma  
Final Fare: 200.0

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
class Booking {
    private int bookingId;
    private String customerName;
    private double distance;
    private double fare;

    public Booking(int bookingId, String customerName, double distance) {
        this.bookingId = bookingId;
        this.customerName = customerName;
        this.distance = distance;
        calculateFare();
    }

    // public void setBookingId(int bookingId) {
    //     this.bookingId = bookingId;
    // }

    public void setCustomerName(String customerName) {
        this.customerName = customerName;
    }

    public void setDistance(double distance) {
        this.distance = distance;
        calculateFare();
    }

    public int getBookingId() {
        return bookingId;
    }
    public String getCustomerName() {
        return customerName;
    }
    public double getDistance() {
        return distance;
    }
    public double getFare() {
        return fare;
    }
    private void calculateFare() {
        fare = 50 + (distance * 10);
        if (distance > 20) {
            fare = fare - (fare * 0.1);
        }
    }
}
```

```

    }
    }
}

class CityCabApp {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        Booking []booking = new Booking[n];

        for (int i = 0; i < n; i++) {
            int id = Integer.parseInt(sc.nextLine());
            String name = sc.nextLine();
            double distance = Double.parseDouble(sc.nextLine());

            booking[i] = new Booking(id, name, distance);

            System.out.println("Booking ID: " + booking[i].getBookingId());
            System.out.println("Customer Name: " + booking[i].getCustomerName());
            System.out.printf("Final Fare: %.1f\n", booking[i].getFare());
        }
        sc.close();
    }
}

```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ram is working as a developer for BrightEdu Coaching Center, which wants to build a student fee management system.

Each student's enrollment has:

An Enrollment ID (integer) A Student Name (string) The Number of Subjects (integer)

The fee calculation rules are:

Registration Fee = 1000 units (flat for every student). Per Subject Fee = 800 units. If the student enrolls in more than 5 subjects, a 20% scholarship (discount) is applied on the total fee.

Ram has been asked to implement this system using:

A class with attributes for student details. A constructor to initialize student details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent student enrollments.

Finally, display each student's details and final fee.

### ***Input Format***

The first line of input contains an integer N, representing the number of students.

For each student:

- The next line contains the Enrollment ID (integer).
- The following line contains the student's name (string).
- The next line contains the Number of subjects (integer).

### ***Output Format***

For each student, print the details in the following format:

- Enrollment ID: <enrollment\_id>
- Student Name: <student\_name>
- Final Fee: <final\_fee> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Ravi Kumar

3

Output: Enrollment ID: 1234

Student Name: Ravi Kumar

Final Fee: 3400.0

### ***Answer***

```
// You are using Java\  
import java.util.*;  
class Student{  
    private int enrollid;
```

```
private String name;  
private int no_sub;  
private double fee;
```

```
public Student(int enrollid,String name,int sub){  
    this.enrollid=enrollid;  
    this.name=name;  
    this.no_sub=no_sub;
```

```
}  
public int getId(){  
    return enrollid;
```

```
}  
public String getName(){  
    return name;
```

```
}  
public double getFee(){  
    return fee;
```

```
}  
public void setFee(int no_sub){  
    this.fee = (no_sub*800) + 1000;  
    if(no_sub>5)  
        this.fee = fee - (fee * 0.20);  
}
```

```
}
```

```
public class Main{  
    public static void main(String[] args){  
        Scanner sc = new Scanner(System.in);  
        int N = sc.nextInt();  
        Student []s =new Student[N];
```

```
  
        for(int i=0;i<N;i++){  
            int enrollid=sc.nextInt();  
            sc.nextLine();  
            String name=sc.nextLine();  
            int no_sub=sc.nextInt();
```

```
  
            s[i]=new Student(enrollid,name,no_sub);  
            s[i].setFee(no_sub);  
            System.out.println("Enrollment ID: "+s[i].getId());
```

```
        System.out.println("Student Name: "+s[i].getName());  
        System.out.println("Final Fee: "+s[i].getFee());  
    }  
}  
}
```

**Status :** Correct

**Marks : 10/10**



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_PAH

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

#### Section 1 : Coding

##### 1. Problem Statement

Neha is working as a developer for CityMovie Theatre, which wants to build a system to calculate total ticket cost for movie-goers based on the number of tickets and type of seats booked.

Each customer's booking has:

Booking ID (integer) Customer Name (string) Number of Tickets (integer) Seat Type (string: "Standard", "Premium", "VIP")

The ticket prices are:

Standard – 250 units per ticket Premium – 400 units per ticket VIP – 600 units per ticket

The calculation rules:

Total Amount = Number of Tickets × Seat Price

If a customer books more than 4 tickets, they get a 10% discount on the total amount.

If the booking is for VIP seats and the total amount exceeds 3000 units, a 5% luxury tax is added after any discount.

Neha has been asked to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Getter and Setter methods to retrieve and update booking details if required. A method to calculate the final ticket cost. Objects of the class to represent bookings.

Finally, display each customer's details and final ticket amount.

### ***Input Format***

The first line contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the Booking ID (integer).
- The next line contains the Customer Name (string).
- The next line contains Number of Tickets (integer).
- The next line contains Seat Type ("Standard", "Premium", or "VIP").

### ***Output Format***

For each booking, print:

- Booking ID: <booking\_id>
- Customer Name: <customer\_name>
- Final Ticket Amount: <final\_amount> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

3

Standard

Output: Booking ID: 1001

Customer Name: Ravi Kumar

Final Ticket Amount: 750.0

### **Answer**

// You are using Java

import java.util.\*;

class Customer{

private int bookingid;

private String name;

private int no\_tickets;

private String stype;

private double amount;

public Customer(int bookingid,String name,int no\_tickets,String stype){

this.bookingid=bookingid;

this.name=name;

this.no\_tickets=no\_tickets;

this.stype=stype;

}

public int getBookingID(){

return bookingid;

}

public String getName(){

return name;

}

public double getAmount(){

return amount;

}

public void setAmount(int no\_tickets,String stype){

double seat\_price=0.0;

switch (stype){

case "VIP":

seat\_price=600.0;

break;

case "Standard":

seat\_price=250.0;

```

        break;
    case "Premium":
        seat_price=400.0;
        break;
    }
    this.amount = no_tickets*seat_price;
    if(no_tickets>4)
        this.amount = amount -(amount * 0.10);

    if(stype.equals("VIP") && amount>3000) //stype=="VIP" will throw error
        this.amount= amount +(amount*0.05);
}
}

public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int N =sc.nextInt();
        Customer []cus=new Customer[N];
        for(int i=0;i<N;i++){
            int bookingid=sc.nextInt();
            sc.nextLine();
            String name=sc.nextLine();
            int no_tickets=sc.nextInt();
            sc.nextLine();
            String stype=sc.nextLine();

            cus[i]=new Customer(bookingid,name,no_tickets,stype);
            cus[i].setAmount(no_tickets,stype);

            System.out.println("Booking ID: "+cus[i].getBookingID());
            System.out.println("Customer Name: "+cus[i].getName());
            System.out.println("Final Ticket Amount: "+cus[i].getAmount());
        }
    }
}

```

**Status : Correct**

**Marks : 10/10**

## 2. Problem Statement

Neha is working as a developer for CityQuiz Platform, which wants to build a system to calculate quiz scores and identify top scorers among participants.

Each participant's record has:

Participant ID (integer) Participant Name (string) An array of scores in 5 quiz rounds (integers, each between 0 and 100)

The system must calculate:

Total Score = sum of scores in all 5 rounds. Average Score = Total Score ÷ 5. If a participant scores above 80 in all rounds, a bonus of 10 points is added to the total score. Identify the Top Scorer among all participants. If two participants have the same total score, the one with the lower Participant ID is considered the top scorer.

Neha has been asked to implement this system using:

A class with attributes for participant details. A constructor to initialize participant details. Getter and setter methods to retrieve or update participant details. A method to calculate total score and average score (including bonus if applicable). Objects of the class to represent participants.

Finally, display each participant's details and announce the Top Scorer.

### ***Input Format***

The first line of input contains an integer N, representing the number of participants.

For each participant:

- Next line: Participant ID (integer)
- Next line: Participant Name (string)
- Next line: 5 integers separated by spaces (scores for 5 quiz rounds)

### ***Output Format***

For each participant:

- Participant ID: <participant\_id>
- Participant Name: <participant\_name>
- Total Score: <total\_score>
- Average Score: <average\_score>

Finally, print "Top Scorer: <participant\_name> with <total\_score> points"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

85 90 88 92 87

Output: Participant ID: 1001

Participant Name: Ravi Kumar

Total Score: 452

Average Score: 90

Top Scorer: Ravi Kumar with 452 points

### **Answer**

// You are using Java

```
import java.util.*;
```

```
class Participant{
```

```
    private int p_id;
```

```
    private String name;
```

```
    private int avg;
```

```
    private int total;
```

```
    public Participant(int p_id,String name){
```

```
        this.p_id=p_id;
```

```
        this.name=name;
```

```
    }
```

```
    public int getID(){
```

```
        return p_id;
```

```

    }
    public String getName(){
        return name;
    }
    public int getTotal(){
        return total;
    }
    public int getAvg(){
        return avg;
    }
    public void setTotal(int total,int flag,int flag2){
        if(flag==1 && flag2==1)
            this.total=total+10;
        else
            this.total=total;
    }
    public void setAvg(int total){
        this.avg=this.total/5;
    }
}

```

```

public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int N=sc.nextInt();
        int max=0;
        String top_scorer="";
        Participant []p=new Participant[N];
        for(int i=0;i<N;i++){
            int p_id=sc.nextInt();
            sc.nextLine();
            String name=sc.nextLine();
            int total=0;
            //int avg=0;
            int flag=0;
            int flag2=1;
            int []arr = new int [5];
            for(int j=0;j<5;j++){
                arr[j]=sc.nextInt();
                total+=arr[j];
                if(arr[j]>80){
                    flag=1;
                }
            }
        }
    }
}

```

```

        else{
            flag=0;
            flag2=0;
        }
    }
    if(sc.hasNextLine()){
        sc.nextLine();
    }
    p[i]=new Participant(p_id,name);
    p[i].setTotal(total,flag,flag2);
    p[i].setAvg(total);
    System.out.println("Participant ID: "+p[i].getID());
    System.out.println("Participant Name: "+p[i].getName());
    System.out.println("Total Score: "+p[i].getTotal());
    System.out.println("Average Score: "+p[i].getAvg());

    if(p[i].getTotal()>max){
        max=p[i].getTotal();
        top_scorer=p[i].getName();
    }
}
System.out.printf("Top Scorer: %s with %d points\n",top_scorer,max);
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Each customer at the bank has an Account Number, Customer Name, and an Initial Balance. The bank allows two types of transactions:

Deposit – Increases the balance. Withdrawal – Decreases the balance, but only if enough funds are available. If the withdrawal amount exceeds the available balance, the transaction should be skipped, and the balance should remain unchanged.



You are required to implement this banking system by:

Creating a class with the necessary attributes to store account details.

Using a constructor to initialize the account details when a new account is created. Providing setter methods to update the details if required. Providing getter methods to retrieve account details. Creating objects of this class to represent different customers, where each customer can perform deposits and withdrawals.

Instructions:

Implement the class to store account details. Implement the logic for performing deposit and withdrawal transactions. Ensure that withdrawals don't exceed the available balance. After performing the transactions, print the account number, customer name, and final balance.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

### ***Output Format***

For each customer, print the details in the following format:

1. Account Number: <account\_number>
2. Customer Name: <customer\_name>
3. Final Balance: <final\_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma

Final Balance: 4000.0

### **Answer**

// You are using Java

```
import java.util.Scanner;
```

```
class Account {
```

```
    private int accountNumber;
```

```
    private String customerName;
```

```
    private double balance;
```

```
    public Account(int accountNumber, String customerName, double balance) {
```

```
        this.accountNumber = accountNumber;
```

```
        this.customerName = customerName;
```

```
        this.balance = balance;
```

```
    }
```

```
    public void setAccountNumber(int accountNumber) {
```

```
        this.accountNumber = accountNumber;
```

```
    }
```

```
    public void setCustomerName(String customerName) {
```

```
        this.customerName = customerName;
```

```
    }
```

```
    public void setBalance(double balance) {
```

```
        this.balance = balance;
```

```
    }
```

```
    public int getAccountNumber() {
```

```
        return accountNumber;
```

```
    }
```

```
    public String getCustomerName() {
```

```

        return customerName;
    }

    public double getBalance() {
        return balance;
    }

    public void deposit(double initBal, double amount) {
        balance = initBal + amount;
    }

    public void withdraw(double withdraw) {
        if (withdraw > balance)
            balance = balance;
        else
            balance = balance - withdraw;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        Account [] acc = new Account[n];
        for (int i = 0; i < n; i++) {
            int accNo = Integer.parseInt(sc.nextLine());
            String name = sc.nextLine();
            double initBal = Double.parseDouble(sc.nextLine());
            double deposit = Double.parseDouble(sc.nextLine());
            double withdraw = Double.parseDouble(sc.nextLine());

            acc[i] = new Account(accNo, name, initBal);
            acc[i].deposit(initBal, deposit);
            acc[i].withdraw(withdraw);

            System.out.println("Account Number: " + acc[i].getAccountNumber());
            System.out.println("Customer Name: " + acc[i].getCustomerName());
            System.out.println("Final Balance: " + acc[i].getBalance());
        }
        sc.close();
    }
}

```

Status : Correct

Marks : 10/10

#### 4. Problem Statement

Ravi is working as a developer for SecureLogin Systems, which wants to build a system to evaluate the strength of user passwords.

Each user record has:

User ID (integer) User Name (string) Password (string)

The system must calculate whether a password is strong or weak.

A password is considered strong if it meets all of the following conditions:

At least 8 characters long. Contains at least one uppercase letter. Contains at least one lowercase letter. Contains at least one digit. Contains at least one special character (from !@#\$%^&\*).

Ravi has been asked to implement this system using:

A class with attributes for user details. A constructor to initialize user details. Getter and setter methods to retrieve or update user details. A method to check whether the password is strong. Objects of the class to represent users.

Finally, display each user's details and indicate whether their password is Strong or Weak.

#### **Input Format**

The first line contains an integer N, representing the number of users.

For each user:

The next line contains the User ID (integer).

The next line contains the User Name (string).

The next line contains the Password (string).

### **Output Format**

For each user, print the details in the following format:

User ID: <user\_id>

User Name: <user\_name>

Password: <password>

Password Strength: <Strong/Weak>

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

Abc@1234

Output: User ID: 1001

User Name: Ravi Kumar

Password: Abc@1234

Password Strength: Strong

### **Answer**

// You are using Java

```
import java.util.*;
```

```
class User{
    private int id;
    private String name;
    private String password;
    private String strength;
    private boolean upper=false;
    private boolean lower=false;
    private boolean digi=false;
    private boolean hasSpecial=false;

    public User(int id,String name,String password){
```

```

    this.id=id;
    this.name=name;
    this.password=password;
}
public int getID(){
    return id;
}
public String getName(){
    return name;
}
public String getPassword(){
    return password;
}
public String getStrength(){
    return strength;
}
public String checkpassword(String password){
    String specialCharacters="!@#$%^&*";
    for(int j=0;j<password.length();j++){
        char ch=password.charAt(j);
        if(Character.isUpperCase(ch))
            upper=true;
        else if(Character.isLowerCase(ch))
            lower=true;
        else if(Character.isDigit(ch))
            digi=true;
        else{
            for (int k = 0; k < specialCharacters.length(); k++) {
                if (ch == specialCharacters.charAt(k)) {
                    hasSpecial = true;
                    break;
                }
            }
        }
    }
    if(password.length()>=8 && upper && lower && digi && hasSpecial)
        strength="Strong";
    else
        strength="Weak";
    return strength;
}

```

```

}
public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int N=sc.nextInt();
        User []u=new User[N];
        for(int i=0;i<N;i++){
            boolean upper=false;
            boolean lower=false;
            boolean digi=false;
            boolean hasSpecial=false;
            int id=sc.nextInt();
            sc.nextLine();
            String name=sc.nextLine();
            String password=sc.nextLine();
            u[i]=new User(id,name,password);
            u[i].checkpassword(password);
            System.out.println("User ID: "+u[i].getID());
            System.out.println("User Name: "+u[i].getName());
            System.out.println("Password: "+u[i].getPassword());
            System.out.println("Password Strength: "+u[i].getStrength());
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Anjali is working as a developer for CityFitness Gym, which wants to build a system to calculate monthly membership fees for gym members based on the type of membership and the number of personal training sessions booked.

Each member's record has:

Member ID (integer) Member Name (string) Membership Type (string: "Basic", "Premium", "Elite") Number of Personal Training Sessions (integer)

The monthly fees are:

Basic – 1000 units Premium – 1500 units Elite – 2000 units

The cost of personal training sessions is 500 units per session.

The calculation rules:

Total Amount = Membership Fee + (Number of Personal Training Sessions × 500) If the number of sessions is more than 5, a 10% discount is applied on the total amount. If the member has Elite membership and the total amount exceeds 4000, an additional 5% service tax is added after discount.

Anjali has been asked to implement this system using:

A class with attributes for member details. A constructor to initialize member details. Getter and Setter methods to retrieve and update member details if required. A method to calculate the final monthly fee. Objects of the class to represent members.

Finally, display each member's details and the final monthly fee.

### ***Input Format***

The first line contains an integer N, representing the number of members.

For each member:

- Next line contains Member ID (integer)
- Next line contains Member Name (string)
- Next line contains Membership Type ("Basic", "Premium", "Elite")
- Next line contains Number of Personal Training Sessions (integer)

### ***Output Format***

For each member, print:

- Member ID: <member\_id>
- Member Name: <member\_name>
- Final Monthly Fee: <final\_fee> (The final fee must be rounded to one decimal place)



Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

Basic

3

Output: Member ID: 1001

Member Name: Ravi Kumar

Final Monthly Fee: 2500.0

### **Answer**

// You are using Java

```
import java.util.*;
```

```
class Gym_member{  
    private int mem_id;  
    private String name;  
    private String m_type;  
    private int sessions;  
    private double tot_fee;
```

```
    public Gym_member(int mem_id,String name,String m_type){  
        this.mem_id=mem_id;  
        this.name=name;  
        this.m_type=m_type;
```

```
    }  
    public int getMemid(){  
        return mem_id;  
    }
```

```
    public String getName(){  
        return name;  
    }
```

```
    public double getFee(){  
        return tot_fee;  
    }
```

```
    public void setFee(int sessions,String m_type){  
        int mem_fee=0;  
        switch(m_type){  
            case "Basic":  
                mem_fee=1000;  
                break;
```

```

        case "Premium":
            mem_fee=1500;
            break;

        case "Elite":
            mem_fee=2000;
            break;
    }
    this.tot_fee = mem_fee + (sessions*500);
    if(sessions>5)
        this.tot_fee = tot_fee - (tot_fee*0.10);
    if(m_type.equals("Elite") && tot_fee>4000)
        this.tot_fee = tot_fee + (tot_fee*0.05);
    }
}

public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int N=sc.nextInt();
        Gym_member []g=new Gym_member[N];
        for(int i=0;i<N;i++){

            int mem_id=sc.nextInt();
            sc.nextLine();
            String name=sc.nextLine();
            String m_type=sc.nextLine();
            int sessions=sc.nextInt();
            g[i]=new Gym_member(mem_id,name,m_type);
            g[i].setFee(sessions,m_type);

            System.out.println("Member ID: "+g[i].getMemid());
            System.out.println("Member Name: "+g[i].getName());
            System.out.println("Final Monthly Fee: "+g[i].getFee());

        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 5\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Anjali is working as a developer for the City Basketball Association, which wants to build a system to track and find the top scorer among basketball players.

Each player's record has:

Player ID (integer) Player Name (string) An array of points scored in 5 matches (integers)

The system must calculate:

The total score of each player (sum of all match points). Identify the highest scorer among all players. If two or more players have the same total score, the one with the lower Player ID is considered the top scorer.

Anjali has been asked to implement this system using:

A class with attributes for player details. A constructor to initialize player details. Getter and Setter methods to retrieve and update player details if required. A method to calculate the total score. Objects of the class to represent players.

Finally, display each player's details and announce the Top Scorer.

### ***Input Format***

The first line of input contains an integer N (number of players).

For each player:

- The next line contains the Player ID (integer).
- The following line contains the Player Name (string).
- The next line contains 5 integers separated by spaces (points scored in 5 matches).

### ***Output Format***

For each player the output prints the following details:

- Player ID: <player\_id>
- Player Name: <player\_name>
- Total Score: <total\_score>

Finally, print "Top Scorer: <player\_name> with <total\_score> points"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

10 20 30 40 50

Output: Player ID: 1001  
Player Name: Ravi Kumar  
Total Score: 150  
Top Scorer: Ravi Kumar with 150 points

**Answer**

```
import java.util.Scanner;

class Player {
    private int id;
    private String name;
    private int[] scores = new int[5];
    private int total;

    public Player(int id, String name, int[] scores) {
        this.id = id;
        this.name = name;
        this.scores = scores;
        this.total = 0;
        for (int i = 0; i < 5; i++) {
            this.total += scores[i];
        }
    }

    public int getId() {
        return id;
    }

    public String getName() {
        return name;
    }

    public int getTotal() {
        return total;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
```

```

Player[] players = new Player[n];

int topScore = -1;
int topId = 9999;
String topName = "";

for (int i = 0; i < n; i++) {
    int id = sc.nextInt();
    sc.nextLine();
    String name = sc.nextLine();
    int[] scores = new int[5];
    int total = 0;
    for (int j = 0; j < 5; j++) {
        scores[j] = sc.nextInt();
        total += scores[j];
    }
    //sc.nextLine();
    players[i] = new Player(id, name, scores);

    System.out.println("Player ID: " + players[i].getId());
    System.out.println("Player Name: " + players[i].getName());
    System.out.println("Total Score: " + players[i].getTotal());

    if (players[i].getTotal() > topScore) {
        topScore = players[i].getTotal();
        topId = players[i].getId();
        topName = players[i].getName();
    } else if (players[i].getTotal() == topScore && players[i].getId() < topId) {
        topId = players[i].getId();
        topName = players[i].getName();
    }
}

System.out.println("Top Scorer: " + topName + " with " + topScore + "
points");
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Meera is working as a developer for CityGas Supply Board, which wants to build a household gas billing system.

Each household's gas account has:

A Customer ID (integer) A Customer Name (string) Units Consumed in cubic meters (double)

The gas bill is calculated based on these rules:

For the first 50 units    4 per unit For the next 100 units (51–150)    6 per unit  
For units above 150    8 per unit If the total bill exceeds 2000, a 15% discount is applied on the final bill.

Meera has been asked to implement this system using:

A class with attributes for customer details. A constructor to initialize customer details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Units Consumed (double).

### ***Output Format***

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Bill: <final\_bill> (The final bill must be rounded to one decimal place.)

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

1001

Ravi Kumar

30

Output: Customer ID: 1001

Customer Name: Ravi Kumar

Final Bill: 120.0

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
class Customer {
    private int id;
    private String name;
    private double units;
    private double bill;

    public Customer(int id, String name, double units) {
        this.id = id;
        this.name = name;
        this.units = units;
        this.bill = 0.0;
    }

    public int getId() {
        return id;
    }

    public String getName() {
        return name;
    }

    public double getUnits() {
        return units;
    }
}
```



```

    public double getBill() {
        return bill;
    }

    public void setBill(double bill) {
        this.bill = bill;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
        Customer[] customers = new Customer[n];

        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            sc.nextLine();
            String name = sc.nextLine();
            double units = sc.nextDouble();

            customers[i] = new Customer(id, name, units);

            double bill = 0.0;

            if (units <= 50) {
                bill = units * 4;
            } else if (units <= 150) {
                bill = (50 * 4) + ((units - 50) * 6);
            } else {
                bill = (50 * 4) + (100 * 6) + ((units - 150) * 8);
            }

            if (bill > 2000) {
                bill = bill - (bill * 0.15);
            }
            customers[i].setBill(bill);

            System.out.println("Customer ID: " + customers[i].getId());
            System.out.println("Customer Name: " + customers[i].getName());
        }
    }
}

```

```
        System.out.println("Final Bill: " + String.format("%.1f",
customers[i].getBill()));
    }
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Anjali is now working as a developer for the City Marathon Association, which wants to build a system to track and find the fastest runner among marathon participants.

Each runner's record has:

Runner ID (integer) Runner Name (string) An array of times (in minutes) taken in 5 marathon events (integers)

The system must calculate:

The average time of each runner (sum of all times / 5). Identify the fastest runner (the one with the lowest average time). If two or more runners have the same average time, the one with the lower Runner ID is considered the fastest runner.

Anjali has been asked to implement this system using:

A class with attributes for runner details. A constructor to initialize runner details. Getter and Setter methods to retrieve and update runner details if required. A method to calculate the average time. Objects of the class to represent runners.

Finally, display each runner's details and announce the Fastest Runner.

#### **Input Format**

The first line of input contains an integer N (number of runners).

For each runner:

- The next line contains the Runner ID (integer).
- The following line contains the Runner Name (string).
- The next line contains 5 integers separated by spaces (times in minutes for 5 marathon events).

### ***Output Format***

For each runner the output prints the following details:

- Runner ID: <runner\_id>
- Runner Name: <runner\_name>
- Average Time: <average\_time>

Finally, print "Fastest Runner: <runner\_name> with <average\_time> minutes"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

240 250 245 255 260

Output: Runner ID: 1001

Runner Name: Ravi Kumar

Average Time: 250

Fastest Runner: Ravi Kumar with 250 minutes

### ***Answer***

// You are using Java

```
import java.util.Scanner;
```

```
class Runner {  
    private int id;  
    private String name;  
    private int[] times = new int[5];  
    private int average;
```

```
public Runner(int id, String name, int[] times) {  
    this.id = id;  
    this.name = name;  
    this.times = times;  
    calculateAverage();  
}
```

```
public void calculateAverage() {  
    int sum = 0;  
    for (int i = 0; i < 5; i++) {  
        sum += times[i];  
    }  
    this.average = sum / 5;  
}
```

```
public int getId() {  
    return id;  
}
```

```
public String getName() {  
    return name;  
}
```

```
public int getAverage() {  
    return average;  
}  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        sc.nextLine();  
        Runner[] runners = new Runner[n];  
        for (int i = 0; i < n; i++) {  
            int id = sc.nextInt();  
            sc.nextLine();  
            String name = sc.nextLine();  
            int[] times = new int[5];  
            for (int j = 0; j < 5; j++) {  
                times[j] = sc.nextInt();  
            }  
        }  
    }  
}
```

```

        //sc.nextLine();
        runners[i] = new Runner(id, name, times);
    }
    for (int i = 0; i < n; i++) {
        System.out.println("Runner ID: " + runners[i].getId());
        System.out.println("Runner Name: " + runners[i].getName());
        System.out.println("Average Time: " + runners[i].getAverage());
    }
    int minAvg = runners[0].getAverage();
    int minId = runners[0].getId();
    String fastestRunner = runners[0].getName();
    for (int i = 1; i < n; i++) {
        int currentAvg = runners[i].getAverage();
        int currentId = runners[i].getId();
        if (currentAvg < minAvg || (currentAvg == minAvg && currentId < minId)) {
            minAvg = currentAvg;
            minId = currentId;
            fastestRunner = runners[i].getName();
        }
    }
    System.out.println("Fastest Runner: " + fastestRunner + " with " + minAvg + "
minutes");
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

You are working as a developer for CityMobile, which wants to build a basic mobile data usage management system.

Each customer has:

A Customer ID (integer) A Customer Name (string) An Initial Data Balance (in GB, double)

The company allows two types of operations:

Recharge – increases the data balance. Usage – decreases the data

balance only if enough data is available.

If the usage amount is greater than the available data balance, the usage should not happen, and the balance should remain the same.

You are required to implement this system using:

A class with attributes for customer details. A constructor to initialize customer details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details after all operations.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Initial Data Balance (double).
- The next line contains the Recharge Amount in GB (double).
- The next line contains the Usage Amount in GB (double).

### ***Output Format***

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Data Balance: <final\_data\_balance> GB (The final balance must be rounded to one decimal place.)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Ravi Kumar

5.0

2.0

3.0

Output: Customer ID: 1234

Customer Name: Ravi Kumar

Final Data Balance: 4.0 GB

### **Answer**

// You are using Java

import java.util.\*;

```
class Customer {  
    private int id;  
    private String name;  
    private double balance;  
  
    public Customer(int id, String name, double balance) {  
        this.id = id;  
        this.name = name;  
        this.balance = balance;  
    }  
  
    public void setBalance(double balance) {  
        this.balance = balance;  
    }  
  
    public int getId() {  
        return id;  
    }  
  
    public String getName() {  
        return name;  
    }  
  
    public double getBalance() {  
        return balance;  
    }  
}
```

```
public void recharge(double amount) {  
    if (amount >= 0) {  
        this.balance += amount;  
    }  
}
```

```
public void useData(double amount) {  
    if (amount <= this.balance) {  
        this.balance -= amount;  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int N = sc.nextInt();  
        sc.nextLine();
```

```
        Customer[] customers = new Customer[N];
```

```
        for (int i = 0; i < N; i++) {  
            int id = sc.nextInt();  
            sc.nextLine();
```

```
            String name = sc.nextLine();  
            double initialBalance = sc.nextDouble();  
            double rechargeAmount = sc.nextDouble();  
            double usageAmount = sc.nextDouble();
```

```
            customers[i] = new Customer(id, name, initialBalance);
```

```
            customers[i].recharge(rechargeAmount);
```

```
            customers[i].useData(usageAmount);  
        }  
}
```



```
for (int i = 0; i < N; i++) {  
    System.out.println("Customer ID: " + customers[i].getId());  
    System.out.println("Customer Name: " + customers[i].getName());  
    System.out.printf("Final Data Balance: %.1f GB\n",  
customers[i].getBalance());  
}  
}  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 6\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 14

#### Section 1 : MCQ

1. What will be the output of the following Java program?

```
class Test {  
    void display(int a, int b) {  
        System.out.println("Method 1");  
    }  
    void display(double a, double b) {  
        System.out.println("Method 2");  
    }  
    public static void main(String[] args) {  
        Test obj = new Test();  
        obj.display(10, 10.0);  
    }  
}
```

**Answer**

Method 2

Status : Correct

Marks : 1/1

2. What will be the output of the following Java program?

```
class A {  
    void display() {  
        System.out.println("Class A");  
    }  
}  
  
class B extends A {  
    void show() {  
        System.out.println("Class B");  
    }  
}  
  
class C extends B {  
    void print() {  
        System.out.println("Class C");  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.display();  
        obj.show();  
        obj.print();  
    }  
}
```

Answer

Class AClass BClass C

Status : Correct

Marks : 1/1

3. Which of the following is true about method overriding in Java?

**Answer**

The method must have the same name, same parameters, and must be in different classes with an inheritance relationship

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following Java program?

```
class Vehicle {  
    void startEngine() {  
        System.out.println("Vehicle engine started");  
    }  
}  
  
class Car extends Vehicle {  
    void startEngine() {  
        System.out.println("Car engine started");  
    }  
}  
  
class Main {  
    public static void main(String[] args) {  
        Vehicle myVehicle = new Car();  
        myVehicle.startEngine();  
    }  
}
```

**Answer**

Car engine started

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
class A {  
    void display() {  
        System.out.println("Display A");  
    }  
}
```

```
}  
class B extends A {  
    void display() {  
        System.out.println("Display B");  
    }  
}
```

```
class C extends B {  
    void display() {  
        super.display();  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.display();  
    }  
}
```

**Answer**

Display B

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following Java program?

```
class Test {  
    void show(int a) {  
        System.out.println("Integer method");  
    }  
    void show(String s) {  
        System.out.println("String method");  
    }  
    public static void main(String[] args) {  
        Test obj = new Test();  
        obj.show(null);  
    }  
}
```

}

**Answer**

Compilation error due to ambiguous method call

**Status :** Wrong

**Marks :** 0/1

7. What will be the output of the following program?

```
class A {  
    int x = 10;  
}  
  
class B extends A {  
    int x = 20;  
}  
  
class C extends B {  
    int x = 30;  
  
    void display() {  
        System.out.println(x);  
        System.out.println(super.x);  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.display();  
    }  
}
```

**Answer**

3020

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following program?

```
class A {  
    public int i;  
    private int j;  
}  
class B extends A {  
    void display() {  
        super.j = super.i + 1;  
        System.out.println(super.i + " " + super.j);  
    }  
}  
class inheritance {  
    public static void main(String args[]) {  
        B obj = new B();  
        obj.i=1;  
        obj.j=2;  
        obj.display();  
    }  
}
```

**Answer**

Compile Time Error

**Status :** Correct

**Marks :** 1/1

9. Select the correct keyword for implementing inheritance through the class.

**Answer**

extends

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
class A {  
    int sum(int x) {  
        return x + 2;  
    }  
}
```

```
}  
class B extends A {  
    int sum(int x) {  
        return super.sum(x) * 2;  
    }  
}
```

```
class C extends B {  
    int sum(int x) {  
        return super.sum(x) - 3;  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        C obj = new C();  
        System.out.println(obj.sum(4));  
    }  
}
```

**Answer**

9

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following Java program?

```
class A {  
    int value = 10;  
    void display() {  
        System.out.println("A's display: " + value);  
    }  
}  
class B extends A {  
    int value = 20;  
    void display() {  
        System.out.println("B's display: " + value);  
    }  
}
```



```
}  
class Test {  
    public static void main(String[] args) {  
        A obj = new B();  
        obj.display();  
        System.out.println("Value: " + obj.value);  
    }  
}
```

**Answer**

B's display: 20 Value: 10

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following Java program?

```
class Vehicle {  
    void start() {  
        System.out.println("Vehicle starts");  
    }  
}  
class Car extends Vehicle {  
    void start() {  
        System.out.println("Car starts");  
    }  
}  
class ElectricCar extends Car {  
    void start() {  
        System.out.println("Electric Car starts silently");  
    }  
}  
class Test {  
    public static void main(String[] args) {  
        Vehicle v = new ElectricCar();  
        v.start();  
    }  
}
```

**Answer**

Electric Car starts silently

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following program?

```
class Vehicle {  
    String type = "Vehicle";  
}  
  
class Car extends Vehicle {  
    String type = "Car";  
}  
  
class Test {  
    public static void main(String[] args) {  
        Car c = new Car();  
        System.out.println(c.type);  
    }  
}
```

**Answer**

Car

**Status :** Correct

**Marks :** 1/1

14. Which of the following is the correct way for class B to inherit from class A?

**Answer**

class B extends A {}

**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following Java program?

```
class Parent {
```

```
void show() {  
    System.out.println("Parent class");  
}  
}  
class Child extends Parent {  
    void show() {  
        System.out.println("Child class");  
    }  
}  
class Test {  
    public static void main(String[] args) {  
        Parent obj = new Child();  
        obj.show();  
    }  
}
```

**Answer**

Child class

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Elsa subscribes to a premium service with a base monthly cost, a service tax and an extra feature cost. Assist her in writing an inheritance program that takes input for these values and calculates the total monthly cost.

Refer to the below class diagram:

##### ***Input Format***

The first line of input consists of a double value, representing the base monthly cost.

The second line consists of a double value, representing the service tax.

The third line consists of a double value, representing the extra feature cost.

### **Output Format**

The output prints "Rs. X" where X is a double value, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10.0

2.5

5.0

Output: Rs. 17.50

### **Answer**

```
import java.util.Scanner;
```

```
// You are using Java
```

```
class Subscription{
```

```
    protected double baseMonthlyCost;
```

```
    protected double serviceTax;
```

```
    public Subscription(double baseMonthlyCost,double serviceTax){
```

```
        this.baseMonthlyCost=baseMonthlyCost;
```

```
        this.serviceTax=serviceTax;
```

```
    }
```

```
}
```

```
class PremiumSubscription extends Subscription{
```

```
    private double extraFeatureCost;
```

```
    public PremiumSubscription(double baseMonthlyCost,double  
serviceTax,double extraFeatureCost){
```

```
        super(baseMonthlyCost,serviceTax);
```

```
        this.extraFeatureCost=extraFeatureCost;
```

```
    }
```

```
    public double calculateMonthlyCost(){
```

```
        return baseMonthlyCost + serviceTax + extraFeatureCost;
```

```
    }
```

```
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double baseMonthlyCost = scanner.nextDouble();  
        double serviceTax = scanner.nextDouble();  
        double extraFeatureCost = scanner.nextDouble();  
  
        PremiumSubscription premiumSubscription = new  
PremiumSubscription(baseMonthlyCost, serviceTax, extraFeatureCost);  
  
        double totalMonthlyCost = premiumSubscription.calculateMonthlyCost();  
  
        System.out.printf("Rs. %.2f%n", totalMonthlyCost);  
  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Alice is managing an online store and wants to implement a program using inheritance to calculate the selling price of products after applying discounts.

Guide her by following the instructions:

Create a base class called Product with a public double attribute price. Create a subclass called DiscountedProduct, which extends Product and includes a private double attribute discount rate. This subclass has a method called calculateSellingPrice() to determine the final selling price after applying the discount.

Formula: Discounted selling price = price \* (1 - discount rate)

**Input Format**

The first line of input consists of a double value p, the initial price of the product.

The second line consists of a double value d, the discount rate.

### **Output Format**

The output prints "Rs. X", where X is a double value, representing the calculated discounted selling price, rounded off to two decimal places.

If the discount rate is greater than 1, print "Not applicable".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 50.00

0.20

Output: Rs. 40.00

### **Answer**

```
import java.util.Scanner;
```

```
// You are using Java
```

```
class Product{
```

```
    public double initialPrice;
```

```
    public Product(double initialPrice){
```

```
        this.initialPrice=initialPrice;
```

```
    }
```

```
}
```

```
class DiscountedProduct extends Product{
```

```
    private double discountRate;
```

```
    public DiscountedProduct(double initialPrice,double discountRate){
```

```
        //this.initialPrice=initialPrice;
```

```
        super(initialPrice);
```

```
        this.discountRate=discountRate;
```

```
    }
```

```
    public double calculateSellingPrice(){
```



```
double discountSP=initialPrice -(initialPrice*discountRate);  
return discountSP;  
}  
}  
  
class ProductPricing {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double initialPrice = scanner.nextDouble();  
        double discountRate = scanner.nextDouble();  
        DiscountedProduct discountedProduct = new  
DiscountedProduct(initialPrice, discountRate);  
        double sellingPrice = discountedProduct.calculateSellingPrice();  
  
        if (sellingPrice >= 0) {  
            System.out.printf("Rs. %.2f%n", sellingPrice);  
        } else {  
            System.out.println("Not applicable");  
        }  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Preethi is working on a project to automate sales tax calculations for items in a store. She wants to create a program that takes the price of an item and the sales tax rate as input and calculates the final price of the item after applying the sales tax.

Write a program using the class SalesTaxCalculator, which contains an overloaded method named calculateFinalPrice to handle both integer and double inputs. The program should also include a Main class that takes user input, calls the appropriate method from SalesTaxCalculator, and prints the final price of the item.

Formula Used: Final price = price + ((price \* sales tax rate) / 100)

**Input Format**

The first line of input consists of an integer price (the price of the item for integer inputs).

The second line of input consists of an integer taxRate (the sales tax rate for integer inputs).

The third line of input consists of a double price (the price of the item for double inputs).

The fourth line of input consists of a double taxRate (the sales tax rate for double inputs).

### ***Output Format***

The first line of output prints an integer, representing the final price of the item after applying the sales tax for integer inputs (a and b).

The second line prints a double value, representing the final price of the item after applying the sales tax for double-value inputs (m and n), rounded to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 100

10

100.0

5.0

Output: 110

105.00

### ***Answer***

```
import java.util.Scanner;
```

```
// You are using Java
```

```
class SalesTaxCalculator{
```

```
    //salesCalculator SalesTaxCalculator=new salesCalculator();
```

```
    protected int intPrice;
```

```
    protected int intTaxRate ;
```

```
    protected double doublePrice;
```

```

protected double doubleTaxRate;

public SalesTaxCalculator(int intPrice,int intTaxRate,double
doublePrice,double doubleTaxRate){
    this.intPrice=intPrice;
    this.intTaxRate=intTaxRate;
    this.doublePrice=doublePrice;
    this.doubleTaxRate=doubleTaxRate;
} //static important because u can access using class name
public static int calculateFinalPrice(int intPrice,int intTaxRate){
    int fSP=intPrice +((intPrice*intTaxRate)/100);
    return fSP;
}
public static double calculateFinalPrice(double doublePrice,double
doubleTaxRate){
    double fsp=doublePrice +((doublePrice*doubleTaxRate)/100);
    return fsp;
}
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        int intPrice = scanner.nextInt();
        int intTaxRate = scanner.nextInt();
        double doublePrice = scanner.nextDouble();
        double doubleTaxRate = scanner.nextDouble();

        int finalPriceInt = SalesTaxCalculator.calculateFinalPrice(intPrice,
intTaxRate);
        double finalPriceDouble =
SalesTaxCalculator.calculateFinalPrice(doublePrice, doubleTaxRate);

        System.out.println(finalPriceInt);
        System.out.format("%.2f", finalPriceDouble);
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Mr.Kapoor wants to create a program to calculate the volume of a Cuboid and a Cube using method overriding.

Implements a base class Cuboid with attributes for length, width, and height. Include a method calculateVolume() that computes the volume of the cuboid.

Extends the base class with a subclass Cube representing a cube, where all sides are equal. Override the calculateVolume() method in the Cube class to compute the volume of the cube.

The program should take user input for the dimensions of the cuboid and the side length of the cube and display the calculated volumes with two decimal places.

### ***Input Format***

The first line of input consists of 3 space-separated double values, representing the cuboid length, width, and height, respectively.

The second line consists of a double value, representing the side length of the cube.

### ***Output Format***

The first line of output prints the volume of the cuboid, rounded off to two decimal places.

The second line prints the volume of the cube, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 60.0 60.0 60.0  
50.0

Output: Volume of Cuboid: 216000.00  
Volume of Cube: 125000.00

### ***Answer***

```
import java.util.Scanner;
// You are using Java
class Cuboid{
    protected double cuboidLength;
    protected double cuboidWidth;
    protected double cuboidBreadth;

    Cuboid(double cuboidLength,double cuboidWidth,double cuboidBreadth){
        this.cuboidLength=cuboidLength;
        this.cuboidWidth=cuboidWidth;
        this.cuboidBreadth=cuboidBreadth;
    }

    public double calculateVolume(){
```

```

        return cuboidLength * cuboidWidth * cuboidBreadth;
    }
}

class Cube extends Cuboid{
    public double cubeSide;

    Cube(double cubeSide){
        super(cubeSide,cubeSide,cubeSide);
        //this.cubeSide=cubeSide;
    }
    @Override
    public double calculateVolume(){
        return cuboidLength * cuboidLength * cuboidLength;//cubeSide * cubeSide *
        cubeSide ;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double cuboidLength = scanner.nextDouble();
        double cuboidWidth = scanner.nextDouble();
        double cuboidHeight = scanner.nextDouble();

        // Regular object instantiation for Cuboid
        Cuboid cuboid = new Cuboid(cuboidLength, cuboidWidth, cuboidHeight);
        System.out.printf("Volume of Cuboid: %.2f\n", cuboid.calculateVolume());

        double cubeSide = scanner.nextDouble();

        // Upcasting - Using superclass reference for subclass object (DMD)
        Cuboid cube = new Cube(cubeSide); // Upcasting
        System.out.printf("Volume of Cube: %.2f", cube.calculateVolume()); // Calls
        Cube's method dynamically

        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem statement:

Tim was tasked with developing a grocery shopping app. You have a class hierarchy that includes Item, Produce, and OrganicProduce. Your goal is to calculate the total cost of a shopping list, which may contain a mix of regular produce and organic produce items. Additionally, you need to apply discounts to organic items. Apply a 10% discount on organic produce items

Class Hierarchy:

Item: Base class for all items.

Produce: Subclass of Item for regular produce items.

OrganicProduce: Subclass of Produce for organic produce items.



### ***Input Format***

The first line of input consists of an integer, 'n'.

For each 'n' item, the user will provide:

- A string 'type' representing the item type ('Regular' or 'Organic').
- A string 'name' represents the item name.
- A double 'price' represents the item price.

### ***Output Format***

The output will display the total cost of the shopping list, including discounts on organic items.

Refer to the sample output for format specifications.

### ***Sample Test Case***

Input: 1

Regular Banana 1.99

Output: 1.99

### ***Answer***

```
import java.util.Scanner;

// You are using Java
class Item{
    protected String name;
    protected double price;

    Item(String name,double price){
        this.name=name;
        this.price=price;
    }
    public double calculateCost(){
        return price;
    }
}

class Produce extends Item{
    Produce(String name,double price){
```

```
        super(name,price);
    }
    @Override
    public double calculateCost(){
        return price;
    }
}
class OrganicProduce extends Produce{
    OrganicProduce(String name,double price){
        super(name,price);
    }
    @Override
    public double calculateCost(){
        return price * 0.90;
    }
}
```

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        sc.nextLine(); // Consume newline

        double totalCost = 0.0;

        for (int i = 0; i < n; i++) {
            String type = sc.next();
            String name = sc.next();
            double price = sc.nextDouble();

            if (type.equals("Regular")) {
                Item item = new Produce(name, price);
                totalCost += item.calculateCost();
            } else if (type.equals("Organic")) {
                Item item = new OrganicProduce(name, price);
                totalCost += item.calculateCost();
            }
        }
    }
}
```

```
        System.out.printf("%.2f%n", totalCost);  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 6\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Sharon, a software developer, is working on a project to automate velocity calculations for various objects. She wants to create a class named VelocityCalculator with overloaded methods calculateVelocity to calculate the velocity. One method will accept distance in meters and time in seconds as integers, while another will accept distance and time as doubles.

Help her in completing the project.

Formula:  $\text{Velocity} = \text{distance} / \text{time}$

##### ***Input Format***

The first line of input consists of an integer, representing the distance in meters

(for the integer method).

The second line consists of an integer, representing the time in seconds (for the integer method).

The third line consists of a double value, representing the distance in meters (for the double method).

The fourth line consists of a double value, representing the time in seconds (for the double method).

### ***Output Format***

The first line prints the velocity calculated using the integer inputs in the format:

Velocity with integer inputs: <velocity> m/s

The second line prints the velocity calculated using the double inputs in the format:

Velocity with double inputs: <velocity> m/s

Note:

The velocity for the double inputs should be printed with two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 100

10

100.5

10.2

Output: Velocity with integer inputs: 10 m/s

Velocity with double inputs: 9.85 m/s

***Answer***

```
import java.util.Scanner;

// You are using Java
class VelocityCalculator{
    public int distanceInt;
    public int timeInt;
    public double distanceDouble;
    public double timeDouble;

    public VelocityCalculator(int distanceInt,int timeInt,double
distanceDouble,double timeDouble){
        this.distanceInt=distanceInt;
        this.timeInt=timeInt;
        this.distanceDouble=distanceDouble;
        this.timeDouble=timeDouble;
    }

    public static int calculateVelocity(int distanceInt,int timeInt){
        return distanceInt/timeInt;
    }

    public static double calculateVelocity(double distanceDouble,double
timeDouble){
        return distanceDouble/timeDouble;
    }
    //VelocityCalculator VelocityCalculator = new VelocityCalculator();
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int distanceInt = scanner.nextInt();
        int timeInt = scanner.nextInt();

        double distanceDouble = scanner.nextDouble();
        double timeDouble = scanner.nextDouble();

        int velocityInt = VelocityCalculator.calculateVelocity(distanceInt, timeInt);
        double velocityDouble =
VelocityCalculator.calculateVelocity(distanceDouble, timeDouble);

        System.out.println("Velocity with integer inputs: " + velocityInt + " m/s");
```

```
System.out.printf("Velocity with double inputs: %.2f m/s", velocityDouble);  
    scanner.close();  
}  
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

In a company, each manager has a unique employee ID and a monthly salary. You are required to design a program that will calculate and display the annual(12 months) salary of a manager based on the input details provided by the user.

Implement the solution using a single inheritance approach.

Employee: The base class with attributes name and employeeID.

Manager: The derived class inheriting from Employee, with an additional attribute salary.

### ***Input Format***

The first line of input consists of a string name, representing the manager's name.

The second line of input consists of an integer employeeID, representing the manager's employee ID.

The third line of input consists of a double salary, representing the manager's monthly salary.

### ***Output Format***

The first line of output prints: Name: <name>

The second line of output prints: Annual Salary: Rs. <annual\_salary> (rounded to two decimal places).

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Davis

234

28750.75

Output: Name: Davis

Annual Salary: Rs. 345009.00

### **Answer**

```
import java.util.Scanner;
import java.text.DecimalFormat;

// You are using Java
class Employee{
    protected String name;
    protected int employeeID;

    Employee(String name,int employeeID){
        this.name=name;
        this.employeeID=employeeID;
    }
}

class Manager extends Employee{
    public double salary;

    Manager(String name,int employeeID,double salary){
        super(name,employeeID);
        this.salary=salary;
    }
    public double calculateAnnualSalary(){
        return salary * 12;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        DecimalFormat df = new DecimalFormat("0.00");

        String name = scanner.nextLine();
```



```
int employeeID = scanner.nextInt();
double salary = scanner.nextDouble();

Manager manager = new Manager(name, employeeID, salary);

System.out.println("Name: " + manager.name);
System.out.println("Annual Salary: Rs. " +
df.format(manager.calculateAnnualSalary()));

    scanner.close();
}
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

John is planning a long road trip and wants to calculate the distance his car can travel based on its speed and fuel capacity. As John knows that different cars have different fuel efficiencies, he wants a program that can help him estimate the travel distance for any given car.

To do this, you are tasked with creating a program that calculates the travel distance of a car based on its speed and fuel capacity. The calculation is simple and follows the formula:

$\text{Travel Distance} = \text{Speed} * \text{Fuel Capacity}$

You need to model this system using a Vehicle class and a Car class. The Vehicle class will have attributes for the speed and fuel capacity, while the Car class will inherit from the Vehicle class and include a method to calculate the travel distance.

#### ***Input Format***

The first line of input consists of a double value representing the speed of the car in km/h.

The second line of input consists of a double value representing the fuel capacity of the car in liters.

### **Output Format**

The first line should print "Speed: X km/h", where X is the speed of the car, rounded to two decimal places.

The second line should print "Fuel Capacity: Y liters", where Y is the fuel capacity of the car, rounded to two decimal places.

The third line should print "Travel Distance: Z km", where Z is the total travel distance the car can cover, rounded to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10.0

1.0

Output: Speed: 10.00 km/h

Fuel Capacity: 1.00 liters

Travel Distance: 10.00 km

### **Answer**

```
import java.util.Scanner;

// You are using Java
class Vehicle{
    protected double speed;
    protected double fuelCapacity;

    Vehicle(double speed,double fuelCapacity){
        this.speed=speed;
        this.fuelCapacity=fuelCapacity;
    }
}

class Car extends Vehicle{
    Car(double speed,double fuelCapacity){
        super(speed,fuelCapacity);
    }
    public double calculateTravelDistance(){
        return speed * fuelCapacity;
    }
}
```

```

}
public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double speed = scanner.nextDouble();
        double fuelCapacity = scanner.nextDouble();

        Car car = new Car(speed, fuelCapacity);

        System.out.println("Speed: " + String.format("%.2f", car.speed) + " km/h");
        System.out.println("Fuel Capacity: " + String.format("%.2f", car.fuelCapacity)
+ " liters");
        System.out.println("Travel Distance: " + String.format("%.2f",
car.calculateTravelDistance()) + " km");

        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Ram is designing a program to calculate the Body Mass Index (BMI). Your task is to assist him by following the given specifications.

Create a base class BMIcalculator with a method calculateBMI() to compute BMI using the formula  $\text{weight} / (\text{height} * \text{height})$ .

Extend the class with a subclass CustomBMIcalculator that overrides the method calculateBMI() to calculate BMI based on custom criteria, assigning categories such as "Underweight," "Normal Weight," "Overweight," or "Obese."

BMI < 18.5, category = "Underweight" BMI >= 18.5 & < 24.9, category = "Normal Weight" BMI >= 25 & < 29.9, category = "Overweight" else category = "Obese"

Implement user input for weight and height and display both the standard

and custom BMI calculations.

### ***Input Format***

The first line of input consists of a double value, representing the weight in kgs.

The second line consists of a double value, representing the height in meters.

### ***Output Format***

The first line of output prints: "Standard BMI Calculation:"

The second line of output prints: "BMI: " followed by the calculated BMI value (to two decimal places).

The third line of output prints: "Custom BMI Calculation:"

The fourth line of output prints: "Category: " followed by the BMI category.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 69.7

2.6

Output: Standard BMI Calculation:

BMI: 10.31

Custom BMI Calculation:

Category: Underweight

### ***Answer***

```
import java.util.Scanner;
```

```
// You are using Java
```

```
class BMIcalculator{  
    protected double weight;  
    protected double height;  
    protected double BMI;
```

```
    BMIcalculator(double weight,double height){  
        this.weight=weight;
```

```

        this.height=height;
    }
    public double displayBMI(){
        BMI=weight / (height * height);
        System.out.printf("BMI: %.2f\n",BMI);
        return BMI;
    }
}
class CustomBMIcalculator extends BMIcalculator{
    CustomBMIcalculator(double weight,double height){
        super(weight,height);
    }
    //@Override
    public void displayCustomBMI(){
        BMI = weight / (height * height);
        String category=" ";
        if (BMI<18.5) {
            category = "Underweight";
            System.out.println("Category: "+category);
        } else if (BMI>= 18.5 && BMI < 24.9) {
            category = "Normal Weight";
            System.out.println("Category: "+category);
        } else if (BMI >= 25 && BMI < 29.9) {
            category = "Overweight";
            System.out.println("Category: "+category);
        } else {
            category = "Obese";
            System.out.println("Category: "+category);
        }
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        double weight = scanner.nextDouble();
        double height = scanner.nextDouble();

        BMIcalculator bmiCalculator = new BMIcalculator(weight, height);
        System.out.println("Standard BMI Calculation:");
        bmiCalculator.displayBMI();
    }
}

```

```
        CustomBMlcalculator customBMlcalculator = new  
CustomBMlcalculator(weight, height);  
        System.out.println("Custom BMI Calculation:");  
        customBMlcalculator.displayCustomBMI();  
  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 6\_CY

Attempt : 2  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Adams has a reputation company with a great number of employees. He must calculate the salary weekly according to the hourly rate and working hours. Create a program to define a class Employee with attributes name and hourly rate. Create a subclass HourlyEmployee that calculates the weekly salary based on the number of hours worked.

(The first 40 hours are based on the regular hour rate. If the work hours are greater than 40 then the work wage is 1.5 times the hourly rate)

Note: Use Math(Math.max, Math.min) functions .

Example

Input:

Chris

10

45

Output:

Weekly Salary: Rs.475.00

Explanation:

Calculation:

The first 40 hours are paid normally:  $40 \times 10 = 400.00$  The extra 5 hours are paid at 1.5 times the hourly rate:  $5 \times (10 \times 1.5) = 5 \times 15 = 75.00$  Total salary:  $400.00 + 75.00 = 475.00$

#### ***Input Format***

The first line of input consists of a string that represents the name of the employee.

The second line consists of a double value that represents the rate for an hour.

The last line consists of an integer that represents the total hours worked.

#### ***Output Format***

The output displays the total salary of the employee, where salary is rounded to two decimal places in the format: "Weekly Salary: Rs.<double value>".

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: Dave

10.0

40

Output: Weekly Salary: Rs.400.00

#### ***Answer***

```
import java.util.Scanner;
```



```
import java.text.DecimalFormat;
```

```
class Employee {  
    private String name;  
    private double hourlyRate;  
  
    public Employee(String name, double hourlyRate) {  
        this.name = name;  
        this.hourlyRate = hourlyRate;  
    }  
  
    public String getName() {  
        return name;  
    }  
  
    public double getHourlyRate() {  
        return hourlyRate;  
    }  
}
```

```
class HourlyEmployee extends Employee {  
    private int hoursWorked;  
  
    public HourlyEmployee(String name, double hourlyRate, int hoursWorked) {  
        super(name, hourlyRate);  
        this.hoursWorked = hoursWorked;  
    }  
  
    public int getHoursWorked() {  
        return hoursWorked;  
    }  
  
    public double calculateWeeklySalary() {  
        int regularHours = Math.min(hoursWorked, 40);  
        int overtimeHours = Math.max(0, hoursWorked - 40);  
        double regularPay = regularHours * getHourlyRate();  
        double overtimePay = overtimeHours * (getHourlyRate() * 1.5);  
        return regularPay + overtimePay;  
    }  
}
```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        String name = scanner.nextLine();
        double hourlyRate = scanner.nextDouble();
        int hoursWorked = scanner.nextInt();

        HourlyEmployee employee = new HourlyEmployee(name, hourlyRate,
hoursWorked);

        double weeklySalary = employee.calculateWeeklySalary();
        DecimalFormat df = new DecimalFormat("#.00");
        String formattedSalary = df.format(weeklySalary);
        System.out.println("Weekly Salary: Rs." + formattedSalary);
        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

A painter needs to determine the cost to paint different shapes based on their surface area. The program should be designed to handle the area of a sphere and calculate the total painting cost using the following formulas:

Area of sphere:  $\text{Area} = 4 * \pi * r^2$  where  $\pi = 3.14$   
 Total painting cost:  $\text{Cost} = \text{cost per square meter} * \text{area of sphere}$

The program will consist of three classes:

Shape class: This class should set the shape type and radius.

Area class: This class should extend Shape to calculate the area.

Cost class: This class should extend Area to calculate the total painting cost.

### **Input Format**

The input consists of a string representing the shape type, a double value representing the radius, and another double value representing the cost per square meter on each line.

### **Output Format**

For a valid shape type of "Sphere":

- The first line prints: "Area of Sphere is: <calculated\_area>" rounded to two decimal places.
- The second line prints: "Cost to paint the shape is: <total\_painting\_cost>" rounded to two decimal places.

For any other shape types, print: "Invalid type".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Sphere

3.4

5.8

Output: Area of Sphere is: 145.19

Cost to paint the shape is: 842.12

### **Answer**

```
import java.util.Scanner;
```

```
class Shape {  
    String shapeName = "";  
    double radius;  
    void setShape(String x, Scanner scanner) {  
        shapeName = x;  
        if (x.equals("Sphere")) {  
            radius = scanner.nextDouble();  
        } else {  
            System.out.println("Invalid type");  
            return;  
        }  
    }  
}
```

```
class Area extends Shape {
```

```

double area;
void calculateArea() {
    if (shapeName.equals("Sphere")) {
        area = 4 * 3.14 * radius * radius;
        System.out.printf("Area of Sphere is: %.2f%n", area);
    }
}

class Cost extends Area {
    double costPerMtrSquare;

    void setCost(double x) {
        costPerMtrSquare = x;
    }
    void calculateCost() {
        double totalCost = costPerMtrSquare * area;
        if (area > 0) {
            System.out.printf("Cost to paint the shape is: %.2f%n", totalCost);
        }
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String s = scanner.next();
        Cost shape = new Cost();
        shape.setShape(s, scanner);
        double costToPaint = scanner.nextDouble();
        shape.calculateArea();
        shape.setCost(costToPaint);
        shape.calculateCost();
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Teena is launching a new airline, Boeing747, and needs to calculate the

total revenue generated from ticket sales based on the ticket cost and seat availability. Teena's airline offers two types of seats: regular and premium. The ticket cost and seat availability for both types of seats need to be considered for revenue calculation.

To help with this, Teena wants to implement a system using multilevel inheritance with three classes:

**Airline:** This class will have the ticket cost as an attribute and defines the method `setCost(double cost)` and `double getCost()`. **Indigo:** This class will extend **Airline** and add the seat availability attribute and defines the method `getSeatAvailability()` and `setSeatAvailability(int seatAvailability)`. **Boeing747:** This class will extend **Indigo** and include a method `calculateTotalRevenue()` based on the ticket cost and seat availability.

Teena needs to calculate the total revenue using the formula:

$$\text{Total Revenue} = \text{ticket cost} * \text{seat availability}$$

Help Teena implement this system for calculating the revenue of her airline.

### ***Input Format***

The first line of input consists of a double value, representing the flight's ticket cost.

The second line consists of an integer, representing seat availability.

### ***Output Format***

The first line of output prints "Ticket Cost: Rs. " followed by a double value representing the ticket cost rounded to one decimal place.

The second line of output prints "Seat Availability: X seats" where X is an integer value representing the seat availability.

The third line of output prints "Total Revenue: Rs. " followed by a double value representing the total revenue rounded to one decimal place.

Refer to the sample output for the exact text and format.

### **Sample Test Case**

Input: 1000.0

100

Output: Ticket Cost: Rs. 1000.0

Seat Availability: 100 seats

Total Revenue: Rs. 100000.0

### **Answer**

```
import java.util.Scanner;
```

```
class Airline {  
    private double cost;  
    public void setCost(double cost) {  
        this.cost = cost;  
    }  
    public double getCost() {  
        return cost;  
    }  
}  
class Indigo extends Airline {  
    private int seatAvailability;  
    public void setSeatAvailability(int seatAvailability) {  
        this.seatAvailability = seatAvailability;  
    }  
    public int getSeatAvailability() {  
        return seatAvailability;  
    }  
}  
class Boeing747 extends Indigo {  
    public double calculateTotalRevenue() {  
        return getCost() * getSeatAvailability();  
    }  
}  
public class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        Boeing747 plane = new Boeing747();  
        double ticketCost = scanner.nextDouble();  
        plane.setCost(ticketCost);
```

```
int seatAvailability = scanner.nextInt();
plane.setSeatAvailability(seatAvailability);

System.out.printf("Ticket Cost: Rs. %.1f\n", plane.getCost());
System.out.println("Seat Availability: " + plane.getSeatAvailability() + "
seats");
System.out.printf("Total Revenue: Rs. %.1f\n",
plane.calculateTotalRevenue());
}
}
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Arun wants to calculate the age gap between the grandfather and the son and determine the father's age after 5 years.

Your task is to assist him in developing a program using three classes: GrandFather, Father, and Son, where the GrandFather stores the grandfather's age, the Father extends GrandFather to include the father's age and calculates his age after 5 years, and Son extends Father to include the son's age and calculate the age difference between the grandfather and the son.

#### **Input Format**

The input consists of three integers representing the ages of the grandfather, father, and son, one per line.

#### **Output Format**

The first line of output prints "Grandfather and son's age gap:" followed by an integer representing the age gap between the grandfather and the son, ending with "years".

The second line prints "Father's Age:" followed by an integer representing the father's age after 5 years, ending with "years".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 50

30

3

Output: Grandfather and son's age gap: 47 years

Father's Age: 35 years

### **Answer**

```
import java.util.Scanner;
```

```
// You are using Java
```

```
class GrandFather{  
    int grandfatherAge;
```

```
    public void setGrandfatherAge(int grandfatherAge){  
        this.grandfatherAge=grandfatherAge;  
    }  
}
```

```
class Father extends GrandFather{  
    protected int fatherAge;
```

```
    public void setFatherAge(int fatherAge){  
        this.fatherAge=fatherAge;  
    }
```

```
    public int calculateFatherAgeAfter5Years(){  
        return fatherAge + 5;  
    }
```

```
}
```

```
class Son extends Father{  
    int sonAge;
```

```
    public void setSonAge(int sonAge){  
        this.sonAge=sonAge;  
    }
```

```
    public int calculateGrandfatherSonAgeDifference(){  
        return grandfatherAge - sonAge;  
    }
```

```
}
```

```
public class Main {
```



```
public static void main(String[] args) {
    Scanner scanner = new Scanner(System.in);
    Son son = new Son();

    int grandfatherAge = scanner.nextInt();
    son.setGrandfatherAge(grandfatherAge);

    int fatherAge = scanner.nextInt();
    son.setFatherAge(fatherAge);

    int sonAge = scanner.nextInt();
    son.setSonAge(sonAge);

    System.out.println("Grandfather and son's age gap: " +
        son.calculateGrandfatherSonAgeDifference() + " years");

    int fatherAgeAfter5Years = son.calculateFatherAgeAfter5Years();
    System.out.println("Father's Age: " + fatherAgeAfter5Years + " years");
}
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 7\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. How can a class explicitly call a default method from an interface if there is a naming conflict?

**Answer**

Using InterfaceName.super.methodName();

**Status : Correct**

**Marks : 1/1**

2. Can a Java interface contain both default and static methods?

**Answer**

Yes, an interface can have both default and static methods.

**Status : Correct**

**Marks : 1/1**

3. Consider a class implementing an interface and extending a class, both having a method with the same name. Which method gets called?

**Answer**

The method from the superclass

**Status :** Correct

**Marks :** 1/1

4. How do you call a static method from an interface MyInterface?

**Answer**

MyInterface.staticMethod();

**Status :** Correct

**Marks :** 1/1

5. What is the output of the following code?

```
interface X {  
    default void show() {  
        System.out.println("X's Default Method");  
    }  
}
```

```
interface Y {  
    default void show() {  
        System.out.println("Y's Default Method");  
    }  
}
```

```
class Z implements X, Y {  
    public void show() {  
        System.out.println("Z's Method");  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Z obj = new Z();  
    }  
}
```

```
        obj.show();
    }
}
```

**Answer**

Z's Method

**Status :** Correct

**Marks :** 1/1

6. What is the output of the following code?

```
interface A {
    default void show() {
        System.out.println("A's Default Method");
    }
}
```

```
class B {
    public void show() {
        System.out.println("B's Method");
    }
}
```

```
class C extends B implements A {
}
```

```
public class Main {
    public static void main(String[] args) {
        C obj = new C();
        obj.show();
    }
}
```

**Answer**

B's Method

**Status :** Correct

**Marks :** 1/1

7. Which of the following statements about Java interfaces is true?

**Answer**

A class can implement multiple interfaces.

**Status :** Correct

**Marks :** 1/1

8. If a class implements two interfaces that have the same default method, what must the class do?

**Answer**

The class must override the method to resolve ambiguity.

**Status :** Correct

**Marks :** 1/1

9. What is the output of the following code?

```
interface A {  
    default void show() {  
        System.out.println("A's Default Method");  
    }  
}
```

```
interface B {  
    default void show() {  
        System.out.println("B's Default Method");  
    }  
}
```

```
class C implements A, B {  
    public void show() {  
        A.super.show();  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        C obj = new C();  
        obj.show();  
    }  
}
```

**Answer**

A's Default Method

**Status :** Correct

**Marks :** 1/1

10. What is the output of the following code?

```
interface MathOperations {  
    static int square(int x) {  
        return x * x;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        System.out.println(MathOperations.square(5));  
    }  
}
```

**Answer**

25

**Status :** Correct

**Marks :** 1/1

11. What is the primary purpose of static methods in Java interfaces?

**Answer**

They allow an interface to provide helper methods without requiring an implementing class.

**Status :** Correct

**Marks :** 1/1

12. Which of the following statements is true regarding default methods in Java interfaces?

**Answer**

A default method can be overridden in a class implementing the interface.

**Status :** Correct

**Marks :** 1/1

13. What is the output of the following code?

```
interface A {  
    static void display() {  
        System.out.println("Static method in A");  
    }  
}
```

```
class B implements A {  
    static void display() {  
        System.out.println("Static method in B");  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        B.display();  
    }  
}
```

**Answer**

Static method in B

**Status :** Correct

**Marks :** 1/1

14. Which of the following is the correct way to declare an interface in Java?

**Answer**

```
interface Vehicle { void start();}
```

**Status :** Correct

**Marks :** 1/1

15. What happens when an implementing class does not override a default method from an interface?

**Answer**

The default method's implementation from the interface will be used.

**Status :** Correct

**Marks :** 1/1



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 7\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement:

Rajiv is analyzing the energy consumption in his household and wants to calculate the total cost based on the daily energy usage. He is given the rate per unit of electricity and the energy consumed for multiple days. To structure this calculation efficiently, he decides to use an interface-based approach.

Implement an interface CostCalculator with the necessary methods to retrieve energy details and compute the cost. The calculations should be handled in the EnergyConsumptionTracker class, while the EnergyConsumptionApp class should only handle input and output.

##### Formula

Energy Cost for one day = Energy Consumed per day \* Rate Per Unit

### ***Input Format***

The first line of input consists of the rate per unit as an 'R' (a double value).

The second line of input consists of the number of days 'N' (an integer).

The third line of input consists of the daily energy consumption values for each day 'D' (double values), separated by space.

### ***Output Format***

The first line of the output prints: "Day-wise Energy Cost:"

The next N lines of the output print the day-wise energy costs(double type) and the total energy cost (double type) in Indian Rupees in the following format: "Day [day\_number]: Rs. [energy\_cost]"

The last line of the output prints: "Total Energy Cost: Rs. [total\_cost]"

Note: energy\_cost and total\_cost are rounded off to two decimal points

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 0.01

3

10.0 20.0 30.0

Output: Day-wise Energy Cost:

Day 1: Rs. 0.10

Day 2: Rs. 0.20

Day 3: Rs. 0.30

Total Energy Cost: Rs. 0.60

### ***Answer***

```
import java.util.Scanner;
```

```
// You are using Java
```

```
interface CostCalculator{
    void getEnergyDetails(Scanner scanner);
    void calculateAndDisplayCost();
}
class EnergyConsumptionTracker implements CostCalculator{
    protected double ratePerUnit;
    private int numDays;
    private double[] dailyconsumption;

    EnergyConsumptionTracker(double ratePerUnit,int numDays){
        this.ratePerUnit=ratePerUnit;
        this.numDays=numDays;
        this.dailyconsumption=new double [numDays];
    }
    public void getEnergyDetails(Scanner scanner){
        for(int i=0;i<numDays;i++){
            dailyconsumption[i]=scanner.nextDouble();
        }
    }
    public void calculateAndDisplayCost(){
        System.out.println("Day-wise Energy Cost:");

        double total=0;
        double daycost;
        for(int j=0;j<numDays;j++){
            daycost = dailyconsumption[j]*ratePerUnit;
            System.out.printf("Day %d: Rs. %.2f%n",j+1,daycost);
            total+=daycost;
        }
        System.out.printf("Total Energy Cost: Rs. %.2f",total);
    }
}
```

```
class EnergyConsumptionApp {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double ratePerUnit = scanner.nextDouble();  
        int numDays = scanner.nextInt();  
  
        CostCalculator tracker = new EnergyConsumptionTracker(ratePerUnit,  
numDays);  
  
        tracker.getEnergyDetails(scanner);  
        tracker.calculateAndDisplayCost();  
  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 7\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Jaheer is working on a health monitoring system to help individuals calculate their Body Mass Index (BMI). He has implemented a basic BMI calculator and an interface called HealthCalculator. It should have a method called calculateBMI.

You are tasked with creating a program that takes weight and height as input, calculates the BMI using the BMI Calculator class, and displays the result. If the height or weight is less than or equal to zero, then return -1.

Formula:  $BMI = \text{weight} / (\text{height} * \text{height})$

##### ***Input Format***

The first line of input consists of a double value W, the person's weight in kilograms.

The second line consists of a double value H, the height of the person in meters.

### **Output Format**

The output displays "BMI: " followed by a double value, representing the calculated BMI, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 70.0

1.75

Output: BMI: 22.86

### **Answer**

```
import java.util.Scanner;

// You are using Java
interface HealthCalculator{
    double calculateBMI(double weight,double height);
}

class BMICalculator implements HealthCalculator{
    public double weight;
    public double height;

    /*BMICalculator(double weight,double height){
        this.weight=weight;
        this.height=height;
    }*/
    public double calculateBMI(double weight,double height){
        if(weight<=0 || height<=0){
            return -1;
        }
        return weight/(height * height);
    }
}

class Main {
```

```
public static void main(String[] args) {  
    Scanner scanner = new Scanner(System.in);  
  
    double weight = scanner.nextDouble();  
    double height = scanner.nextDouble();  
  
    BMICalculator bmiCalculator = new BMICalculator();  
  
    double bmi = bmiCalculator.calculateBMI(weight, height);  
  
    System.out.printf("BMI: %.2f\n", bmi);  
  
    scanner.close();  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 7\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

A financial analyst, Alex, needs a program to calculate simple interest for various financial transactions. He requires a straightforward tool that takes in the principal amount, interest rate, and time in years and computes the interest.

The formula to be used is:  $\text{Interest} = \text{Principal} \times \text{Rate} \times \text{Time} / 100$

Implement this functionality using the InterestCalculator interface and the SimpleInterestCalculator class.

##### ***Input Format***

The first line of input consists of the principal amount P as a double value.



The second line of input consists of the annual interest rate  $r$  as a double value.

The third line of input consists of the number of years  $t$  as a positive integer, which is an integer value.

### ***Output Format***

The output displays the calculated simple interest in the following format: "Simple Interest: [interest\_value]", Here, [interest\_value] should be replaced with the actual interest value calculated by the program.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 1000.00

5.00

2

Output: Simple Interest: 100.0

### ***Answer***

```
import java.util.Scanner;
```

```
interface InterestCalculator{  
    double simpleInterest(double principal,double rate,int time);  
}
```

```
class SimpleInterestCalculator implements InterestCalculator{  
    public double simpleInterest(double principal,double rate,int time){  
        return (principal * rate * time)/100 ;  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
  
        double principal = scanner.nextDouble();  
  
        double rate = scanner.nextDouble();  
  
        int time = scanner.nextInt();
```

```
InterestCalculator calculator = new SimpleInterestCalculator();  
double interest = calculator.simpleInterest(principal, rate, time);  
  
System.out.println("Simple Interest: " + interest);  
  
}  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 7\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 8.5

#### Section 1 : Coding

##### 1. Problem Statement

Maria, a software developer, is working on an inventory management system project using Java that utilizes an inventory interface to manage a store's products.

The interface should define two methods: `addProduct`, which adds a product by accepting its name, price, and quantity, and `calculateTotalValue`, which computes the total value of all products in the inventory. Implement the interface in a class called `SimpleInventory`, which internally manages a list of `Product` objects.

Each `Product` object should encapsulate the product's name, price, and quantity and include a method to calculate its value as  $\text{price} \times \text{quantity}$ . The system should allow users to dynamically add products to the inventory and calculate the total value of all products stored.

Help Maria achieve the task.

### ***Input Format***

The first line of input consists of an integer to choose one of the following options:

- 1 - to add a product to the inventory.
- 2 - to calculate and view the total inventory value.
- 3 - to exit the program.

For Choice 1 (Add Product):

The next input line is the string representing the product name as a string (single or multi-word, without quotes).

The next line is a double value representing the price as a decimal value

The next line is an integer value representing the quantity as an integer

For Choices 2 and 3, no additional input is required

### ***Output Format***

The output displays the results of the commands as follows:

- For the addProduct command, the program should display "Product added to inventory."
- For choice 2, the program should display "Total inventory value [totalvalue].  
"The total value should be displayed with one decimal place. If there is no product in the inventory, print the total as 0.0.
- For choice 3, the program should exit

If the choice is not 1, 2, or 3, then print "Invalid choice. Please select a valid option (1/2/3).".

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 1

Laptop

800.0

3

2

5

3

Output: Product added to inventory.

Total inventory value: \$2400.0

Invalid choice. Please select a valid option (1/2/3).

### Answer

```
import java.util.Scanner;
```

```
// You are using Java
```

```
interface Inventory {
```

```
    void addProduct(String productName, double price, int quantity);
```

```
    double calculateTotalValue();
```

```
}
```

```
class SimpleInventory implements Inventory{
```

```
    public String productName;
```

```
    public double price;
```

```
    public int quantity;
```

```
    public int prod;
```

```
    public SimpleInventory(int prod){
```

```
        this.prod=prod;
```

```
    }
```

```
    public void addProduct(String productName, double price, int quantity){
```

```
        this.productName = productName;
```

```
        this.price = price;
```

```
        this.quantity = quantity;
```

```
        System.out.println("Product added to inventory.");
```

```
    }
```

```
    public double calculateTotalValue(){
```

```
        return price * quantity;
```

```
    }
```

```
}
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
Scanner scanner = new Scanner(System.in);
Inventory inventory = new SimpleInventory(10);
while (true) {
    int choice = scanner.nextInt();
    if (choice == 1) {
        scanner.nextLine();
        String productName = scanner.nextLine();
        double price = scanner.nextDouble();
        int quantity = scanner.nextInt();
        inventory.addProduct(productName, price, quantity);
    } else if (choice == 2) {
        double totalValue = inventory.calculateTotalValue();
        System.out.println("Total inventory value: $" + totalValue);
    } else if (choice == 3) {
        break;
    } else {
        System.out.println("Invalid choice. Please select a valid option
(1/2/3).");
    }
}
scanner.close();
}
```

**Status :** Partially correct

**Marks :** 8.5/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 7\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Raj is curious about how old he is in the current year.

He has asked you to create a simple program that calculates a person's age based on their birth year. You decide to implement this functionality using the AgeCalculator interface and the HumanAgeCalculator class.

Note: The current year is 2024. Calculate the current age by using the formula: current year - birth year.

##### ***Input Format***

The input consists of an integer representing the birth year.

##### ***Output Format***

The output displays "You are X years old." where X is an integer representing the calculated age based on the entered birth year.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1934

Output: You are 90 years old.

### **Answer**

```
import java.util.Scanner;
// You are using Java
interface AgeCalculator{
    int current_year=2024;
    int calculateAge(int birthYear);
}
class HumanAgeCalculator implements AgeCalculator{
    public int birthYear;
    public int age;

    public int calculateAge(int birthYear){
        return current_year-birthYear;
    }
}
class AgeCalculatorApp {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        AgeCalculator ageCalculator = new HumanAgeCalculator();

        int birthYear = scanner.nextInt();
        int age = ageCalculator.calculateAge(birthYear);

        System.out.println("You are " + age + " years old.");
    }
}
```

**Status : Correct**

**Marks : 10/10**



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 7\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Develop a program for managing employee information that caters to both full-time and part-time employees. The program should be capable of computing the salary for each category of employee and presenting their particulars. To achieve this, create two classes, FullTimeEmployee and PartTimeEmployee, that adhere to the Employee interface.

The program is expected to accept input data, including the name and monthly salary for full-time employees, as well as the name, hourly rate, and hours worked for part-time employees. Subsequently, it should calculate and exhibit the employee details and their respective salaries.

For Full-Time employees, the annual salary should be calculated as 12 times the monthly salary.

For Part-Time employees, the salary calculation should be based on the formula: hourly rate \* hours worked.

### ***Input Format***

The first line of input should be a string representing the name of a full-time employee.

The second line of input should be an integer representing the monthly salary of the full-time employee.

The third line of input should be a string representing the name of a part-time employee.

The fourth line of input should be an integer representing the hourly rate of the part-time employee.

The fifth line of input should be an integer representing the number of hours worked by the part-time employee.

### ***Output Format***

The output displays the following details:

Full-Time Employee Details:

Name: [Full-Time Employee Name] (string)

Monthly Salary: \$[Monthly Salary] (integer)

Annual Salary: \$[12 times Monthly Salary] (integer)

Part-Time Employee Details:

Name: [Part-Time Employee Name] (string)

Hourly Rate: \$[Hourly Rate] (integer)

Hours Worked: [Hours Worked] hours (integer)

Monthly Salary: \$[Calculated Monthly Salary] (integer)

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: John Smith

15000

Mary Johnson

100

100

Output: Full-Time Employee Details:

Name: John Smith

Monthly Salary: \$15000

Annual Salary: \$180000

Part-Time Employee Details:

Name: Mary Johnson

Hourly Rate: \$100

Hours Worked: 100 hours

Monthly Salary: \$10000

### **Answer**

```
import java.util.Scanner;
```

```
interface Employee {  
    void displayDetails();  
}
```

```
class FullTimeEmployee implements Employee{  
    String fullName;  
    int fullTimeSalary;
```

```
    public FullTimeEmployee(String fullName,int fullTimeSalary){  
        this.fullName=fullName;  
        this.fullTimeSalary=fullTimeSalary;
```

```
    }  
    public void displayDetails(){
```

```

        System.out.println("Full-Time Employee Details:");
        System.out.println("Name: "+fullName);
        System.out.printf("Monthly Salary: $%d %n",fullTimeSalary);
        System.out.printf("Annual Salary: $%d %n",fullTimeSalary * 12);
    }
}

class PartTimeEmployee implements Employee{
    String partTimeName;
    int hourlyRate;
    int hoursWorked;

    public PartTimeEmployee(String partTimeName,int hourlyRate,int
hoursWorked){
        this.partTimeName=partTimeName;
        this.hourlyRate=hourlyRate;
        this.hoursWorked=hoursWorked;
    }
    public void displayDetails(){
        System.out.println("Part-Time Employee Details:");
        System.out.println("Name: "+partTimeName);
        System.out.printf("Hourly Rate: $%d %n",hourlyRate);
        System.out.printf("Hours Worked: %d hours %n",hoursWorked);
        System.out.printf("Monthly Salary: $%d %n",hourlyRate * hoursWorked);
    }
}

```

```

class EmployeeInheritanceDemo {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String fullName = scanner.nextLine();
        int fullTimeSalary = scanner.nextInt();
        scanner.nextLine();
        String partTimeName = scanner.nextLine();
        int hourlyRate = scanner.nextInt();
        int hoursWorked = scanner.nextInt();
        FullTimeEmployee fullTimeEmployee = new FullTimeEmployee(fullName,
fullTimeSalary);
        PartTimeEmployee partTimeEmployee = new
PartTimeEmployee(partTimeName, hourlyRate, hoursWorked);
        fullTimeEmployee.displayDetails();
    }
}

```

```
        System.out.println();
        partTimeEmployee.displayDetails();
        scanner.close();
    }
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Oviya is fascinated by automorphic numbers and wants to create a program to determine whether a given number is an automorphic number or not.

An automorphic number is a number whose square ends with the same digits as the number itself. For example,  $25 = (25)^2 = 625$

Oviya has defined two interfaces: NumberInput for taking user input and AutomorphicChecker for checking if a given number is automorphic. The class AutomorphicNumber implements both interfaces.

Help her complete the task.

### **Input Format**

The input consists of a single integer n.

### **Output Format**

If the input number is an automorphic number, print "n is an automorphic number". Otherwise, print "n is not an automorphic number".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 25

Output: 25 is an automorphic number

### Answer

```
import java.util.Scanner;

interface NumberInput{
    public int getInput();
}

interface AutomorphicChecker{
    boolean checkAutomorphic(int inputNumber);
}

class AutomorphicNumber implements NumberInput, AutomorphicChecker{
    private int n;

    public int getInput(){
        Scanner sc = new Scanner(System.in);
        return sc.nextInt();
    }

    public boolean checkAutomorphic(int inputNumber){
        int count=0;
        int sq=inputNumber * inputNumber;
        int temp = inputNumber;
        while(temp>0){

            //int digit=temp%10;
            temp=temp/10;
            count++;

        }
        int mod=(int) Math.pow(10,count);
        if(inputNumber==(sq%mod)){
            return true;
        }
        else
            return false;
    }

}

public class Main {
    public static void main(String[] args) {
```

```

AutomorphicNumber automorphicNumber = new AutomorphicNumber();
int inputNumber = automorphicNumber.getInput();

boolean isAutomorphic =
automorphicNumber.checkAutomorphic(inputNumber);

if (isAutomorphic) {
    System.out.println(inputNumber+" is an automorphic number");
} else {
    System.out.println(inputNumber+" is not an automorphic number");
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Sophia is developing a matrix analysis tool for a data analytics company. The tool needs to analyze square matrices and extract insights from the matrix diagonals.

To organize the code properly, Sophia creates an interface named Matrix that declares a method for finding the smallest and largest elements along the principal and secondary diagonals of the matrix.

Sophia then creates a class named MatrixAnalyzer that implements the Matrix interface. This class provides the logic to process a given square matrix and print:

The smallest and largest elements in the principal diagonal (from top-left to bottom-right). The smallest and largest elements in the secondary diagonal (from top-right to bottom-left).

Your task is to implement the Matrix interface and the MatrixAnalyzer class. The main driver program (in the class Main) will read the input matrix, create an instance of MatrixAnalyzer, and invoke its method to display the results.

**Input Format**

The first line contains an integer n, representing the size of the square matrix.

The next n lines each contain n integers separated by spaces, representing the elements of the matrix.

### **Output Format**

The output prints the four lines:

"Smallest Element - 1: <smallest element in the principal diagonal>" (integer)

"Largest Element - 1: <largest element in the principal diagonal>" (integer)

"Smallest Element - 2: <smallest element in the secondary diagonal>" (integer)

"Largest Element - 2: <largest element in the secondary diagonal>" (integer)

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

7 8 9 0 1

2 3 4 5 6

5 4 2 0 8

23 5 6 8 9

12 5 6 7 32

Output: Smallest Element - 1: 2

Largest Element - 1: 32

Smallest Element - 2: 1

Largest Element - 2: 12

### **Answer**

```
import java.util.Scanner;
```

```
// You are{ using Jav
```

```
interface Matrix{
```

```
    void diagonalsMinMax(int[][] matrix);
```

```
}
```

```
class MatrixAnalyzer implements Matrix{
```



```

public void diagonalsMinMax(int[][] matrix){
    int n=matrix.length;
    int [] p_arr = new int [n];
    int [] s_arr = new int [n];
    //int p_sum=0;
    int p_min=99;
    int p_max=0;
    int s_min=99;
    int s_max=0;
    for(int i=0;i<n;i++){
        for(int j=0;j<n;j++){
            if(i==j){
                p_arr[i] = matrix[i][j];
            }
            if(i+1==n-j){
                s_arr[i]=matrix[i][j];
            }
        }
    }
    //Arrays.sort(p_arr);
    for(int k=0;k<n;k++){
        if(p_min>p_arr[k]){
            p_min=p_arr[k];
        }
        if(p_max<p_arr[k])
            p_max=p_arr[k];

        if(s_min>s_arr[k])
            s_min=s_arr[k];

        if(s_max<s_arr[k])
            s_max=s_arr[k];
    }
    System.out.println("Smallest Element - 1: "+p_min);
    System.out.println("Largest Element - 1: "+p_max);
    System.out.println("Smallest Element - 2: "+s_min);
    System.out.println("Largest Element - 2: "+s_max);
}
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
    }
}

```

```

int n = sc.nextInt();
int[][] matrix = new int[n][n];
for (int i = 0; i < n; i++) {
    for (int j = 0; j < n; j++) {
        matrix[i][j] = sc.nextInt();
    }
}
MatrixAnalyzer analyzer = new MatrixAnalyzer();
analyzer.diagonalsMinMax(matrix);
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement:

Alice has been tasked with implementing a simple calculator interface and a corresponding class for performing basic addition and subtraction operations. The task is to create an interface called Calculator with two methods: add and subtract. The add method should take two numbers as input and return their sum, while the subtract method should take two numbers as input and return their difference.

Implement a class called SimpleCalculator that implements the Calculator interface. This class should provide the functionality for adding and subtracting numbers. Write a code that satisfies the above requirements.

#### **Input Format**

The first line of input consists of a single integer, representing the choice

If the choice is 1 or 2, the next two lines consist of 2 double values, representing the numbers to do addition or subtraction.

#### **Output Format**

The output prints a float-value with one decimal value representing the sum of two number or difference of two number.

Refer to the sample output for format specification.

### **Sample Test Case**

Input: 1

5.5

3.5

Output: Result: 9.0

### **Answer**

```
import java.util.Scanner;
```

```
// You are using Java
```

```
interface Calculator {
```

```
    double add(double num1,double num2);
```

```
    double subtract(double num1,double num2);
```

```
}
```

```
class SimpleCalculator implements Calculator {
```

```
    //Type your code here
```

```
    public double num1;
```

```
    public double num2;
```

```
    public double add(double num1,double num2){
```

```
        return num1 + num2;
```

```
    }
```

```
    public double subtract(double num1,double num2){
```

```
        return num1 - num2;
```

```
    }
```

```
}
```

```
class MathOperationsProgram {
```

```
    public static void main(String[] args) {
```

```
        Scanner scanner = new Scanner(System.in);
```

```
        SimpleCalculator calculator = new SimpleCalculator();
```

```
        int choice = scanner.nextInt();
```

```
        if (choice == 1) {
```

```
double num1 = scanner.nextDouble();
double num2 = scanner.nextDouble();
double result = calculator.add(num1, num2);
System.out.println("Result: " + result);
} else if (choice == 2) {
    double num1 = scanner.nextDouble();
    double num2 = scanner.nextDouble();
    double result = calculator.subtract(num1, num2);
    System.out.println("Result: " + result);
} else {
    System.out.println("Invalid choice. Please choose 1 for addition or 2 for
subtraction.");
}
scanner.close();
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 7\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Maria, an online store owner, is looking to implement a pricing system that calculates the final price of products after applying discounts. She needs a program that takes the original price of a product and the discount percentage as input and computes the final discounted price. The discount is applied as a percentage of the original price. Maria wants to ensure that the final price is formatted to display exactly two decimal places.

Implement this functionality using the PriceCalculator interface and the DiscountCalculator class.

##### ***Input Format***

The first line of input consists of the original price (a double value).

The second line of input consists of a discount percentage (a double value).

### **Output Format**

The output displays the final price after the discount, adhering to the following format: "Final Price after discount: \$[final\_price]".

Here, [final\_price] should be replaced with the calculated final price, formatted as a currency value with two decimal places.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 100.0  
10.0

Output: Final Price after discount: \$90.00

### **Answer**

```
import java.util.Scanner;

// You are using Java
interface PriceCalculator{
    double calculatePrice(double originalPrice,double discount);
}
class DiscountCalculator implements PriceCalculator{
    public double calculatePrice(double originalPrice,double discount){
        return originalPrice - (originalPrice * (discount/100));
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        double originalPrice = scanner.nextDouble();
        double discount = scanner.nextDouble();
        PriceCalculator calculator = new DiscountCalculator();
        double finalPrice = calculator.calculatePrice(originalPrice, discount);
        System.out.printf("Final Price after discount: $%.2f\n", finalPrice); //
        Formats output to 2 decimal places
    }
}
```

Status : Correct

Marks : 10/10

## 2. Problem Statement:

Rathish is planning a road trip and needs a program to convert speeds between miles per hour (MPH) and kilometers per hour (KPH).

Create an interface, SpeedConverter, with a method convertSpeed(double mph). Implement the interface with MPHtoKPHConverter class, allowing Rathish to input MPH and receive the converted speed in KPH, rounded to two decimal points.

Formula: Speed in KPH = 1.60934 \* Speed in MPH.

### **Input Format**

The input consists of a single double-point number representing the speed in miles per hour (MPH).

### **Output Format**

The output displays the converted speed (double-point number) in kilometers per hour (KPH) rounded off to two decimal points in the following format:

"Speed in KPH: <<converted speed>>".

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 1.0

Output: Speed in KPH: 1.61

### **Answer**

```
import java.util.Scanner;

// You are using Java
interface SpeedConverter{

    double convertSpeed(double speedInMPH);
```

```

    }
    class MPHtoKPHConverter implements SpeedConverter{
        public double convertSpeed(double speedInMPH){
            return speedInMPH * 1.60934;
        }
    }
    class SpeedConversionApp {
        public static void main(String[] args) {
            Scanner scanner = new Scanner(System.in);

            double speedInMPH = scanner.nextDouble();

            SpeedConverter converter = new MPHtoKPHConverter();

            double speedInKPH = converter.convertSpeed(speedInMPH);

            System.out.printf("Speed in KPH: %.2f\n", speedInKPH);

            scanner.close();
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Alex and Bob are designing a control system for household appliances, and one of the appliances is a washing machine. You want to create a program to help them that models the washing machine as a motor and calculates its electricity consumption based on its capacity.

Define an interface named Motor with the following methods:

void run() double consume(double capacity)

Create a class called WashingMachine that implements the Motor interface.



In the WashingMachine class:

Implement the run() method to print "Washing machine is running." Implement a consume() method to print "Washing machine is consuming electricity." Implement the consume(double capacity) method to calculate the electricity consumption (in kWh) of the washing machine based on its capacity. The formula for electricity consumption is (capacity \* 0.05).

### ***Input Format***

The input consists of a double value representing the capacity of the washing machine in kW.

### ***Output Format***

The first line of output prints "Washing machine is running."

The second line prints "Washing machine is consuming electricity."

The third line prints "Electricity consumption: X kWh" where X is a double value, rounded off to two decimal places, representing the electricity consumption.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 2.5

Output: Washing machine is running.

Washing machine is consuming electricity.

Electricity consumption: 0.13 kWh

### ***Answer***

```
import java.util.Scanner;

// You are using Java
interface motor {
    void run();
    void consume();
    double consume(double capacity);
}
class WashingMachine implements motor{
```

```

    public void run(){
        System.out.println("Washing machine is running.");
    }
    public void consume(){
        System.out.println("Washing machine is consuming electricity.");
    }
    public double consume(double capacity){
        return capacity * 0.05;
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        WashingMachine washingMachine = new WashingMachine();

        double capacity = scanner.nextDouble();

        washingMachine.run();
        washingMachine.consume();

        double consumption = washingMachine.consume(capacity);
        System.out.printf("Electricity consumption: %.2f kWh", consumption);

        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

John is developing a car loan calculator and has structured his program using two interfaces, Principal and InterestRate, defining methods for principal and interest rate retrieval.

The Loan class implements these interfaces, taking principal and annual interest rates as parameters. User input is solicited for these values, and the program ensures their validity before performing calculations. If input

values are invalid (less than or equal to zero), an error message is displayed.

Note: Total interest = principal \* interest rate \* years

### ***Input Format***

The first line of input consists of a double value P, representing the principal.

The second line consists of a double value R, representing the annual interest rate.

The third line consists of an integer value N, representing the loan duration in years.

### ***Output Format***

If the input values are valid, print "Total interest paid: Rs. " followed by a double value, representing the total interest paid, rounded off to two decimal places.

If the input values are invalid (negative or zero values for principal, annual interest rate, or loan duration), print "Invalid input values!".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 20000.00  
0.05  
5

Output: Total interest paid: Rs.5000.00

### ***Answer***

```
import java.util.Scanner;  
  
// You are using Java  
//Type your code here  
interface Principal{  
  
}  
interface InterestRate{
```

```

    }
    class Loan implements Principal,InterestRate{
        public double carPrice;
        public double AnnualInterestRate;
        public int loanDuration;

        public Loan(double carPrice,double AnnualInterestRate){
            this.carPrice = carPrice;
            this.AnnualInterestRate = AnnualInterestRate;
        }
        public double calculateTotalInterest(int loanDuration){
            return carPrice * AnnualInterestRate * loanDuration;
        }
    }

    public class Main {
        public static void main(String[] args) {
            Scanner scanner = new Scanner(System.in);

            double carPrice = scanner.nextDouble();

            double annualInterestRate = scanner.nextDouble();

            int loanDuration = scanner.nextInt();

            if (carPrice <= 0 || annualInterestRate <= 0 || loanDuration <= 0) {
                System.out.println("Invalid input values!");
                return;
            }

            Loan carLoan = new Loan(carPrice, annualInterestRate);
            double totalInterest = carLoan.calculateTotalInterest(loanDuration);

            System.out.printf("Total interest paid: Rs.%.2f%n", totalInterest);
        }
    }

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 8\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. What will be the output for the following code?

```
class InvalidUsernameException extends Exception {  
    public InvalidUsernameException(String message) {  
        super(message);  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        try {  
            String username = "abc";  
            if (username.length() < 5) {  
                throw new InvalidUsernameException("Username must be at  
least 5 characters long");  
            }  
        }  
    }  
}
```

```

    } catch (InvalidUsernameException e) {
        System.out.println(e.getMessage());
    }
}

```

**Answer**

Username must be at least 5 characters long

**Status :** Correct

**Marks :** 1/1

2. What will be the output for the following code?

```

class InvalidVotingAgeException extends Exception {
    public InvalidVotingAgeException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = 15;
            if (age < 18) {
                throw new InvalidVotingAgeException("You are not eligible to
vote");
            }
            System.out.println("Eligible to vote");
        } catch (InvalidVotingAgeException e) {
            System.out.println(e.getMessage());
        }
    }
}

```

**Answer**

You are not eligible to vote

**Status :** Correct

**Marks :** 1/1

3. How do you create an unchecked custom exception?

**Answer**

By extending RuntimeException

**Status : Correct**

**Marks : 1/1**

4. What will be the output for the following code?

```
import java.io.*;

class OutOfStockException extends Exception {
    public OutOfStockException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int stock = 0;
            if (stock == 0) {
                throw new OutOfStockException("Item is out of stock");
            }
        } catch (OutOfStockException e) {
            System.out.println(e.getMessage());
        }
    }
}
```

**Answer**

Item is out of stock

**Status : Correct**

**Marks : 1/1**

5. what is the output of the following code?

```
class MyException extends Exception {
```

```

    public MyException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            throw new MyException("Error occurred");
        } catch (MyException e) {
            System.out.println(e);
        }
    }
}

```

**Answer**

MyException: Error occurred

**Status :** Correct

**Marks :** 1/1

6. What will be the output for the following code?

```

import java.io.*;

class UnderageException extends Exception {
    public UnderageException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = 17;
            if (age < 18) {
                throw new UnderageException("Underage, cannot proceed");
            }
        } catch (UnderageException e) {
            System.out.println(e.getMessage());
        }
    }
}

```



**Answer**

Underage, cannot proceed

**Status :** Correct

**Marks :** 1/1

7. What is the purpose of a custom exception in Java?

**Answer**

To create user-defined exceptions for specific scenarios

**Status :** Correct

**Marks :** 1/1

8. What will be the output for the following code?

```
import java.io.*;
```

```
class TemperatureTooHighException extends Exception {  
    public TemperatureTooHighException(String message) {  
        super(message);  
    }  
}
```

```
class Test {  
    public static void main(String[] args) {  
        try {  
            int temperature = 110;  
            if (temperature > 100) {  
                throw new TemperatureTooHighException("Temperature too  
high");  
            }  
        } catch (TemperatureTooHighException e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

}

**Answer**

Temperature too high

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
class MyException extends Exception {  
    public MyException() {  
        super("Default Exception Message");  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        try {  
            throw new MyException();  
        } catch (MyException e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

**Answer**

Default Exception Message

**Status :** Correct

**Marks :** 1/1

10. Which of the following is true about custom exceptions?

**Answer**

Custom exceptions must extend either Exception or RuntimeException

**Status :** Correct

**Marks :** 1/1

11. Which keyword is used to explicitly throw a custom exception?

**Answer**

throw

**Status :** Correct

**Marks :** 1/1

12. What will be the output for the following code?

```
class NegativeBalanceException extends Exception {  
    public NegativeBalanceException(String message) {  
        super(message);  
    }  
}  
  
class Test {  
    public static void main(String[] args) {  
        try {  
            double balance = -500;  
            if (balance < 0) {  
                throw new NegativeBalanceException("Balance cannot be  
negative");  
            }  
        } catch (NegativeBalanceException e) {  
            System.out.println("Error: " + e.getMessage());  
        }  
    }  
}
```

**Answer**

Error: Balance cannot be negative

**Status :** Correct

**Marks :** 1/1

13. What will happen if a checked custom exception is thrown inside a method without being caught or declared?

**Answer**

Compilation Error

**Status :** Correct

**Marks :** 1/1

14. What will be the output for the following code?

```
import java.io.*;

class NegativeAgeException extends Exception {
    public NegativeAgeException(String message) {
        super(message);
    }
}

class Test {
    public static void main(String[] args) {
        try {
            int age = -5;
            if (age < 0) {
                throw new NegativeAgeException("Age cannot be negative");
            }
        } catch (NegativeAgeException e) {
            System.out.println(e.getMessage());
        }
    }
}
```

**Answer**

Age cannot be negative

**Status :** Correct

**Marks :** 1/1

15. what is the output of the following code?

```
class MyException extends Exception {
    public MyException(String message) {
        super(message);
    }
}
```

```
class Test {  
    static void check() throws MyException {  
        throw new MyException("Custom Exception Occurred");  
    }  
  
    public static void main(String[] args) {  
        try {  
            check();  
        } catch (Exception e) {  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

**Answer**

Custom Exception Occurred

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Write a program to validate the email address and display suitable exceptions if there is any mistake.

Create 3 custom exception classes as below

DotException AtTheRateException DomainException

A typical email address should have a "." character, and a "@" character, and also the domain name should be valid. Valid domain names for practice be 'in', 'com', 'net', or 'biz'.

Display Invalid Dot usage, Invalid @ usage, or Invalid Domain message based on email id.

Get the email address from the user, validate the email by checking the

above-mentioned criteria, and print the validity status of the input email address.

### ***Input Format***

The first line of input contains the email to be validated.

### ***Output Format***

The output prints a Valid email address or an Invalid email address along with the suitable exception

If email ends with . or contains not exactly one . after @, it throws:

DotException: Invalid Dot usage

Invalid email address

If @ appears not exactly once, it throws:

AtTheRateException: Invalid @ usage

Invalid email address

If the part after the last dot is not among accepted domains:

DomainException: Invalid Domain

Invalid email address

If all conditions satisfied then print:

Valid email address

Refer to the sample input and output for format specifications.

### **Sample Test Case**

Input: sample@gmail.com

Output: Valid email address

### **Answer**

```
// You are using Java
import java.util.Scanner;
```

```
class DotException extends Exception {
    public DotException(String message) {
        super(message);
    }
}
```

```
class AtTheRateException extends Exception {
    public AtTheRateException(String message) {
        super(message);
    }
}
```

```
class DomainException extends Exception {
    public DomainException(String message) {
        super(message);
    }
}
```

```
public class Main {
```

```
    public static void validateEmail(String email) throws DotException,
    AtTheRateException, DomainException {
```

```
        int atCount = 0;
        int atIndex = -1;
        for (int i = 0; i < email.length(); i++) {
            if (email.charAt(i) == '@') {
                atCount++;
                atIndex = i;
            }
        }
    }
}
```



```

    }
}

if (atCount != 1) {
    throw new AtTheRateException("Invalid @ usage");
}

if (email.startsWith("@") || email.startsWith(".") || email.endsWith("@") ||
email.endsWith(".")) {
    throw new DotException("Invalid Dot usage");
}

if (email.contains("..") || email.contains("@@") || email.contains(".@") ||
email.contains("@.")) {
    throw new DotException("Invalid Dot usage");
}

String domainPart = email.substring(atIndex + 1);

if (!domainPart.contains(".")) {
    throw new DotException("Invalid Dot usage");
}

int lastDot = email.lastIndexOf('.');
if (lastDot <= atIndex || lastDot == email.length() - 1) {
    throw new DotException("Invalid Dot usage");
}

String extension = email.substring(lastDot + 1);

if (!(extension.equals("com") || extension.equals("in") ||
extension.equals("net") || extension.equals("biz"))) {
    throw new DomainException("Invalid Domain");
}
}

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    String email = sc.nextLine().trim();

    try {
        validateEmail(email);
    }
}

```

```
        System.out.println("Valid email address");
    } catch (DotException e) {
        System.out.println("DotException: " + e.getMessage());
        System.out.println("Invalid email address");
    } catch (AtTheRateException e) {
        System.out.println("AtTheRateException: " + e.getMessage());
        System.out.println("Invalid email address");
    } catch (DomainException e) {
        System.out.println("DomainException: " + e.getMessage());
        System.out.println("Invalid email address");
    }
}

sc.close();
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Elsa, a busy professional, is using a scheduling application to plan her meetings efficiently. The application requires users to input meeting durations in minutes, ensuring that the duration is a positive integer and does not exceed 240 minutes (4 hours). Elsa needs a program to assist her in scheduling meetings securely with proper exception handling.

Create a Java class named ElsaMeetingScheduler. Implement a custom exception: InvalidDurationException for invalid meeting duration entries. Implement the main method to interactively take user input for a meeting duration. Implement the validateMeetingDuration method to validate the meeting duration based on the specified rules and throw a custom exception if the validation fails. Print appropriate success or error messages based on the meeting duration.

Implement a custom exception, `InvalidDurationException`, to handle cases where the entered meeting duration does not meet the specified criteria.

### ***Input Format***

The input consists of an integer value 'n', representing the meeting duration.

### ***Output Format***

The output is displayed in the following format:

If the entered meeting duration meets the specified criteria, the program outputs

"Meeting scheduled successfully!"

If the entered meeting duration is invalid, the program outputs an error message indicating the issue.

"Error: Invalid meeting duration. Please enter a positive integer not exceeding 240 minutes (4 hours)."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 120

Output: Meeting scheduled successfully!

### ***Answer***

```
// You are using Java
import java.util.*;
```

```
class InvalidDurationException extends Exception{
    public InvalidDurationException(String message){
        super(message);
    }
}
```

```
public class Main{
    public static void validateMeetingDuration(int n) throws
    InvalidDurationException {
```

```
        if(n<0 || n>240){
            throw new InvalidDurationException("Error: Invalid meeting duration.
Please enter a positive integer not exceeding 240 minutes (4 hours).");
        }
        else {
            System.out.println("Meeting scheduled successfully!");
        }
    }

    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        try{
            validateMeetingDuration(n);
        }
        catch (InvalidDurationException e) {
            System.out.println(e.getMessage());
        }
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In a user registration system, there is a requirement to implement a username validation module. Users attempting to register must adhere to specific criteria for their usernames to be considered valid.

Your task is to develop a program that takes user input for a desired username and validates it according to the following rules:

The username must not contain any spaces. The username must be at least 5 characters long.

Implement a custom exception, `InvalidUsernameException`, to handle cases where the entered username does not meet the specified criteria.

##### ***Input Format***

The input consists of a string S, representing the desired username.

### **Output Format**

If the username is valid, print "Username is valid: [S]".

If the username is invalid:

1. If the username is short, print "Invalid Username: Username must be at least 5 characters long"
2. If the username contains spaces, print "Invalid Username: Username cannot contain spaces"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: John

Output: Invalid Username: Username must be at least 5 characters long

### **Answer**

```
// You are using Java
import java.util.*;
```

```
class InvalidUsernameException extends Exception{
    public InvalidUsernameException(String message){
        super(message);
    }
}

public class Main{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        String s=sc.nextLine();
        try{
            if(s.contains(" ")){
                throw new InvalidUsernameException("Invalid Username: Username
cannot contain spaces");
            }
            if(s.length()<5){
                throw new InvalidUsernameException("Invalid Username: Username
must be at least 5 characters long");
            }
        }
    }
}
```

```
}  
    else{  
        System.out.println("Username is valid: "+s);  
    }  
}  
catch(InvalidUsernameException e){  
    System.out.println(e.getMessage());  
}  
}  
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

A local municipality is implementing an online voting system for a community event and wants to ensure that only eligible voters (those aged 18 or older) can participate.

Your task is to develop a program that validates the age of individuals attempting to vote online. If the user's age is below 18, the program should throw a custom exception, `InvalidAgeException`, preventing them from casting their vote. If the input is invalid, catch the appropriate `InputMismatchException` and print the in-built exception message.

##### ***Input Format***

The input consists of an integer representing the age.

##### ***Output Format***

If the age is 18 or older, print "Eligible to vote"

If the age is below 18, print "Exception occurred: InvalidAgeException: Age is not valid to vote"

If there is any other type of exception, print "An error occurred: " followed by the in-built exception message.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 20

Output: Eligible to vote

### **Answer**

```
// You are using Java
import java.util.*;
class InvalidAgeException extends Exception{
    public InvalidAgeException(String message){
        super(message);
    }
}
public class Main{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        try{
            int n=sc.nextInt();
            if(n<18){
                throw new InvalidAgeException("Exception occurred:
InvalidAgeException: Age is not valid to vote");
            }
            else{
                System.out.println("Eligible to vote");
            }
        }
        catch(InputMismatchException e){
            System.out.println("An error occurred: java.util.InputMismatchException");
        }
    }
}
```

```
        catch(InvalidAgeException e){  
            System.out.println(e.getMessage());  
        }  
    }  
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 8\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In a file management system, users are required to provide a valid file name when creating new files. The system enforces specific rules for file names to maintain consistency and avoid potential issues. Your task is to implement a Java program named FileNameValidator that takes user input for a file name and validates it according to the specified rules.

Rules for Valid File Name:

The file name must consist of alphanumeric characters (letters and digits) only. The file name must have a minimum length of 3 characters.

Implement a custom exception, FileNameValidator, to handle cases where the entered filename does not meet the specified criteria.

***Input Format***

The input consists of a string S, representing the desired filename.

### **Output Format**

The output is displayed in the following format:

If the entered file name meets the specified criteria, the program outputs

"Valid file name"

If the entered file name does not meet the criteria and triggers the InvalidFileNameException, the program outputs

"Error: Invalid file name. It must be alphanumeric and have a minimum length of 3 characters."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: myfile123

Output: Valid file name

### **Answer**

```
import java.util.Scanner;
```

```
class InvalidFileNameException extends Exception {  
    public InvalidFileNameException(String message) {  
        super(message);  
    }  
}
```

```
class FileNameValidator {
```

```
    public static void validateFileName(String fileName) throws  
        InvalidFileNameException {
```

```
        if (fileName.length() < 3 || !fileName.matches("[A-Za-z0-9]+")) {  
            throw new InvalidFileNameException("Error: Invalid file name. It must be
```

alphanumeric and have a minimum length of 3 characters.");

```
    }  
}
```

```
public static void main(String[] args) {  
    Scanner sc = new Scanner(System.in);  
    String fileName = sc.nextLine();
```

```
    try {  
        validateFileName(fileName);  
        System.out.println("Valid file name");  
    } catch (InvalidFileNameException e) {  
        System.out.println(e.getMessage());
```

```
    }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 8\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

You are tasked to create a program that defines a custom exception GradeException. The program should include a Student class with fields for the student's name, age, and grade. Implement a method in the Student class that checks the grade, and if the grade is below 40, it should throw a GradeException. Otherwise, it should display the student's details.

##### ***Input Format***

The input consists of three parameters in separate lines:

1. A string representing the student's name.
2. An integer representing the student's age.
3. An integer representing the student's grade.

##### ***Output Format***

The output will display the student's details if the grade is valid.

If the grade is below 40, the program will display an error message "Grade is below 40".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Alice

20

85

Output: Name: Alice

Age: 20

Grade: 85

### **Answer**

// You are using Java

```
import java.util.*;
```

```
class GradeException extends Exception{  
    public GradeException(String message){  
        super(message);  
    }  
}
```

```
class Student{  
    public static void checkGrade(int grade) throws GradeException{  
        if(grade<40){  
            throw new GradeException("Grade is below 40");  
        }  
    }  
}
```

```
public static void main(String[] args){  
    Scanner sc = new Scanner(System.in);  
    String name=sc.nextLine();  
    int age=sc.nextInt();  
    int grade=sc.nextInt();  
    try{  
        checkGrade(grade);  
        System.out.println("Name: "+name);  
        System.out.println("Age: "+age);  
    }  
}
```



```
        System.out.println("Grade: "+grade);
    }
    catch(GradeException e){
        System.out.println(e.getMessage());
    }
}
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Daniel is developing a program to verify the age of users. He wants to ensure that the entered age is within a valid range. Write a program to help Daniel implement this age-checking feature using custom exceptions.

Daniel needs a program that takes an integer input representing a person's age. If the age is between 0 and 150 (inclusive), the program should print "Age is valid!". If the age is less than 0 or greater than 150, the program should throw a custom exception (InvalidAgeException) with the message "Invalid age. Please enter an age between 0 and 150."

Implement a custom exception, InvalidAgeException, to handle cases where the entered age does not meet the specified criteria.

### **Input Format**

The input consists of an integer value 'n', representing the age.

### **Output Format**

The output is displayed in the following format:

If the age is valid (between 0 and 150, inclusive), print

"Age is valid!".

If the age is invalid, print

"Error: Invalid age. Please enter an age between 0 and 150."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 45

Output: Age is valid!

### **Answer**

```
// You are using Java
import java.util.*;
class InvalidAgeException extends Exception{
    public InvalidAgeException(String message){
        super(message);
    }
}
class user{
    public static void checkage(int age) throws InvalidAgeException{
        if(age<0 || age>150){
            throw new InvalidAgeException("Error: Invalid age. Please enter an age
between 0 and 150.");
        }
    }
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        int age=sc.nextInt();
        try{
            checkage(age);
            System.out.println("Age is Valid!");
        }
        catch(InvalidAgeException e){
            System.out.println(e.getMessage());
        }
    }
}
```

**Status :** Correct

**Marks : 10/10**

### **3. Problem Statement**

Enigma is developing a simple web application that takes a user-input URL,

validates it, and throws a custom exception `InvalidURLExceptionFormatException` if the URL does not start with "http://" or "https://".

The main method prompts the user for input, validates the URL, and prints whether it is valid or not.

### ***Input Format***

The input consists of a string, representing the URL entered by the user.

### ***Output Format***

The output displays one of the following results:

If the entered URL is valid according to the specified format, the program prints:

"[URL] is a valid URL"

If the entered URL is not valid according to the specified format, the program prints:

"Invalid URL format: [URL]"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: `http://www.example.com`

Output: `http://www.example.com is a valid URL`

### ***Answer***

```
// You are using Java
import java.util.*;
```

```
class InvalidURLExceptionFormatException extends Exception{
    public InvalidURLExceptionFormatException(String message){
        super(message);
    }
}
```

```

}
class URL{
    public static void checkurl(String str) throws InvalidURLExceptionFormatException{
        if(!(str.startsWith("http://") || str.startsWith("https://"))){
            throw new InvalidURLExceptionFormatException("Invalid URL format: ");
        }
    }
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        String str=sc.nextLine();
        try{
            checkurl(str);
            System.out.println(str+"is a valid URL");
        }
        catch(InvalidURLExceptionFormatException e){
            System.out.println(e.getMessage()+" "+ str);
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

An HR software system is being developed to process employee payrolls. During payroll processing, the system must ensure that no employee has a negative salary and that no employee's salary exceeds 2,00,000. If either condition occurs, the system should throw a custom exception.

Create a custom exception InvalidSalaryException and a class Employee that processes salary according to the following rules:

If salary < 0, throw InvalidSalaryException with the message: "Salary cannot be negative". If salary > 200000, throw InvalidSalaryException with the message: "Salary exceeds threshold limit". Otherwise, display: "Salary processed successfully for <empName>: <salary>".

The payroll processing should always display: "Payroll process completed" at the end, regardless of whether an exception occurs.

### ***Input Format***

The first line of input contains an integer representing the employee ID.

The second line contains a string representing the employee's name.

The third line contains a floating-point number representing the salary of the employee.

### ***Output Format***

If the salary is valid: "Salary processed successfully for <empName>: <salary>"

"Payroll process completed"

If the salary is invalid: "<Exception Message>"

"Payroll process completed"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 101

Rahul

150000.0

Output: Salary processed successfully for Rahul: 150000.0

Payroll process completed

### ***Answer***

// You are using Java

import java.util.\*;

```
class InvalidSalaryException extends Exception{
    public InvalidSalaryException(String message){
        super(message);
    }
}
class Salary{
    public static void checksalary(float salary) throws InvalidSalaryException {
        if(salary<0){
```

```

        throw new InvalidSalaryException("Salary cannot be negative");
    }
    else if(salary>200000){
        throw new InvalidSalaryException("Salary exceeds threshold limit");
    }
}
public static void main(String[] args){
    Scanner sc = new Scanner(System.in);
    int eid=sc.nextInt();
    sc.nextLine();
    String name=sc.nextLine();

    float salary=sc.nextFloat();
    try{
        checksalary(salary);
        System.out.printf("Salary processed successfully for %s: %.1f\n",name,salary);
    }
    catch(InvalidSalaryException e){
        System.out.println(e.getMessage());
    }
    finally{
        System.out.println("Payroll process completed");
    }
}
}

```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 8\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Faustus is managing his bank account and wants to create a program to update his account balance based on certain conditions. However, he needs to handle specific scenarios related to invalid inputs and insufficient balances. Faustus wants to update his account balance. He inputs the current balance and the amount to be updated.

The initial account balance should be positive. If Faustus enters a negative initial balance, the program should throw an `InvalidAmountException` with the message "Invalid amount. Please enter a positive initial balance." If the amount to be updated is negative, the program should check if the subtraction results in a negative balance. If so, it should throw an `InsufficientBalanceException` with the message "Insufficient balance." If the amount to be updated is positive, it should be added to the current balance, and the new balance should be printed.

Implement a custom exception, `InvalidAmountException`, and `InsufficientBalanceException`, to manage his bank account.

### ***Input Format***

The first line of input consists of a double value 'd', representing the initial account balance.

The second line of input consists of a double value 'd1', representing the amount to be updated.

### ***Output Format***

The output is displayed in the following format:

If the validation passes, print

"Account balance updated successfully! New balance: {new\_balance}"

where {new\_balance} is the updated account balance.

If the initial bank amount is negative it displays

"Error: Invalid amount. Please enter a positive initial balance."

If the updated amount exceeds the initial account balance in withdrawal it displays

"Error: Insufficient balance."

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1000  
500

Output: Account balance updated successfully! New balance: 1500.0

### ***Answer***

```
import java.util.*;  
class InvalidAmountException extends Exception{
```



```

    public InvalidAmountException(String message){
        super(message);
    }
}
class InsufficientBalanceException extends Exception{
    public InsufficientBalanceException(String message){
        super(message);
    }
}
class bank{
    public static double checkbalance(double d,double d1) throws
InvalidAmountException,InsufficientBalanceException{
        double balance=d+d1;
        if(d<0){
            throw new InvalidAmountException("Error: Invalid amount. Please enter a
positive initial balance.");
        }
        if(balance<0){
            throw new InsufficientBalanceException("Error: Insufficient balance.");
        }
        return balance;
    }
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        double d=sc.nextDouble();
        double d1=sc.nextDouble();
        try{
            double bal=checkbalance(d,d1);
            System.out.println("Account balance updated successfully! New balance.
"+bal);
        }
        catch(InvalidAmountException e){
            System.out.println(e.getMessage());
        }
        catch(InsufficientBalanceException e){
            System.out.println(e.getMessage());
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Theo is trying to update his payment information on a subscription-based streaming service. To proceed, the system requires Theo to provide a valid credit card number consisting of 16 digits. However, Theo wants to make sure that the credit card number he enters meets the specified criteria with proper exception handling.

The credit card number must consist of exactly 16 digits. If the entered credit card number does not meet the specified criteria, the program should throw a custom exception, `InvalidCreditCardException`, and provide Theo with specific error messages: If the length of the credit card number is not 16 digits, the exception message should be: "Invalid credit card number length." If the credit card number contains non-numeric characters, the exception message should be: "Invalid credit card number format."

Implement a custom exception, `InvalidCreditCardException`, to fulfill Theo's requirements and keep his payment information secure.

### ***Input Format***

The input consists of a string value 's', consisting of the 16-digit credit card number.

### ***Output Format***

The output is displayed in the following format:

If the entered credit card number is valid, the program should output a success message:

"Payment information updated successfully!"

If the entered credit card has more than 16 digits or less than 16 digits it displays

"Error: Invalid credit card number length."

If the entered 16-digit credit card has non-integers it displays

"Error: Invalid credit card number format."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1234567890123456

Output: Payment information updated successfully!

### **Answer**

// You are using Java

import java.util.\*;

```
class InvalidCreditCardException extends Exception{
    public InvalidCreditCardException(String message){
        super(message);
    }
}

class credit{
    public static void checkcno(String no) throws InvalidCreditCardException{
        if(no.length()<16 || no.length()>16 ){
            throw new InvalidCreditCardException("Error: Invalid credit card number
length.");
        }
        else if(!(no.matches("[0-9]+"))){
            throw new InvalidCreditCardException("Error: Invalid credit card number
format.");
        }
    }

    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String no=sc.nextLine();
        try{
            checkcno(no);
            System.out.println("Payment information updated successfully!");
        }
        catch(InvalidCreditCardException e){
            System.out.println(e.getMessage());
        }
    }
}
```

**Status : Correct**

**Marks : 10/10**

### 3. Problem Statement

Hemanth is designing a banking system for XYZ Bank. The system should allow customers to perform deposit, withdrawal, and balance inquiry operations. Implement exception handling for scenarios involving invalid transaction amounts or insufficient funds.

Create two custom exception classes, `InvalidAmountException` and `InsufficientFundsException`, both extending the `Exception` class. Throw an `InvalidAmountException` with a message if the deposit amount is less than or equal to zero. Throw an `InsufficientFundsException` if the withdrawal amount is greater than the available balance. Deduct the withdrawal amount from the balance if the withdrawal is successful.

Assist Hemanth in designing the program.

#### ***Input Format***

The first line of input consists of a double value `B`, representing the initial balance.

The second line consists of a double value `D`, representing the deposit amount.

The third line consists of a double value `W`, representing the withdrawal amount.

#### ***Output Format***

If the withdrawal is successful, print the amount withdrawn and the current balance, rounded off to one decimal place.

If an `InvalidAmountException` occurs, print "Error: [`D`] is not valid".

If an `InsufficientFundsException` occurs, print "Error: Insufficient funds".

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: 1050.1  
270.2  
150.3

Output: Amount Withdrawn: 150.3  
Current Balance: 1170.0

**Answer**

```
import java.util.Scanner;

class InvalidAmountException extends Exception {
    public InvalidAmountException(String message) {
        super(message);
    }
}

class InsufficientFundsException extends Exception {
    public InsufficientFundsException(String message) {
        super(message);
    }
}

class HDFCBank {
    private double balance;

    public static void main(String[] args) {
        HDFCBank hdfcBank = new HDFCBank();
        hdfcBank.processTransactions();
    }

    public void processTransactions() {
        Scanner scanner = new Scanner(System.in);

        try {
            balance = scanner.nextDouble();
            double depositAmount = scanner.nextDouble();
            deposit(depositAmount);

            double withdrawAmount = scanner.nextDouble();
            double withdrawnAmount = withdraw(withdrawAmount);

            System.out.printf("Amount Withdrawn: %.1f\n", withdrawnAmount);
            balanceEnquiry();
        } catch (InvalidAmountException | InsufficientFundsException e) {
            System.out.println("Error: " + e.getMessage());
        } finally {
```

```

        scanner.close();
    }
}

public void deposit(double amount) throws InvalidAmountException {
    if (amount <= 0) {
        throw new InvalidAmountException(amount + " is not valid");
    }
    balance = balance + amount;
}

public double withdraw(double amount) throws InsufficientFundsException {
    if (balance < amount) {
        throw new InsufficientFundsException("Insufficient funds");
    }
    balance = balance - amount;
    return amount;
}

public void balanceEnquiry() {
    System.out.printf("Current Balance: %.1f\n", balance);
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Tim was tasked with creating a user profile system that validates the user's date of birth input. The system should throw a custom exception, `InvalidDateOfBirthException`, if the date is not in the specified format "dd-mm-yyyy" or if it represents an invalid calendar date.

The main method takes user input, validates the date of birth, and prints whether it is valid or not.

##### **Input Format**

The input consists of a string, representing the date of birth of the user.

##### **Output Format**

The output displays one of the following results:

If the entered date of birth is valid according to the specified format, the program prints:

"[Date] is a valid date of birth"

If the entered date of birth is not valid according to the specified format, the program prints:

"Invalid date: [Date]"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 01-01-2000

Output: 01-01-2000 is a valid date of birth

### **Answer**

```
import java.util.*;
import java.text.*;
```

```
class InvalidDateOfBirthException extends Exception {
    public InvalidDateOfBirthException(String message) {
        super(message);
    }
}
```

```
public class Main {
    public static void validateDOB(String dob) throws InvalidDateOfBirthException
    {
        SimpleDateFormat sdf = new SimpleDateFormat("dd-MM-yyyy");
        sdf.setLenient(false);

        try {
            Date date = sdf.parse(dob);
        } catch (ParseException e) {
            throw new InvalidDateOfBirthException("Invalid date: " + dob);
        }
    }
}
```

```
}  
}  
  
public static void main(String[] args) {  
    Scanner sc = new Scanner(System.in);  
    String dob = sc.nextLine();  
  
    try {  
        validateDOB(dob);  
        System.out.println(dob + " is a valid date of birth");  
    } catch (InvalidDateOfBirthException e) {  
        System.out.println(e.getMessage());  
    }  
    sc.close();  
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. How can you access the first element of an ArrayList named as list?

**Answer**

list.get(0);

**Status : Correct**

**Marks : 1/1**

2. What will be the output of the following code?

```
import java.util.*;  
public class Main {  
    public static void main(String[] args) {  
        Stack<Integer> s = new Stack<>();  
        s.push(10);  
        s.push(20);
```

```
s.push(30);  
System.out.println(s.peek());  
}  
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
import java.util.*;  
class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> list = new ArrayList<>();  
        list.add(10);  
        list.add(20);  
        list.add(30);  
        list.remove(1);  
        System.out.println(list);  
    }  
}
```

**Answer**

[10, 30]

**Status :** Correct

**Marks :** 1/1

4. Which of the following methods removes and returns the last element from a LinkedList?

**Answer**

removeLast()

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.add(5);
        System.out.println(list.get(3));
    }
}
```

**Answer**

4

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(10);
        list.add(20);
        list.add(30);
        System.out.println("Size of the list: " + list.size());
    }
}
```

**Answer**

Size of the list: 3

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following code?

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
        Stack<Integer> stack = new Stack<>();
        for (int i = 1; i <= 3; i++)
            stack.push(i * 2);
        stack.pop();
        stack.push(10);
        System.out.println(stack.peek());
    }
}
```

**Answer**

10

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Apple");
        list.add("Banana");
        list.remove("Apple");
        System.out.println(list);
    }
}
```

**Answer**

[Banana]

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("Java");
        list.add("Python");
        list.add("Java");
        list.add("C++");
        System.out.println(list.indexOf("Java"));
    }
}
```

**Answer**

0

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<String> list = new ArrayList<>();
        list.add("apple");
        list.add("banana");
        list.add("cherry");
        list.add("banana");
        System.out.println(list.lastIndexOf("banana"));
    }
}
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

11. What is the correct way to create an ArrayList in Java?

**Answer**

`ArrayList<String> list = new ArrayList<>();`

**Status :** Correct

**Marks :** 1/1

12. Which method is used to add an element to the top of the stack?

**Answer**

`push()`

**Status :** Correct

**Marks :** 1/1

13. What is Collection in Java?

**Answer**

A group of objects

**Status :** Correct

**Marks :** 1/1

14. What does the `addFirst()` method of `LinkedList` do?

**Answer**

Adds an element to the beginning of the list

**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        ArrayList<Integer> list = new ArrayList<>();
        list.add(1);
        list.add(2);
        list.add(3);
        list.add(4);
        list.set(2, 10);
    }
}
```

```
        System.out.println(list);  
    }  
}
```

**Answer**

[1, 2, 10, 4]

**Status :** Correct

**Marks : 1/1**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Bobby is tasked with processing a sequence of numbers from a monitoring system. He needs to extract a strictly increasing subsequence using an ArrayList. The program should dynamically add numbers to the ArrayList only if they are greater than the last number currently stored in the list. Bobby aims to efficiently utilize the dynamic resizing and indexing features of the ArrayList to solve this problem.

Help Bobby implement this solution.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements.



The second line consists of N space-separated integers, representing the elements.

### **Output Format**

The output prints the list of integers in increasing sequence, ignoring out-of-order elements.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 7

3 5 9 1 11 7 13

Output: [3, 5, 9, 11, 13]

### **Answer**

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner sc= new Scanner(System.in);
        ArrayList<Integer> inclist = new ArrayList<Integer>();
        int n=sc.nextInt();
        for(int i=0;i<n;i++){
            int num=sc.nextInt();
            if(inclist.isEmpty() || num>inclist.get(inclist.size()-1))
                inclist.add(num);
        }
        System.out.println(inclist);
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Vikram loves listening to music and wants to create a simple playlist manager using Java Collections. The playlist supports the following operations:

"ADD <song>" Adds the song to the end of the playlist."REMOVE <song>" Removes the first occurrence of the song from the playlist. If the song is not found, do nothing."SHOW" Displays all songs in the playlist in order. If the playlist is empty, print "EMPTY". "NEXT" Moves to the next song in the playlist and prints its name. If the playlist is empty, print "EMPTY".

The playlist maintains a "current song" position that starts at the first song when it's added. The NEXT command moves to the next song and prints it, wrapping around to the first song after reaching the last song. When removing songs, the current position adjusts accordingly to maintain

proper navigation.

Help Vikram implement this playlist manager.

### ***Input Format***

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <song>"
- "REMOVE <song>"
- "SHOW"
- "NEXT"

### ***Output Format***

For each "SHOW" command, print the songs in order, separated by spaces.

For each "NEXT" command, print the next song in the playlist.

If no song exists, print "EMPTY".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

ADD song1

ADD song2

SHOW

NEXT

REMOVE song2

SHOW

NEXT

Output: song1 song2

song2

song1

song1

### ***Answer***

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        LinkedList<String> playlist = new LinkedList<>();
        int currentIndex = -1;

        for (int i = 0; i < n; i++) {
            String cmd = sc.next();

            if (cmd.equals("ADD")) {
                String song = sc.next();
                playlist.add(song);
                if (currentIndex == -1) currentIndex = 0;

            } else if (cmd.equals("REMOVE")) {
                String song = sc.next();
                int removeIndex = playlist.indexOf(song);
                if (removeIndex != -1) {
                    playlist.remove(removeIndex);
                    if (playlist.isEmpty()) currentIndex = -1;
                    else if (removeIndex < currentIndex) currentIndex--;
                    else if (removeIndex == currentIndex && currentIndex >=
playlist.size())
                        currentIndex = 0;
                }

            } else if (cmd.equals("SHOW")) {
                if (playlist.isEmpty()) {
                    System.out.println("EMPTY");
                } else {
                    for (String s : playlist) System.out.print(s + " ");
                    System.out.println();
                }

            } else if (cmd.equals("NEXT")) {
                if (playlist.isEmpty()) {
                    System.out.println("EMPTY");
                } else {
```

}

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 9\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Assist Pranitha in developing a program that takes an integer N as input, representing the number of names to be read. Then read N names and store them in an ArrayList. Finally, input a search string and output the frequency of that string in the list of names.

Note: Some parts of the code are provided as snippets, and you need to complete the remaining sections by writing the necessary code.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of names to be read.

The following N lines consist of N names, as a string.

The last line consists of a string, representing the name to be searched.

### **Output Format**

The output prints a single integer, representing the frequency of the specified name in the given list.

If the specified name is not found, print 0.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

Alice

Bob

Ankit

Alice

Pranitha

Alice

Output: 2

### **Answer**

// You are using Java

```
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        ArrayList<String> names= new ArrayList<>();
        int n=sc.nextInt();
        sc.nextLine();
        for(int i=0;i<n;i++){
            String a=sc.nextLine();
            names.add(a);
        }
        String search=sc.nextLine();
        int count=0;
        for(int j=0;j<n;j++){
            if(search.equals(names.get(j))){
                count++;
            }
        }
        System.out.println(count);
    }
}
```

```
}  
    }  
    System.out.println(count);  
}  
}
```

**Status :** Correct

**Marks :** 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

#### Section 1 : Coding

##### 1. Problem Statement

Aditi is analyzing stock market trends and wants to find the Next Greater Element (NGE) for each stock price in a list. The Next Greater Element for an element  $x$  in an array is the first element to the right that is greater than  $x$ . If no greater element exists, return -1 for that position.

Your task is to help Aditi by efficiently computing the Next Greater Element for each element in the given array using a Stack.

Example:

Input:

6

4 5 2 10 8 6

Output:

5 10 10 -1 -1 -1

Explanation:

For each element:

4 5 (next greater element)5 102 1010 -1 (No greater element)8 -16 -1

### ***Input Format***

The first line contains an integer n, representing the number of elements.

The second line contains n space-separated integers arr[i], where arr[i] is the stock price on the i-th day.

### ***Output Format***

The output prints n space-separated integers representing the Next Greater Element for each element in the array.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 6

4 5 2 10 8 6

Output: 5 10 10 -1 -1 -1

### ***Answer***

```
// You are using Java
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        Stack <Integer> nge = new Stack<>();
        int n=sc.nextInt();
        int []arr=new int[n];
        for(int i=0;i<n;i++){
            arr[i]=sc.nextInt();
```

```

    }
    int max=-1;
    for(int j=0;j<n;j++){
        max=-1;
        for(int k=j;k<n;k++){
            if(arr[j]<arr[k]){
                max=arr[k];
                break;
            }
        }
        nge.push(max);
    }
    for(int a:nge){
        System.out.print(a + " ");
    }
}
}

```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

Rekha is a teacher who wants to calculate the average of marks scored by her students in a test. She needs to store all the marks dynamically because the number of students may vary each time. Using an ArrayList allows her to easily add any number of marks without worrying about the initial size.

Help her implement the task.

### **Input Format**

The first line of input is an integer n, representing the number of students..

The second line of input consists of n double values, representing the marks of each student, separated by a space.

### **Output Format**

The output prints: "Average of the list: " followed by the average value formatted

to two decimal places.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

1.0 2.0 3.0 4.0 5.0

Output: Average of the list: 3.00

### **Answer**

// You are using Java

```
import java.util.*;
```

```
public class Main{
    public static void main(String[] args){
        Scanner sc = new Scanner(System.in);
        ArrayList<Double> marks=new ArrayList<>();
        int n=sc.nextInt();
        double avg=0;
        for(int i=0;i<n;i++){
            double a=sc.nextDouble();
            avg+=a;
            marks.add(a);
        }
        System.out.printf("Average of the list: %.2f",avg/n);
    }
}
```

**Status :** Correct

**Marks : 10/10**

### **3. Problem Statement**

Arun is building a task manager to keep track of tasks using a LinkedList. The task manager supports the following operations:

"ADD <task>" Adds the given task to the end of the list."REMOVE"

Removes the first task from the list."SHOW" Displays all tasks in the list in

order. If the list is empty, print "EMPTY".

Help Arun implement this functionality using a LinkedList.

### ***Input Format***

The first line of the input consists of an integer n, the number of operations.

The next n lines, each containing a command:

- "ADD <task>"
- "REMOVE"
- "SHOW"

### ***Output Format***

For each "SHOW" command, the output prints the tasks in order, separated by spaces.

If no tasks exist, print "EMPTY".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5  
ADD homework  
ADD project  
SHOW  
REMOVE  
SHOW

Output: homework project  
project

### ***Answer***

```
// You are us
import java.util.*;

public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
```

```

LinkedList<String> tasks = new LinkedList<>();
int n=sc.nextInt();
//sc.nextLine();
for(int i=0;i<n;i++){
    String command=sc.next();

    if(command.equals("ADD")){
        String ad=sc.next();
        tasks.add(ad);
    }
    else if(command.equals("REMOVE")){
        if(!tasks.isEmpty()){
            tasks.remove();
        }
    }
    else if(command.equals("SHOW")){
        if(tasks.isEmpty()){
            System.out.println("EMPTY");
        }
        else{
            for(String t : tasks){
                System.out.print(t + " ");
            }
            System.out.println();
        }
    }
}
}
}
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Aarav is developing a music playlist application where users can manage their favorite songs. He wants to implement a feature that allows users to reorder the playlist by moving a song from one position to another.

You need to implement a function that performs the following operations using a LinkedList:

Add songs to the playlist in the given order. Move a song from a specified position to another position in the playlist. Print the final playlist after all operations.

##### ***Input Format***

The first line of the input consists of an integer  $n$  representing the number of songs.

The next n lines, each containing a string representing a song name.

After the songs are given the next line contains an integer m, the number of move operations.

The next m lines, each containing two integers x and y representing the move operation where the song at position x (0-based index) should be moved to position y.

### **Output Format**

The output prints the final playlist, each song on a new line.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

SongA

SongB

SongC

SongD

SongE

2

2 4

0 3

Output: SongB

SongD

SongE

SongA

SongC

### **Answer**

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
        LinkedList<String> playlist = new LinkedList<>();
```



```

    for (int i = 0; i < n; i++) playlist.add(sc.nextLine());
    int m = sc.nextInt();
    for (int i = 0; i < m; i++) {
        int x = sc.nextInt();
        int y = sc.nextInt();
        String song = playlist.remove(x);
        playlist.add(y, song);
    }
    for (String song : playlist) System.out.println(song);
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Rahul, a stock trader, wants to analyze the stock prices of a company over several days. For each day, he wants to determine the stock span, which is the number of consecutive days (including the current day) where the stock price is less than or equal to the price on that day.

The stock span helps him understand how long a stock has been continuously increasing or staying the same. You need to help Rahul by computing the stock span for each day using a Stack data structure efficiently.

**Example:**

**Input:**

7

100 80 60 70 60 75 85

**Output:**

1 1 1 2 1 4 6

**Explanation:**

For each day:

Day 1: Price = 100    Span = 1 (Only this day) Day 2: Price = 80    Span = 1

(Only this day)Day 3: Price = 60 Span = 1 (Only this day)Day 4: Price = 70 Span = 2 (Includes today and previous day)Day 5: Price = 60 Span = 1 (Only this day)Day 6: Price = 75 Span = 4 (Includes today and previous three days)Day 7: Price = 85 Span = 6 (Includes today and previous five days)

### ***Input Format***

The first line contains an integer n, the number of days.

The second line contains n space-separated integers prices[i], where prices[i] represents the stock price on the i-th day.

### ***Output Format***

The output prints n space-separated integers representing the stock span for each day.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 7

100 80 60 70 60 75 85

Output: 1 1 1 2 1 4 6

### ***Answer***

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();

        int[] prices = new int[n];
        for (int i = 0; i < n; i++) {
            prices[i] = sc.nextInt();
        }
    }
}
```

```

int[] span = new int[n];
Stack<Integer> stack = new Stack<>();

for (int i = 0; i < n; i++) {

    while (!stack.isEmpty() && prices[stack.peek()] <= prices[i]) {
        stack.pop();
    }

    if (stack.isEmpty()) {
        span[i] = i + 1;
    } else {
        span[i] = i - stack.peek();
    }

    stack.push(i);
}

for (int i = 0; i < n; i++) {
    if (i > 0) System.out.print(" ");
    System.out.print(span[i]);
}

sc.close();
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Raman, a computer science teacher, is responsible for registering students for his programming class. To streamline the registration process, he wants to develop a program that stores students' names and allows him to retrieve a student's name based on their index in the list.

Raman has decided to use an ArrayList to store the names of students, as

it provides efficient dynamic resizing and indexing.

Write a program that enables Raman to input the names of students and fetch a student's name using the specified index. If the entered index is invalid, the program should return an appropriate message.

### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of students to register.

The next  $n$  lines of input consist of the names of each student, one by one.

The last line of input is an integer, representing the index (0-indexed) of the element to retrieve.

### ***Output Format***

If the index is valid (within the bounds of the ArrayList), print "Element at index [index]: " followed by the element (student name as string).

If the index is invalid, print "Invalid index".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

Alice

Bob

Ankit

Alice

Prajit

2

Output: Element at index 2: Ankit

### ***Answer***

```
// You are using Java
```

```
import java.util.*;
```

```
public class Main {
```

```

public static void main(String[] args) {
    Scanner sc = new Scanner(System.in);
    int n = sc.nextInt();
    sc.nextLine();
    ArrayList<String> students = new ArrayList<>();
    for (int i = 0; i < n; i++) {
        students.add(sc.nextLine());
    }
    int index = sc.nextInt();
    if (index >= 0 && index < students.size()) {
        System.out.println("Element at index " + index + ": " + students.get(index));
    } else {
        System.out.println("Invalid index");
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Rahul is working on a list manipulation problem where he needs to reverse a specific subarray using a stack. Given an array and two indices  $l$  and  $r$ , he wants to reverse only the portion of the array from index  $l$  to  $r$  (both inclusive) while keeping the rest of the array unchanged.

Since Rahul wants to solve this problem efficiently, he decides to use a stack to reverse the subarray in  $O(r - l)$  time.

Your task is to help Rahul by implementing this functionality.

##### **Input Format**

The first line contains an integer  $n$ , the size of the array.

The second line contains  $n$  space-separated integers  $arr[i]$ .

The third line contains two integers  $l$  and  $r$ , denoting the start and end indices of the subarray to reverse.

Note: The array follows 0-based indexing.

### **Output Format**

The output prints the modified array after reversing the subarray between indices l and r.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 6

1 2 3 4 5 6

1 4

Output: 1 5 4 3 2 6

### **Answer**

```
import java.util.*;
```

```
public class Main {
```

```
// You are using Java
```

```
    public static void main(String[] args) {  
        Scanner sc=new Scanner(System.in);  
        int n=sc.nextInt();
```

```
        int arr[]=new int[n];  
        Stack <Integer> st = new Stack<>();
```

```
        for(int i=0;i<n;i++){  
            arr[i]=sc.nextInt();  
        }
```

```
        int l=sc.nextInt();  
        int r=sc.nextInt();
```

```
        for (int i = l; i <= r; i++) {  
            st.push(arr[i]);  
        }
```

```
        for (int i = l; i <= r; i++) {
```

```
        arr[i] = st.pop();
    }

    for (int i = 0; i < n; i++) {
        System.out.print(arr[i] + " ");
    }

}

}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. What happens if two keys have the same hash code in a HashMap?

**Answer**

A linked list is used to store values with the same hash

**Status : Correct**

**Marks : 1/1**

2. What will happen if you add elements in descending order in a TreeSet?

**Answer**

They are sorted in ascending order

**Status : Correct**

**Marks : 1/1**



3. Which of the following is true about TreeMap?

**Answer**

It maintains natural ordering

**Status : Correct**

**Marks : 1/1**

4. Which of the following is true about HashMap?

**Answer**

It is not synchronized

**Status : Correct**

**Marks : 1/1**

5. Which of the following allows null keys in Java?

**Answer**

HashMap

**Status : Correct**

**Marks : 1/1**

6. What is the time complexity of retrieving an element from a HashSet?

**Answer**

$O(1)$

**Status : Correct**

**Marks : 1/1**

7. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("A", 1);
        map.put("B", 2);
        map.put("C", 3);
    }
}
```

```
        System.out.println(map.containsKey("B"));
    }
}
```

**Answer**

true

**Status :** Correct

**Marks :** 1/1

8. How does HashSet check for duplicate elements?

**Answer**

Using equals() and hashCode()

**Status :** Correct

**Marks :** 1/1

9. Which method removes all elements from a Set?

**Answer**

clear()

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, String> map = new HashMap<>();
        map.put("A", "Apple");
        map.put("B", "Banana");
        map.put("C", "Cherry");
        map.replace("B", "Blueberry");
        System.out.println(map);
    }
}
```

**Answer**

{A=Apple, B=Blueberry, C=Cherry}

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following code?

```
import java.util.*;
class Main {
    public static void main(String[] args) {
        HashMap<String, Integer> map = new HashMap<>();
        map.put("X", 10);
        map.put("Y", 20);
        map.put("Z", 30);
        map.remove("Y");
        System.out.println(map);
    }
}
```

**Answer**

{X=10, Z=30}

**Status :** Correct

**Marks :** 1/1

12. What will happen if you add a null element to a TreeSet?

**Answer**

An exception occurs

**Status :** Correct

**Marks :** 1/1

13. Which statement is true about HashSet and TreeSet?

**Answer**

TreeSet provides sorted elements

**Status :** Correct

**Marks :** 1/1

14. Which method retrieves the lowest key in a TreeMap?

**Answer**

firstKey()

**Status :** Correct

**Marks :** 1/1

15. What happens when you add duplicate elements to a HashSet?

**Answer**

The duplicate is ignored

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

A city traffic management system needs to track vehicles entering a toll booth. Each vehicle is uniquely identified by its registration number. The system should allow adding vehicles to a record, ensuring that no duplicate registration numbers exist. The vehicles should be stored in a HashSet, which does not guarantee any specific order.

Your task is to implement a program using a HashSet that allows adding vehicle details and displaying the records.

##### ***Input Format***

The first line of input contains an integer N - the number of vehicles.

The next N lines contain details of each vehicle in the format: "RegNumber

OwnerName VehicleType"

1. RegNumber (String) - A unique registration number (Alphanumeric).
2. OwnerName (String) - The name of the vehicle owner.
3. VehicleType (String, Car, Bike, or Truck) - The type of vehicle.

If a vehicle with the same registration number is already present, ignore the duplicate entry.

### **Output Format**

The output prints the unique vehicle records in any order (since HashSet does not maintain order).

Output format: "RegNumber OwnerName VehicleType"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

KA01AB1234 John Car

MH02CD5678 Alice Bike

DL03EF9012 Bob Truck

TN04GH3456 Mike Car

KA01AB1234 John Car

Output: TN04GH3456 Mike Car

KA01AB1234 John Car

MH02CD5678 Alice Bike

DL03EF9012 Bob Truck

### **Answer**

// You are using Java

```
import java.util.*;
```

```
public class Main{  
    public static void main(String[] args){
```

```
        Scanner sc= new Scanner(System.in);
```

```
        HashSet<String> vehicles = new HashSet<>();
```

```
        HashSet<String> regnos = new HashSet<>();
```

```
int n=sc.nextInt();
sc.nextLine();
//for(int i=0;i<n;i++){
//  String a=sc.nextLine().trim();
//  vehicles.add(a);
//}
for(int i=0;i<n;i++){
    String a=sc.nextLine().trim();
    String regno = a.split(" ")[0];

    if(!vehicles.contains(regno)){
        vehicles.add(a);
        regnos.add(regno);
    }
}
for(String b:vehicles){
    System.out.println(b);
}
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

John is organizing a fruit festival, and the quantities of various fruits are stored in a HashMap where fruit names are keys and quantities are values.

Help him develop a program to find the total quantity of fruits for the festival by summing up the values in the HashMap.

##### ***Input Format***

The input consists of fruit quantities in the format 'fruitName:quantity', where fruitName is the name of the fruit(a string), and quantity is a double value representing the quantity.

The input is terminated by entering "done".

##### ***Output Format***



The output prints a double value, representing the sum of values in the HashMap, rounded off to two decimal places.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are entered, print "Invalid format".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Banana:15.2

Orange:56.3

Mango:47.3

done

Output: 118.80

### **Answer**

```
import java.util.*;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        HashMap<String,Double> map = new HashMap<>();
```

```
        int flag=1;
```

```
        while(true){
```

```
            String input = sc.nextLine().trim();
```

```
            if(input.equals("done")){
```

```
                break;
```

```
            }
```

```
            else if(!input.contains(":")){
```

```
                System.out.println("Invalid format");
```

```
                flag=0;
```

```
                break;
```

```
            }
```

```
            String []parts=input.split(":");
```

```
            String name=parts[0];
```

```
            String qty=parts[1];
```

```
try{
    double quantity = Double.parseDouble(qty);
    map.put(name,quantity);
}
catch(NumberFormatException e){
    System.out.println("Invalid input");
    flag=0;
    break;
}

}
double total=0;
if(flag==1){
    for(double a:map.values()){
        total+=a;
    }
    System.out.printf("%.2f",total);
}

sc.close();
}
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

Priya is analyzing encrypted messages in a research project. She wants to analyze the frequency of each character in a given paragraph. The characters should be stored in a TreeMap so that the output is sorted in ascending order of characters automatically.

You are required to build a Java program that:

Uses a `TreeMap<Character, Integer>` to count how many times each character appears in the message. Ignores spaces and considers only alphabets (case-sensitive). Outputs the frequencies of characters in sorted order.

You must use a TreeMap in the class named MessageAnalyzer.

**Input Format**

The first line of input contains an integer n, the number of lines in the message.

The next n lines each contain a string (the encrypted message line).

### **Output Format**

The first line of output prints: "Character Frequency:"

Then print each character and its frequency in the format: "<character>: <count>"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 2  
Hello World  
Java

Output: Character Frequency:

H: 1

J: 1

W: 1

a: 2

d: 1

e: 1

l: 3

o: 2

r: 1

v: 1

### **Answer**

```
// You are using Java
import java.util.*;
```

```
class Main{
    public static void main(String[] args){
        Scanner sc =new Scanner(System.in);
        TreeMap<Character,Integer> map = new TreeMap<>();
        int n =sc.nextInt();
        sc.nextLine();
        int count=0;
        System.out.println("Character Frequency:");
```

```

String a="";
for(int i=0;i<n;i++){
    String b=sc.nextLine().trim();
    a+=b;
}
char []letters=a.toCharArray();

for(int j=0;j<letters.length;j++){
    count=0;

    for(int k=0;k<letters.length;k++){
        if(letters[j]==letters[k]){
            count+=1;
        }
        map.put(letters[j],count);
    }
    //if(letters[j]!=' '){
    //    System.out.println(a.get()+"."+a.getValue());
    //}
}

for(var c:map.entrySet()){
    if(c.getKey()!=' ')
        System.out.println(c.getKey()+"."+c.getValue());
}
}
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 10\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : COD

##### 1. Problem Statement

In a ticket reservation system, you store the available seat numbers in a TreeSet. Users input their desired seat number, and the program checks whether the chosen seat is available.

Using a TreeSet ensures quick and efficient verification of seat availability, ensuring a smooth and organized ticket booking process.

##### ***Input Format***

The first line of input contains a single integer  $n$ , representing the number of available seats.

The second line contains  $n$  space-separated integers, representing the available seat numbers.

The third line contains an integer  $m$ , representing the seat number that needs to be searched.

### **Output Format**

The output displays "[ $m$ ] is present!" if the given seat is available. Otherwise, it displays "[ $m$ ] is not present!"

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 4

2 4 5 6

5

Output: 5 is present!

### **Answer**

// You are using Java

import java.util.\*;

```
public class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=sc.nextInt();
        sc.nextLine();
        Set<Integer> seat=new TreeSet<Integer>();
        for(int i=0;i<n;i++){
            int a=sc.nextInt();
            seat.add(a);
        }
        int search=sc.nextInt();
        if(seat.contains(search)){
            System.out.printf("%d is present!",search);
        }
        else{
            System.out.printf("%d is not present!",search);
        }
    }
}
```

Status : Correct

Marks : 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

#### Section 1 : Coding

##### 1. Problem Statement

A university maintains a list of student records and wants to store them in a sorted manner based on their GPA. If two students have the same GPA, they should be further sorted by their name in lexicographical order. Implement a program that uses a TreeSet to store student records and ensures unique student IDs.

##### ***Input Format***

The first line contains an integer N - the number of students.

The next N lines contain details of each student in the format: "StudentID Name GPA"

- StudentID (Integer) - A unique identifier.
- Name (String) - The student's name (can contain spaces).

- GPA (Double) - The Grade Point Average.

### **Output Format**

The output prints the list of students in ascending order of GPA.

If two students have the same GPA, sort them by name.

Print details in the format: "StudentID Name GPA" in the output, GPA is rounded to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

101 John 8.5

102 Alice 9.1

103 Bob 8.5

104 Zoe 7.3

105 Charlie 9.1

Output: 104 Zoe 7.30

103 Bob 8.50

101 John 8.50

102 Alice 9.10

105 Charlie 9.10

### **Answer**

```
import java.util.*;
class Student implements Comparable<Student> {
    int studentID;
    String name;
    double gpa;

    public Student(int studentID, String name, double gpa) {
        this.studentID = studentID;
        this.name = name;
        this.gpa = gpa;
    }

    public int compareTo(Student other) {
```

```

        if (this.gpa != other.gpa) {
            return Double.compare(this.gpa, other.gpa);
        }
        return this.name.compareTo(other.name);
    }

    public String toString() {
        return studentID + " " + name + " " + String.format("%.2f", gpa);
    }
}

class UniversityRecords {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
        TreeSet<Student> studentSet = new TreeSet<>();
        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            String name = sc.next();
            double gpa = sc.nextDouble();
            studentSet.add(new Student(id, name, gpa));
        }
        for (Student s : studentSet) {
            System.out.println(s);
        }
        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Riya is building a calendar event scheduler where each event is stored in chronological order using a TreeMap. The key represents the event time in 24-hour format (HH:MM), and the value is the event description.

She wants the system to:

Automatically sort events by time. Avoid duplicate time entries — if a duplicate time is entered, ignore the new entry. Print all scheduled events in

order.

Implement this logic using a class named EventManager.

### ***Input Format***

The first line of the input contains an integer n, representing the number of events.

The next n lines each contain a string in the format: "HH:MM Description"

(Example: 09:00 TeamMeeting).

### ***Output Format***

The first line of the output prints "Scheduled Events:"

The next k lines print each event in the format: "HH:MM - Description"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

09:00 TeamMeeting

13:30 LunchBreak

11:00 ProjectUpdate

09:00 Standup

15:00 ClientCall

Output: Scheduled Events:

09:00 - TeamMeeting

11:00 - ProjectUpdate

13:30 - LunchBreak

15:00 - ClientCall

### ***Answer***

```
import java.util.*;
class EventManager {
    TreeMap<String, String> schedule;
    public EventManager() {
```

```

    schedule = new TreeMap<>();
}

public void addEvent(String time, String description) {
    if (!schedule.containsKey(time)) {
        schedule.put(time, description);
    }
}

public void printSchedule() {
    System.out.println("Scheduled Events:");
    for (Map.Entry<String, String> entry : schedule.entrySet()) {
        System.out.println(entry.getKey() + " - " + entry.getValue());
    }
}

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        EventManager manager = new EventManager();

        for (int i = 0; i < n; i++) {
            String line = sc.nextLine();
            int spaceIndex = line.indexOf(' ');
            String time = line.substring(0, spaceIndex);
            String desc = line.substring(spaceIndex + 1);
            manager.addEvent(time, desc);
        }

        manager.printSchedule();
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Sarah is working on a spam detection system that analyzes incoming messages for unique patterns. Spammers often use repetitive character

sequences, making it important to identify the first non-repeating character in a message.

Given a string, Sarah needs to determine the first character that appears only once. If all characters repeat, the system should return -1.

She decides to use a HashMap to efficiently track character frequencies and find the solution.

### ***Input Format***

The first line contains an integer N representing , the length of the string.

The second line contains a string of N lowercase English letters (a-z).

### ***Output Format***

The output prints a character representing the first non-repeating character. If none exist, print -1.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 10  
abacabadac

Output: d

### ***Answer***

```
import java.util.*;
class NonRepeatingCharacterFinder {

    public char findFirstNonRepeatingCharacter(String str) {
        HashMap<Character, Integer> charCount = new HashMap<>();

        for (char ch : str.toCharArray()) {
            charCount.put(ch, charCount.getOrDefault(ch, 0) + 1);
        }

        for (char ch : str.toCharArray()) {
```

```
        if (charCount.get(ch) == 1) {
            return ch;
        }
    }

    return '\0';
}

class FirstNonRepeatingCharacter {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int N = sc.nextInt();
        String str = sc.next();

        NonRepeatingCharacterFinder finder = new NonRepeatingCharacterFinder();
        char result = finder.findFirstNonRepeatingCharacter(str);

        if (result == '\0') {
            System.out.println(-1);
        } else {
            System.out.println(result);
        }

        sc.close();
    }
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 10\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : COD

##### 1. Problem Statement

Bob wants to develop a score-tracking application for a gaming tournament. Each player's score is stored in a HashMap with the player's name as the key and the score as the value.

Write a program to assist Bob that takes user input to enter player scores, calculates the maximum score from the HashMap, and prints the player with the highest score.

##### ***Input Format***

The input consists of strings representing player details in the format "playerName:score".

The input is terminated by entering "done".



### **Output Format**

The output displays a string, representing the player's name who scored the maximum.

If the value is not numeric, print "Invalid input".

If any special characters other than ':' are given, print "Invalid format".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Alice:15

Bob:56

done

Output: Bob

### **Answer**

```
import java.util.*;
```

```
class ScoreTracker {
```

```
    Map<String, Integer> scoreMap = new HashMap<>();
```

```
    boolean processInput(String input) {
```

```
        if (input.split(":").length != 2) {  
            System.out.println("Invalid format");  
            return false;  
        }
```

```
        String[] parts = input.split(":");
```

```
        String playerName = parts[0].trim();
```

```
        String scoreStr = parts[1].trim();
```

```
        try {
```

```
            int score = Integer.parseInt(scoreStr);
```

```
            if (score < 1 || score > 100) {
```

```
                System.out.println("Invalid input");  
                return false;  
            }
```

```
        scoreMap.put(playerName, score);
        return true;
    } catch (NumberFormatException e) {
        System.out.println("Invalid input");
        return false;
    }
}
```

```
String findTopPlayer() {
    int maxScore = Integer.MIN_VALUE;
    String topPlayer = "";
```

```
    for (Map.Entry<String, Integer> entry : scoreMap.entrySet()) {
        if (entry.getValue() > maxScore) {
            maxScore = entry.getValue();
            topPlayer = entry.getKey();
        }
    }
```

```
    return topPlayer;
}
```

```
public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        ScoreTracker tracker = new ScoreTracker();
        boolean validInput = true;
```

```
        while (true) {
            String input = scanner.nextLine();

            if (input.toLowerCase().equals("done")) {
                break;
            }
```

```
            if (!tracker.processInput(input)) {
                validInput = false;
                break;
            }
        }
```

```
        if (validInput && !tracker.scoreMap.isEmpty()) {  
            System.out.println(tracker.findTopPlayer());  
        }  
  
        scanner.close();  
    }  
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Arjun is working on a program that checks if one set of numbers is a subset of another. If Set B is a subset of Set A, the program should print "YES" followed by the sorted elements of Set B. If Set B is not a subset of Set A, the program should print "NO" followed by the average of all elements from both sets combined, rounded to two decimal places.

Implement a class Solution with the required method to perform the subset check using TreeSet in Java.

### **Input Format**

The first line contains an integer n - the number of elements in Set A.

The second line contains n space-separated integers - the elements of Set A.

The third line contains an integer m - the number of elements in Set B.

The fourth line contains m space-separated integers - the elements of Set B.

### **Output Format**

If Set B is a subset of Set A, print "YES" followed by the sorted values of Set B.

Otherwise, print "NO" followed by the average of all numbers in both sets (rounded to two decimal places).

Refer to the sample output for formatting specifications.

### Sample Test Case

Input: 5

1 2 3 4 5

3

2 3 5

Output: YES 2 3 5

### Answer

```
import java.util.*;
```

```
class Solution {  
    public static void checkSubset(TreeSet<Integer> setA, TreeSet<Integer> setB,  
int totalElements, double sum) {  
        if (setA.containsAll(setB)) {  
            System.out.print("YES ");  
            for (int num : setB) {  
                System.out.print(num + " ");  
            }  
            System.out.println();  
        } else {  
            double average = sum / totalElements;  
            System.out.printf("NO %.2f%n", average);  
        }  
    }  
}
```

```
class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);  
        int n = sc.nextInt();  
        TreeSet<Integer> setA = new TreeSet<>();  
        long sum = 0;  
        for (int i = 0; i < n; i++) {  
            int num = sc.nextInt();  
            setA.add(num);  
            sum += num;  
        }  
        int m = sc.nextInt();  
        TreeSet<Integer> setB = new TreeSet<>();  
        for (int i = 0; i < m; i++) {  
            int num = sc.nextInt();  
            setB.add(num);  
        }  
    }  
}
```

```
        sum += num;
    }
    Solution.checkSubset(setA, setB, n + m, sum);
    sc.close();
}
}
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

David is managing an employee database where each employee has a unique ID, name, and department. He wants to ensure that duplicate employee IDs are not added to the system. Implement a Java program that allows adding employees to the system, displaying all employees, and checking if an employee exists based on the given ID.

Implement a class `EmployeeDatabase` that contains a `HashSet` to store employee records. The `Employee` class should be a user-defined object containing employee details. The main class should handle user operations and interact with the `EmployeeDatabase` class.

#### **Input Format**

The first line contains an integer `n` representing the number of employees to be added.

The next `n` lines follow, each containing:

1. An integer `employee_id`
2. A string `name`
3. A string `department`

The next line contains an integer `m` representing the number of queries.

The next `m` lines follow, each containing an employee ID to check for existence.

#### **Output Format**

The output prints a list of all employees added in the format:

"ID: <employee\_id>, Name: <name>, Department: <department>"

For each query, output "Employee exists" if the ID is found, otherwise "Employee not found".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

101 John IT

102 Alice HR

103 Bob Finance

2

101

104

Output: ID: 101, Name: John, Department: IT

ID: 102, Name: Alice, Department: HR

ID: 103, Name: Bob, Department: Finance

Employee exists

Employee not found

### **Answer**

```
import java.util.*;
```

```
class Employee {  
    int employeeId;  
    String name, department;
```

```
    public Employee(int employeeId, String name, String department) {  
        this.employeeId = employeeId;  
        this.name = name;  
        this.department = department;  
    }
```

```
    public int hashCode() {  
        return Objects.hash(employeeId);  
    }
```

```
    public boolean equals(Object obj) {
```

```

    if (this == obj) return true;
    if (obj == null || getClass() != obj.getClass()) return false;
    Employee e = (Employee) obj;
    return this.employeeId == e.employeeId;
}

    public String toString() {
        return "ID: " + employeeId + ", Name: " + name + ", Department: " +
department;
    }
}

class EmployeeDatabase {
    HashSet<Employee> employees = new HashSet<>();

    public void addEmployee(int id, String name, String department) {
        employees.add(new Employee(id, name, department));
    }

    public void displayEmployees() {
        for (Employee e : employees) {
            System.out.println(e);
        }
    }

    public boolean checkEmployee(int id) {
        return employees.contains(new Employee(id, "", ""));
    }
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        EmployeeDatabase db = new EmployeeDatabase();
        int n = sc.nextInt();
        for (int i = 0; i < n; i++) {
            int id = sc.nextInt();
            String name = sc.next();
            String department = sc.next();
            db.addEmployee(id, name, department);
        }
        db.displayEmployees();
        int m = sc.nextInt();
    }
}

```

```

    for (int i = 0; i < m; i++) {
        int id = sc.nextInt();
        if (db.checkEmployee(id))
            System.out.println("Employee exists");
        else
            System.out.println("Employee not found");
    }
    sc.close();
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A linguist named Meera is classifying a list of words based on their first character. She wants to store words grouped by their starting letter using a `TreeMap` so that the groups appear in sorted order of characters (i.e., 'a' to 'z'). For each letter, all words starting with that letter should be stored in the order they appear.

Implement the logic inside a class named `WordClassifier` using the `TreeMap<Character, List<String>>` collection.

##### **Input Format**

The first line of the input contains an integer `n`, representing the number of words.

The next `n` lines each contain a word.

##### **Output Format**

The first line of the output prints: "Grouped Words by Starting Letter:"

The next lines print each character key and its list of words in the format:

"letter: word1 word2 word3..."

..."



Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

dog

deer

cat

cow

camel

Output: Grouped Words by Starting Letter:

c: cat cow camel

d: dog deer

### **Answer**

```
import java.util.*;
```

```
class WordClassifier {
```

```
    public void classifyWords(List<String> words) {
```

```
        TreeMap<Character, List<String>> map = new TreeMap<>();
```

```
        for (String word : words) {
```

```
            char initial = word.charAt(0);
```

```
            if (!map.containsKey(initial)) {
```

```
                map.put(initial, new ArrayList<>());
```

```
            }
```

```
            map.get(initial).add(word);
```

```
        }
```

```
        System.out.println("Grouped Words by Starting Letter:");
```

```
        for (Map.Entry<Character, List<String>> entry : map.entrySet()) {
```

```
            System.out.print(entry.getKey() + ": ");
```

```
            for (String word : entry.getValue()) {
```

```
                System.out.print(word + " ");
```

```
            }
```

```
            System.out.println();
```

```
        }
```

```
    }
```

```
}
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
Scanner sc = new Scanner(System.in);
int n = Integer.parseInt(sc.nextLine());

List<String> words = new ArrayList<>();
for (int i = 0; i < n; i++) {
    words.add(sc.nextLine());
}

WordClassifier classifier = new WordClassifier();
classifier.classifyWords(words);
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 11

Attempt : 1  
Total Mark : 20  
Marks Obtained : 20

#### Section 1 : Project

##### 1. Problem Statement

Create a JDBC-based Hospital Management System that handles runtime input to manage patient records. The system should allow users to:

Add a new patient (patient ID, name, age, status).

Update a patient's status.

View a specific patient's record by patient ID.

Display all patient records in the database.

Exit the application.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri\_db

USER: test

PWD: test123

The patients table has already been created with the following structure:

Table Name: patients

### ***Input Format***

The first line of input consists of an integer choice, representing the operation to be performed:

(1 for Add Patient, 2 for Update Patient Status, 3 for View Patient Record, 4 for Display All Patients, 5 for Exit)

For choice 1 (Add Patient):

- The second line consists of an integer patient\_id.
- The third line consists of a string name.
- The fourth line consists of an integer age.
- The fifth line consists of a string status.

For choice 2 (Update Patient Status):

- The second line consists of an integer patient\_id.
- The third line consists of a string new\_status.

For choice 3 (View Patient Record):

- The second line consists of an integer patient\_id.

For choice 4 (Display All Patients):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

### **Output Format**

For choice 1 (Add Patient):

- Print "Patient added successfully" if the patient was added.
- Print "Failed to add patient." if the insertion failed.

For choice 2 (Update Patient Status):

- Print "Patient status updated successfully" if the update was successful.
- Print "Patient not found." if the specified patient ID does not exist.

For choice 3 (View Patient Record):

- Display the patient details in the format:
- ID: [patient\_id] | Name: [name] | Age: [age] | Status: [status]
- Print "Patient not found." if the specified patient ID does not exist.

For choice 4 (Display All Patients):

- Display each patient on a new line in the format:
- ID | Name | Age | Status
- If no records are available, print nothing (or handle it with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Hospital Management System."

For invalid input:

- Print "Invalid choice. Please try again."

### **Sample Test Case**

Input: 1

101

John Doe

45

Admitted

4

5

Output: Patient added successfully

ID | Name | Age | Status

101 | John Doe | 45 | Admitted

Exiting Hospital Management System.

### **Answer**

```
import java.sql.*;
import java.util.Scanner;

class HospitalManagementSystem {
    public static void main(String[] args) {
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://
localhost/ri_db", "test", "test123");
        Scanner scanner = new Scanner(System.in)) {

            boolean running = true;

            while (running) {

                int choice = scanner.nextInt();

                switch (choice) {
                    case 1:
                        addPatient(conn, scanner);
                        break;
                    case 2:
                        updatePatientStatus(conn, scanner);
                        break;
                    case 3:
                        viewPatientRecord(conn, scanner);
                        break;
                    case 4:
                        displayAllPatients(conn);
                        break;
                    case 5:
                        System.out.println("Exiting Hospital Management System.");
                        running = false;
                        break;
                    default:
                        System.out.println("Invalid choice. Please try again.");
                }
            }
        }
    }
}
```

```

    }
} catch (SQLException e) {
    e.printStackTrace();
}
}

```

```

public static void addPatient(Connection conn, Scanner scanner) {
    int patientId = scanner.nextInt();
    scanner.nextLine(); // Consume newline

```

```

    String name = scanner.nextLine();

```

```

    int age = scanner.nextInt();

```

```

    scanner.nextLine(); // Consume newline
    String status = scanner.nextLine();

```

```

    String insertQuery = "INSERT INTO patients (patient_id, name, age, status)
VALUES (?, ?, ?, ?)";

```

```

    try (PreparedStatement stmt = conn.prepareStatement(insertQuery)) {
        stmt.setInt(1, patientId);
        stmt.setString(2, name);
        stmt.setInt(3, age);
        stmt.setString(4, status);

```

```

        int rowsInserted = stmt.executeUpdate();
        System.out.println(rowsInserted > 0 ? "Patient added successfully" :
"Failed to add patient.");
    } catch (SQLException e) {
        System.out.println("Error adding patient: " + e.getMessage());
    }
}

```

```

public static void updatePatientStatus(Connection conn, Scanner scanner) {
    int patientId = scanner.nextInt();
    scanner.nextLine(); // Consume newline

```

```

    String newStatus = scanner.nextLine();

```

```

    String updateQuery = "UPDATE patients SET status = ? WHERE patient_id
= ?";

```

```

try (PreparedStatement stmt = conn.prepareStatement(updateQuery)) {
    stmt.setString(1, newStatus);
    stmt.setInt(2, patientId);

    int rowsUpdated = stmt.executeUpdate();
    System.out.println(rowsUpdated > 0 ? "Patient status updated
successfully" : "Patient not found.");
} catch (SQLException e) {
    System.out.println("Error updating patient status: " + e.getMessage());
}
}

```

```

public static void viewPatientRecord(Connection conn, Scanner scanner) {
    int patientId = scanner.nextInt();

```

```

    String selectQuery = "SELECT * FROM patients WHERE patient_id = ?";
    try (PreparedStatement stmt = conn.prepareStatement(selectQuery)) {
        stmt.setInt(1, patientId);

```

```

        ResultSet rs = stmt.executeQuery();
        if (rs.next()) {
            System.out.printf("ID: %d | Name: %s | Age: %d | Status: %s%n",
                rs.getInt("patient_id"),
                rs.getString("name"),
                rs.getInt("age"),
                rs.getString("status"));

```

```

        } else {
            System.out.println("Patient not found.");
        }
    } catch (SQLException e) {
        System.out.println("Error retrieving patient record: " + e.getMessage());
    }
}

```

```

public static void displayAllPatients(Connection conn) {
    String displayQuery = "SELECT * FROM patients ORDER BY patient_id";
    try (Statement stmt = conn.createStatement();
        ResultSet rs = stmt.executeQuery(displayQuery)) {

```

```

        System.out.println("ID | Name | Age | Status");
        while (rs.next()) {
            System.out.printf("%d | %s | %d | %s%n",

```



```

        rs.getInt("patient_id"),
        rs.getString("name"),
        rs.getInt("age"),
        rs.getString("status"));
    }
} catch (SQLException e) {
    System.out.println("Error displaying patients: " + e.getMessage());
}
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

In ABC Corporation, employee records are stored in a database.

To efficiently manage employee details using Java and JDBC, you are tasked with building an Employee Management System that supports the following functionalities:

Adding a new employee

Updating an employee's salary

Viewing an employee's details

Displaying all employees

You are given two files:

File 1: Employee.java (POJO Class)

This class represents the Employee entity.

An Employee contains the following details:

Field Description

employeeId Unique Employee ID (Integer)

name Employee Name (String)

department Employee Department (String)

salary Employee Salary (Double)

Students must write code in the marked area:

```
class Employee {  
    private int employeeId;  
    private String name;  
    private String department;  
    private double salary;  
    public Employee() {}  
    public Employee(int employeeId, String name, String department, double  
salary) {  
        // write your code here  
    }  
  
    // Include getters and setters  
}
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: EmployeeDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class EmployeeDAO {  
    public void addEmployee(Connection conn, Employee employee) throws
```

```
SQLException {
```

```
    // write your code here
```

```
}
```

```
    public void updateSalary(Connection conn, int employeeId, double  
newSalary) throws SQLException {
```

```
        // write your code here
```

```
}
```

```
    public void deleteEmployee(Connection conn, int employeeId) throws  
SQLException {
```

```
        // write your code here
```

```
}
```

```
    public Employee viewEmployeeRecord(Connection conn, int employeeId)  
throws SQLException {
```

```
        // write your code here
```

```
}
```

```
    public List<Employee> displayAllEmployees(Connection conn) throws  
SQLException {
```

```
        // write your code here
```

```
}
```

```
    private Employee mapToEmployee(ResultSet rs) throws SQLException {
```

```
        return new Employee(
```

```
            // write your code here
```

```
        );
```

```
}
```

```
}
```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to Employee objects using mapToEmployee().

Return a List<Employee> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri\_dbUsername: testPassword: test123

The employees table has already been created with the following structure:

### ***Input Format***

The first line of input consists of an integer choice, representing the operation to be performed:

(1 for Add Employee, 2 for Update Salary, 3 for View Employee Record, 4 for Display All Employees, 5 for Exit)

For choice 1 (Add Employee):

1. The second line consists of an integer employee\_id.
2. The third line consists of a string name.
3. The fourth line consists of a string department.
4. The fifth line consists of a double salary (must be at least 30000).

For choice 2 (Update Salary):

1. The second line consists of an integer employee\_id.
2. The third line consists of a double new\_salary (must be at least 30000).

For choice 3 (View Employee Record):

1. The second line consists of an integer employee\_id.

For choice 4 (Display All Employees).

For choice 5 (Exit).

### **Output Format**

For choice 1 (Add Employee),

1. Print "Employee added successfully" if the employee was added.

For choice 2 (Update Salary),

1. Print "Salary updated successfully" if the salary update was successful.
2. Print "Employee not found." if the specified employee ID does not exist.
3. Print "Salary must be at least 30000." if the provided salary is below the minimum.

For choice 3 (View Employee Record),

1. Display the employee details in the format:
2. ID: [employee\_id] | Name: [name] | Department: [department] | Salary: [salary]
3. Print "Employee not found." if the specified employee ID does not exist.

For choice 4 (Display All Employees),

1. Display each employee on a new line in the format:
2. ID | Name | Department | Salary

For choice 5 (Exit),

1. Print "Exiting Employee Management System."

For invalid input:

1. Print "Invalid choice. Please try again."

### **Sample Test Case**

Input: 1

101

Alice Johnson

Engineering

31000.75

4

6

5

Output: Employee added successfully

ID | Name | Department | Salary

101 | Alice Johnson | Engineering | 31000.75

Invalid choice. Please try again.

Exiting Employee Management System.

### **Answer**

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class Employee {  
    private int employeeId;  
    private String name;  
    private String department;  
    private double salary;
```

```
    // Constructor
```

```
    public Employee(int employeeId, String name, String department, double  
salary) {  
        this.employeeId = employeeId;  
        this.name = name;  
        this.department = department;  
        this.salary = salary;  
    }
```

```
    // Getters and Setters
```

```
    public int getEmployeeId() { return employeeId; }
```

```

    public void setEmployeeId(int employeeId) { this.employeeId = employeeId; }

    public String getName() { return name; }
    public void setName(String name) { this.name = name; }

    public String getDepartment() { return department; }
    public void setDepartment(String department) { this.department =
department; }

    public double getSalary() { return salary; }
    public void setSalary(double salary) { this.salary = salary; }
}

```

```

class EmployeeManagementSystem {

    // Add Employee
    public static void addEmployee(Connection conn, Scanner scanner) {
        int employeeId = scanner.nextInt();
        scanner.nextLine(); // Consume newline
        String name = scanner.nextLine();
        String department = scanner.nextLine();
        double salary = scanner.nextDouble();

        if (salary < 30000) {
            System.out.println("Salary must be at least 30000.");
            return;
        }

        // Create an Employee POJO object
        Employee employee = new Employee(employeeId, name, department,
salary);

        String insertQuery = "INSERT INTO employees (employee_id, name,
department, salary) VALUES (?, ?, ?, ?)";
        try (PreparedStatement stmt = conn.prepareStatement(insertQuery)) {
            stmt.setInt(1, employee.getEmployeeId());
            stmt.setString(2, employee.getName());
            stmt.setString(3, employee.getDepartment());
            stmt.setDouble(4, employee.getSalary());

            int rowsInserted = stmt.executeUpdate();

```

```
        System.out.println(rowsInserted > 0 ? "Employee added successfully" :  
"Failed to add employee.");  
    } catch (SQLException e) {  
        System.out.println("Error adding employee: " + e.getMessage());  
    }  
}
```

// Update Salary

```
public static void updateSalary(Connection conn, Scanner scanner) {  
    int employeeId = scanner.nextInt();  
    double newSalary = scanner.nextDouble();
```

```
    if (newSalary < 30000) {  
        System.out.println("Salary must be at least 30000.");  
        return;  
    }
```

```
    String updateQuery = "UPDATE employees SET salary = ? WHERE  
employee_id = ?";  
    try (PreparedStatement stmt = conn.prepareStatement(updateQuery)) {  
        stmt.setDouble(1, newSalary);  
        stmt.setInt(2, employeeId);
```

```
        int rowsUpdated = stmt.executeUpdate();  
        System.out.println(rowsUpdated > 0 ? "Salary updated successfully" :  
"Employee not found.");  
    } catch (SQLException e) {  
        System.out.println("Error updating salary: " + e.getMessage());  
    }  
}
```

// View Employee Record

```
public static void viewEmployeeRecord(Connection conn, Scanner scanner) {  
    int employeeId = scanner.nextInt();  
    String selectQuery = "SELECT * FROM employees WHERE employee_id = ?";
```

```
    try (PreparedStatement stmt = conn.prepareStatement(selectQuery)) {  
        stmt.setInt(1, employeeId);  
        ResultSet rs = stmt.executeQuery();
```

```
        if (rs.next()) {  
            Employee employee = new Employee(  

```



```

        rs.getInt("employee_id"),
        rs.getString("name"),
        rs.getString("department"),
        rs.getDouble("salary")
    );
    System.out.printf("ID: %d | Name: %s | Department: %s | Salary: %.2f%n",
        employee.getEmployeeId(),
        employee.getName(),
        employee.getDepartment(),
        employee.getSalary());
    } else {
        System.out.println("Employee not found.");
    }
} catch (SQLException e) {
    System.out.println("Error retrieving employee record: " + e.getMessage());
}
}

```

// Display All Employees

```

public static void displayAllEmployees(Connection conn) {
    String displayQuery = "SELECT * FROM employees";

```

```

    try (Statement stmt = conn.createStatement();
        ResultSet rs = stmt.executeQuery(displayQuery)) {

```

```

        System.out.println("ID | Name | Department | Salary");

```

```

        while (rs.next()) {

```

```

            Employee employee = new Employee(

```

```

                rs.getInt("employee_id"),

```

```

                rs.getString("name"),

```

```

                rs.getString("department"),

```

```

                rs.getDouble("salary")

```

```

            );

```

```

            System.out.printf("%d | %s | %s | %.2f%n",

```

```

                employee.getEmployeeId(),

```

```

                employee.getName(),

```

```

                employee.getDepartment(),

```

```

                employee.getSalary());

```

```

        }

```

```

    } catch (SQLException e) {

```

```

        System.out.println("Error displaying employees: " + e.getMessage());

```

```

    }

```

```

    }
    public static void main(String[] args) {
        String url = "jdbc:mysql://localhost/ri_db";
        String username = "test";
        String password = "test123";

        try (Connection conn = DriverManager.getConnection(url, username,
password);
            Scanner scanner = new Scanner(System.in)) {

            int choice;
            do {
                choice = scanner.nextInt();

                switch (choice) {
                    case 1 -> addEmployee(conn, scanner);
                    case 2 -> updateSalary(conn, scanner);
                    case 3 -> viewEmployeeRecord(conn, scanner);
                    case 4 -> displayAllEmployees(conn);
                    case 5 -> System.out.println("Exiting Employee Management
System.");
                    default -> System.out.println("Invalid choice. Please try again.");
                }

            } while (choice != 5);

        } catch (SQLException e) {
            System.out.println("Database Error: " + e.getMessage());
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_Week 12\_Java\_Lamba Expressions\_MCQ

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : MCQ

1. Can a lambda expression have more than one parameter?

**Answer**

Yes, it can have multiple parameters

**Status : Correct**

**Marks : 1/1**

2. Which of the following is a valid lambda expression in Java?

**Answer**

All of the mentioned options

**Status : Correct**

**Marks : 1/1**

3. Which of the following interfaces is NOT a functional interface in Java?

**Answer**

Iterable

**Status : Correct**

**Marks : 1/1**

4. What is the syntax for a basic lambda expression in Java?

**Answer**

(parameters) -> expression

**Status : Correct**

**Marks : 1/1**

5. Which functional interface is commonly used with lambda expressions in Java?

**Answer**

Runnable

**Status : Correct**

**Marks : 1/1**

6. Which functional interface in Java takes two arguments and returns a result?

**Answer**

BiFunction

**Status : Correct**

**Marks : 1/1**

7. Can a lambda expression in Java have a body with multiple statements?

**Answer**

Yes, if the statements are enclosed in curly braces

**Status : Correct**

**Marks : 1/1**

8. What is the return type of a lambda expression in Java?

**Answer**

The return type is inferred from the context

**Status :** Correct

**Marks :** 1/1

9. Can a lambda expression in Java have a body with multiple statements?

**Answer**

Yes, if the statements are enclosed in curly braces

**Status :** Correct

**Marks :** 1/1

10. What is a lambda expression in Java?

**Answer**

A way to define anonymous methods

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Sabrina is working on a project that involves analyzing a set of numbers. In her exploration, she encounters scenarios where extracting even numbers and finding their sum is essential.

Create a program that calculates the sum of even numbers from a given array of integers using a lambda expression.

##### ***Input Format***

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, representing the elements of the array.

##### ***Output Format***

The output prints the sum of the even integers from the array.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

29 37 45

Output: 0

### **Answer**

```
// You are using Jav
import java.util.*;

interface even{
    void sum_(int[] arr);
}

class Main{
    public static void main(String[] args){
        Scanner ss=new Scanner(System.in);
        int n=ss.nextInt();
        int[] arr=new int[n];
        for(int i=0;i<n;i++){
            arr[i]=ss.nextInt();
        }

        even e = (arr1) ->{
            int total=0;
            for(int j=0;j<n;j++){
                if(arr1[j]%2==0){
                    total+=arr1[j];
                }
            }
            System.out.println(total);
        };
        e.sum_(arr);
    }
}
```

Status : Correct

Marks : 10/10



# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Alex is learning about Java's functional interfaces and lambda expressions.

He wants to write a simple program that prints the square of each number in an array using a predefined functional interface.

Help Alex complete this task using the Consumer functional interface.

##### ***Input Format***

- The first line contains an integer N, the number of elements in the array.
- The second line contains N space-separated integers.

##### ***Output Format***

- Print the squares of all elements in the array, separated by a space.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4

1 2 3 4

Output: 1 4 9 16

### **Answer**

// You are using Java

```
import java.util.*;
```

```
interface square{
```

```
    void calc(int []arr);
```

```
}
```

```
public class Main{
```

```
    public static void main(String []args){
```

```
        Scanner sc =new Scanner (System.in);
```

```
        int n=sc.nextInt();
```

```
        int[] arr=new int[n];
```

```
        for(int i=0;i<n;i++){
```

```
            arr[i]=sc.nextInt();
```

```
        }
```

```
        square s=(arr_func) ->{ // here separate func sp diff name
```

```
            for(int j=0;j<n;j++){
```

```
                int m=(int) Math.pow(arr_func[j],2);
```

```
                System.out.print(m + " ");
```

```
            }
```

```
        };
```

```
        s.calc(arr); //function calling use same name used
```

```
    }
```

```
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In the mystical realm of programming, there exists a magical incantation to reveal hidden words.

Elara, the skilled enchantress, wishes to summon a word using her spell and then reverse its characters to uncover its enchanted reflection.

Write a program that uses the predefined functional interface `Supplier<String>` and a lambda expression to:

Supply (generate) a string, and

Display its reversed form.

**Input Format**

No input is required from the user.

The string must be supplied internally using a Supplier<String>.

### **Output Format**

Print the reversed version of the supplied string.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Wizard!!

Output: !!draziW

### **Answer**

```
// You are using Java
import java.util.*;
```

```
interface word{
    void rev();
}
class Main{
    public static void main(String [] args){
        Scanner ss = new Scanner(System.in);
        String normal=ss.next();
        word r = () ->{
            for(int i=0;i<normal.length();i++){
                //String b="";
                System.out.print("'" + normal.charAt(normal.length()-i-1) );
            }
        };
        r.rev();
    }
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 12\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Abi is working on a text analysis project where she needs to categorize words based on their length.

Words that have three or fewer characters are considered "Short", while words with more than three characters are classified as "Long."

Write a Java program that takes a sentence as input, analyzes each word, and prints a list showing whether each word is "Short" or "Long."

Use the predefined functional interface `Function<String, String>` along with a lambda expression for categorization.

##### ***Input Format***

A single line containing a sentence (words separated by spaces).

### **Output Format**

- A single line with each word categorized as "Short" or "Long", separated by spaces.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: I love my cat

Output: Short Long Short Short

### **Answer**

```
// You are
import java.util.*;

interface function{
    void lenchecker(String []words);
}
class Main{
    public static void main(String[] args){
        Scanner ss=new Scanner(System.in);
        String a=ss.nextLine();
        String[] words=a.split(" ");
        function f = (alt_words) ->{
            for(int i=0;i<alt_words.length;i++){
                String b=alt_words[i];
                if(b.length()<=3)
                    System.out.print("Short ");
                else
                    System.out.print("Long ");
            }
        };
        f.lenchecker(words);
    }
}
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_Week 12\_Java\_Lamba Expressions\_PAH

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : COD

##### 1. Problem Statement

Emily, an analyst at a data processing firm, is tasked with cleaning up datasets to remove duplicate values from lists of integers.

Create a Java program that allows Emily to input a series of integers, with the program then utilizing a lambda expression to efficiently remove any duplicates.

##### ***Input Format***

The first line of input consists of an integer N, representing the size of the array.

The second line consists of N space-separated integers, each denoting an array element.

##### ***Output Format***

The output prints the array elements after removing the duplicates inside the square bracket separated by a comma and space.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 15

1 2 3 4 3 2 1 2 3 4 4 4 5 5 6

Output: [1, 2, 3, 4, 5, 6]

### **Answer**

```
// You are using Java
import java.util.*;
```

```
class Main{
    public static void main(String[] args){
        Scanner sc =new Scanner(System.in);
        int n=sc.nextInt();
        //List<Integer> nums = new ArrayList<>();
        Set<Integer> numsSet = new LinkedHashSet<>();
        for(int i=0;i<n;i++){
            numsSet.add(sc.nextInt());
        }
        List<Integer> numsList = new ArrayList<>(numsSet);
        System.out.println(numsList);
    }
}
```

**Status :** Correct

**Marks : 10/10**

## **2. Problem Statement**

Aditya is developing a reading app that recommends books to users based on a predefined list.



Each time a user opens the app, it should supply the next book title in the list, one at a time, using a lambda expression and the Supplier functional interface.

When all books have been recommended, the list should start again from the beginning.

### ***Input Format***

The first line contains an integer  $n$  — the total number of available book titles.

The next  $n$  lines each contain a book title (a string).

The next line contains an integer  $m$  — the number of times users open the app (i.e., the number of recommendations to be made).

### ***Output Format***

Print the supplied book title for each recommendation, one per line.

If  $m > n$ , repeat the list from the start.

### ***Sample Test Case***

Input: 3

The Alchemist

Atomic Habits

Ikigai

5

Output: The Alchemist

Atomic Habits

Ikigai

The Alchemist

Atomic Habits

### ***Answer***

```
// You are using Java
```

```
import java.util.*;
```

```
interface bookSupplier{  
    void supply(List<String> books);  
}
```

```
class Main{
```

```

public static void main(String[] args){
    Scanner sc=new Scanner(System.in);
    int n=sc.nextInt();
    sc.nextLine();
    List<String> books = new ArrayList<>();
    for(int i=0;i<n;i++){
        books.add(sc.nextLine().trim());
    }
    int m=sc.nextInt();
    bookSupplier obj = (books_) ->{
        for(int j=0;j<m;j++){
            System.out.println(books_.get(j%n)); // ***
        }
    };
    obj.supply(books);
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Rishi is working as an HR analyst in a software company. He wants to filter a list of employees based on their salary using modern Java techniques. He has a list of employee names and salaries and wants to use lambda expressions to filter those who earn more than a specific threshold.

Implement a program using lambda expressions and functional interfaces to print the names of employees whose salary is greater than or equal to 50,000.

#### **Input Format**

The first line of input consists of an integer n, representing the number of employees.

The next n lines. Each line contains a String (employee name) and an int (salary).

#### **Output Format**

The output prints the names of employees whose salary is greater than or equal to 50000, each on a new line.

If no employee found with salary greater than 50000, print: No employee found with salary  $\geq$  50000

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4  
Amit 45000  
Sneha 50000  
Ravi 60000  
Priya 30000  
Output: Sneha  
Ravi

### **Answer**

```
import java.util.*;
import java.util.function.Predicate;
import java.util.stream.Collectors;

class Employee {
    String name;
    int salary;

    Employee(String name, int salary) {
        this.name = name;
        this.salary = salary;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        List<Employee> employees = new ArrayList<>();

        for (int i = 0; i < n; i++) {
            String name = sc.next();
            int salary = sc.nextInt();
```

```

    employees.add(new Employee(name, salary));
}

Predicate<Employee> highSalary = e -> e.salary >= 50000;

List<String> result = employees.stream()
    .filter(highSalary)
    .map(e -> e.name)
    .collect(Collectors.toList());

if (result.isEmpty()) {
    System.out.println("No employee found with salary >= 50000");
} else {
    result.forEach(System.out::println);
}
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Sneha is developing a feature for an e-commerce application that helps display product details after applying a seasonal discount.

She decides to use lambda expressions with the Consumer functional interface to print each product's name, original price, and discounted price neatly.

The program should:

Accept a list of product names and their prices. Apply a 15% discount on all products. Use a Consumer lambda expression to display the details in a formatted manner.

#### **Input Format**

The first line of input consists of an integer  $n$ , representing the number of products.

The next  $n$  lines each contain a String (product name) and a double (price)

separated by a space.

### **Output Format**

For each product, print the details in the format:

Product: <name>, Original Price: <price>, Discounted Price: <discounted price>

If there are no products, print:

No products available

### **Sample Test Case**

Input: 1

Phone 60000

Output: Product: Phone, Original Price: 60000.0, Discounted Price: 51000.0

### **Answer**

```
import java.util.ArrayList;
import java.util.Scanner;
import java.util.function.Consumer;
```

```
class Product {
    String name;
    double price;

    Product(String name, double price) {
        this.name = name;
        this.price = price;
    }

    double getDiscountedPrice() {
        return price * 0.85; // 15% discount
    }
}
```

```
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());

        ArrayList<Product> products = new ArrayList<>();
```

```

    for (int i = 0; i < n; i++) {
        String line = sc.nextLine();
        String[] parts = line.split(" ", 2);
        String name = parts[0];
        double price = Double.parseDouble(parts[1]);
        products.add(new Product(name, price));
    }

    // Lambda expression using Consumer
    Consumer<Product> display = p ->
        System.out.printf("Product: %s, Original Price: %.1f, Discounted Price: %.1f
%n",
            p.name, p.price, p.getDiscountedPrice());

    if (products.isEmpty()) {
        System.out.println("No products available");
    } else {
        products.forEach(display);
    }

    sc.close();
}
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: KRITHESHWARAN R  
Email: 241901049@rajalakshmi.edu.in  
Roll no: 241901049  
Phone: 9843565002  
Branch: REC  
Department: CSE (CS) - Section 2  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_Week 12\_Java\_Lambda Expressions\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### **Section 1 : Coding**

##### **1. Problem Statement**

###### **Problem Statement**

Sophia, a data analyst, is studying experimental results collected from various lab sensors. Each sensor provides a list of numeric readings, and Sophia wants to calculate the average of these readings to analyze consistency.

She decides to use lambda expressions and the Function functional interface to compute the average of all the recorded values efficiently.

###### **Your Task**

Write a Java program that:

Reads the total number of measurements. Reads all the measurement values as doubles. Uses a `Function<double[], Double>` lambda expression

to calculate the average value. Displays the final average, formatted to two decimal places.

### ***Input Format***

The first line of input consists of an integer N, representing the number of measurements.

The second line contains N space-separated double values.

### ***Output Format***

Print the average of the entered values, rounded to two decimal places.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 6

2.2 1.2 5.4 4.6 2.9 55.7

Output: 12.00

### ***Answer***

// You are using Java

import java.util.\*;

```
interface findavg{
    double avg(List<Double> values);
}
class Main{
    public static void main(String[] args){
        Scanner ss=new Scanner(System.in);
        int n=ss.nextInt();
        List<Double> values = new ArrayList<>();
        for(int i=0;i<n;i++){
            values.add(ss.nextDouble());
        }
    }
}
```

```
findavg obj = (lam_values)->{
    double total=0;
    for(int j=0;j<n;j++){
```



```
        total+=lam_values.get(j);
    }
    return total/n;
};
System.out.printf("%.2f",obj.avg(values));

}
}
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Nethra is a researcher working on a project that involves analyzing experimental data. As part of her analysis, she needs to determine whether a given word is a palindrome or not.

Create a Java program that allows Nethra to input a word, and then check and display whether the entered word is a palindrome. Use lambda expressions to perform the palindrome check.

### **Input Format**

The first line of input consists of a word.

### **Output Format**

The output prints whether the given word is a palindrome or not in the following format:

"<input> is palindrome" or "<input> is not palindrome".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: malayalam

Output: malayalam is palindrome

**Answer**

```
// You are using Java
import java.util.*;

interface palindrome{
    boolean checkpal();
}

class Main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        String a=sc.next();

        palindrome obj = () ->{
            boolean pal=false;
            for(int i=0;i<a.length()/2;i++){
                pal=false;
                if(a.charAt(i) == (a.charAt(a.length()-i-1)) ){
                    pal=true;
                }
                else
                    break;
            }
            return pal;
        };
        if(obj.checkpal())
            System.out.printf("%s is palindrome",a);
        else
            System.out.printf("%s is not palindrome",a);
    }
}
```

**Status : Correct**

**Marks : 10/10**

### 3. Problem Statement

Riya is developing a college admission system that assigns unique roll numbers to each newly admitted student.

Each roll number should follow this fixed format:

<DEPT>-<YEAR>-<4-digit-sequence>

where:

<DEPT> is the department code (in uppercase, e.g., CSE, ECE, MECH). <YEAR> is the admission year (e.g., 2025). <4-digit-sequence> starts from a given number and increases sequentially for each student. Write a Java program using a Supplier<String> lambda to generate and print the roll numbers for n students.

### **Input Format**

First line: integer n — number of roll numbers to generate

Second line: string DEPT — department code (uppercase letters only)

Third line: integer YEAR — admission year

Fourth line: integer start — starting sequence number ( $0 \leq \text{start} \leq 9999$ )

### **Output Format**

Print n roll numbers, one per line, in the required format

Sequence must be zero-padded to 4 digits

If sequence exceeds 9999, wrap around to 0000

### **Sample Test Case**

Input: 5

CSE

2025

98

Output: CSE-2025-0098

CSE-2025-0099

CSE-2025-0100

CSE-2025-0101

CSE-2025-0102

### **Answer**

```
import java.util.*;  
import java.util.function.Supplier;
```

```

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        String dept = sc.next();
        int year = sc.nextInt();
        int start = sc.nextInt();

        final int[] current = { start };

        Supplier<String> rollNumberSupplier = () -> {
            String roll = String.format("%s-%d-%04d", dept, year, current[0]);
            current[0] = (current[0] + 1) % 10000;
            return roll;
        };

        for (int i = 0; i < n; i++) {
            System.out.println(rollNumberSupplier.get());
        }

        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A company named TechNova is collecting feedback from its customers. Each customer gives a feedback score (an integer between 1 and 10) along with their name.

The company wants to:

Display each customer's name along with their feedback in a formatted way using a lambda expression and a Consumer functional interface. After displaying all feedbacks, calculate and display the average feedback score. You need to implement this functionality using Java lambda expressions and streams, emphasizing the Consumer interface for

displaying formatted output.

### ***Input Format***

The first line of input contains an integer n, representing the number of customers.

The next n lines each contain a String (customer name) followed by an int (feedback score).

### ***Output Format***

- Each line prints a customer's name and feedback in the format:
- Customer: <name>, Feedback Score: <score>

- After all customers are displayed, print the average feedback as:
- Average Feedback: <average\_value>

(Average should be displayed up to two decimal places.)

### ***Sample Test Case***

Input: 3

Ravi 7

Ananya 9

Kiran 8

Output: Customer: Ravi, Feedback Score: 7

Customer: Ananya, Feedback Score: 9

Customer: Kiran, Feedback Score: 8

Average Feedback: 8.00

### ***Answer***

```
import java.util.*;  
import java.util.function.Consumer;
```

```
class Customer {  
    String name;  
    int feedback;
```

```

Customer(String name, int feedback) {
    this.name = name;
    this.feedback = feedback;
}
}

class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        List<Customer> customers = new ArrayList<>();

        for (int i = 0; i < n; i++) {
            String name = sc.next();
            int feedback = sc.nextInt();
            customers.add(new Customer(name, feedback));
        }

        Consumer<Customer> displayFeedback = c ->
            System.out.println("Customer: " + c.name + ", Feedback Score: " +
c.feedback);

        customers.forEach(displayFeedback);

        double avgFeedback = customers.stream()
            .mapToInt(c -> c.feedback)
            .average()
            .orElse(0.0);

        System.out.printf("Average Feedback: %.2f", avgFeedback);
        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10