RAJALAKSHMI ENGINEERING COLLEGE

V R Krithika Sree 250701371-2025-CSE

V2

Started on	Wednesday, 16 September 2026, 8:58 AM
State	Finished
Completed on	Wednesday, 16 September 2026, 9:06 AM
Time taken	7 mins 43 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
#include<stdlib.h>

int compare(const void*a,const void*b){
    return *(int *)a-*(int*)b;
}

int compareDescending(const void*a,const void*b){
    return *(int *)b-*(int*)a;
}

int main(){
    int n;
    scanf("%d",&n);
    int arr1[n],arr2[n];
    for(int i=0;i<n;i++){
        scanf("%d",&arr1[i]);
    }
    for(int i=0;i<n;i++){
        scanf("%d",&arr2[i]);
    }

    qsort(arr1,n,sizeof(int),compare);
    qsort(arr2,n,sizeof(int),compareDescending);

    int total=0;
    for(int i=0;i<n;i++){
        total+=arr1[i]*arr2[i];
    }
    printf("%d",total);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course