Safari File Edit View History Bookmarks Window Help Sun May 3 11:36 PM

gemini.google.com

Gemini

C++ Random Excuse Generator Program

New chat

My stuff

Gems

Chats

C++ Random Excuse Generator Progr...

C++ AI Roast Generator Code

C++ AI Roast Generator Tutorial

Movie Ticket Booking System Implem...

AI/ML vs. Cybersecurity Startup Paths

SolidWorks Engineering Graphics Pra...

Debugging Array Parity Pathfinding C...

Exam Study Videos: Electromagnetics...

Newme Offline Sale Information

Settings & help

Write a beginner-friendly C++ console program that generates random excuses for students.
The program should:
- Ask for the student's name
- Store at least 10 excuse templates in a vector...

Building a random excuse generator is a classic way to practice string manipulation and randomization in C++. This program uses a `std::vector` to store the templates and the `<random>` library to pick one fairly.

The Excuse Generator Code

C++

```
#include <iostream>
#include <string>
#include <vector>
#include <random> // For better random number generation
```

Enter a prompt for Gemini

Tools

Fast

Your The NorthCap University chats aren't used to improve our models. Gemini is AI and can make mistakes. Your privacy & Gemini

Safari File Edit View History Bookmarks Window Help Sun May 3 11:39 PM

gemini.google.com

Gemini

C++ Random Excuse Generator Program

New chat

My stuff

Gems

Chats

C++ Random Excuse Generator Progr...

C++ AI Roast Generator Code

C++ AI Roast Generator Tutorial

Movie Ticket Booking System Implem...

AI/ML vs. Cybersecurity Startup Paths

SolidWorks Engineering Graphics Pra...

Debugging Array Parity Pathfinding C...

Exam Study Videos: Electromagnetics...

Newme Offline Sale Information

Settings & help

Improve my C44 excuse generator by creating more creative and funny excuse templates.
Give me at least 10 unique excuses using (name) as a placeholder.
Make them sound realistic but humorous.

To level up your generator, the best excuses are the ones that start off sounding like a normal student problem but then take a sharp turn into the absurd.

Here are 10 creative templates that balance "academic struggle" with "total chaos." You can copy and paste these directly into your `std::vector`.

---

10 Creative & Humorous Excuses

- " (name) 's internet became self-aware and refused to load anything but cat videos."
- "A localized gravitational anomaly only affected (name) 's alarm clock this morning."
- " (name) successfully finished the essay, but it was written in invisible ink that only appears under moonlight."

Enter a prompt for Gemini

Tools

Fast

Your The NorthCap University chats aren't used to improve our models. Gemini is AI and can make mistakes. Your privacy & Gemini

Safari File Edit View History Bookmarks Window Help Sun May 3 11:40 PM
gemini.google.com

New chat
My stuff
Gems
Chats
C++ Random Excuse Generator Progr...
C++ AI Roast Generator Code
C++ AI Roast Generator Tutorial
Movie Ticket Booking System Implem...
AI/ML vs. Cybersecurity Startup Paths
SolidWorks Engineering Graphics Pra...
Debugging Array Parity Pathfinding C...
Exam Study Videos: Electromagnetics...
Newme Offline Sale Information
Settings & help

Please fix the issue so all occurrences of (name) are replaced with the user's input.
Explain what was wrong and show the corrected code.

The issue in the previous version was that `std::string::replace` only executes **once**. If a template had "(name)" written twice, the program would find the first one, swap it, and then stop, leaving the second one as literal text.

To fix this, we use a `while` **loop**. We tell the computer: "Keep looking for '(name)'. As long as you keep finding it, keep replacing it."

The Logic Gap

In the old code, `if (pos != std::string::npos)` was a one-time check. By changing `if` to `while`, we ensure the program scans the entire string until no more matches exist.

The Corrected Code

C++

Enter a prompt for Gemini
Tools
Fast
Your The NorthCap University chats aren't used to improve our models. Gemini is AI and can make mistakes. Your privacy & Gemini

Safari File Edit View History Bookmarks Window Help Sun May 3 11:38 PM
gemini.google.com

New chat
My stuff
Gems
Chats
C++ Random Excuse Generator Progr...
C++ AI Roast Generator Code
C++ AI Roast Generator Tutorial
Movie Ticket Booking System Implem...
AI/ML vs. Cybersecurity Startup Paths
SolidWorks Engineering Graphics Pra...
Debugging Array Parity Pathfinding C...
Exam Study Videos: Electromagnetics...
Newme Offline Sale Information
Settings & help

why is this happening nd how can I fix it so output is different each time ? explain simply nd correct the code

The reason your code might have been outputting the same "random" excuse every time is because computers are actually quite bad at being random. They follow a mathematical formula to generate numbers. If you don't give that formula a different starting point (called a **seed**), it will produce the exact same sequence of "random" numbers every time you run the program.

Why it happens: The "Seed" Problem

Imagine a book filled with millions of random numbers. If you always start reading from **Page 1, Line 1**, you will always get the same numbers in the same order.

To fix this, we use the **current time** (which is always changing) as a "seed." This tells the computer: "Start reading the random number book from a different page every time."

The Corrected, Simplified Code

Enter a prompt for Gemini
Tools
Fast
Your The NorthCap University chats aren't used to improve our models. Gemini is AI and can make mistakes. Your privacy & Gemini

c lab

EXPLORER

C LAB
- .vscode
- output
- rrr
  - output
  - rr1
- ttt.c
- feb.c
- feb10class.cpp
- func.cpp
- idk.c
- me
- new
- new.c
- p2
- p2.c
- pandey.c
- penguin.c
- pls.c
- rectangle.cpp
- result.cpp

OUTLINE

TIMELINE

pandey.c | pls.c | func.cpp | result.cpp | feb.c

func.cpp > main()

```cpp
        "{name} couldn't finish because the system froze unexpectedly.",
        "{name} tried to complete the assignment, but the internet was too slow.",
        "{name} lost the homework when the computer crashed.",
        "{name} accidentally saved the file in the wrong format.",
        "{name} was about to submit when the website stopped responding."
    };

    // Seed random number generator
    srand(time(0));

    // Generate random index
    int randomIndex = rand() % excuses.size();

    string excuse = excuses[randomIndex];

    // Replace {name} with actual input
    size_t pos = excuse.find("{name}");
    while (pos != string::npos) {
        excuse.replace(pos, 6, name);
        pos = excuse.find("{name}");
    }

    // Display result
    cout << "\nGenerated Excuse:\n";
    cout << excuse << endl;

    return 0;
}
```

PROBLEMS | OUTPUT | DEBUG CONSOLE | TERMINAL | PORTS

```
cd "/Users/kritikamra/c lab/output"
./"func"
kritikamra@Kritis-MacBook-Air c lab % cd "/Users/kritika
mra/c lab/output"
kritikamra@Kritis-MacBook-Air output % ./"func"
Enter student name: kriti

Generated Excuse:
kriti couldn't submit the homework because the file got deleted mysteriously.
kritikamra@Kritis-MacBook-Air output %
```

C/C++ ...
C/C++ Co...

CHAT

Build with Agent

AI responses may be inaccurate

Generate Agent Instructions to onboard AI onto your codebase.

func.cpp

Describe what to build

Auto

Local | Default Approvals

0 0 | c lab | Debug | Debug | Compile | Compile & Run | Update is ready, click to restart. | Ln 49, Col 2 | Spaces: 4 | UTF-8 | LF | C++ | macos-clang-x64