

Pizza Sales Project

Problem Statements:

1. Retrieve the total number of orders placed.

```
1      # Retrieve the total no of orders placed
2
3 •    SELECT COUNT(*) AS total_orders FROM orders;
```

Result Grid	
	total_orders
▶	21350

2. Calculate the total revenue generated from pizza sales.

```
1      -- Calculate the total revenue generated from pizza sales
2 •    SELECT
3      ROUND(SUM(od.quantity * p.price), 2) AS total_revenue
4      FROM
5      order_details od
6      JOIN
7      pizzas p ON od.pizza_id = p.pizza_id;
```

Result Grid	
	total_revenue
▶	817860.05

3. Identify the highest-priced pizza.

```

1  -- identify the highest priced pizza
2
3  • SELECT
4      pt.name, p.price
5  FROM
6      pizza_types pt
7      JOIN
8      pizzas p ON pt.pizza_type_id = p.pizza_type_id
9  ORDER BY p.price DESC
10 LIMIT 1;

```

Result Grid			Filter Rows:
	name	price	
▶	The Greek Pizza	35.95	

4. Identify the most common pizza size ordered.

```

1  -- identify the most common pizza size ordered
2
3  • SELECT
4      p.size, COUNT(od.order_details_id) AS order_count
5  FROM
6      order_details od
7      JOIN
8      pizzas p ON od.pizza_id = p.pizza_id
9  GROUP BY p.size
10 ORDER BY order_count DESC;

```

Result Grid			Filter Rows:
	size	order_count	
▶	L	18526	
	M	15385	
	S	14137	
	XL	544	
	XXL	28	

5. List the top 5 most ordered pizza types along with their quantities.

```

1  -- list the top 5 most ordered pizza types along with their quantities
2
3  • SELECT
4      pt.name, SUM(od.quantity) AS quantity
5  FROM
6      pizza_types pt
7      JOIN
8      pizzas p ON pt.pizza_type_id = p.pizza_type_id
9      JOIN
10     order_details od ON od.pizza_id = p.pizza_id
11 GROUP BY pt.name
12 ORDER BY quantity DESC
13 LIMIT 5;

```

Result Grid   Filter Rows:		
	name	quantity
▶	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371

6. Join the necessary tables to find the total quantity of each pizza category ordered.

```

1  -- join the necessary tables to find the total quantity of each pizza category
2  • SELECT
3      pt.category, SUM(od.quantity) AS total_quantity
4  FROM
5      order_details od
6      JOIN
7      pizzas p ON od.pizza_id = p.pizza_id
8      JOIN
9      pizza_types pt ON p.pizza_type_id = pt.pizza_type_id
10 GROUP BY pt.category
11 ORDER BY total_quantity DESC;

```

Result Grid   Filter Rows:		
	category	total_quantity
▶	Classic	14888
	Supreme	11987
	Veggie	11649
	Chicken	11050

7. Determine the distribution of orders by hour of the day.

```

1  -- determine the distribution of orders by hour of the day
2  • SELECT
3      HOUR(order_time) AS order_hour,
4      COUNT(order_id) AS order_count
5  FROM
6      orders
7  GROUP BY HOUR(order_time)
8  ORDER BY COUNT(order_id) DESC;

```

Result Grid   Filter Rows		
	order_hour	order_count
▶	12	2520
	13	2455
	18	2399
	17	2336
	19	2009
	16	1920
	20	1642
	14	1472
	15	1468
	11	1231
	21	1198
	22	663
	23	28
	10	8
	9	1

8. Join relevant tables to find the category-wise distribution of pizzas.

```

1  -- find category wise distribution of pizzas
2
3  • SELECT
4      category, COUNT(pizza_type_id) AS pizza_count
5  FROM
6      pizza_types
7  GROUP BY category
8  ORDER BY pizza_count DESC;

```

Result Grid   Filter Rows		
	category	pizza_count
▶	Supreme	9
	Veggie	9
	Classic	8
	Chicken	6

9. Group the orders by date and calculate the average number of pizzas ordered per day.

```

1  -- group the orders by date and calculate the average number of pizzas per day
2
3  • SELECT
4      ROUND(AVG(order_quantity), 0) AS average_pizza_ordered_per_day
5  FROM
6      (SELECT
7          o.order_date AS dates, SUM(od.quantity) AS order_quantity
8        FROM
9          orders o
10         JOIN order_details od ON o.order_id = od.order_id
11        GROUP BY dates) AS order_table;

```

Result Grid		Filter Rows:
	average_pizza_ordered_per_day	
▶	138	

10. Determine the top 3 most ordered pizza types based on revenue.

```

1  -- determine the top 3 most ordered pizza types based on the revenue
2  -- revenue = price*quantity
3  • SELECT
4      pt.name, SUM(p.price * od.quantity) AS total_revenue
5  FROM
6      pizzas p
7      JOIN
8      order_details od ON p.pizza_id = od.pizza_id
9      JOIN
10     pizza_types pt ON pt.pizza_type_id = p.pizza_type_id
11  GROUP BY pt.name
12  ORDER BY total_revenue DESC
13  LIMIT 3;

```

Result Grid			Filter Rows:
	name	total_revenue	
▶	The Thai Chicken Pizza	43434.25	
	The Barbecue Chicken Pizza	42768	
	The California Chicken Pizza	41409.5	

11. Calculate the percentage contribution of each pizza type to total revenue.

```

1  -- calculate the percentage contribution of each pizza type to total revenue
2  • SELECT pt.category, ROUND(SUM(od.quantity*p.price) *100/ (SELECT
3      ROUND(SUM(od.quantity * p.price), 2) AS total_revenue
4      FROM
5      order_details od
6      JOIN
7      pizzas p ON od.pizza_id = p.pizza_id), 2) AS revenue
8
9
10 FROM pizza_types pt JOIN pizzas p
11 ON pt.pizza_type_id = p.pizza_type_id
12 JOIN order_details od
13 ON od.pizza_id = p.pizza_id
14 GROUP BY pt.category
15 ORDER BY revenue DESC;

```

Result Grid			Filter Rows:
	category	revenue	
▶	Classic	26.91	
	Supreme	25.46	
	Chicken	23.96	
	Veggie	23.68	

12. Analyze the cumulative revenue generated over time.

```

1  -- analyze the cumulative revenue generated over time
2  • SELECT order_date, SUM(total_revenue) OVER(order by order_date) AS cum_revenue
3  FROM
4  (SELECT o.order_date, SUM(od.quantity*p.price) AS total_revenue
5      FROM order_details od JOIN pizzas p
6      ON od.pizza_id = p.pizza_id
7      JOIN orders o
8      ON o.order_id = od.order_id
9      GROUP BY o.order_date) AS sales;

```

Result Grid			Filter Rows:
	order_date	cum_revenue	
▶	2015-01-01	2713.8500000000004	
	2015-01-02	5445.75	
	2015-01-03	8108.15	
	2015-01-04	9863.6	
	2015-01-05	11929.55	
	2015-01-06	14358.5	
	2015-01-07	16560.7	
	2015-01-08	19399.05	
	2015-01-09	21526.4	
	2015-01-10	23990.350000000002	
	2015-01-11	25862.65	
	2015-01-12	27781.7	
	2015-01-13	29831.300000000003	
	2015-01-14	32358.700000000004	
	2015-01-15	34343.50000000001	
	2015-01-16	36937.65000000001	
	2015-01-17	39001.75000000001	
	2015-01-18	40978.600000000006	
	2015-01-19	43365.75000000001	
	2015-01-20	45763.65000000001	
	2015-01-21	47804.20000000001	
	2015-01-22	50300.90000000001	
	2015-01-23	52724.600000000006	
	2015-01-24	55013.850000000006	

13. Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```

1  -- determine the top 3 most ordered pizza types based on revenue for each pizza category
2
3  •  SELECT name, revenue
4      FROM
5      (SELECT category, name, revenue,
6         RANK() OVER(PARTITION BY category ORDER BY revenue DESC) AS rn
7      FROM
8      (SELECT pizza_types.category, pizza_types.name, SUM((order_details.quantity) * pizzas.price) AS revenue
9      FROM pizza_types JOIN pizzas
10     ON pizza_types.pizza_type_id = pizzas.pizza_type_id
11     JOIN order_details
12     ON order_details.pizza_id = pizzas.pizza_id
13     GROUP BY pizza_types.category, pizza_types.name) AS a) AS b
14  WHERE rn<=3;
15

```

Result Grid				 Filter Rows:	
	name	revenue			
▶	The Thai Chicken Pizza	43434.25			
	The Barbecue Chicken Pizza	42768			
	The California Chicken Pizza	41409.5			
	The Classic Deluxe Pizza	38180.5			
	The Hawaiian Pizza	32273.25			
	The Pepperoni Pizza	30161.75			
	The Spicy Italian Pizza	34831.25			
	The Italian Supreme Pizza	33476.75			
	The Sicilian Pizza	30940.5			
	The Four Cheese Pizza	32265.70000000065			
	The Mexicana Pizza	26780.75			
	The Five Cheese Pizza	26066.5			