NAME

kpsetool – script to make teTeX-style kpsetool, kpsexpand, and kpsepath available

SYNOPSIS

```
kpsetool [ OPTIONS... ] COMMAND kpsexpand [ OPTIONS... ] STRING kpsepath [ OPTIONS... ] PATHTYPE
```

DESCRIPTION

kpsetool is a Bourne shell script that makes a teTeX-style **kpsetool**, **kpsexpand**, and **kpsepath** available. **kpsetool** uses **web2c**'s (new) **kpsexpand** binary, so the syntax for **kpsexpand** is incompatible with teTeX's as of version 0.4.

OPTIONS

-m mode

set Metafont mode

-n progname

pretend to be progname to kpathsea

-p act like **kpsepath**(1)

-v act like **kpsexpand**(1)

-w act like **kpsewhich**(1)

USAGE

PATHTYPE can be

base Metafont memory dump

bib BibTeX bibliography source

bst BibTeX style files

cnf Kpathsea runtime configuration files

dvips_config

dvips config files

dvips_header

dvips header files

fmt TeX memory dump

gf generic font bitmap

mem MetaPost memory dump

mf Metafont source

mfpool Metafont program strings

mp MetaPost source

mppool

MetaPost program strings

mpsupport

MetaPost support files

pict Other kinds of figures

pk packed bitmap font

tex TeX source

texpool

TeX program strings

tfm TeX font metrics

troff_font

troff fonts

vf virtual font

SEE ALSO

kpsewhich(1)

Kpathsea: A library for path searching (info or DVI file)

Web page: http://tug.org/teTeX/>

BUGS

None known, but report any bugs found to <tetex@dbs.uni-hannover.de> (mailing list).

AUTHOR

kpsetool was written by Thomas Esser <te@dbs.uni-hannover.de> in March, 1997. **kpsetool** is in the public domain.

This manual page was written by C.M. Connelly <c@eskimo.com>, for the Debian GNU/Linux system. It may be used by other distributions without contacting the author. Any mistakes or omissions in the manual page are my fault; inquiries about or corrections to this manual page should be directed to me (and not to the primary author).