



Java 8 New
Features in
Simple Way



Predefined Functional Interface

Supplier

Study Material



Supplier (I)

Sometimes our requirement is we have to get some value based on some operation like

supply Student object
Supply Random Name
Supply Random OTP
Supply Random Password
etc

For this type of requirements we should go for Supplier.
Supplier can be used to supply items (objects).

Supplier won't take any input and it will always supply objects.
Supplier Functional Interface contains only one method get().

```
1) interface Supplier<R>
2) {
3)     public R get();
4) }
```

Supplier Functional interface does not contain any default and static methods.

Demo Program-1 For Supplier to generate Random Name:

```
1) import java.util.function.Supplier;
2) class Test
3) {
4)     public static void main(String[] args)
5)     {
6)         Supplier<String> s =()->{
7)             String[] s1={"Sunny", "Bunny", "Chinny", "Pinny"};
8)             int x =(int)(Math.random()*4);
9)             return s1[x];
10)        };
11)        System.out.println(s.get());
12)        System.out.println(s.get());
13)        System.out.println(s.get());
14)    }
15) }
```



Java 8 New Features in Simple Way



Output:

```
D:\durgaclasses>java Test
Chinny
Bunny
Pinny
```

```
D:\durgaclasses>java Test
Bunny
Pinny
Bunny
```

Demo Program-2 For Supplier to supply System Date:

```
1) import java.util.function.*;
2) import java.util.*;
3) class Test
4) {
5)     public static void main(String[] args)
6)     {
7)         Supplier<Date> s=()->new Date();
8)         System.out.println(s.get());
9)         System.out.println(s.get());
10)        System.out.println(s.get());
11)    }
12) }
```

```
D:\durgaclasses>java Test
Sun Aug 05 21:34:06 IST 2018
Sun Aug 05 21:34:06 IST 2018
Sun Aug 05 21:34:06 IST 2018
```

Demo Program-3 For Supplier to supply 6-digit Random OTP:

```
1) import java.util.function.*;
2) import java.util.*;
3) class Test
4) {
5)     public static void main(String[] args)
6)     {
7)         Supplier<String> otps=()->{
8)             String otp="";
9)             for(int i =1;i<=6;i++)
10)            {
11)                otp=otp+(int)(Math.random()*10);
12)            }
13)            return otp;
14)        }
15) }
```



Java 8 New Features in Simple Way



```
14)    };
15)    System.out.println(otps.get());
16)    System.out.println(otps.get());
17)    System.out.println(otps.get());
18)    System.out.println(otps.get());
19)    }
20) }
```

Output:

492499
055284
531389
925530

Demo Program-4 For Supplier to supply Random Passwords:

Rules:

1. length should be 8 characters
2. 2,4,6,8 places only digits
3. 1,3,5,7 only Capital Uppercase characters,@,#,\$

```
1) import java.util.function.*;
2) import java.util.*;
3) class Test
4) {
5)     public static void main(String[] args)
6)     {
7)         Supplier<String> s={()->
8)         {
9)             String symbols="ABCDEFGHJKLMNOPQRSTUVWXYZ#$@";
10)            Supplier<Integer> d={()->(int)(Math.random()*10);
11)            Supplier<Character> c={()->symbols.charAt((int)(Math.random()*29));
12)            String pwd="";
13)            for(int i =1;i<=8;i++)
14)            {
15)                if(i%2==0)
16)                {
17)                    pwd=pwd+d.get();
18)                }
19)                else
20)                {
21)                    pwd=pwd+c.get();
22)                }
23)            }
24)            return pwd;
25)        };
26)        System.out.println(s.get());
```



Java 8 New Features in Simple Way



```
27) System.out.println(s.get());  
28) System.out.println(s.get());  
29) System.out.println(s.get());  
30) System.out.println(s.get());  
31) }  
32) }
```

Output:

G2W3Y8W5
W7M8\$0L3
T5T5N2F3
O9N2L0V2
A4I1\$1P6

Comparison Table of Predicate, Function, Consumer and Supplier

Property	Predicate	Function	Consumer	Supplier
1) Purpose	To take some Input and perform some conditional checks	To take some Input and perform required Operation and return the result	To consume some Input and perform required Operation. It won't return anything.	To supply some Value base on our Requirement.
2) Interface Declaration	interface Predicate <T> { }	interface Function <T, R> { }	interface Consumer <T> { }	interface Supplier <R> { }
3) Single Abstract Method (SAM)	public boolean test (T t);	public R apply (T t);	public void accept (T t);	public R get();
4) Default Methods	and(), or(), negate()	andThen(), compose()	andThen()	-
5) Static Method	isEqual()	identify()	-	-