

Deep Learning

16 Transformer Applications

Dr. Konda Reddy Mopuri
Dept. of AI, IIT Hyderabad
Jan-May 2024

Transformer Layer - Powerful Building Block

- ① Highly flexible building block → powerful models

Transformer Layer - Powerful Building Block

- ① Highly flexible building block → powerful models
- ② E.g., Large Language Models (LLMs)

Transformer Applications - NLP

Transformer Applications - NLP

- ① Three broad configurations - based on the form of i/p and o/p

- ① Sequential input to a single variable output (Transformer acts as an 'Encoder')

- ① Sequential input to a single variable output (Transformer acts as an 'Encoder')
 - E.g., Sentiment classification

Transformer Applications - NLP

- ① A single vector as input and a sequence as output (Transformer acts as a 'Decoder')

- ① A single vector as input and a sequence as output (Transformer acts as a 'Decoder')
 - E.g., Caption generation from an image

Transformer Applications - NLP

① Sequence-to-Sequence processing tasks

Transformer Applications - NLP

- ① Sequence-to-Sequence processing tasks
 - E.g., Machine Translation

Decoder Transformers

- ① Can be used as ‘Generative Models’

Decoder Transformers

- ① Can be used as 'Generative Models'
- ② E.g., GPT (Generative Pre-trained Transformer)

Decoder Transformers

- ① Can be used as 'Generative Models'
- ② E.g., GPT (Generative Pre-trained Transformer)
- ③ Goal: use the transformer architecture to construct an 'Autoregressive' model

Decoder Transformers

- ① Can be used as 'Generative Models'
- ② E.g., GPT (Generative Pre-trained Transformer)
- ③ Goal: use the transformer architecture to construct an 'Autoregressive' model
- ④ $p(x_n/x_1, x_2, \dots, x_{n-1})$

Decoder Transformers - GPT

- 1 Stack of transformer layers

Decoder Transformers - GPT

- ① Stack of transformer layers
- ② i/p - x_1, x_2, \dots, x_N each of D dimensions

Decoder Transformers - GPT

- ① Stack of transformer layers
- ② i/p - x_1, x_2, \dots, x_N each of D dimensions
- ③ o/p - $\tilde{x}_1, \tilde{x}_2, \dots, \tilde{x}_N$


Decoder Transformers - GPT

- ① Stack of transformer layers
- ② i/p - x_1, x_2, \dots, x_N each of D dimensions
- ③ o/p - $\tilde{x}_1, \tilde{x}_2, \dots, \tilde{x}_N$
- ④ Each o/p token needs to represent a probability distribution over the dictionary (say, K words)

- ① Linear transformation of o/p tokens with $\mathbf{W}^{(p)}$ (dimensions - $K \times D$)

- ① Linear transformation of o/p tokens with $\mathbf{W}^{(p)}$ (dimensions - $K \times D$)
- ② $\mathbf{Y} = \text{Softmax}(\tilde{\mathbf{X}}\mathbf{W}^{(p)})$

Decoder Transformers



Bishop's Book

Decoder Transformers

- ① Can be trained over a large corpus of unlabelled text

Decoder Transformers

- ① Can be trained over a large corpus of unlabelled text
- ② Self-supervised approach

Decoder Transformers


- ① Can be trained over a large corpus of unlabelled text
- ② Self-supervised approach
- ③ Predicting x_{n+1} from an input of x_1, x_2, \dots, x_{n-1}

Decoder Transformers

- ① Employs 'Masked' or 'Causal' attention

Decoder Transformers

- ① Employs 'Masked' or 'Causal' attention
- ② Sets the attention weights of all the 'later' tokens



Bishop's Book

- ① Take sequences as input and produce fixed-length vectors


- ① Take sequences as input and produce fixed-length vectors
 - E.g., class label (sentiment) as output

- ① Take sequences as input and produce fixed-length vectors
 - E.g., class label (sentiment) as output
- ② E.g., BERT (Bidirectional Encoder Representations from Transformers)

- ① Take sequences as input and produce fixed-length vectors
 - E.g., class label (sentiment) as output
- ② E.g., BERT (Bidirectional Encoder Representations from Transformers)
- ③ Goal is to pre-train a language model using a large corpus of text

- ① Take sequences as input and produce fixed-length vectors
 - E.g., class label (sentiment) as output
- ② E.g., BERT (Bidirectional Encoder Representations from Transformers)
- ③ Goal is to pre-train a language model using a large corpus of text
 - Then, to fine-tune it for a broad range of downstream tasks

Encoder Transformers



Bishop's Book

Decoder Transformers

- ① First token of every input is a special token $< class >$

Decoder Transformers

- ① First token of every input is a special token $< class >$
- ② O/p of this is ignored during pre-training

Decoder Transformers

- ① First token of every input is a special token $< class >$
- ② O/p of this is ignored during pre-training
- ③ Pre-training goal is to predict the missing tokens

- ① A random 15% of the tokens are replaced with $\langle \text{mask} \rangle$ and the training predicts them

Decoder Transformers

- ① A random 15% of the tokens are replaced with $\langle mask \rangle$ and the training predicts them
- ② The cat $\langle mask \rangle$ sleeping on the $\langle mask \rangle$ next to the sofa.

- ① A random 15% of the tokens are replaced with $\langle mask \rangle$ and the training predicts them
- ② The cat $\langle mask \rangle$ sleeping on the $\langle mask \rangle$ next to the sofa.
- ③ Model should predict **is** and **floor** at 3 and 7 nodes respectively

- ① 'Bidirectional' \leftarrow model can access words both before and after the masked word

Decoder Transformers

- ① 'Bidirectional' \leftarrow model can access words both before and after the masked word
- ② Only a fraction of tokens act as labels

Decoder Transformers

- ① 'Bidirectional' \leftarrow model can access words both before and after the masked word
- ② Only a fraction of tokens act as labels
- ③ Doesn't generate sequences

Decoder Transformers

- ① After the pre-training, the Encoder model can be finetuned

Decoder Transformers

- ① After the pre-training, the Encoder model can be finetuned
- ② E.g., Tex classification: $< class >$ token is used for prediction

- ① After the pre-training, the Encoder model can be finetuned
- ② E.g., Tex classification: $\langle class \rangle$ token is used for prediction
- ③ A new layer (LSM in the figure) predicts the probability distribution over the dictionary

Sequence-to-Sequence Transformers

- ① Combines an encoder with a decoder

Sequence-to-Sequence Transformers

- ① Combines an encoder with a decoder
- ② E.g., machine translation from English to French


Sequence-to-Sequence Transformers

- ① Combines an encoder with a decoder
- ② E.g., machine translation from English to French
- ③ Decoder model generates the token sequence corresponding to the French o/p

Sequence-to-Sequence Transformers


- ① Combines an encoder with a decoder
- ② E.g., machine translation from English to French
- ③ Decoder model generates the token sequence corresponding to the French o/p
- ④ Conditioned on the entire input sequence corresponding to the English sentence → 'cross attention'

Sequence-to-Sequence Transformers



Bishop's Book

Sequence-to-Sequence Transformers



Bishop's Book

LLM - Large Language Models

① Recent development in ML and NLP

- ① Recent development in ML and NLP
- ② 'Large' → Billions of parameters

- ① Recent development in ML and NLP
- ② 'Large' → Billions of parameters
- ③ Large datasets and Powerful GPUs


- ① Recent development in ML and NLP
- ② 'Large' → Billions of parameters
- ③ Large datasets and Powerful GPUs
- ④ Unlike earlier language models, these are self-supervised first on large corpuses then finetuned with (small) labeled data

- ① 'Foundation Model' \leftarrow A model with broad capabilities that can be subsequently fine-tuned for specific tasks

- ① An Efficient approach to fine-tuning is called low-rank adaptation (LoRA)

LLM- Finetuning

- ① An Efficient approach to fine-tuning is called low-rank adaptation (LoRA)
- ② A trained overparameterized model has a low intrinsic dimensionality with respect to fine-tuning




Bishop's Book

- ① With their growing size, the need for fine-tuning is reducing

- ① With their growing size, the need for fine-tuning is reducing
- ② Generative language models are now able to solve a broad range of tasks through text-based interaction (prompt)

- ① With their growing size, the need for fine-tuning is reducing
- ② Generative language models are now able to solve a broad range of tasks through text-based interaction (prompt)
- ③ Fine-tuning large language models through human evaluation of generated output (e.g., reinforcement learning through human feedback or RLHF)

Transformers - Computer Vision



Bishop's Book