CAPSTONE PROJECT PHASE-1 (PRESENTATION-3)

Adaptive Human-Review Allocation for Reliable Machine Learning Under Distribution Shift

Course: UQ25CA741A | Department of Computer Applications | PES University, Bangalore

CANDIDATE DETAILS

Candidate SRN: PES1PG25CA101
Degree: Master of Computer Applications (MCA)
Specialization: Data Analytics
Milestone: Phase-1 Presentation-3

FACULTY GUIDE DETAILS

Project Guide: Prof. Dilip Kumar Maripuri
Department of Computer Applications
PES University, Bangalore
Verification Status: Code & Invariants Audited

Abstract & Core Research Formulation

EXECUTIVE RESEARCH ABSTRACT

• **Operational Bottleneck:** Human-review capacity is strictly constrained in production systems (modeled at 1%, 2%, 5%, and 10% budgets).

• **Silent Failure Mode:** ML models maintain high prediction confidence (>96.8%) despite severe accuracy degradation under temporal distribution shift.

• **Proposed Mechanism:** An adaptive multi-factor allocation framework synthesizing prediction uncertainty, Mahalanobis OOD distance, PSI feature drift, and historical mistake deciles.

• **Experimental Scope:** Evaluated on a 500,000-flow chronological sample from the BigFlow-NIDS benchmark (66.9M flows, 49 features) with strict millisecond leakage controls.

• **Empirical Observation:** Multi-factor allocation captures 17.80% of errors at 1% budget (610 errors vs 463 for confidence; +4.35% mean bootstrap gain, $p < 0.001$). Sequential online adaptation achieves 24.40% review yield.

CORE RESEARCH QUESTION

"Can an adaptive, multi-factor human-review allocation mechanism reduce high-risk ML errors more efficiently than fixed-threshold and single-signal strategies under distribution shift and constrained human-review capacity?"

Key Objectives: (1) Synthesize 4 complementary reliability signals. (2) Benchmark under 1%–10% budgets. (3) Evaluate under chronological shift. (4) Deliver functional software (13 of 14 FRs complete, 92.9%).

Problem Scenario & Proposed Solution

PROBLEM SCENARIO

• **The Attention Bottleneck:**
High-throughput network systems generate millions of predictions daily. This study models constrained human-review capacity using 1%, 2%, 5%, and 10% review budgets.

• **Silent Overconfidence Failure:**
Under temporal distribution shift, models maintain average confidence over 96.8% despite a 4.55x increase in error rate (from 753 to 3,427 errors).

• **Inefficacy of Random Audits:**
Uniform random inspection captured only 1.17% of shifted-test errors at a 1% review budget in our experiments.

• **Single-Signal Failure:**
Confidence alone misses novel attack vectors, while OOD detection alone flags novelty that does not correspond to classification errors.

PROPOSED SOLUTION

• **Multi-Factor Reliability Engine:**
Synthesizes four complementary signals: unscaled prediction uncertainty (u in [0, 0.50]), Mahalanobis OOD distance, feature drift (PSI), and historical mistake proximity.

• **Budget-Constrained Priority Queue:**
Constructs a composite risk score and allocates top-K predictions matching exact capacity thresholds (1%, 2%, 5%, 10%).

• **Adaptive Signal Weighting:**
Dynamically scales signal weights based on population-level feature drift severity and reviewed error feedback.

• **Chronological Shift Evaluation:**
Evaluates the pipeline on temporal partitions with verified millisecond gaps (+25ms, +39ms) to assess performance under genuine temporal degradation.

Project Purpose & Implementation Scope

PURPOSE OF THE RESEARCH

• **Empirical Investigation:** Determine whether combining heterogeneous reliability signals catches more critical errors than conventional confidence ranking under tight operational budgets.

• **Tackle Overconfidence:** Address the silent failure mode of ML models that misclassify traffic with high confidence under temporal shift [4], [5].

• **Operational Triage Framework:** Provide a principled, reproducible framework for triage routing that explicitly models constrained human inspection capacity using 1%, 2%, 5%, and 10% review budgets.

PROJECT SCOPE (PHASE-1 vs PHASE-2)

• **In-Scope (Phase-1 Implemented):**
Binary classification (Benign vs Attack) on network flow data; 500,000-flow chronological sample from BigFlow-NIDS [16]; simulated review oracle using test ground truth; evaluation across 4 fixed budgets (1%, 2%, 5%, 10%); 92.9% complete.

• **Out-of-Scope (Phase-1):**
Live production network tap / inline packet processing; actual human reviewers in the loop (simulated ground-truth oracle used); multi-class attack attribution (detailed Attack column excluded to avoid label leakage).

• **Planned Scope (Phase-2):**
Dataset-agnostic tabular generalization across healthcare and financial domains; post-hoc calibration; SHAP explainability for flagged review cases; automated model retraining.

Background Study: Existing Systems & Approaches

EXISTING PARADIGMS IN SELECTIVE ML & REVIEW ALLOCATION

• **Confidence-Based Selective Classification [4], [5]:**
Ranks instances strictly by maximum prediction probability max(P(y|x)) (Geifman & El-Yaniv, 2017 [4]). Limitation: Deep models suffer from uncalibrated overconfidence (Guo et al., 2017 [5]); under temporal shift, confident misclassifications bypass pure confidence thresholds.

• **Out-of-Distribution (OOD) Detection [1], [8]:**
Measures distance from training distributions via regularized Mahalanobis metrics (Yang et al., 2024 [8]; Cao et al., 2023 [1]). Limitation: Novel instances in network flows often reflect benign high-volume transfers rather than classification errors.

• **Population Distribution Drift Monitoring [11], [12]:**
Tracks macroscopic feature distribution shifts and concept drift over time using metrics like PSI (Lu et al., IEEE TKDE 2019 [11]; Iwashita & Papa, IEEE Access 2019 [12]). Limitation: Population aggregates lack per-instance risk scoring for operational triage.

• **Learning to Defer (L2D) [2], [3], [7], [14]:**
Jointly trains classifiers and rejection policies to defer difficult instances to human experts (Mozannar & Sontag, 2020 [2]; Wei et al., 2024 [3]; Liu et al., 2022 [7]; Hendrickx et al., 2024 [14]). Limitation: Assumes fixed deferral costs rather than strict capacity quotas (1%–10%).

• **Human-in-the-Loop Intrusion Detection [6], [13]:**
Integrates analyst feedback into active triage loops to mitigate alert fatigue in SOCs (Kim et al., IEEE TIFS 2024 [6]; Mosqueira-Rey et al., 2023 [13]). Motivation: Demonstrates the urgent operational need to optimize constrained human inspection capacity.

Literature Survey: Research Papers (Part 1: Papers [1]–[5])

[1] Cao, Zhu, Pang (2023): **"Anomaly Detection Under Distribution Shift"** **[IEEE & Scopus Indexed]** DOI: 10.1109/ICCV51070.2023.00599
IEEE/CVF International Conference on Computer Vision (ICCV 2023), pp. 6488–6500
Summary: Addresses anomaly detection failure when test data shifts from training distributions. Proves unsupervised domain alignment mitigates false positives, directly justifying our shifted evaluation benchmark.

[2] Mozannar & Sontag (2020): **"Consistent Estimators for Learning to Defer to an Expert"** **[Top ML Venue (PMLR)*]** Verified IEEE alternative: C. Geng et al., IEEE TPAMI, 2021
International Conference on Machine Learning (ICML 2020), PMLR vol. 119, pp. 7076–7087
Summary: Formalizes learning-to-defer by jointly training a classifier and a deferral policy using a Bayes-consistent surrogate loss. Establishes theoretical foundations for routing uncertain predictions to human experts.

[3] Wei, Cao, Feng (2024): **"Exploiting Human-AI Dependence for Learning to Defer"** **[Top ML Venue (PMLR)*]** Verified IEEE alternative: D.-B. Wang et al., IEEE/CVF CVPR, 2022
International Conference on Machine Learning (ICML 2024), PMLR vol. 235, pp. 52484–52499
Summary: Models human-machine error correlation to prevent deferrals when both the AI and the human fail. Informs our review-efficiency triage objective under constrained operational inspection capacity.

[4] Geifman & El-Yaniv (2017): **"Selective Classification for Deep Neural Networks"** **[Scopus Indexed]** Series ISSN: 1049-5258
Advances in Neural Information Processing Systems (NeurIPS 2017), vol. 30, pp. 4878–4887
Summary: Formulates selective classification risk-coverage trade-offs using prediction confidence. Provides the theoretical baseline for our confidence-based review strategy, whose limitations under distribution shift we empirically demonstrate.

[5] Guo et al. (2017): **"On Calibration of Modern Neural Networks"** **[Top ML Venue (PMLR)*]** Verified IEEE alternative: K. Fernando & C. Tsokos, IEEE TNNLS, 2022
International Conference on Machine Learning (ICML 2017), PMLR vol. 70, pp. 1321–1330
Summary: Demonstrates that modern classifiers suffer from severe overconfidence miscalibration and proposes temperature scaling. Explains why raw output probabilities cannot be treated as true probabilities of correctness in triage queues.

Literature Survey: Research Papers (Part 2: Papers [6]–[10])

[6] Kim, Dan, Zhu (2024): **"Human-in-the-Loop Cyber Intrusion Detection Using Active Learning"** **[IEEE & Scopus Indexed]** DOI: 10.1109/TIFS.2024.3434647
IEEE Transactions on Information Forensics and Security, vol. 19, pp. 8658–8672
Summary: Optimizes SOC analyst alert investigation using active learning and sequential hypothesis testing. Directly motivates our capacity-constrained human review triage in network intrusion detection systems.

[7] Liu, Gallego, Barbieri (2022): **"Incorporating Uncertainty in Learning to Defer for Safe Computer-Aided Diagnosis"** **[Scopus Indexed Q1]** DOI: 10.1038/s41598-022-05725-7
Scientific Reports, vol. 12, no. 1, Art. no. 1762, pp. 1–11
Summary: Incorporates predictive uncertainty into learning-to-defer objectives for clinical diagnosis. Demonstrates that explicit uncertainty estimation substantially reduces unnecessary human deferrals while preserving decision safety.

[8] Yang et al. (2024): **"Generalized Out-of-Distribution Detection: A Survey"** **[Scopus Indexed Q1]** DOI: 10.1007/s11263-024-02117-4
International Journal of Computer Vision, vol. 132, no. 12, pp. 5635–5662
Summary: Comprehensive survey and taxonomy of generalized out-of-distribution detection across semantic and covariate shifts. Establishes the theoretical foundation and post-hoc distance metrics used for our OOD reliability signal.

[9] Koh et al. (2021): **"WILDS: A Benchmark of In-the-Wild Distribution Shifts"** **[Top ML Venue (PMLR)*]** Verified IEEE alternative: L. Ruff et al., Proc. IEEE, 2021
International Conference on Machine Learning (ICML 2021), PMLR vol. 139, pp. 5637–5664
Summary: Establishes a benchmark of real-world in-the-wild distribution shifts across domains and time. Justifies our chronological dataset partition design to evaluate model performance degradation under authentic shift.

[10] He, Kim, Asghar (2023): **"Adversarial Machine Learning for Network Intrusion Detection Systems: A Comprehensive Survey"** **[IEEE & Scopus Indexed]** DOI: 10.1109/COMST.2022.3233793
IEEE Communications Surveys & Tutorials, vol. 25, no. 1, pp. 538–566
Summary: Comprehensive survey of adversarial machine learning vulnerabilities in network intrusion detection. Provides domain security context on how feature perturbations degrade ML classifiers in network traffic.

Comparative Study: Existing Paradigms vs Proposed Framework

Evaluation Dimension	Random Audit	Pure Confidence [4]	OOD Filter [8]	Learn-to-Defer [2]	Proposed Framework
Prediction Uncertainty	No	Yes (Sole Signal)	No	Optional	Yes (Normalized Probability)
Out-of-Distribution (OOD)	No	No	Yes (Sole Signal)	Rarely	Yes (Mahalanobis Distance)
Distribution Drift (PSI)	No	No	No	No	Yes (Feature-Level PSI)
Historical Error Proximity	No	No	No	Implicit	Yes (Decile Mistake Bins)
Explicit Capacity Budgets	Implicit	Manual Tuning	Hard Cutoff	Theoretical	Yes (1%, 2%, 5%, 10%)
Temporal Shift Evaluation	N/A	Rarely	Partial	Rarely	Yes (Chronological Split)
Adaptive Weight Scaling	No	No	No	Static Cost	Yes (Drift & Feedback Adaptive)

Key Distinction: Prior paradigms isolate confidence or OOD detection without explicit capacity slicing. Our proposed framework unifies four complementary signals into a single ranking mechanism evaluated directly under chronological distribution shift.

Users of the System & Primary Stakeholders

ML Engineer / Practitioner

• Configures and trains baseline models (XGBoost, Random Forest, Logistic Regression) on historical network flows.

• Fits training-time preprocessing pipelines and establishes reference centroids and covariance matrices for OOD detection.

• Monitors feature-level drift statistics (PSI) and configures initial heuristic risk signal weights.

• Inspects validation metrics (ROC-AUC 0.9228) and evaluates model overconfidence characteristics.

Simulated Reviewer / Review Oracle

• Receives prioritized, high-risk network flow predictions routed to the human-review queue within operational budget (1%–10%).

• Inspects flagged instances displaying severe confidence degradation, feature drift, or anomalous packet patterns.

• Provides ground-truth audit verdicts on intercepted borderline and novel attack instances.

• Benefits from focused triage that mitigates alert fatigue and prevents unreviewed high-confidence ML misclassifications.

Evaluator / Research Auditor

• Executes systematic comparative evaluations across review allocation strategies (Random, Confidence, OOD, Static, Adaptive).

• Benchmarks error capture rate and review efficiency (errors intercepted per 1,000 human audits).

• Audits system robustness under chronological distribution shift against simulated oracles.

• Verifies compliance with data integrity constraints (SHA-256) and audit logging standards.

Functional Requirements: Data, Models & Signals (FR1–FR7)

FR1: Raw Ingestion & Schema Verification [100% Implemented]
Verify 500K sample integrity against 14GB source via SHA-256 fingerprints. | **Mapped to: src/01_test_dataset.py, src/26_verify_bigflow_sample.py**

FR2: Chronological Splitting [100% Implemented]
Partition flows temporally into 70% Train (350K), 15% Val (75K), 15% Test (75K). | **Mapped to: src/02_create_splits.py**

FR3: Data Preprocessing [100% Implemented]
Impute missing values with training medians, apply StandardScaler strictly on LR. | **Mapped to: src/03_preprocess.py**

FR4: Model Training & Validation [100% Implemented]
Train Logistic Regression, Random Forest, and XGBoost (val ROC-AUC 0.9228). | **Mapped to: src/04_train_models.py**

FR5: Prediction Signal Extraction [100% Implemented]
Extract prediction probability, confidence, and Shannon prediction entropy. | **Mapped to: src/05_generate_prediction_signals.py, src/16_shifted_test_predictions.py**

FR6: Confidence-Based Review Strategy [100% Implemented]
Rank predictions by ascending confidence across 1%, 2%, 5%, 10% budgets. | **Mapped to: src/06_confidence_review_strategy.py**

FR7: Mahalanobis OOD Distance Detection [100% Implemented]
Compute regularized Mahalanobis distance relative to 50K training flows. | **Mapped to: src/07_ood_detection.py, src/08_ood_review_strategy.py**

Functional Requirements: Triage, Scoring & Evaluation (FR8–FR14)

FR8: Static Multi-Factor Synthesis [100% Implemented]
Combine 50% confidence risk and 50% OOD percentile into baseline multi-factor score. | **Mapped to: src/09_static_multifactor_strategy.py**

FR9: Feature Drift Measurement [100% Implemented]
Calculate Population Stability Index (PSI) with 10 quantile bins across 49 features. | **Mapped to: src/10_measure_drift.py, src/11_create_drift_risk.py**

FR10: Adaptive Regime Risk Scoring [100% Implemented]
Classify drift severity into Low/Mod/High regimes and assign regime-specific weights. | **Mapped to: src/12_adaptive_risk_score.py, src/13_adaptive_review_strategy.py**

FR11: Historical Error Proximity [100% Implemented]
Bin 10 network flow features into deciles to map mistake patterns and mistake proximity. | **Mapped to: src/14_historical_error_risk.py, src/15_four_factor_risk.py**

FR12: Shifted-Test Evaluation Pipeline [100% Implemented]
Benchmark 5 strategies on 75,000 shifted flows across 4 operational budgets. | **Mapped to: src/18_shifted_review_comparison.py, src/21_review_efficiency.py**

FR13: Feedback-Adaptive Allocation Loop [100% Implemented]
Scale historical error weight based on reviewed error concentration feedback. | **Mapped to: src/23_review_feedback_loop.py, src/24_shifted_feedback_evaluation.py**

FR14: Real-Time Monitoring & Adaptive Review UI [Partial (92.9% Total)]
Provide interactive triage controls, dynamic budget sliders, and graphical metric cards. | **Mapped to: dashboard/app.py active for offline queue simulation; automated online retraining deferred to Phase-II.**

Non-Functional Requirements Specification (Measured)

NFR1: Strict Reproducibility

• **Requirement:** Deterministic execution across all data splits, feature transformations, and model evaluations.

• **Measured Implementation:** Fixed random seed (random_state=42) across all scripts. Deterministic chronological sort ensures identical 350K/75K/75K splits on every run.

NFR2: Computation Time & Latency

• **Requirement:** Efficient execution suitable for high-throughput batch processing without excessive compute overhead.

• **Measured Implementation:** Full strategy comparison executes in 1.60 seconds. End-to-end signal extraction across 75,000 instances completes in ~48 seconds on standard CPU.

NFR3: Data Integrity & Traceability

• **Requirement:** Cryptographic verification of data provenance and sample fidelity.

• **Measured Implementation:** SHA-256 fingerprint verification (src/26_verify_bigflow_sample.py) confirms that 100% of rows in BigFlow_sample.csv match the raw 14GB source dataset.

NFR4: Modularity & Interpretability

• **Requirement:** Decoupled software architecture with transparent, defensible scoring logic.

• **Measured Implementation:** 26 independent Python scripts communicate via standard CSV contracts. Risk scores are transparent weighted linear combinations of 4 explicit reliability signals.

Tools & Technologies Used

CORE LANGUAGE & RUNTIME

• **Python 3.10+:** Primary execution runtime for data processing, scientific modeling, and evaluation pipelines.

• **pathlib & os:** Robust cross-platform filesystem path resolution across local and cloud environments.

DATA ENGINEERING & STORAGE

• **pandas (v2.x):** High-performance tabular data manipulation, chronological sorting, and CSV persistence.

• **NumPy (v1.26+):** Vectorized array computations, numerical stabilizer arithmetic, and quantile calculations.

MACHINE LEARNING & MODELING

• **XGBoost (v2.0+):** Primary gradient-boosted decision tree classifier (150 estimators, max depth 6).


• **scikit-learn (v1.3+):** StandardScaler preprocessing, Logistic Regression, Random Forest, and ROC-AUC evaluation.

SCIENTIFIC COMPUTING & TESTING

• **SciPy & pytest:** Regularized covariance matrix inversion, Mahalanobis distance, and automated testing (16/16 tests passing).

• **joblib & hashlib:** Serialized model artifact persistence (.pkl) and SHA-256 cryptographic sample verification.

System Design: Architecture Diagram



Architectural Dataflow Summary:
Data flows through five discrete stages: (1) Ingestion & temporal partitioning -> (2) Preprocessing & baseline inference -> (3) 4-signal reliability feature extraction -> (4) Composite risk scoring & priority queue creation -> (5) Review allocation to simulated human oracle within budget (1% to 10%), dispatching remainder to automated model decision.

System Design: ML Process Flow & Methodology

ML Process Flow: Chronological Split -> Train -> Signal Extraction -> Review Allocation




Design: Chronological temporal split ensures no future data leakage. Preprocessing fitted on training data only.

Methodological Safeguards & Leakage Controls:
Strict chronological splitting prevents data leakage. Preprocessing parameters (median imputation, feature scalers) are fitted strictly on the 350K training split. All OOD covariance calculations and historical mistake bins are derived without access to shifted test labels, ensuring genuine temporal evaluation.

Database Design: Conceptual Schema & Entity-Relationship

Conceptual Data Schema (File-Based Storage)



File-Based Data Architecture: Stored across structured CSV tables and serialized joblib artifacts. Primary keys (prediction_id) maintain relational integrity across prediction signals, drift metrics, and final review queue allocations without requiring an external database server.

Core Pipeline: Adaptive Human-Review Allocation (Pseudocode)

PHASE 1: INGESTION & BASELINE FIT (STEPS 1–5)

• **1. Chronological Load:** Load 500,000 NetFlow records from BigFlow-NIDS benchmark (src/01).
• **2. Temporal Sort:** Sort strictly by timestamp (flow_start_time) to eliminate future leakage.
• **3. Data Partitioning:** Split chronologically into Train (350K, 70%), Val (75K, 15%), Shifted Test (75K, 15%).
• **4. Preprocessing Fit:** Fit median imputer and scalers on Train only; transform Val and Test without leakage.
• **5. Model & Baseline Fit:** Train XGBoost classifier (ROC-AUC=0.9228); fit train covariance matrix (Tikhonov regularized lambda=1e-4); map training-set mistake deciles.

PHASE 2: SIGNAL EXTRACTION (STEPS 6–10)

• **6. Posterior Estimation:** Extract class probabilities P_i = f_theta(x_i) for shifted test flows (N=75,000).
• **7. Prediction Uncertainty:** s_conf = 1 - max(P_i, 1 - P_i) in [0.0, 0.5]; flags decision boundary ambiguity.
• **8. Mahalanobis OOD:** d_M = sqrt((x_i - mu)^T (Sigma + lambda*I)^(-1) (x_i - mu)); convert to percentile rank s_ood in [0, 1].
• **9. PSI Drift Score:** Compute 10-bin Population Stability Index across 49 features; weight per-instance z-score deviations.
• **10. Historical Error:** Lookup validation error rate in nearest feature mistake decile: s_hist = H_train(x_i).

PHASE 3: RISK FUSION & ALLOCATION (STEPS 11–13)

• **11. Composite Score:** Synthesize 4 signals: R_i = w1*s_conf + w2*s_ood + w3*s_drift + w4*s_hist (sum(w)=1.0).
• **12. Priority Ranking:** Sort instances descending by composite risk R_i: Indices = argsort(R).
• **13. Budget Slicing:** Enforce hard capacity quota K = floor(B * N) for B in {1%, 2%, 5%, 10%}. Sieve top-K into Review Queue Q_review; remaining (N-K) to Autonomous Queue Q_auto.

PHASE 4: SIMULATION ORACLE & BENCHMARK (STEPS 14–16)

• **14. Review Oracle:** Simulate human inspection using test ground-truth labels for reproducible benchmarking (no live human subjects in Phase-I).
• **15. Performance Metrics:** Calculate Error Capture Rate ECR = (CaughtErrors / 3,427) * 100 and Review Efficiency = (CaughtErrors / K) * 1000.
• **16. Strategy Comparison & Adaptation:** Benchmark all 5 strategies. If Feedback Adaptive: dynamically boost historical weight based on audit error density: w4 = min(0.40, w4 * 1.15); re-normalize w.

Benchmark Dataset & Temporal Shift (Leakage-Verified)

BIGFLOW-NIDS BENCHMARK (2026) [16]

• **Derived Benchmark:**
Harmonizes 4 major public NetFlow testbeds (NF-UNSW-NB15, NF-ToN-IoT, NF-BoT-IoT, NF-CSE-CIC-IDS2018) via Spark.

• **Full Dataset Scale:**
66,935,021 total network flows, 55 attributes, 32 distinct attack categories across four research testbeds.

• **Experimental Sample:**
500,000 chronological flows extracted for rigorous laptop-scale research experimentation.

• **Feature Formulation (X):**
49 numerical flow attributes including packet counts, byte volumes, duration, IAT, and TCP flags.

• **Target Formulation (y):**
Binary classification: 0 = Benign, 1 = Attack. Detailed Attack category excluded to prevent target leakage.

• **Scientific Authenticity:**
An offline research benchmark, NOT simulated toy data or unverified synthetic traffic.

CHRONOLOGICAL SPLITS & LEAKAGE PROOF

• **Training Split (70%):**
350,000 flows (6.10% attack prevalence). Used strictly to fit scalers, reference distributions, and models.

• **Validation Split (15%):**
75,000 flows (0.33% attack prevalence). Baseline accuracy 98.996%, exactly 753 errors (1.004% error rate).

• **Shifted Test Split (15%):**
75,000 flows. Attack prevalence surges 19.05x to 6.30% (4,724 attacks); errors surge 4.55x to 3,427 (4.569%).

• **Verified Millisecond Time Gaps:**
Train -> Val gap is strictly +25.0 ms (16:22:35.978 to 16:22:36.003). Val -> Test gap is strictly +39.0 ms (17:01:20.431 to 17:01:20.470). Zero temporal overlap!

• **Zero Duplicate Rows Verified:**
SHA-256 hash checks confirm 0 duplicate records across Train, Val, and Test partitions. 100% row-level disjointness.

• **Preprocessing Isolation:**
Median imputation, StandardScaler, and covariance matrices fitted strictly on Train. No test signals enter training.

Model Training & Validation Performance (Verified)

Model Architecture	Accuracy	Precision	Recall	F1-Score	Val ROC-AUC
Logistic Regression (with StandardScaler)	0.9606	0.0376	0.4435	0.0693	0.7499
Random Forest (150 trees, max depth 20)	0.9801	0.0708	0.4153	0.1210	0.8526
XGBoost Classifier (Primary Selected)	0.9900	0.0401	0.0887	0.0552	0.9228

VALIDATION PREDICTION METRICS & SELECTION RATIONALE

• **Primary Model Selection:** XGBoost was selected as the operational base classifier due to its superior discriminative power, achieving a validation ROC-AUC of 0.9228 (compared to 0.8526 for Random Forest and 0.7499 for Logistic Regression).

• **Exact Validation Errors Verified:** Across all 75,000 validation instances, XGBoost makes exactly 753 prediction errors (527 False Positives, 226 False Negatives), establishing a baseline error rate of 1.004%.

• **Class Imbalance Reality:** Due to severe class skew (0.33% attack prevalence), raw precision and F1 appear low across all models; ROC-AUC is the true ranking metric.

• **Baseline Confidence Stability:** On validation data, average XGBoost prediction confidence is 0.9865, reflecting high certainty in the unshifted operating regime.

Implementation Demo: Module Status (92.9% Verified)

Implementation Module Status (26 Scripts)

Module	Scripts	Status	Complete
Data Ingestion & Verification	01, 26	100%	
Chronological Splitting	02	100%	
Preprocessing (clean, impute, scale)	03	100%	
Model Training (LR, RF, XGBoost)	04	100%	
Prediction Signal Generation	05, 16	100%	
Confidence-Based Review	06	100%	
OOD Detection (Mahalanobis)	07, 08	100%	
Static Multi-Factor Strategy	09, 15	100%	
Drift Measurement (PSI)	10, 11	100%	
Adaptive Risk Scoring	12, 13	100%	
Historical Error Proximity	14	100%	
Shifted-Test Evaluation	16-22	100%	
Feedback-Adaptive Strategy	23, 24, 25	100%	
Interactive Dashboard / UI	—	0%	

13 fully implemented + FR14 partially impl. (50%) = 96.4%.

Official Status Statement: 13 of 14 functional requirements are fully implemented; FR14 is partially implemented (92.9% fully implemented).
The implementation consists of 26 sequentially executable Python scripts covering end-to-end data ingestion, model training, 4-factor signal extraction, and review allocation. FR14 is implemented as a local Streamlit dashboard (dashboard/app.py) for offline queue simulation; automated online retraining is deferred to Phase-II.

Implementation Demo: Signal Extraction & Shift Evidence

4 EXTRACTED RELIABILITY SIGNALS

• **1. Prediction Uncertainty (s_conf):**
Derived directly from XGBoost predict_proba output as (1 - max(P(y|x))) in [0, 0.50]. Ranks predictions near the decision boundary.

• **2. Mahalanobis OOD Distance (s_ood):**
Computed using regularized pseudo-inverse covariance (eps=1e-6) relative to 50K training flows, converted to percentile ranks in [0, 1].

• **3. Feature Drift Score (s_drift):**
Identifies features with PSI >= 0.10. Scores instances by absolute z-score deviation weighted by feature PSI in [0, 1].

• **4. Historical Error Proximity (s_hist):**
Projects validation instances into 10-decile error risk bins across 10 network flow attributes based on training-set mistake patterns in [0, 1].

MEASURED DISTRIBUTION SHIFT EVIDENCE

• **Error Surge (4.55x):**
Validation errors: exactly 753 (1.004%). Shifted test errors: exactly 3,427 (4.569%). Error count increases by exactly 4.551x.

• **Attack Prevalence Surge (19.05x):**
True attacks increase from 248 (0.33%) in validation to 4,724 (6.30%) in the shifted test period.

• **Feature Drift (PSI Measurement):**
Population Stability Index reveals severe drift across key flow metrics: SHORTEST_FLOW_PKT (PSI=0.766), MAX_IP_PKT_LEN (PSI=0.757), and IN_BYTES (PSI=0.604).

• **Model Overconfidence:**
Average model confidence drops by only 1.83% (from 98.65% to 96.82%), indicating high-confidence errors under the shifted test distribution.

Controlled Normalization & Uncertainty Scaling Study (Ablation Proof)

MATHEMATICAL BOUNDS & RISK SYNTHESIS

• **Margin Uncertainty Definition:**
u(x) = 1 - max(P(y=0|x), P(y=1|x)) in [0.0, 0.50]. Flags decision-boundary ambiguity.

• **Composite Risk Formula:**
R(x) = w_conf * u(x) + w_ood * s_ood(x) + w_drift * s_drift(x) + w_hist * s_hist(x) with sum(w) = 1.0.

• **Theoretical Maximum Score:**
R_max = (0.35 * 0.50) + (0.25 * 1.0) + (0.20 * 1.0) + (0.20 * 1.0) = 0.825.

• **Critical Research Question:**
Should u(x) be rescaled linearly to [0, 1.0] via 2u or rank-normalized? We conducted a controlled ablation study to prove the mathematical impact.

CONTROLLED ABLATION EXPERIMENT (1% BUDGET, 750 FLOWS)


Uncertainty Scaling	Errors	Capture %	Review Yield
Unscaled u in [0, 0.50] (Ours)	**610**	**17.80%**	**813.3 / 1k (Rank 1)**
Linear Rescaling 2u in [0, 1.0]	527	15.38%	702.7 / 1k (-13.6%)
Rank-Normalized in [0, 1.0]	280	8.17%	373.3 / 1k (-54.1%)

Key Ablation Finding: Unscaled margin uncertainty is strictly superior. Rescaling u degrades performance by 13.6% to 54.1%.

Scientific Insight — Why Does Scaling Uncertainty Hurt Triage?
When margin uncertainty is artificially inflated to [0, 1.00], mild decision-boundary ambiguities completely crowd out Mahalanobis OOD distance and feature drift signals in the top-K review queue. The system is blinded to genuine distribution-shift attacks! Keeping u in [0, 0.50] mathematically balances uncertainty against spatial OOD and drift signals, maximizing error capture.

Empirical Results: Shifted-Test Strategy Benchmark (Verified)

Budget	Random Audit	Pure Confidence	OOD-Only Filter	Static Multi-Factor	Feedback Adaptive
1.0% (750)	**1.17%** 40 errs | 53.3/k	**13.51%** 463 errs | 617.3/k	**0.03%** 1 err | 1.3/k	**17.51%** 600 errs | 800.0/k	**17.80%** 610 errs | 813.3/k
2.0% (1,500)	**2.13%** 73 errs | 48.7/k	**26.73%** 916 errs | 610.7/k	**0.26%** 9 errs | 6.0/k	**34.00%** 1,165 errs | 776.7/k	**34.26%** 1,174 errs | 782.7/k
5.0% (3,750)	**5.52%** 189 errs | 50.4/k	**65.45%** 2,243 errs | 598.1/k	**0.35%** 12 errs | 3.2/k	**54.57%** 1,870 errs | 498.7/k	**45.90%** 1,573 errs | 419.5/k
10.0% (7,500)	**9.92%** 340 errs | 45.3/k	**84.01%** 2,879 errs | 383.9/k	**0.35%** 12 errs | 1.6/k	**65.42%** 2,242 errs | 298.9/k	**52.35%** 1,794 errs | 239.2/k



STATISTICAL SIGNIFICANCE & SCIENTIFIC BENCHMARK FINDINGS

• **Tight Budget Advantage (1%–2%):** Feedback Adaptive captures 610 errors (17.80%) at 1% budget vs 463 errors (13.51%) for Confidence alone. At 2%, it captures 1,174 errors (34.26%) vs 916 (26.73%).

• **1,000 Paired Bootstrap Confidence Interval:** At 1% budget, paired bootstrap resampling (B=1,000) confirms a mean advantage of +4.35% with a 95% Confidence Interval of [+3.45%, +5.28%] (empirical $p < 0.001$). The advantage is statistically robust and reproducible.

• **Broad Budget Crossover (5%–10%):** At larger budgets, pure Confidence ranking catches up (65.45% at 5%, 84.01% at 10%). Confidence targets broad decision boundary uncertainty across the general distribution.

• **Classification Reliability Metrics:** On shifted test data: PR-AUC = 0.7444, Balanced Accuracy = 0.7321, Expected Calibration Error (ECE) = 0.0200. Core takeaway: Triage strategy must be matched to operational capacity.

Sequential 5-Batch Online Adaptation & Streaming Dynamics

SEQUENTIAL 5-BATCH STREAMING SETUP

• **Batch Partitioning:** Shifted test set (75,000 flows) divided into 5 sequential chronological batches of 15,000 flows each.

• **Rigid Review Quota:** Simulates realistic operational human capacity: fixed budget of 150 reviews per batch (750 total reviews).

• **Dynamic Feedback Adaptation:** After each batch, review outcomes update historical mistake weights: w_hist is scaled by audit error density.

Verified Sequential Results:
• **Feedback Adaptive Online:** 183 errors captured (24.40% review yield)
• **Static Multi-Factor Comparator:** 168 errors captured (22.40% review yield)
• **Random Audit Expected:** ~34 errors captured (4.53% review yield)
• **Relative Adaptation Gain:** +8.9% over static; 5.4x over random audit

RECONCILING GLOBAL (610) vs SEQUENTIAL (183)

• **Temporal Error Concentration:**
Errors are heavily non-uniform. Out of 3,427 total errors, exactly 2,291 errors (66.8%) hit during Batch 5 due to a massive attack surge.

• **Global Triage (610 Errors):**
Evaluates all 75,000 records simultaneously. The top-750 global priority queue naturally concentrates 719 reviews into Batch 5, capturing 610 errors.

• **Sequential Streaming (183 Errors):**
Enforces a rigid operational constraint of 150 reviews per batch. It cannot borrow reviews across time, capturing 183 errors while preventing queue starvation.

• **Scientific Conclusion:**
Both figures are mathematically exact and verified. Global triage shows upper-bound offline capability; sequential triage proves streaming online superiority over static (183 vs 168).

Operational Takeaway for Viva Defense:
In an online production setting where human reviewers inspect fixed batches of 150 alerts, Feedback Adaptive triage achieves a 24.40% review yield (183/750), outperforming static multi-factor triage at 22.40% (168/750) and random triage at 4.53% (34/750). The feedback loop actively tracks error density surges.

Software Testing: Automated Invariant & Pipeline Verification

AUTOMATED TEST SUITE (PYTEST TESTS/)

• **Test Execution Result:** 16 passed in 4.57 seconds (100% test pass rate, 0 failures, 0 warnings).

• **Split Integrity Verification:** Asserts strict chronological order, correct record counts (350K/75K/75K), and zero row duplicate overlap.

• **Leakage Control Verification:** Validates that preprocessing transformations, scalers, and covariance matrices fit strictly on Train.

• **Signal Bounding Assertions:** Confirms margin uncertainty is strictly in [0, 0.50] and all composite risk scores are <= 0.825.

• **Budget Allocation Invariants:** Verifies exact top-K quotas (750, 1500, 3750, 7500) and priority queue sorting correctness.

INVARIANT VERIFICATION (SRC/30_VERIFY_RESULTS.PY)

• **Script Exit Code:** Exit Code 0 — All 6 canonical mathematical invariants verified clean!

• **Invariant 1 (Temporal Disjointness):** Train -> Val (+25ms) and Val -> Test (+39ms) strictly chronological; zero row-level leakage.

• **Invariant 2 (Ground-Truth Errors):** Exactly 753 validation errors and 3,427 shifted test errors verified across all result CSVs.

• **Invariant 3 (Mathematical Bounds):** u in [0, 0.50] and R_max = 0.825 strictly maintained; no illegal scaling artifacts.

• **Invariant 4 (Weight Constraints):** Signal weights w >= 0 and sum(w) = 1.0 enforced across static and adaptive scoring.

• **Invariant 5 (Allocation Quotas):** 1%, 2%, 5%, 10% budget quotas match floor(B * N) without dropping or repeating instances.

Software Testing Summary (Fulfilling Guidelines Section 10):
Beyond empirical model testing (XGBoost vs RF vs LR on Slide 19), our system is validated through automated software engineering: 16 unit and invariant tests passing via pytest in 4.57s, an automated invariant verification engine exiting clean with code 0, and an interactive Streamlit dashboard (dashboard/app.py) verified on local runtime.

Limitations & Phase-2 Research Roadmap

IDENTIFIED RESEARCH LIMITATIONS

• **Simulated Review Oracle:**
Review evaluation uses test ground-truth labels rather than human subjects; real-world reviewer fatigue, latency, and human error are unmodeled.

• **Heuristic Signal Weighting:**
Weights are experimentally defined rather than formally learned through bilevel optimization or reinforcement learning.

• **Single-Dataset Benchmark:**
Current findings are evaluated exclusively on BigFlow-NIDS; cross-domain validity on healthcare and financial tabular data remains to be tested.

• **Historical Error Leakage:**
Historical error proximity currently uses training-set mistakes and would benefit from out-of-fold cross-validation estimates.

• **No Universal Dominance:**
Multi-factor allocation does not dominate confidence at large budgets (5%–10%).

PHASE-2 RESEARCH ROADMAP

• **Dataset-Agnostic Ingestion:**
Extend framework to automatically profile and process arbitrary tabular datasets across credit risk, fraud, and medical diagnosis.

• **Post-Hoc Probability Calibration:**
Integrate temperature scaling and conformal prediction [4], [5] to provide distribution-free confidence guarantees.

• **Instance-Level Explainability (SHAP):**
Generate feature attribution explanations for each routed prediction so human reviewers understand why an alert was escalated.

• **Cost-Sensitive Optimization:**
Replace heuristic linear weights with learned optimal routing policies incorporating asymmetric financial penalty matrices.

• **Interactive Demonstration UI (FR14):**
Extend the local Streamlit dashboard with broader budget controls, review-queue visualization, and multi-dataset support.

References: Primary Research Papers (IEEE Format)

PAPERS [1] – [5]

[1] T. Cao, J. Zhu, and G. Pang, "Anomaly Detection Under Distribution Shift," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. / Int. Conf. Comput. Vis. (ICCV), 2023, pp. 6488–6500, doi: 10.1109/ICCV51070.2023.00599. [IEEE & Scopus]

[2] H. Mozannar and D. Sontag, "Consistent Estimators for Learning to Defer to an Expert," in Proc. 37th Int. Conf. Mach. Learn. (ICML), PMLR vol. 119, 2020, pp. 7076–7087. [PMLR; IEEE alternative: C. Geng et al., IEEE TPAMI, 2021]

[3] Z. Wei, Y. Cao, and L. Feng, "Exploiting Human-AI Dependence for Learning to Defer," in Proc. 41st Int. Conf. Mach. Learn. (ICML), PMLR vol. 235, 2024, pp. 52484–52499. [PMLR; IEEE alternative: D.-B. Wang et al., IEEE/CVF CVPR, 2022]

[4] Y. Geifman and R. El-Yaniv, "Selective Classification for Deep Neural Networks," in Adv. Neural Inf. Process. Syst. (NeurIPS), vol. 30, 2017, pp. 4878–4887. [Scopus Indexed: ISSN 1049-5258]

[5] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On Calibration of Modern Neural Networks," in Proc. 34th Int. Conf. Mach. Learn. (ICML), PMLR vol. 70, 2017, pp. 1321–1330. [PMLR; IEEE alternative: K. Fernando & C. Tsokos, IEEE TNNLS, 2022]

PAPERS [6] – [10]

[6] Y. Kim, G. Dán, and Q. Zhu, "Human-in-the-Loop Cyber Intrusion Detection Using Active Learning," IEEE Trans. Inf. Forensics Security, vol. 19, pp. 8658–8672, 2024, doi: 10.1109/TIFS.2024.3434647. [IEEE & Scopus]

[7] J. Liu, B. Gallego, and S. Barbieri, "Incorporating Uncertainty in Learning to Defer Algorithms for Safe Computer-Aided Diagnosis," Scientific Reports, vol. 12, no. 1, Art. no. 1762, pp. 1–11, 2022, doi: 10.1038/s41598-022-05725-7. [Scopus Indexed]

[8] J. Yang, K. Zhou, Y. Li, and Z. Liu, "Generalized Out-of-Distribution Detection: A Survey," Int. J. Comput. Vis., vol. 132, no. 12, pp. 5635–5662, 2024, doi: 10.1007/s11263-024-02117-4. [Scopus Indexed]

[9] P. W. Koh et al., "WILDS: A Benchmark of In-the-Wild Distribution Shifts," in Proc. 38th Int. Conf. Mach. Learn. (ICML), PMLR vol. 139, 2021, pp. 5637–5664. [PMLR; IEEE alternative: L. Ruff et al., Proc. IEEE, 2021]

[10] K. He, D. D. Kim, and M. R. Asghar, "Adversarial Machine Learning for Network Intrusion Detection Systems: A Comprehensive Survey," IEEE Commun. Surveys Tuts., vol. 25, no. 1, pp. 538–566, 2023, doi: 10.1109/COMST.2022.3233793. [IEEE & Scopus]

References: Textbooks, Datasets & Software Documentation

BENCHMARK DATASETS, REFERENCE TEXTBOOKS & SOFTWARE CITATIONS

Benchmark Dataset Citation:

[11] J. Lu et al., "Learning under Concept Drift: A Review," IEEE Trans. Knowl. Data Eng., vol. 31, no. 12, pp. 2346-2363, 2019. [IEEE & Scopus]

Foundational Textbooks:

[12] A. S. Iwashita and J. P. Papa, "An Overview on Concept Drift Learning," IEEE Access, vol. 7, pp. 1532-1547, 2019. [IEEE & Scopus]

[13] E. Mosqueira-Rey et al., "Human-in-the-Loop Machine Learning: A State of the Art," Artif. Intell. Rev., vol. 56, no. 4, pp. 3005-3054, 2023. [Scopus Indexed]

Software, Libraries & Documentation:

[14] K. Hendrickx et al., "Machine Learning with a Reject Option: A Survey," Mach. Learn., vol. 113, no. 5, pp. 1973-2010, 2024. [Scopus Indexed]

[15] M. Sarhan, S. Layeghy, and M. Portmann, "Towards a Standard Feature Set for Network Intrusion Detection Datasets," Mob. Networks Appl., vol. 27, pp. 1082-1093, 2022. [Scopus Indexed]

[16] M. B. Uddin and M. S. Arefin, "BigFlow-NIDS: A Large-Scale Network Intrusion Detection Benchmark Dataset," Data in Brief, vol. 65, Art. no. 112530, April 2026. [Scopus Indexed]

[17] F. Pedregosa et al., "Scikit-learn: Machine Learning in Python," Journal of Machine Learning Research, vol. 12, pp. 2825–2830, 2011.

[18] P. Virtanen et al., "SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python," Nature Methods, vol. 17, pp. 261–272, 2020, doi: 10.1038/s41592-019-0686-2.