



TECHNISCHE
UNIVERSITÄT
WIEN
Vienna University of Technology

VIENNA UNIVERSITY OF TECHNOLOGY

INSTITUTE OF APPLIED PHYSICS

SURFACE SCIENCE

Bachelors Thesis

Title

Author:
Martin Kronberger
Group 119

Tutor:

December 1, 2024

Contents

1	Theory	3
1.1	Formulary	3
	Thermodynamics	3
	Continuous one-dimensional flow	3
1.2	Foundational principles	4
	Idealized flow regimes	4
	Turbulence	4
	Mach regimes	4
	Dimensionality of the flow	4
2	Analytical work	5
2.1	Scope and objectives	5
2.2	Framework for Analysis	5
	Important assumptions	5
	Regions of interest	5
	Limits of the theory	5
2.3	Analytical Descriptions	6
3	Discussion	7
4	Conclusion	8
	References	9

1 Theory

1.1 Formulary

Thermodynamics

Continuous one-dimensional flow

Thermal equation of state:

$$\frac{p}{\rho} = RT \quad [\text{term perf}] \quad (1)$$

Dynamic equation:

$$\frac{1}{\rho} dp + V dV = 0 \quad (2)$$

Speed of Sound:

$$a = \sqrt{\left(\frac{\partial p}{\partial \rho}\right)_s} = \sqrt{\gamma \left(\frac{\partial p}{\partial \rho}\right)_T} \quad (3)$$

$$a = \sqrt{\gamma \frac{p}{\rho}} = \sqrt{\gamma RT} \quad [\text{term perf}] \quad (36)$$

Mach Number:

$$M = \frac{V}{a} \quad (4)$$

Dynamic Pressure:

$$q = \frac{1}{2} \rho V^2 \quad (5)$$

$$q = \frac{\gamma}{2} p M^2 \quad (6)$$

From the dynamic equation and the speed of sound relation:

$$\frac{p}{\rho^\gamma} = \text{constant} = \frac{p_t}{\rho_t^\gamma} \quad [\text{isen, perf}] \quad (34)$$

From which:

$$\frac{p}{p_t} = \left(\frac{\rho}{\rho_t}\right)^\gamma = \left(\frac{T}{T_t}\right)^{\frac{\gamma}{\gamma-1}} = \left(\frac{a}{a_t}\right)^{\frac{2\gamma}{\gamma-1}} \quad [\text{isen, perf}] \quad (35)$$

Combining the above equations gives Bernoulli's equation for compressible flow:

$$\frac{\gamma}{\gamma-1} \left(\frac{p_t}{\rho_t}\right)^{\frac{\gamma-1}{\gamma}} \left(\frac{p}{p_t}\right)^{\frac{1}{\gamma}} + \frac{V^2}{2} = \frac{\gamma}{\gamma-1} \frac{p_t}{\rho_t} \quad [\text{isen, perf}] \quad (36)$$

Usefull Ratios

$$\frac{T}{T_t} = \left(1 + \frac{\gamma-1}{2} M^2\right)^{-1} \quad [\text{adiab, perf}] \quad (43)$$

$$\frac{p}{p_t} = \left(1 + \frac{\gamma-1}{2} M^2\right)^{-\frac{\gamma}{\gamma-1}} \quad [\text{isen, perf}] \quad (44)$$

$$\frac{\rho}{\rho_t} = \left(1 + \frac{\gamma-1}{2} M^2\right)^{-\frac{1}{\gamma-1}} \quad [\text{isen, perf}] \quad (45)$$

$$\frac{a}{a_t} = \left(1 + \frac{\gamma-1}{2} M^2\right)^{-\frac{1}{2}} \quad [\text{adiab, perf}] \quad (46)$$

1.2 Foundational principles

Idealized flow regimes

Turbulence

Mach regimes

Dimensionality of the flow

2 Analytical work

2.1 Scope and objectives

2.2 Framework for Analysis

Important assumptions

Regions of interest

Limits of the theory

2.3 Analytical Descriptions

Testing the waters. Lets do this.

3 Discussion

4 Conclusion

this is a test

List of Figures

List of Tables