Function 0

```
Block 0 (PC 0–8)
  0: DeclareGlobalVar  "test"
  1: CreateEnvironment r1
  2: CreateClosure     r1, r1, Function<test>1
  3: GetGlobalObject   r2
  4: PutById           r2, r1, 1, "test"
  5: LoadConstUndefined r2
  6: Mov               r1, r2
  7: Ret               r1
```

Unconditional

EXIT

Function 1

```
Block 0 (PC 0–17)
   0: CreateEnvironment r1
   1: LoadConstUndefined r2
   2: StoreNPToEnvironment r1, 0, r2
   3: LoadConstUndefined r2
   4: StoreNPToEnvironment r1, 1, r2
   5: LoadConstUndefined r2
   6: StoreNPToEnvironment r1, 2, r2
   7: LoadConstUInt8     r2, 42
   8: StoreNPToEnvironment r1, 0, r2
   9: LoadConstUInt8     r2, 10
  10: StoreNPToEnvironment r1, 1, r2
  11: LoadFromEnvironment r2, r1, 0
  12: LoadFromEnvironment r3, r1, 1
  13: Add                 r2, r2, r3
  14: StoreToEnvironment r1, 2, r2
  15: LoadFromEnvironment r1, r1, 2
  16: Ret                 r1
```

Unconditional

EXIT