

Министерство образования Республики Беларусь  
Учреждение образования  
«Брестский государственный технический университет»  
Кафедра ИИТ

**Лабораторная работа №10**

По дисциплине «СПП»

Выполнил:  
студент 3 курса  
группы ПО-5  
Брич М.Н.

Проверил:  
Крощенко А.А.

Брест, 2022

**Цель работы:** приобрести практические навыки разработки многооконных приложений на JavaFX для работы с базами данных.

### **Задание:**

На основе БД, разработанной в лабораторной работе №9, реализовать многооконное приложение-клиент, позволяющее выполнять основные операции над таблицей в БД (добавление, удаление, модификацию данных).

Основные требования к приложению:

- Для отображения выбирать таблицу с внешними ключами;
- Осуществлять вывод основных данных в табличном представлении;
- При выводе краткого представления записи в таблице (т.е. если выводятся не все поля), по щелчку мышкой на запись осуществлять вывод всех полей в подготовленные компоненты на форме;
- Для всех полей, представленных внешними ключами, выводить их текстовое представление из связанных таблиц (например, таблица-справочник «Времена года» содержит два поля – идентификатор и название сезона, в связанной таблице «Месяц года» есть внешний ключ на таблицу «Времена года»; в этом случае при выводе таблицы «Месяц года» нужно выводить название сезона, а не его идентификатор);
- При выводе предусмотреть упорядочивание по столбцу;
- Реализовать простейший фильтр данных по одному-двум полям;
- При добавлении новых данных в таблицу использовать дополнительное окно для ввода;
- При модификации данных можно использовать ту же форму, что и для добавления, но с внесенными актуальными значениями полей;
- При добавлении/модификации выводить варианты значений полей с внешним ключом с помощью выпадающего списка;
- При удалении данных осуществлять удаление записи, на которой в данный момент находится фокус.

### **Код программы:**

```
package FacultyCompany.Actions;

import javafx.scene.Scene;
import javafx.scene.control.Label;
import javafx.scene.layout.StackPane;
import javafx.scene.layout.VBox;
import javafx.stage.Modality;
import javafx.stage.Stage;

public class InfoDialog {
    public InfoDialog(Stage primaryStage, String groupname, String subjectname,
        Integer semesterid, Integer weekday, String lessonTime, String
        lecturerFullName) {
        StackPane secondaryLayout = new StackPane();

        final VBox vbox = new VBox();

        vbox.setSpacing(5);

        Label groupLabel = new Label("Group name: " + groupname);
        Label subjectLabel = new Label("Subject name: " + subjectname);
        Label semestrLabel = new Label("Semester id: " + semesterid);
        Label weekLabel = new Label("Week day: " + weekday);
        Label lessonLabel = new Label("Lesson time: " + lessonTime);
        Label lecturerNameLabel = new Label("Lecturer name: " + lecturerFullName);

        vbox.getChildren().addAll(groupLabel, subjectLabel, semestrLabel, weekLabel,
        lessonLabel, lecturerNameLabel);
        secondaryLayout.getChildren().addAll(vbox);

        Scene secondScene = new Scene(secondaryLayout, 250, 150);

        // New window (Stage)
        Stage newWindow = new Stage();
```

```

newWindow.setTitle("Information");
newWindow.setScene(secondScene);

// Specifies the modality for new window.
newWindow.initModality(Modality.WINDOW_MODAL);

// Specifies the owner Window (parent) for new window
newWindow.initOwner(primaryStage);

// Set position of second window, related to primary window.
newWindow.setX(primaryStage.getX() + 200);
newWindow.setY(primaryStage.getY() + 100);

newWindow.setHeight(200);
newWindow.setWidth(300);

newWindow.setResizable(false);

newWindow.show();
    }
}

package FacultyCompany.Actions;

import FacultyCompany.Core.RepositoryManager;
import FacultyCompany.Entities.*;

import javafx.collections.FXCollections;

import javafx.scene.Scene;
import javafx.scene.control.Button;
import javafx.scene.control.ComboBox;
import javafx.scene.control.Label;
import javafx.scene.control.TextField;
import javafx.scene.layout.StackPane;
import javafx.scene.layout.VBox;

import javafx.stage.Modality;
import javafx.stage.Stage;

import java.sql.SQLException;
import java.util.List;

public class TimeTableAddDialog {
    Label tittleLabel;
    Button addButton;

    Label weekDayLabel;
    TextField weekDayField;

    ComboBox<Subject> subjectComboBox;
    ComboBox<Group> groupComboBox;
    ComboBox<Lecturer> lecturerComboBox;
    ComboBox<Calendar> calendarComboBox;

    public TimeTableAddDialog(Stage primaryStage) {
        initControls();

        List<Subject> subjects;
        List<Group> groups;
        List<Lecturer> lecturers;
        List<Calendar> calendars;

        try {
            RepositoryManager repositoryManager = new RepositoryManager();

            subjects = repositoryManager.subjectRepository.GetAll();
            groups = repositoryManager.groupRepository.GetAll();
            lecturers = repositoryManager.lecturerRepository.GetAll();
            calendars = repositoryManager.calendarRepository.GetAll();

            var subjectObservableList = FXCollections.observableArrayList(subjects);
            var groupObservableList = FXCollections.observableArrayList(groups);
            var lecturerObservableList = FXCollections.observableArrayList(lecturers);

```

```

var calendarObservableList = FXCollections.observableArrayList(calendars);

subjectComboBox = new ComboBox<>(subjectObservableList);
groupComboBox = new ComboBox<>(groupObservableList);
lecturerComboBox = new ComboBox<>(lecturerObservableList);
calendarComboBox = new ComboBox<>(calendarObservableList);

subjectComboBox.setValue(subjectObservableList.get(0));
groupComboBox.setValue(groupObservableList.get(0));
lecturerComboBox.setValue(lecturerObservableList.get(0));
calendarComboBox.setValue(calendarObservableList.get(0));
}
catch (SQLException throwables) {
    throwables.printStackTrace();
}

StackPane secondaryLayout = new StackPane();
final VBox vbox = new VBox();

vbox.setSpacing(5);

vbox.getChildren().addAll(tittleLabel, weekDayLabel, weekDayField,
    new Label("Enter subject"), subjectComboBox,
    new Label("Enter group"), groupComboBox,
    new Label("Enter lecturer"), lecturerComboBox,
    new Label("Enter lesson"), calendarComboBox, addButton);
secondaryLayout.getChildren().addAll(vbox);

Scene secondScene = new Scene(secondaryLayout, 300, 240);

// New window (Stage)
Stage newWindow = new Stage();
newWindow.setTitle("Add new information");
newWindow.setScene(secondScene);

// Specifies the modality for new window.
newWindow.initModality(Modality.WINDOW_MODAL);

// Specifies the owner Window (parent) for new window
newWindow.initOwner(primaryStage);

// Set position of second window, related to primary window.
newWindow.setX(primaryStage.getX() + 200);
newWindow.setY(primaryStage.getY() + 200);

newWindow.setHeight(400);
newWindow.setWidth(250);
newWindow.setResizable(false);

newWindow.show();

addButton.setOnAction(event -> {
    Integer weekDay = Integer.parseInt(weekDayField.getText());

    Integer subjectId = subjectComboBox.getSelectionModel().getSelectedItem().getId();
    Integer groupId = groupComboBox.getSelectionModel().getSelectedItem().getId();
    Integer lecturerId = lecturerComboBox.getSelectionModel().getSelectedItem().getId();
    Integer calendarId = calendarComboBox.getSelectionModel().getSelectedItem().getId();

    if (weekDay > 7 || weekDay <= 0)
        return;

    try {
        RepositoryManager repositoryManager = new RepositoryManager();
        repositoryManager.timeTableRepository.Add(new TimeTable(groupId, subjectId,
lecturerId, weekDay, calendarId));
        newWindow.close();
    }
    catch (SQLException throwables) {
        throwables.printStackTrace();
    }
});
}

```

```

    public void initControls()
    {
        tittleLabel = new Label("Enter the information:");

        weekDayLabel = new Label("Week day");
        weekDayField = new TextField();

        addButton = new Button("Add the information");

        weekDayField.setMaxSize(50, 50);
    }
}

package FacultyCompany.Actions;

import FacultyCompany.Core.RepositoryManager;
import FacultyCompany.Entities.*;
import javafx.collections.FXCollections;
import javafx.scene.Scene;
import javafx.scene.control.Button;
import javafx.scene.control.ComboBox;
import javafx.scene.control.Label;
import javafx.scene.control.TextField;
import javafx.scene.layout.StackPane;
import javafx.scene.layout.VBox;
import javafx.stage.Modality;
import javafx.stage.Stage;

import java.sql.SQLException;
import java.util.List;

public class TimeTableUpdateDialog {
    Label tittleLabel;
    Button addButton;

    Label weekDayLabel;
    TextField weekDayField;

    ComboBox<Subject> subjectComboBox;
    ComboBox<Group> groupComboBox;
    ComboBox<Lecturer> lecturerComboBox;
    ComboBox<Calendar> calendarComboBox;

    public TimeTableUpdateDialog(Stage primaryStage, TimeTable table) {
        initControls();

        List<Subject> subjects;
        List<Group> groups;
        List<Lecturer> lecturers;
        List<Calendar> calendars;

        try {
            RepositoryManager repositoryManager = new RepositoryManager();

            subjects = repositoryManager.subjectRepository.GetAll();
            groups = repositoryManager.groupRepository.GetAll();
            lecturers = repositoryManager.lecturerRepository.GetAll();
            calendars = repositoryManager.calendarRepository.GetAll();

            var subjectObservableList = FXCollections.observableArrayList(subjects);
            var groupObservableList = FXCollections.observableArrayList(groups);
            var lecturerObservableList = FXCollections.observableArrayList(lecturers);
            var calendarObservableList = FXCollections.observableArrayList(calendars);

            subjectComboBox = new ComboBox<>(subjectObservableList);
            groupComboBox = new ComboBox<>(groupObservableList);
            lecturerComboBox = new ComboBox<>(lecturerObservableList);
            calendarComboBox = new ComboBox<>(calendarObservableList);

            subjectComboBox.setValue(subjectObservableList.get(table.getSubjectid() - 1));
            groupComboBox.setValue(groupObservableList.get(table.getGroupid() - 1));
            lecturerComboBox.setValue(lecturerObservableList.get(table.getLecturerid()));
            calendarComboBox.setValue(calendarObservableList.get(table.getLessonid() - 1));
        }
    }
}

```

```

        String text = Integer.toString(table.getWeekday());
        weekDayField.setText(text);
    }
    catch (SQLException throwables) {
        throwables.printStackTrace();
    }
}

StackPane secondaryLayout = new StackPane();
final VBox vbox = new VBox();

vbox.setSpacing(5);

vbox.getChildren().addAll(tittleLabel, weekDayLabel, weekDayField,
    new Label("Enter subject"), subjectComboBox,
    new Label("Enter group"), groupComboBox,
    new Label("Enter lecturer"), lecturerComboBox,
    new Label("Enter lesson"), calendarComboBox, addButton);
secondaryLayout.getChildren().addAll(vbox);

Scene secondScene = new Scene(secondaryLayout, 300, 240);

// New window (Stage)
Stage newWindow = new Stage();
newWindow.setTitle("Update cell");
newWindow.setScene(secondScene);

// Specifies the modality for new window.
newWindow.initModality(Modality.WINDOW_MODAL);

// Specifies the owner Window (parent) for new window
newWindow.initOwner(primaryStage);

// Set position of second window, related to primary window.
newWindow.setX(primaryStage.getX() + 200);
newWindow.setY(primaryStage.getY() + 200);

newWindow.setHeight(400);
newWindow.setWidth(250);
newWindow.setResizable(false);

newWindow.show();

addButton.setOnAction(event -> {
    Integer id = table.getId();

    Integer weekDay = Integer.parseInt(weekDayField.getText());
    Integer subjectId = subjectComboBox.getSelectionModel().getSelectedItem().getId();
    Integer groupId = groupComboBox.getSelectionModel().getSelectedItem().getId();
    Integer lecturerId = lecturerComboBox.getSelectionModel().getSelectedItem().getId();
    Integer calendarId = calendarComboBox.getSelectionModel().getSelectedItem().getId();

    if (weekDay > 7 || weekDay < 0)
        return;

    try {
        RepositoryManager repositoryManager = new RepositoryManager();
        repositoryManager.timeTableRepository.Update(new TimeTable(id, groupId,
            subjectId, lecturerId, weekDay, calendarId));
        newWindow.close();
    }
    catch (SQLException throwables) {
        throwables.printStackTrace();
    }
});
}

public void initControls()
{
    tittleLabel = new Label("Enter the information:");

    weekDayLabel = new Label("Week day");
    weekDayField = new TextField();

    addButton = new Button("Update cell");

```

```

        weekDayField.setMaxSize(50, 50);
    }
}

package FacultyCompany.Constants;

public class ConfigurationConstants
{
    public static final String URL = "jdbc:postgresql://localhost:5433/NordSPP";
    public static final String USER = "postgres";
    public static final String PASSWORD = "nird12";
}

package FacultyCompany.Core;

import FacultyCompany.Constants.ConfigurationConstants;

import java.sql.DriverManager;
import java.sql.SQLException;

public final class Connection {

    public java.sql.Connection GetConnection() throws SQLException {
        var connectionURL = ConfigurationConstants.URL;
        var connectionUser = ConfigurationConstants.USER;
        var connectionPassword = ConfigurationConstants.PASSWORD;

        var connection = DriverManager.getConnection(connectionURL, connectionUser,
connectionPassword);
        return connection;
    }
}

package FacultyCompany.Core;

import FacultyCompany.Entities.*;
import FacultyCompany.Persistence.Interfaces.IBaseRepository;
import FacultyCompany.Persistence.Repositories.*;

import java.sql.SQLException;

public class RepositoryManager {
    public IBaseRepository<Subject> subjectRepository;
    public IBaseRepository<Group> groupRepository;
    public IBaseRepository<Lecturer> lecturerRepository;
    public IBaseRepository<Calendar> calendarRepository;
    public IBaseRepository<TimeTable> timeTableRepository;

    private static Connection connection = new Connection();

    public RepositoryManager() throws SQLException {
        this.subjectRepository = new SubjectRepository(connection.GetConnection());
        this.groupRepository = new GroupRepository(connection.GetConnection());
        this.lecturerRepository = new LecturerRepository(connection.GetConnection());
        this.calendarRepository = new CalendarRepository(connection.GetConnection());
        this.timeTableRepository = new TimeTableRepository(connection.GetConnection());
    }
}

package FacultyCompany.Entities;

public class Calendar {
    private int id;
    private int semesterid;
    private int weekday;
    private int lessonid;
    private String lesstime;

    public Calendar() {}

    public Calendar(int semesterId, int weekDay, int lessonId, String lessonTime) {
        this.semesterid = semesterId;
        this.weekday = weekDay;
        this.lessonid = lessonId;
    }
}

```

```

        this.lesstime = lessonTime;
    }

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public int getSemesterid() {
        return semesterid;
    }

    public void setSemesterid(int semesterId) {
        this.semesterid = semesterId;
    }

    public int getWeekday() {
        return weekday;
    }

    public void setWeekday(int weekDay) {
        this.weekday = weekDay;
    }

    public int getLessonid() {
        return lessonid;
    }

    public void setLessonid(int lessonId) {
        this.lessonid = lessonId;
    }

    public String getLesstime() {
        return lesstime;
    }

    public void setLesstime(String lessonTime) {
        this.lesstime = lessonTime;
    }

    @Override
    public String toString()
    {
        return getLesstime();
    }
}

package FacultyCompany.Entities;

public class Group {
    private int id;
    private String groupname;

    public Group() {}

    public Group(String groupName) {
        this.groupname = groupName;
    }

    public String getGroupname() {
        return groupname;
    }

    public void setGroupname(String groupName) {
        this.groupname = groupName;
    }

    public int getId() {
        return id;
    }
}

```



```

        public void setId(int id) {
            this.id = id;
        }

        @Override
        public String toString()
        {
            return getGroupname();
        }
    }

package FacultyCompany.Entities;

public class Lecturer {
    private int id;
    private String firstname;
    private String lastname;
    private String patronymic;

    public Lecturer() {}

    public Lecturer(String firstName, String lastName, String patronymic) {
        this.firstname = firstName;
        this.lastname = lastName;
        this.patronymic = patronymic;
    }

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstName) {
        this.firstname = firstName;
    }

    public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastName) {
        this.lastname = lastName;
    }

    public String getPatronymic() {
        return patronymic;
    }

    public void setPatronymic(String patronymic) {
        this.patronymic = patronymic;
    }

    @Override
    public String toString()
    {
        return getFirstname() + " " + getLastname();
    }
}

package FacultyCompany.Entities;

public class Subject {
    private int id;
    private String subjectName;

    public Subject() {}

```

```

    public Subject(String subjectName) {
        this.subjectName = subjectName;
    }

    public String getSubjectName() {
        return subjectName;
    }

    public void setSubjectName(String subjectName) {
        this.subjectName = subjectName;
    }

    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    @Override
    public String toString()
    {
        return getSubjectName();
    }
}

package FacultyCompany.Entities;

public class TimeTable {
    private int id;

    private int groupid;
    private Group group;

    private int subjectid;
    private Subject subject;

    private int lecturerid;
    private Lecturer lecturer;

    private int weekday;

    private int lessonid;
    private Calendar calendar;

    public TimeTable() {}

    public TimeTable(int groupId, int subjectId, int lecturerId, int weekDay, int lessonId) {
        this.groupid = groupId;
        this.subjectid = subjectId;
        this.lecturerid = lecturerId;
        this.weekday = weekDay;
        this.lessonid = lessonId;
    }

    public TimeTable(int id) {
        this.id = id;
    }

    public TimeTable(int id, int groupId, int subjectId, int lecturerId, int weekDay, int lessonId) {
        this.id = id;
        this.groupid = groupId;
        this.subjectid = subjectId;
        this.lecturerid = lecturerId;
        this.weekday = weekDay;
        this.lessonid = lessonId;
    }

    public int getId() {
        return id;
    }
}

```

```
public void setId(int id) {
    this.id = id;
}

public int getGroupid() {
    return groupid;
}

public void setGroupid(int groupId) {
    this.groupid = groupId;
}

public Group getGroup() {
    return group;
}

public void setGroup(Group group) {
    this.group = group;
}

public int getSubjectid() {
    return subjectid;
}

public void setSubjectid(int subjectId) {
    this.subjectid = subjectId;
}

public Subject getSubject() {
    return subject;
}

public void setSubject(Subject subject) {
    this.subject = subject;
}

public int getLecturerid() {
    return lecturerid;
}

public void setLecturerid(int lecturerId) {
    this.lecturerid = lecturerId;
}

public String getLecturerName() {
    return lecturer.getFirstname() + " " + lecturer.getLastname();
}

public Lecturer getLecturer() {
    return lecturer;
}

public void setLecturer(Lecturer lecturer) {
    this.lecturer = lecturer;
}

public int getWeekday() {
    return weekday;
}

public void setWeekday(int weekDay) {
    this.weekday = weekDay;
}

public int getLessonid() {
    return lessonid;
}

public void setLessonid(int lessonId) {
    this.lessonid = lessonId;
}

public Calendar getCalendar() {
    return calendar;
}
```

```

    }

    public void setCalendar(Calendar calendar) {
        this.calendar = calendar;
    }
}

package FacultyCompany.Persistence.Interfaces;

import java.sql.SQLException;
import java.util.ArrayList;

public interface IBaseRepository<T> {
    T Add(T entity) throws SQLException;
    void Update(T entity) throws SQLException;
    void Delete(T entity) throws SQLException;
    T GetByIdOrNull(int id) throws SQLException;
    ArrayList<T> GetAll() throws SQLException;
}

package FacultyCompany.Persistence.Repositories;

import FacultyCompany.Entities.Calendar;
import FacultyCompany.Persistence.Interfaces.IBaseRepository;

import java.sql.Connection;
import java.sql.SQLException;
import java.sql.Statement;
import java.util.ArrayList;

public class CalendarRepository implements IBaseRepository<Calendar> {

    private final Connection connection;

    public CalendarRepository(Connection connection) {
        this.connection = connection;
    }

    @Override
    public Calendar Add(Calendar entity) throws SQLException {
        var query =
            "INSERT INTO public.calendar( " +
                " semesterid, weekday, lessonid, lesstime) " +
                " VALUES (?, ?, ?, ?)";

        var statement = connection.prepareStatement(query, Statement.RETURN_GENERATED_KEYS);
        statement.setInt(1, entity.getSemesterid());
        statement.setInt(2, entity.getWeekday());
        statement.setInt(3, entity.getLessonid());
        statement.setString(4, entity.getLesstime());

        statement.execute();

        var generatedKeys = statement.getGeneratedKeys();
        generatedKeys.next();
        entity.setId(generatedKeys.getInt(1));

        return entity;
    }

    @Override
    public void Update(Calendar entity) throws SQLException {
        var query = "UPDATE public.calendar " +
            " SET semesterid=?, weekday=?, lessonid=?, lesstime=? " +
            " WHERE id=?";

        var statement = connection.prepareStatement(query);
        statement.setInt(1, entity.getSemesterid());
        statement.setInt(2, entity.getWeekday());
        statement.setInt(3, entity.getLessonid());
        statement.setString(4, entity.getLesstime());
        statement.setInt(5, entity.getId());

        statement.executeUpdate();
    }
}

```

```

    }

    @Override
    public void Delete(Calendar entity) throws SQLException {
        var query = "DELETE FROM public.calendar" +
            " WHERE id=?";
        var statement = connection.prepareStatement(query);
        statement.setInt(1, entity.getId());

        statement.executeUpdate();
    }

    @Override
    public Calendar GetByIdOrNull(int id) throws SQLException {
        var query =
            "SELECT * FROM public.calendar" +
            " WHERE Id = ?";

        var statement = connection.prepareStatement(query);
        statement.setInt(1, id);

        var reader = statement.executeQuery();
        if(reader.next())
        {
            var result = new Calendar();
            result.setId(reader.getInt("id"));
            result.setLessonid(reader.getInt("lessonid"));
            result.setSemesterid(reader.getInt("semesterid"));
            result.setWeekday(reader.getInt("weekday"));
            result.setLessovertime(reader.getString("lessovertime"));
            return result;
        }

        return null;
    }

    @Override
    public ArrayList<Calendar> GetAll() throws SQLException {
        var query =
            "SELECT * FROM public.calendar Order by id";

        var statement = connection.prepareStatement(query);

        var reader = statement.executeQuery();
        var result = new ArrayList<Calendar>();
        while (reader.next())
        {
            var calendar = new Calendar();
            calendar.setId(reader.getInt("id"));
            calendar.setLessonid(reader.getInt("lessonid"));
            calendar.setSemesterid(reader.getInt("semesterid"));
            calendar.setWeekday(reader.getInt("weekday"));
            calendar.setLessovertime(reader.getString("lessovertime"));

            result.add(calendar);
        }

        return result;
    }
}

package FacultyCompany.Persistence.Repositories;

import FacultyCompany.Entities.Group;
import FacultyCompany.Persistence.Interfaces.IBaseRepository;

import java.sql.Connection;
import java.sql.SQLException;
import java.sql.Statement;
import java.util.ArrayList;

public class GroupRepository implements IBaseRepository<Group> {
    private final Connection connection;

```

```

public GroupRepository(Connection connection) {
    this.connection = connection;
}

@Override
public Group Add(Group entity) throws SQLException {
    var query =
        "INSERT INTO public.groups(" +
        "    groupname)" +
        "    VALUES (?)";

    var statement = connection.prepareStatement(query, Statement.RETURN_GENERATED_KEYS);
    statement.setString(1, entity.getGroupname());

    statement.execute();

    var generatedKeys = statement.getGeneratedKeys();
    generatedKeys.next();
    entity.setId(generatedKeys.getInt(1));

    return entity;
}

@Override
public void Update(Group entity) throws SQLException {
    var query =
        "UPDATE public.groups" +
        "    SET groupname = ?" +
        "    WHERE id = ?";

    var statement = connection.prepareStatement(query);
    statement.setString(1, entity.getGroupname());
    statement.setInt(2, entity.getId());

    statement.executeUpdate();
}

@Override
public void Delete(Group entity) throws SQLException {
    var query = "DELETE FROM public.groups" +
        "    WHERE id=?";

    var statement = connection.prepareStatement(query);
    statement.setInt(1, entity.getId());

    statement.executeUpdate();
}

@Override
public Group GetByIdOrNull(int id) throws SQLException {
    var query =
        "SELECT * FROM public.groups" +
        "    WHERE Id = ?";

    var statement = connection.prepareStatement(query);
    statement.setInt(1, id);

    var reader = statement.executeQuery();
    if(reader.next())
    {
        var result = new Group();
        result.setId(reader.getInt("id"));
        result.setGroupname(reader.getString("groupname"));
        return result;
    }

    return null;
}

@Override
public ArrayList<Group> GetAll() throws SQLException {
    var query =
        "SELECT * FROM public.groups Order by id";

    var statement = connection.prepareStatement(query);

```

```

        var reader = statement.executeQuery();
        var result = new ArrayList<Group>();
        while (reader.next())
        {
            var group = new Group();
            group.setId(reader.getInt("id"));
            group.setGroupname(reader.getString("groupname"));

            result.add(group);
        }

        return result;
    }
}

package FacultyCompany.Persistence.Repositories;

import FacultyCompany.Entities.Lecturer;
import FacultyCompany.Persistence.Interfaces.IBaseRepository;

import java.sql.Connection;
import java.sql.SQLException;
import java.sql.Statement;
import java.util.ArrayList;

public class LecturerRepository implements IBaseRepository<Lecturer> {

    private final Connection connection;

    public LecturerRepository(Connection connection) {
        this.connection = connection;
    }

    @Override
    public Lecturer Add(Lecturer entity) throws SQLException {
        var query =
            "INSERT INTO public.lecturers(" +
                "firstname, lastname, patronymic)" +
                " VALUES (?, ?, ?)";

        var statement = connection.prepareStatement(query, Statement.RETURN_GENERATED_KEYS);
        statement.setString(1, entity.getFirstname());
        statement.setString(2, entity.getLastname());
        statement.setString(3, entity.getPatronymic());

        statement.execute();

        var generatedKeys = statement.getGeneratedKeys();
        generatedKeys.next();
        entity.setId(generatedKeys.getInt(1));

        return entity;
    }

    @Override
    public void Update(Lecturer entity) throws SQLException {
        var query =
            "UPDATE public.lecturers" +
                " SET firstname=?, lastname=?, patronymic=?" +
                " WHERE id=?";

        var statement = connection.prepareStatement(query);
        statement.setString(1, entity.getFirstname());
        statement.setString(2, entity.getLastname());
        statement.setString(3, entity.getPatronymic());
        statement.setInt(4, entity.getId());

        statement.executeUpdate();
    }

    @Override
    public void Delete(Lecturer entity) throws SQLException {

```

```

        var query = "DELETE FROM public.lecturers" +
            " WHERE id=?";
        var statement = connection.prepareStatement(query);
        statement.setInt(1, entity.getId());

        statement.executeUpdate();
    }

    @Override
    public Lecturer GetByIdOrNull(int id) throws SQLException {
        var query =
            "SELECT * FROM public.lecturers" +
            " WHERE Id = ?";

        var statement = connection.prepareStatement(query);
        statement.setInt(1, id);

        var reader = statement.executeQuery();
        if(reader.next())
        {
            var result = new Lecturer();
            result.setId(reader.getInt("id"));
            result.setFirstname(reader.getString("firstname"));
            result.setLastname(reader.getString("lastname"));
            result.setPatronymic(reader.getString("patronymic"));
            return result;
        }

        return null;
    }

    @Override
    public ArrayList<Lecturer> GetAll() throws SQLException {
        var query =
            "SELECT * FROM public.lecturers Order by id";

        var statement = connection.prepareStatement(query);

        var reader = statement.executeQuery();
        var result = new ArrayList<Lecturer>();
        while (reader.next())
        {
            var lecturer = new Lecturer();
            lecturer.setId(reader.getInt("id"));
            lecturer.setFirstname(reader.getString("firstname"));
            lecturer.setLastname(reader.getString("lastname"));
            lecturer.setPatronymic(reader.getString("patronymic"));

            result.add(lecturer);
        }

        return result;
    }
}

package FacultyCompany.Persistence.Repositories;

import FacultyCompany.Entities.Subject;
import FacultyCompany.Persistence.Interfaces.IBaseRepository;

import java.sql.Connection;
import java.sql.SQLException;
import java.sql.Statement;
import java.util.ArrayList;

public class SubjectRepository implements IBaseRepository<Subject> {

    private final Connection connection;

    public SubjectRepository(Connection connection) {
        this.connection = connection;
    }

    @Override

```



```

public Subject Add(Subject entity) throws SQLException {
    var query =
        "INSERT INTO public.subjects(" +
            " subjectname)" +
            " VALUES (?)";

    var statement = connection.prepareStatement(query, Statement.RETURN_GENERATED_KEYS);
    statement.setString(1, entity.getSubjectName());

    statement.execute();

    var generatedKeys = statement.getGeneratedKeys();
    generatedKeys.next();
    entity.setId(generatedKeys.getInt(1));

    return entity;
}

@Override
public void Update(Subject entity) throws SQLException {
    var query =
        "UPDATE public.subjects" +
            " SET subjectname = ?" +
            " WHERE id = ?";

    var statement = connection.prepareStatement(query);
    statement.setString(1, entity.getSubjectName());
    statement.setInt(2, entity.getId());

    statement.executeUpdate();
}

@Override
public void Delete(Subject entity) throws SQLException {
    var query = "DELETE FROM public.subjects" +
        " WHERE id=?";

    var statement = connection.prepareStatement(query);
    statement.setInt(1, entity.getId());

    statement.executeUpdate();
}

@Override
public Subject GetByIdOrNull(int id) throws SQLException {
    var query =
        "SELECT * FROM public.subjects" +
            " WHERE Id = ? " +
            "Order by id";

    var statement = connection.prepareStatement(query);
    statement.setInt(1, id);

    var reader = statement.executeQuery();
    if(reader.next())
    {
        var result = new Subject();
        result.setId(reader.getInt("id"));
        result.setSubjectName(reader.getString("subjectname"));
        return result;
    }

    return null;
}

@Override
public ArrayList<Subject> GetAll() throws SQLException {
    var query =
        "SELECT * FROM public.subjects Order by id";

    var statement = connection.prepareStatement(query);

    var reader = statement.executeQuery();
    var result = new ArrayList<Subject>();

```

```

        while (reader.next())
        {
            var subject = new Subject();
            subject.setId(reader.getInt("id"));
            subject.setSubjectName(reader.getString("subjectname"));

            result.add(subject);
        }

        return result;
    }
}

package FacultyCompany.Persistence.Repositories;

import FacultyCompany.Entities.TimeTable;
import FacultyCompany.Persistence.Interfaces.IBaseRepository;

import java.sql.Connection;
import java.sql.SQLException;
import java.sql.Statement;
import java.util.ArrayList;

public class TimeTableRepository implements IBaseRepository<TimeTable> {

    private final Connection connection;

    public TimeTableRepository(Connection connection) {
        this.connection = connection;
    }

    @Override
    public TimeTable Add(TimeTable entity) throws SQLException {
        var query =
            "INSERT INTO public.timetable(" +
                "groupid, subjectid, lecturerid, weekday, lessonid)" +
            " VALUES (?, ?, ?, ?, ?);";

        var statement = connection.prepareStatement(query, Statement.RETURN_GENERATED_KEYS);
        statement.setInt(1, entity.getGroupid());
        statement.setInt(2, entity.getSubjectid());
        statement.setInt(3, entity.getLecturerid());
        statement.setInt(4, entity.getWeekday());
        statement.setInt(5, entity.getLessonid());

        statement.execute();

        var generatedKeys = statement.getGeneratedKeys();
        generatedKeys.next();
        entity.setId(generatedKeys.getInt(1));

        return entity;
    }

    @Override
    public void Update(TimeTable entity) throws SQLException {

        var query = "UPDATE public.timetable " +
            " SET groupid=?, subjectid=?, lecturerid=?, weekday=?, lessonid=? " +
            " WHERE id=?";

        var statement = connection.prepareStatement(query);
        statement.setInt(1, entity.getGroupid());
        statement.setInt(2, entity.getSubjectid());
        statement.setInt(3, entity.getLecturerid());
        statement.setInt(4, entity.getWeekday());
        statement.setInt(5, entity.getLessonid());
        statement.setInt(6, entity.getId());

        statement.executeUpdate();
        return;
    }

    @Override

```

```

public void Delete(TimeTable entity) throws SQLException {
    var query = "DELETE FROM public.timetable" +
        " WHERE id=?";

    var statement = connection.prepareStatement(query);
    statement.setInt(1, entity.getId());

    statement.executeUpdate();
}

@Override
public TimeTable GetByIdOrNull(int id) throws SQLException {
    var query =
        "SELECT * FROM public.timetable" +
        " WHERE Id = ?";

    var statement = connection.prepareStatement(query);
    statement.setInt(1, id);

    var reader = statement.executeQuery();
    if(reader.next())
    {
        var result = new TimeTable();
        result.setId(reader.getInt("id"));
        result.setLessonid(reader.getInt("lessonid"));
        result.setWeekday(reader.getInt("weekday"));
        result.setGroupid(reader.getInt("groupid"));
        result.setSubjectid(reader.getInt("subjectid"));
        return result;
    }

    return null;
}

@Override
public ArrayList<TimeTable> GetAll() throws SQLException {
    var query =
        "SELECT * FROM public.timetable Order by id";

    var statement = connection.prepareStatement(query);

    var reader = statement.executeQuery();
    var result = new ArrayList<TimeTable>();
    while (reader.next())
    {
        var timeTable = new TimeTable();
        timeTable.setId(reader.getInt("id"));
        timeTable.setGroupid(reader.getInt("groupid"));
        timeTable.setSubjectid(reader.getInt("subjectid"));
        timeTable.setLecturerid(reader.getInt("lecturerid"));
        timeTable.setWeekday(reader.getInt("weekday"));
        timeTable.setLessonid(reader.getInt("lessonid"));

        result.add(timeTable);
    }

    return result;
}
}

package FacultyCompany.ViewModels;

import FacultyCompany.Entities.*;

public class TimeTableViewModel {
    private int id;

    private String groupname;

    private String subjectName;

    private String lecturerFullName;

    private int semesterid;

```

```

private int weekday;
private String lessontime;

private int groupid;
private int subjectid;
private int lecturerid;
private int lessonid;

public TimeTableViewModel(TimeTable table) {
    this.id = table.getId();
    this.groupname = table.getGroup().getGroupname();
    this.subjectName = table.getSubject().getSubjectName();
    this.semesterid = table.getCalendar().getSemesterid();
    this.weekday = table.getWeekday();
    this.lessontime = table.getCalendar().getLessontime();
    this.groupid = table.getGroupid();
    this.subjectid = table.getSubjectid();
    this.lessonid = table.getLessonid();
    this.lecturerFullName = table.getLecturerName();
}

public int getId() {
    return id;
}

public void setId(int id) {
    this.id = id;
}

public String getGroupname() {
    return groupname;
}

public void setGroupname(String groupname) {
    this.groupname = groupname;
}

public String getSubjectName() {
    return subjectName;
}

public void setSubjectName(String subjectName) {
    this.subjectName = subjectName;
}

public int getSemesterid() {
    return semesterid;
}

public void setSemesterid(int semesterid) {
    this.semesterid = semesterid;
}

public int getWeekday() {
    return weekday;
}

public void setWeekday(int weekday) {
    this.weekday = weekday;
}

public int getLessonid() {
    return lessonid;
}

public void setLessonid(int lessonid) {
    this.lessonid = lessonid;
}

public String getLessontime() {
    return lessontime;
}

public void setLessontime(String lessontime) {

```

```

        this.lesstime = lesstime;
    }

    public String getLecturerFullName() {
        return lecturerFullName;
    }
}

```

## App

```

package FacultyCompany;

import FacultyCompany.Actions.InfoDialog;
import FacultyCompany.Actions.TimeTableAddDialog;
import FacultyCompany.Actions.TimeTableUpdateDialog;
import FacultyCompany.Core.RepositoryManager;
import FacultyCompany.Entities.*;
import FacultyCompany.ViewModels.TimeTableViewModel;
import javafx.application.Application;
import javafx.collections.FXCollections;
import javafx.fxml.FXMLLoader;
import javafx.geometry.Insets;
import javafx.scene.Parent;
import javafx.scene.Scene;
import javafx.scene.control.Button;
import javafx.scene.control.Label;
import javafx.scene.control.TableColumn;
import javafx.scene.control.TableView;
import javafx.scene.control.cell.PropertyValueFactory;
import javafx.scene.layout.GridPane;
import javafx.scene.layout.VBox;
import javafx.stage.Stage;

import java.sql.SQLException;

import java.util.ArrayList;

public class App extends Application {
    private static RepositoryManager repositoryManager;

    public App() throws SQLException {
        repositoryManager = new RepositoryManager();
    }

    TableView<TimeTableViewModel> tableTimeTables;

    @Override
    public void start(Stage primaryStage) throws Exception {
        var timeTables= repositoryManager.timeTableRepository.GetAll();

        var timeTablesWithData = convertWithData(timeTables);

        ArrayList<TimeTableViewModel> VmTimeTable = new ArrayList<>();

        timeTablesWithData.forEach(t -> {
            VmTimeTable.add(new TimeTableViewModel(t));
        });

        var observableTimeTables = FXCollections.observableArrayList(VmTimeTable);

        tableTimeTables = new TableView<>(observableTimeTables);

        tableTimeTables.setColumnResizePolicy(TableView.CONSTRAINED_RESIZE_POLICY);
        tableTimeTables.setPrefSize(720,200);

        TableColumn<TimeTableViewModel, Integer> idColumn = new TableColumn<>("Id");
        idColumn.setCellValueFactory(new PropertyValueFactory<>("id"));
        tableTimeTables.getColumns().add(idColumn);

        TableColumn<TimeTableViewModel, String> groupnameColumn = new TableColumn<>("Group
Name");
        groupnameColumn.setCellValueFactory(new PropertyValueFactory<>("groupname"));
        tableTimeTables.getColumns().add(groupnameColumn);
    }
}

```

```

        TableColumn<TimeTableViewModel, String> subjectNameColumn = new TableColumn<>("Subject
Name");
        subjectNameColumn.setCellValueFactory(new PropertyValueFactory<>("subjectName"));
        tableTimeTables.getColumns().add(subjectNameColumn);

        TableColumn<TimeTableViewModel, Integer> semesteridColumn = new TableColumn<>("Semestre
Id");
        semesteridColumn.setCellValueFactory(new PropertyValueFactory<>("semesterid"));
        tableTimeTables.getColumns().add(semesteridColumn);

        TableColumn<TimeTableViewModel, Integer> weekdayColumn = new TableColumn<>("Week Day");
        weekdayColumn.setCellValueFactory(new PropertyValueFactory<>("weekday"));
        tableTimeTables.getColumns().add(weekdayColumn);

        TableColumn<TimeTableViewModel, String> lesstontimeColumn = new TableColumn<>("Lesson
Time");
        lesstontimeColumn.setCellValueFactory(new PropertyValueFactory<>("lesstontime"));
        tableTimeTables.getColumns().add(lesstontimeColumn);

        executeRefresh();

        final VBox vbox = new VBox();
        vbox.setSpacing(5);
        vbox.setPadding(new Insets(10, 10, 10, 10));
        vbox.getChildren().addAll(new Label("TimeTable"), tableTimeTables);

        Button addCellButton = new Button();
        addCellButton.setText("Add a new cell");

        addCellButton.setOnAction(event -> {
            new TimeTableAddDialog(primaryStage);
        });

        vbox.getChildren().addAll(addCellButton);

        Button infoButton = new Button();
        infoButton.setText("Cell's details");

        infoButton.setOnAction(event -> {
            TimeTableViewModel infoTimeTable =
tableTimeTables.getSelectionModel().getSelectedItem().get(0);
            new InfoDialog(primaryStage, infoTimeTable.getGroupname(),
infoTimeTable.getSubjectName(), infoTimeTable.getSemesterid(),
                infoTimeTable.getWeekday(), infoTimeTable.getLesstontime(),
infoTimeTable.getLecturerFullName());
        });

        vbox.getChildren().addAll(infoButton);

        Button updateButton = new Button();
        updateButton.setText("Update cell");

        updateButton.setOnAction(event -> {
            TimeTableViewModel updateTimeTable =
tableTimeTables.getSelectionModel().getSelectedItem().get(0);
            TimeTable vmtable = new TimeTable();

            try {
                vmtable =
repositoryManager.timeTableRepository.GetByIdOrNull(updateTimeTable.getId());
            }
            catch (SQLException throwables) {
                throwables.printStackTrace();
            }

            new TimeTableUpdateDialog(primaryStage, vmtable);
        });

        vbox.getChildren().addAll(updateButton);

        Button deleteCellButton = new Button();
        deleteCellButton.setText("Delete cell");

        deleteCellButton.setOnAction(event -> {

```

```

        try {
            executeDelete();
            executeRefresh();
        }
        catch (SQLException throwables) {
            throwables.printStackTrace();
        }
    });

    vbox.getChildren().addAll(deleteCellButton);

    Button refreshCellButton = new Button();
    refreshCellButton.setText("Refresh table");

    refreshCellButton.setOnAction(event -> {
        try {
            executeRefresh();
        }
        catch (SQLException throwables) {
            throwables.printStackTrace();
        }
    });
    vbox.getChildren().addAll(refreshCellButton);
    Parent root = FXMLLoader.load(getClass().getResource("/sample.fxml"));
    primaryStage.setTitle("TimeTable");

    Scene scene = new Scene(root, 500, 500);
    ((GridPane) scene.getRoot()).getChildren().addAll(vbox);
    primaryStage.setScene(scene);

    primaryStage.setHeight(425);
    primaryStage.setWidth(550);

    primaryStage.setResizable(false);

    primaryStage.show();
}

public static void main(String[] args) {
    launch(args);
}

private void executeRefresh() throws SQLException {
    tableTimeTables.getItems().clear();

    var timeTables= repositoryManager.timeTableRepository.GetAll();

    var timeTablesWithData = convertWithData(timeTables);
    ArrayList<TimeTableViewModel> VmTimeTable = new ArrayList<>();

    timeTablesWithData.forEach(t -> {
        VmTimeTable.add(new TimeTableViewModel(t));
    });

    var observableTimeTables = FXCollections.observableArrayList(VmTimeTable);

    tableTimeTables.getItems().addAll(observableTimeTables);
}

private void executeDelete() throws SQLException {
    TimeTableViewModel deletedTimeTable =
tableTimeTables.getSelectionModel().getSelectedItem().get(0);
    repositoryManager.timeTableRepository.Delete(new TimeTable(deletedTimeTable.getId()));
}

public static ArrayList<TimeTable> convertWithData(ArrayList<TimeTable> table) {
    table.forEach(t -> {
        try {
            t.setGroup(repositoryManager.groupRepository.GetByIdOrNull(t.getGroupid()));

t.setSubject(repositoryManager.subjectRepository.GetByIdOrNull(t.getSubjectid()));

t.setLecturer(repositoryManager.lecturerRepository.GetByIdOrNull(t.getLecturerid()));

```


```

t.setCalendar(repositoryManager.calendarRepository.GetByIdOrNull(t.getLessonid()));
    }
    catch (SQLException throwables) {
        throwables.printStackTrace();
    }
});

return table;
}
}

```

## Тестирование:



Индексы									
Действие	Имя индекса	Тип	Уникальный	Упакован	Столбец	Уникальных элементов	Сравнение	Null	Комментарий
Изменить  Удалить	PRIMARY	BTREE	Да	Нет	ID 2	2	A	Нет	
Изменить  Удалить	WeekDay	BTREE	Нет	Нет	WeekDay 2	2	A	Да	
Изменить  Удалить	LecturerID	BTREE	Нет	Нет	LecturerID 1	1	A	Да	
Изменить  Удалить	GroupID	BTREE	Нет	Нет	GroupID 1	1	A	Да	
Изменить  Удалить	LessonID	BTREE	Нет	Нет	LessonID 2	2	A	Да	
Изменить  Удалить	SubjectID	BTREE	Нет	Нет	SubjectID 2	2	A	Да	

Lab10

Расписание

Id	Group Na...	Subject N...	Semestre Id	Week Day	Lesson Ti...
2	PO-5	Math	6	4	12:00 - 13:20
4	PO-5	Physics	7	3	13:40 - 15:10

Добавить

Детально

Изменить

Удалить

Обновить таблицу

Добавить элемент

Добавить новый элемент:

День недели

Введите subject


Введите group

Введите lecturer

Введите lesson

Добавить





**Выводы:** в ходе выполнения лабораторной работы были приобретены практические навыки разработки многооконных приложений на JavaFX для работы с базами данных.