EMSSON

— SIGNATURE SOLUTION · INDUSTRIAL SAFETY

SMART ILS

MULTISIG SMART LOCKING SYSTEM

Worker participation

Mobile app · operations

Industrial safety solution



An industrial safety solution for clearer control of lockout procedures and work status.

SMART ILS / SILS-920-LBN

LOCK THE ENERGY. CONNECT EVERY WORKER.

— 01 / SOLUTION OVERVIEW

One device, participation by each worker

SMART ILS는 smart lock · Mobile app · operations을 연결하는 현장 잠금 솔루션입니다.

01 Smart lock
Field lock device

02 Mobile app
Worker authentication · participation

03 Operations
상태·History check

— WHY SMART ILS

From traditional lockout
to connected safety management

Worker participation
Supports an operating structure where multiple workers can use one smart lock together. Permissions and participation are configured for the site.

Mobile access
Configure the system to check lock/unlock procedures and device status through a smartphone app.

Group · multi-party confirmation
Designed to operate manager and worker lockout procedures by group and confirm participation status.

Work history
Supports checking work status and history for field operating records.

Connects the lock, workers and work information in one flow.

SMART ILS key features

Supports field lockout work by connecting the product, app and operating system.

01 IoT smart lock

Manages lock status based on a physical locking device.

02 Mobile app integration

Selects devices and performs lock/unlock procedures on a smartphone.

03 MULTISIG

Supports lock participation and confirmation by multiple workers.

04 Group lock operations

Configures manager and worker group procedures for the site.

05 HMI status monitoring

Can be configured to check device and work status in an integrated environment.

06 Work history

Checks work and user history for operating records.

Review together for field deployment

Target equipment · user permissions · communications · HMI/server integration · installation · maintenance

Actual features and integration scope are agreed with site safety rules and operating standards.

— 03 / FIELD APPLICATION

SMART ILS in the field

Install the smart lock on equipment or a lockout target and check its status through the mobile app.



This field photo is for explaining product application. The actual configuration may vary by site conditions.

Field device

Install the smart lock on the target and check device information.

Mobile check

Check the device and status in the app and follow the procedure based on permissions.

Operating history

Check and manage work status and history according to site standards.

Connecting product, workers and operations

Field device의 상태 확인, 작업자별 참여, 작업 완료 후 History check을 하나의 운영 흐름으로 검토합니다.

A clear lockout procedure from start to finish

Detailed permissions and approvals are configured according to site safety rules and operating standards.

01 Work registration · user authentication

Confirm the target and participants, then verify user permissions in the app.

02 Target device check

Check the equipment name, device ID and location to select the correct target.

03 Lock participation

Managers and workers participate in lockout according to the field procedure.

04 Work status check

Check lock status and participation before maintenance work.

05 Work completion · unlock

Confirm completion and personnel withdrawal, then unlock through the approved procedure.

06 History check

Check status and history after completion and manage operating records.

Safety operating principle

The smart lock does not replace energy isolation or work-permit procedures. It must be operated with site safety procedures, including isolation checks, residual-energy control and worker confirmation.

EMSSON

— 05 / SPECIFICATION & CONTACT

Specifications & contact

SILS-920-LBN · SMART ILS

Item	Specification
Product model	SILS-920-LBN
Lock type	U-shaped · SUS shackle
Shackle dimensions	Length 53 mm · diameter 7 Φ · width 26 mm
Lock/unlock method	Bluetooth · NFC
Product dimensions	120 mm (H) × 65.5 mm (W) × 38 mm (D)
Weight / housing	230 g · Black / aluminum
Operating conditions	−20 °C 60 °C · Indoor and outdoor use
Battery	Lithium polymer 3.7 V / 1200 mA · built-in
Charging	외부 Charging기 3 h · 본체 Type-C Max 1 A
Status / protection	BLE 5.0 · IP67

※ Based on supplied materials Specification이며, final delivery Specification·configuration은 계약 및 기술 협의 시 최종 확인합니다.

Contact

EMSSON CO., LTD. · CEO Son Je-yoon · Business registration 781-86-02886

053-812-8122 · msson@emsson.com · 27 Sampung-ro, Gyeongsan-si, Gyeongsangbuk-do, Korea

EMSSON