

Web Vulnerabilities

Daniel Zappala

CS 360 Internet Programming
Brigham Young University

Web Vulnerabilities

- once you put up a site, you *will* be attacked
- web applications make you vulnerable
 - database = opportunity to steal, modify, or add information
 - place an order in your Amazon account
 - add comment/link spam to a web site
 - delete your email
 - Javascript = opportuntiy to run a program on user's machine
 - ▶ redirect you to a site
 - ▶ trick user into entering password
 - steal cookies or login credentials
 - change DNS entry to impersonate your bank
- two common attacks: XSS, CSRF

XSS

XSS

- Cross-Site Scripting (XSS) attack
 - attacker injects client-side script into a web page viewed by someone else
 - relies on browser trusting the scripts given to it by the current web site
- *if I visit Facebook, I should be safe to execute scripts the Facebook site gives me*

Example Vulnerability

```
1 http://www.google.com/search?q=flowers
2
3 <p>Your search for 'flowers'
4 returned the following results:</p>
```

- if server does not check the input, then an attacker can inject a script

Example Vulnerability

```
1 http://www.google.com/search?q=flowers+<script>alert(1)
2 </script>
3
4 <p>Your search for 'flowers<script>alert(1)</script>'
5 returned the following results:</p>
```

- if you can execute a script, then you can
 - redirect to malware
 - deface a web site
 - steal cookies, passwords, clipboard

XSS Statistics

- WhiteHat Web Site Security Statistics Report, 2010
 - 64% of web sites vulnerable to XSS attack
 - 105 days on average to fix it (banking is faster, retail is slower)
- why aren't they fixed?
 - no one at organization understands them or is responsible for fixing them
 - features prioritized ahead of security
 - code owned by an unresponsive third party
 - risk is accepted

XSS Types


- reflected
 - user input read from request parameters in URL and written directly to output
 - attack usually delivered via email or a neutral web site
 - get user to click on URL
- persistent
 - script stored directly on a web site (e.g. a Facebook status or Flickr caption)
 - when victim visits the web page, viewing the page triggers the attack

XSS Vulnerability, Django

```
1 c = Comment()  
2 c.text = request.POST['text']  
3 c.save()
```

- site accepts comments, stores input directly from user
- when comment is displayed, it can include anything, including script

Example

-  list-o-matic
- load the page xss.html in a browser
- use Firefox, compare with Chrome

Protection from XSS

- filter input
- escape output
- many web development frameworks do this for you automatically

CSRF

CSRF

- Cross-Site Request Forgery (CSRF) attack
 - attacker tricks victim into executing a script on a site where the victim has an account
 - relies on server trusting the user's identity
- *if the user logs in to my bank and sends me a request to withdraw funds that contains his login cookie, then I can trust that it is really her*

Example Vulnerability


```
1 <html>
2 <body>
3 <p>Welcome!</p>
4 <img src=http://bank.example.com/transfer?fromaccount=bob&
5     amount=1000000&toaccount=mallory">
6 </html>
```

- if you are currently logged into your bank, then the bank cannot tell that this request isn't coming from you

CSRF Statistics

- WhiteHat Web Site Security Statistics Report, 2010
 - 24% of web sites vulnerable to CSRF attack
 - hard to capture because web site logs make it look like a legitimate user request, may be under-reported
- identified on ING Direct (banking), YouTube, MetaFilter, The NY Times in 2008

Example

-  list-o-matic
- load the page csrf.html in a browser
- use Firefox, compare with Chrome

Protection from CSRF

- tokens
 - require a GET request to get a form before accepting a POST request for the form
 - send a token in the GET request that must be echoed back in the POST
 - token should be random and unique to that form
 - expire the token after a short time
- require user authorization for significant transactions