Plane -> Notion Connector

NOV 2026

CURRENT ARCHITECTURE | ONE SPRING BOOT SERVICE, ONE MONGO JOB QUEUE

1 REQUESTS AND BACKGROUND QUEUE

COMPONENT
Browser UI
React + TypeScript
Config, project, and sync views

COMPONENT
REST controllers
Health, Plane, config, job APIs

COMPONENT
Application services
ConfigService + project catalog
SyncJobService + ScheduleService

MANUAL / SCHEDULED / CONFIGURATION

COMPONENT
Mongo job queue
sync_jobs collection
Durable pending / held / run state

COMPONENT
SyncJobWorker
Polls every 5 seconds
Atomic claim; dispatches by job_type

2 WORKER DISPATCH

MANUAL / SCHEDULED

COMPONENT
MANUAL / SCHEDULED SYNC
WorkItemSyncService fetches active, non-draft work items.
Checkpointed reads; mappings and hashes skip unchanged writes.

CONFIGURATION RESULT

COMPONENT
CONFIGURATION CREATE / UPDATE
ConfigService provisions or applies settings asynchronously.
NotionHierarchyService refreshes workspace and parent summaries.

COMPONENT
UI OPERATION STATES
PROVISIONING -> READY / FAILED
UPDATING -> READY / FAILED

3 PROVIDER INTEGRATION AND NOTION DESTINATIONS

COMPONENT
PlaneClient
Resolve workspace, project,
and work item; page Plane reads.

COMPONENT
Plane API
Workspaces, projects,
states, labels, work items

COMPONENT
Destination selection
Configured project: use its IDs.
Unconfigured task URL: shared ad hoc.

COMPONENT
NotionClient
Pages, databases, data sources,
and work-item properties

COMPONENT
NotionBlockClient
Read/write blocks, summaries,
and archive pages

COMPONENT
Notion API
Pages, database containers,
data sources, and blocks

NOTION DESTINATION RULE

Project page -> database container -> data source. Configured IDs live on plane_projects; notion_destinations stores the lazy shared ad hoc destination.

4 MONGODB: plane_to_notion

sync_jobs
Shared queue; only MANUAL / SCHEDULED appear in run history

sync_configs
Project reference, options, schedule, config + operation status

plane_projects
Plane catalog + configured Notion page / database / data source IDs

plane_workspaces
Workspace slug -> Notion workspace page mapping

notion_destinations
Single shared ad hoc Notion destination IDs

sync_mappings
Data-source-scoped work-item mapping + source hash

Plane remains authoritative. Notion is a read-only projection; the connector stores IDs, checkpoints, and run state in MongoDB.