

OpenGraph Lite Viewer - English documentation v4505

This document is the first maintained English documentation track for the OpenGraph Lite Viewer. Dutch linguistic examples remain unchanged because they are the test data.

Interface language can be switched in the viewer. Help texts, config labels, render comments and the carousel documentation are maintained alongside the Dutch version.

Main concepts

OpenGraph/JAN uses free nodes and branches on a grid. The central tree is not forced into a traditional gravity-like tree direction. Independent projection axes can be drawn around the same source: LEX at the west side, SYNTAX at the east side, and LOG/FT at the south side.

Tree first is a notation and teaching order: first show the central source tree, then show the projections. Recursive box layout is the technical drawing method: leaves are measured first, then categories and subtrees are combined bottom-up. These two notions must not be confused.

LEX rendering

The LEX axis is a separate render layer. Lexical material is first projected to base positions. Local movement rules may then fill free slots, and the old base position can be shown as a trace. The central tree itself is not rewritten by these LEX movements.

For Dutch main clauses, the current simple rule moves the first phrase to slot 1 and the finite verb to slot 2. Subordinate clauses with *omdat* do not use the same V2 movement. Insertions such as *VANDAAG* are attached to the LEX axis, not inserted as new central syntax nodes.

OSV-! warning

OSV-! is deliberately marked with an exclamation mark. The box approach can never produce OSV as a base alternative: VP still groups object and verb as a subtree. A pure box flip is therefore insufficient.

To render the visible LEX axis correctly, an explicit movement rule is always required. OSV-! is not a base layout or linguistic alternative. It is a warning/test label for an impossible box variant. SOV, SVO, OVS, VSO and VOS remain layout variants; OSV-! is marked as different.

The v4505 change does not alter other LOG-order trees and does not alter existing user flip settings. Only the OSV label and explanation are changed.

Render order

Layout order, growth order and render order are separate. Layout order computes x/y positions. Growth order controls which precomputed elements are visible at a given presentation step. Render order controls SVG layering. Render must not change layout. Growth must not recompute layout.

The render explanation in the viewer now states that OSV-! cannot be produced by box layout and requires a LEX movement rule. This is also included in the Dutch and English documentation.

Carousel

The explanatory image module is named *carousel*. It lives in its own *carousel/* folder and can be extracted from the project zip as a self-contained module. The spelling *carousel* is used deliberately.

Current Dutch test sentences

HOND BIJT MAN; VROUW HEEFT TRUI GEBREID; OMDAT HOND MAN BIJT; HOND BIJT VANDAAG MAN. These examples remain Dutch in the English interface.