

```
-- phpMyAdmin SQL Dump
-- version 4.0.10deb1
-- http://www.phpmyadmin.net
--
-- Host: localhost
-- Erstellungszeit: 13. Dez 2016 um 19:23
-- Server Version: 5.5.38-0ubuntu0.14.04.1
-- PHP-Version: 5.5.9-1ubuntu4.4

SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
SET time_zone = "+00:00";

/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */;
/*!40101 SET NAMES utf8 */;

--
-- Datenbank: `ConnectingSports`
--

--
-- Tabellenstruktur für Tabelle `Bewertung`
--

CREATE TABLE IF NOT EXISTS `Bewertung` (
  `bewertung_id` int(11) NOT NULL,
  `mitglied_id` int(11) NOT NULL,
  `event_id` int(11) NOT NULL,
  `war_anwesend` int(1) DEFAULT NULL,
  `war_sympathisch` int(1) DEFAULT NULL,
  PRIMARY KEY (`bewertung_id`),
  KEY `mitglied_id` (`mitglied_id`),
  KEY `event_id` (`event_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

--
-- Tabellenstruktur für Tabelle `Event`
--

CREATE TABLE IF NOT EXISTS `Event` (
  `event_id` int(11) NOT NULL,
  `titel` varchar(255) DEFAULT NULL,
  `beschreibung` varchar(255) DEFAULT NULL,
  `ort` varchar(255) DEFAULT NULL,
  `datum` date DEFAULT NULL,
  PRIMARY KEY (`event_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

--
-- Daten für Tabelle `Event`
--

INSERT INTO `Event` (`event_id`, `titel`, `beschreibung`, `ort`, `datum`) VALUES
(0, 'Test-Event', 'Beschreibung vom Test-Event', 'Ort des Test-Events', '2016-12-13');

--
-- Tabellenstruktur für Tabelle `Kommentar`
--

CREATE TABLE IF NOT EXISTS `Kommentar` (
  `kommentar_id` int(11) NOT NULL AUTO_INCREMENT,
  `mitglied_id` int(11) DEFAULT NULL,
  `event_id` int(11) DEFAULT NULL,
  `datum` timestamp NULL DEFAULT NULL,
  `text` varchar(255) DEFAULT NULL,
  PRIMARY KEY (`kommentar_id`),
```

```
KEY `event_id` (`event_id`),
KEY `mitglied_id` (`mitglied_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1 AUTO_INCREMENT=2 ;

--
--
-- Tabellenstruktur für Tabelle `Mitglied`
--

CREATE TABLE IF NOT EXISTS `Mitglied` (
  `mitglied_id` int(11) NOT NULL,
  `pseudonym` varchar(255) DEFAULT NULL,
  `facebook_id` varchar(255) DEFAULT NULL,
  `passwort` varchar(255) DEFAULT NULL,
  `geburtstag` date DEFAULT NULL,
  `meine_stadt` varchar(255) DEFAULT NULL,
  PRIMARY KEY (`mitglied_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

--
-- Daten für Tabelle `Mitglied`
--

INSERT INTO `Mitglied` (`mitglied_id`, `pseudonym`, `facebook_id`, `passwort`, `geburtstag`, `meine_stadt`)
VALUES
(0, 'Test', 'fb_test', 'pw_test', NULL, 'Rosenheim');

--
--
-- Tabellenstruktur für Tabelle `Sportart`
--

CREATE TABLE IF NOT EXISTS `Sportart` (
  `sportart_id` int(11) NOT NULL,
  `titel` varchar(255) DEFAULT NULL,
  `bild_url` varchar(255) DEFAULT NULL,
  PRIMARY KEY (`sportart_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

--
--
-- Tabellenstruktur für Tabelle `V_Mitglied_Event`
--

CREATE TABLE IF NOT EXISTS `V_Mitglied_Event` (
  `event_id` int(11) NOT NULL,
  `mitglied_id` int(11) NOT NULL,
  PRIMARY KEY (`event_id`,`mitglied_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

--
--
-- Tabellenstruktur für Tabelle `V_Sportart_Mitglied`
--

CREATE TABLE IF NOT EXISTS `V_Sportart_Mitglied` (
  `sportart_id` int(11) NOT NULL,
  `mitglied_id` int(11) NOT NULL,
  `beschreibung` varchar(255) DEFAULT NULL,
  PRIMARY KEY (`sportart_id`,`mitglied_id`)
) ENGINE=InnoDB DEFAULT CHARSET=latin1;

/*!40101 SET CHARACTER_SET_CLIENT=@OLD_CHARACTER_SET_CLIENT */;
/*!40101 SET CHARACTER_SET_RESULTS=@OLD_CHARACTER_SET_RESULTS */;
/*!40101 SET COLLATION_CONNECTION=@OLD_COLLATION_CONNECTION */;
```