

CSS Position Tutorial: Complete Guide

CSS Learning Resources

May 9, 2026

Contents

1	Introduction	2
1.1	Why Position Matters	2
2	Position Values Overview	2
2.1	Position Types	2
3	Static Position (Default)	2
3.1	Static Basics	2
3.2	Static Characteristics	3
4	Relative Position	3
4.1	Relative Basics	3
4.2	Relative Characteristics	3
4.3	Relative Examples	3
5	Absolute Position	4
5.1	Absolute Basics	4
5.2	Absolute Characteristics	4
5.3	Finding Positioned Ancestor	5
5.4	Absolute Examples	5
5.5	Absolute Centering Techniques	6
6	Fixed Position	7
6.1	Fixed Basics	7
6.2	Fixed Characteristics	7
6.3	Fixed Examples	7
7	Sticky Position	9
7.1	Sticky Basics	9
7.2	Sticky Characteristics	9
7.3	Sticky Examples	9
8	Real-World Examples	10
8.1	Example 1: Modal Overlay	10
8.2	Example 2: Sticky Navigation	11
8.3	Example 3: Floating Action Button	12
8.4	Example 4: Tooltip with Absolute Positioning	13

8.5	Example 5: Positioned Card Badge	14
9	Positioning and Z-Index	15
9.1	Stacking Context	15
10	Common Positioning Patterns	16
10.1	Fixed Header + Content	16
10.2	Absolute Within Relative	16
10.3	Sticky With Fixed Header	16
11	Browser Support and Accessibility	17
11.1	Compatibility Table	17
11.2	Accessibility Considerations	17
12	Common Mistakes	18
12.1	Mistake 1: Absolute Without Relative Parent	18
12.2	Mistake 2: Sticky Without Required Property	18
12.3	Mistake 3: Fixed Width on Positioned Element	19
12.4	Mistake 4: Z-Index on Static Elements	19
13	Quick Reference	19
13.1	Position Values	19
13.2	Production Checklist	20
14	Summary	20

1 Introduction

The `position` property is fundamental to precise element placement in CSS. It determines how an element is positioned within the document flow and enables developers to create overlays, fixed headers, sticky sidebars, tooltips, and complex layouts. Understanding the five position values—static, relative, absolute, fixed, and sticky—is essential for controlling element placement and creating sophisticated interactive interfaces.

Each position value has unique behavior and use cases. Mastering these positioning techniques enables developers to create responsive, accessible interfaces that work seamlessly across all devices.

1.1 Why Position Matters

- **Precise Placement:** Control exact element location on page
- **Overlays:** Create modals, popovers, tooltips
- **Fixed Elements:** Header navigation, chat widgets, floating buttons
- **Sticky Behavior:** Keep elements visible while scrolling
- **Complex Layouts:** Layer elements for creative designs
- **Responsive Design:** Position adapts to viewport changes
- **Interactive Effects:** Enable dynamic positioning with JavaScript

2 Position Values Overview

2.1 Position Types

Value	Behavior	Use Case
static	Default, normal flow	Regular document flow
relative	Offset from normal position	Adjust element within flow
absolute	Removed from flow, relative to parent	Overlays, positioned layers
fixed	Removed from flow, relative to viewport	Fixed headers, floating buttons
sticky	Hybrid of relative and fixed	Sticky headers, sidebars

3 Static Position (Default)

Static positioning is the default value where elements follow normal document flow.

3.1 Static Basics

```
1 /* Default positioning (normal document flow) */
2 position: static;
3
4 /* top, right, bottom, left properties are ignored */
5 .element {
6     position: static;
7     top: 100px; /* Has no effect */
8     left: 50px; /* Has no effect */
9 }
```

3.2 Static Characteristics

- Default positioning value
- Elements flow normally in document
- Top, right, bottom, left properties have no effect
- Element contributes to normal layout flow
- z-index has no effect

4 Relative Position

Relative positioning offsets an element from its normal position while preserving its space in the document flow.

4.1 Relative Basics

```
1  /* Position relative to its normal position */
2  position: relative;
3
4  /* Offset properties work with relative */
5  .element {
6      position: relative;
7      top: 20px;      /* Move down 20px from normal */
8      left: 30px;     /* Move right 30px from normal */
9      bottom: 20px;   /* Move up 20px */
10     right: 30px;    /* Move left 30px */
11 }
```

4.2 Relative Characteristics

- Element is positioned relative to its normal position
- Space preserved in document flow
- Top, right, bottom, left offsets work
- Useful for fine-tuning element position
- Creates new stacking context
- Does not remove element from flow

4.3 Relative Examples

```
1  /* Adjust heading position */
2  h1 {
3      position: relative;
4      top: 10px;
5      color: #333;
```

```
6 }
7
8 /* Offset badge */
9 .badge {
10     position: relative;
11     top: -5px;
12     right: -5px;
13 }
14
15 /* Move element on hover */
16 .button {
17     position: relative;
18     transition: top 0.2s;
19 }
20
21 .button:hover {
22     top: -2px;
23 }
24
25 /* Create new stacking context for child positioning */
26 .container {
27     position: relative;
28     z-index: 1;
29 }
```

5 Absolute Position

Absolute positioning removes an element from the normal document flow and positions it relative to its nearest positioned ancestor.

5.1 Absolute Basics

```
1 /* Position relative to nearest positioned ancestor */
2 position: absolute;
3
4 .absolute-element {
5     position: absolute;
6     top: 50px;
7     left: 100px;
8     width: 200px;
9     height: 100px;
10 }
```

5.2 Absolute Characteristics

- Removed from normal document flow
- Positioned relative to nearest positioned ancestor
- If no positioned ancestor, positioned relative to `<html>`

- Does not contribute to parent height
- Top, right, bottom, left properties work
- Can overlap other elements
- z-index controls stacking order

5.3 Finding Positioned Ancestor

```
1  /* .child is positioned relative to .parent */
2  .parent {
3      position: relative;
4      width: 400px;
5      height: 300px;
6      border: 1px solid #ddd;
7  }
8
9  .child {
10     position: absolute;
11     top: 50px;
12     left: 50px;
13     width: 100px;
14     height: 100px;
15     background: blue;
16 }
17
18 /* If no positioned ancestor */
19 .orphan {
20     position: absolute;
21     top: 50px;
22     left: 50px;
23     /* Positioned relative to <html> element */
24 }
```

5.4 Absolute Examples

```
1  /* Badge on image */
2  .image-badge {
3      position: absolute;
4      top: 10px;
5      right: 10px;
6      background: red;
7      color: white;
8      padding: 5px 10px;
9      border-radius: 50%;
10 }
11
12 /* Modal centered on screen */
13 .modal {
14     position: absolute;
15     top: 50%;
```

```
16     left: 50%;
17     transform: translate(-50%, -50%);
18     background: white;
19     padding: 2rem;
20     box-shadow: 0 4px 12px rgba(0, 0, 0, 0.15);
21 }
22
23 /* Tooltip positioning */
24 .tooltip {
25     position: absolute;
26     bottom: 100%;
27     left: 50%;
28     transform: translateX(-50%);
29     background: #333;
30     color: white;
31     padding: 0.5rem 1rem;
32     border-radius: 4px;
33     white-space: nowrap;
34 }
35
36 /* Overlay fill */
37 .overlay {
38     position: absolute;
39     top: 0;
40     left: 0;
41     width: 100%;
42     height: 100%;
43     background: rgba(0, 0, 0, 0.5);
44 }
```

5.5 Absolute Centering Techniques

```
1  /* Method 1: Transform (recommended) */
2  .centered-transform {
3      position: absolute;
4      top: 50%;
5      left: 50%;
6      transform: translate(-50%, -50%);
7  }
8
9  /* Method 2: Margin auto with dimensions */
10 .centered-margin {
11     position: absolute;
12     top: 0;
13     right: 0;
14     bottom: 0;
15     left: 0;
16     width: 200px;
17     height: 200px;
18     margin: auto;
19 }
20
21 /* Method 3: Inset values */
```

```
22 .centered-inset {  
23     position: absolute;  
24     inset: 0;  
25     width: 200px;  
26     height: 200px;  
27     margin: auto;  
28 }
```

6 Fixed Position

Fixed positioning removes an element from the document flow and positions it relative to the viewport, making it stay in place while scrolling.

6.1 Fixed Basics

```
1  /* Position relative to viewport */  
2  position: fixed;  
3  
4  .fixed-header {  
5      position: fixed;  
6      top: 0;  
7      left: 0;  
8      width: 100%;  
9      height: 60px;  
10     background: #333;  
11     color: white;  
12     z-index: 100;  
13 }
```

6.2 Fixed Characteristics

- Removed from normal document flow
- Positioned relative to viewport
- Stays in place when scrolling
- Does not move with page scroll
- Width defaults to auto if not specified
- Can create scrollable overflow if larger than viewport
- z-index controls stacking order

6.3 Fixed Examples

```
1  /* Fixed header navigation */  
2  header {  
3      position: fixed;  
4      top: 0;
```



```
5     left: 0;
6     width: 100%;
7     height: 60px;
8     background: white;
9     box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
10    z-index: 1000;
11  }
12
13  /* Add top margin to body to prevent content overlap */
14  body {
15    margin-top: 60px;
16  }
17
18  /* Fixed floating button */
19  .floating-button {
20    position: fixed;
21    bottom: 20px;
22    right: 20px;
23    width: 50px;
24    height: 50px;
25    border-radius: 50%;
26    background: #007bff;
27    color: white;
28    border: none;
29    cursor: pointer;
30    box-shadow: 0 4px 12px rgba(0, 0, 0, 0.2);
31    z-index: 999;
32  }
33
34  /* Fixed sidebar */
35  .sidebar {
36    position: fixed;
37    left: 0;
38    top: 60px;
39    width: 250px;
40    height: calc(100vh - 60px);
41    background: #f5f5f5;
42    overflow-y: auto;
43  }
44
45  /* Fixed chat widget */
46  .chat-widget {
47    position: fixed;
48    bottom: 0;
49    right: 20px;
50    width: 300px;
51    height: 400px;
52    background: white;
53    border-radius: 8px 8px 0 0;
54    box-shadow: 0 -2px 8px rgba(0, 0, 0, 0.1);
55  }
56
57  /* Scroll into view indicator */
58  .scroll-indicator {
```

```
59     position: fixed;
60     top: 0;
61     left: 0;
62     height: 3px;
63     background: linear-gradient(to right, #007bff, #0056b3);
64     width: 0%;
65     z-index: 999;
66 }
```

7 Sticky Position

Sticky positioning is a hybrid between relative and fixed, allowing elements to scroll normally until they reach a threshold, then stick to that position.

7.1 Sticky Basics

```
1  /* Hybrid relative/fixed positioning */
2  position: sticky;
3
4  /* Define when sticking occurs */
5  .sticky-header {
6      position: sticky;
7      top: 0;
8      background: white;
9      z-index: 100;
10 }
```

7.2 Sticky Characteristics

- Hybrid of relative and fixed positioning
- Scrolls normally until reaching threshold (top/left/bottom/right)
- Then sticks to viewport at that position
- Only sticks within parent container
- Requires at least one of top/right/bottom/left to work
- Must have space in parent to scroll
- Browser support: 93

7.3 Sticky Examples

```
1  /* Sticky table header */
2  table {
3      width: 100%;
4  }
5
6  thead {
```

```
7     position: sticky;
8     top: 0;
9     background: white;
10    box-shadow: 0 2px 4px rgba(0, 0, 0, 0.1);
11 }
12
13 /* Sticky section heading */
14 .section-title {
15     position: sticky;
16     top: 60px; /* Below fixed header */
17     background: #f5f5f5;
18     padding: 1rem;
19     border-bottom: 1px solid #ddd;
20     z-index: 99;
21 }
22
23 /* Sticky sidebar */
24 .sidebar {
25     position: sticky;
26     top: 20px;
27     height: calc(100vh - 40px);
28     overflow-y: auto;
29 }
30
31 /* Sticky category filter */
32 .filter-bar {
33     position: sticky;
34     top: 60px; /* Below header */
35     background: white;
36     padding: 1rem;
37     border-bottom: 1px solid #ddd;
38     z-index: 98;
39 }
40
41 /* Sticky navigation within page section */
42 .article-nav {
43     position: sticky;
44     top: 120px; /* Below header and main nav */
45     background: white;
46     padding: 1rem;
47     border: 1px solid #ddd;
48     border-radius: 4px;
49 }
```

8 Real-World Examples

8.1 Example 1: Modal Overlay

```
1 <div class="modal-overlay">
2   <div class="modal">
3     <button class="close">&times;</button>
4     <h2>Modal Title</h2>
```

```
5     <p>Modal content</p>
6   </div>
7 </div>

1 .modal-overlay {
2   position: fixed;
3   top: 0;
4   left: 0;
5   width: 100%;
6   height: 100%;
7   background: rgba(0, 0, 0, 0.5);
8   display: flex;
9   align-items: center;
10  justify-content: center;
11  z-index: 1000;
12 }
13
14 .modal {
15   position: relative;
16   background: white;
17   border-radius: 8px;
18   padding: 2rem;
19   max-width: 500px;
20   width: 90%;
21   box-shadow: 0 4px 20px rgba(0, 0, 0, 0.15);
22 }
23
24 .modal .close {
25   position: absolute;
26   top: 1rem;
27   right: 1rem;
28   background: none;
29   border: none;
30   font-size: 1.5rem;
31   cursor: pointer;
32 }
```

8.2 Example 2: Sticky Navigation

```
1 <header class="main-header">
2   <h1>Site Title</h1>
3 </header>
4
5 <nav class="sticky-nav">
6   <ul>
7     <li><a href="#section1">Section 1</a></li>
8     <li><a href="#section2">Section 2</a></li>
9     <li><a href="#section3">Section 3</a></li>
10  </ul>
11 </nav>
12
13 <main>
```

```
14 <!-- Content -->
15 </main>
```

```
1 .main-header {
2   padding: 2rem;
3   background: #333;
4   color: white;
5 }
6
7 .sticky-nav {
8   position: sticky;
9   top: 0;
10  background: white;
11  border-bottom: 1px solid #ddd;
12  z-index: 999;
13 }
14
15 .sticky-nav ul {
16   list-style: none;
17   padding: 0;
18   margin: 0;
19   display: flex;
20   gap: 2rem;
21 }
22
23 .sticky-nav a {
24   display: block;
25   padding: 1rem;
26   text-decoration: none;
27   color: #333;
28   border-bottom: 3px solid transparent;
29   transition: border-color 0.3s;
30 }
31
32 .sticky-nav a:hover {
33   border-bottom-color: #007bff;
34 }
```

8.3 Example 3: Floating Action Button

```
1 .fab {
2   position: fixed;
3   bottom: 30px;
4   right: 30px;
5   width: 56px;
6   height: 56px;
7   border-radius: 50%;
8   background: linear-gradient(135deg, #667eea, #764ba2);
9   color: white;
10  border: none;
11  font-size: 1.5rem;
12  cursor: pointer;
```

```
13     box-shadow: 0 4px 12px rgba(0, 0, 0, 0.3);
14     transition: transform 0.3s, box-shadow 0.3s;
15     z-index: 50;
16 }
17
18 .fab:hover {
19     transform: scale(1.1);
20     box-shadow: 0 6px 16px rgba(0, 0, 0, 0.4);
21 }
22
23 .fab:active {
24     transform: scale(0.95);
25 }
26
27 /* Mobile adjustment */
28 @media (max-width: 768px) {
29     .fab {
30         bottom: 20px;
31         right: 20px;
32         width: 48px;
33         height: 48px;
34         font-size: 1.25rem;
35     }
36 }
```

8.4 Example 4: Tooltip with Absolute Positioning

```
1 <button class="tooltip-trigger">
2     Hover me
3     <div class="tooltip">Helpful information</div>
4 </button>
```

```
1 .tooltip-trigger {
2     position: relative;
3     background: #007bff;
4     color: white;
5     border: none;
6     padding: 0.75rem 1.5rem;
7     border-radius: 4px;
8     cursor: pointer;
9 }
10
11 .tooltip {
12     position: absolute;
13     bottom: 100%;
14     left: 50%;
15     transform: translateX(-50%) translateY(-10px);
16     background: #333;
17     color: white;
18     padding: 0.5rem 1rem;
19     border-radius: 4px;
20     white-space: nowrap;
```

```
21     opacity: 0;
22     visibility: hidden;
23     pointer-events: none;
24     transition: opacity 0.3s, visibility 0.3s, transform 0.3s;
25     z-index: 10;
26 }
27
28 .tooltip-trigger:hover .tooltip {
29     opacity: 1;
30     visibility: visible;
31     transform: translateX(-50%) translateY(-15px);
32 }
33
34 /* Arrow using pseudo-element */
35 .tooltip::after {
36     content: '';
37     position: absolute;
38     top: 100%;
39     left: 50%;
40     transform: translateX(-50%);
41     width: 0;
42     height: 0;
43     border-left: 5px solid transparent;
44     border-right: 5px solid transparent;
45     border-top: 5px solid #333;
46 }
```

8.5 Example 5: Positioned Card Badge

```
1  .card {
2      position: relative;
3      background: white;
4      border-radius: 8px;
5      overflow: hidden;
6      box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
7  }
8
9  .card-image {
10     width: 100%;
11     height: 200px;
12     object-fit: cover;
13 }
14
15 .card-badge {
16     position: absolute;
17     top: 10px;
18     right: 10px;
19     background: #ff6b6b;
20     color: white;
21     padding: 0.5rem 1rem;
22     border-radius: 4px;
23     font-size: 0.875rem;
24     font-weight: 600;
```

```
25 }
26
27 .card-discount {
28     position: absolute;
29     bottom: 10px;
30     left: 10px;
31     background: #28a745;
32     color: white;
33     padding: 0.5rem 1rem;
34     border-radius: 4px;
35 }
36
37 .card-content {
38     padding: 1.5rem;
39 }
```

9 Positioning and Z-Index

9.1 Stacking Context

```
1  /* Higher z-index appears on top */
2  .element-1 {
3      position: relative;
4      z-index: 1;
5  }
6
7  .element-2 {
8      position: absolute;
9      z-index: 10;
10 }
11
12 .element-3 {
13     position: fixed;
14     z-index: 1000;
15 }
16
17 /* z-index only works with positioned elements */
18 .static-element {
19     position: static;
20     z-index: 9999; /* Has no effect */
21 }
22
23 /* Stacking context hierarchy */
24 header {
25     position: relative;
26     z-index: 100;
27 }
28
29 nav {
30     position: sticky;
31     z-index: 99;
32 }
```



```
33
34 .modal {
35     position: fixed;
36     z-index: 1000;
37 }
38
39 .tooltip {
40     position: absolute;
41     z-index: 10;
42 }
```

10 Common Positioning Patterns

10.1 Fixed Header + Content

```
1 header {
2     position: fixed;
3     top: 0;
4     width: 100%;
5     height: 60px;
6     background: white;
7     z-index: 100;
8 }
9
10 main {
11     margin-top: 60px;
12     padding: 2rem;
13 }
```

10.2 Absolute Within Relative

```
1 .container {
2     position: relative;
3     width: 100%;
4     height: 300px;
5 }
6
7 .overlay {
8     position: absolute;
9     top: 0;
10    left: 0;
11    width: 100%;
12    height: 100%;
13    background: rgba(0, 0, 0, 0.3);
14 }
```

10.3 Sticky With Fixed Header

```
1  /* Fixed header */
2  header {
3      position: fixed;
4      top: 0;
5      width: 100%;
6      height: 60px;
7  }
8
9  /* Sticky below fixed header */
10 .sticky-section {
11     position: sticky;
12     top: 60px;
13     background: white;
14     padding: 1rem;
15 }
16
17 body {
18     padding-top: 60px;
19 }
```

11 Browser Support and Accessibility

11.1 Compatibility Table

Feature	Chrome	Firefox	Safari	Edge
position: relative	All	All	All	All
position: absolute	All	All	All	All
position: fixed	All	All	All	All
position: sticky	56+	59+	13+	16+

11.2 Accessibility Considerations

```
1  /* Fixed elements can hide content */
2  /* Ensure enough space for content */
3  header {
4      position: fixed;
5      height: 60px;
6  }
7
8  body {
9      padding-top: 60px; /* Prevent overlap */
10 }
11
12 /* Ensure positioned elements are accessible */
13 .modal {
14     position: fixed;
15     outline: 2px solid transparent;
16 }
17
18 .modal:focus-within {
19     outline: 2px solid #007bff;
```

```
20 }
21
22 /* Keyboard navigation */
23 .fixed-menu {
24     position: fixed;
25 }
26
27 .fixed-menu a:focus {
28     outline: 2px solid white;
29 }
```

12 Common Mistakes

12.1 Mistake 1: Absolute Without Relative Parent

Wrong:

```
1 .child {
2     position: absolute;
3     top: 50px;
4 }
5 /* Positioned relative to html, not intended parent */
```

Correct:

```
1 .parent {
2     position: relative;
3 }
4
5 .child {
6     position: absolute;
7     top: 50px;
8 }
```

12.2 Mistake 2: Sticky Without Required Property

Wrong:

```
1 .element {
2     position: sticky;
3     /* Missing top, right, bottom, or left */
4 }
```

Correct:

```
1 .element {
2     position: sticky;
3     top: 0; /* Required for sticking */
4 }
```

12.3 Mistake 3: Fixed Width on Positioned Element

Problem:

```
1 .fixed-element {
2     position: fixed;
3     width: 100%;
4     /* Can extend beyond viewport */
5 }
```

Better:

```
1 .fixed-element {
2     position: fixed;
3     left: 0;
4     right: 0;
5     /* Width stretches between edges */
6 }
```

12.4 Mistake 4: Z-Index on Static Elements

Wrong:

```
1 .element {
2     position: static;
3     z-index: 999; /* Has no effect */
4 }
```

Correct:

```
1 .element {
2     position: relative;
3     z-index: 999; /* Works now */
4 }
```

13 Quick Reference

13.1 Position Values

```
1 /* Default - normal flow */
2 position: static;
3
4 /* Offset from normal position */
5 position: relative;
6 top: 10px; left: 10px;
7
8 /* Removed from flow, relative to positioned parent */
9 position: absolute;
10 top: 50px; left: 50px;
11
12 /* Removed from flow, relative to viewport */
13 position: fixed;
14 top: 0; left: 0;
```

```
15 /* Hybrid - sticky while scrolling */
16 position: sticky;
17 top: 0;
```

13.2 Production Checklist

- Use relative positioning for parent containers
- Always set top/right/bottom/left for positioned elements
- Use z-index to manage stacking order
- Add margin-top/padding-top for fixed headers
- Test sticky elements on actual content
- Ensure positioned elements don't hide content
- Test keyboard navigation with positioned elements
- Verify fixed elements on mobile devices
- Check z-index values for conflicts
- Use transform instead of top/left when possible

14 Summary

The `position` property is essential for precise element placement. Key takeaways:

1. Static is default; elements flow normally
2. Relative positions elements relative to normal position
3. Absolute removes from flow, positions relative to parent
4. Fixed removes from flow, stays in place during scroll
5. Sticky is hybrid, sticks when reaching threshold
6. Always set positioned parent for absolute children
7. Use z-index to manage stacking order
8. Add margin/padding to prevent content overlap
9. Test positioning across devices
10. Consider accessibility impact of positioning

Master CSS positioning to create sophisticated layouts with fixed headers, sticky navigation, modals, tooltips, and complex overlays that enhance user experience across all devices.