

CSS Visibility: Complete Guide

CSS Learning Resources

May 9, 2026

Contents

1	Introduction	2
1.1	Why Visibility Matters	2
2	Understanding Visibility	2
2.1	Basic Syntax	2
2.2	Visibility Values	2
3	Visibility vs. Display vs. Opacity	2
3.1	Comparison Table	3
3.2	When to Use Each	3
4	Visibility Values	3
4.1	Visible (Default)	3
4.2	Hidden	4
4.3	Collapse	4
5	Visibility with Transitions	4
5.1	Basic Transitions	4
5.2	Advanced Transitions	5
6	Real-World Examples	6
6.1	Example 1: Toggle Visibility	6
6.2	Example 2: Tooltip	6
6.3	Example 3: Dropdown Menu	6
6.4	Example 4: Modal Dialog	7
6.5	Example 5: Accordion	8
6.6	Example 6: Loading State	9
7	Visibility and Inheritance	10
7.1	Inheritance Behavior	10
7.2	Selective Child Visibility	10
8	Visibility with Display	11
8.1	Combinations	11

9	Accessibility Considerations	11
9.1	Screen Reader Impact	11
9.2	Focus Management	12
10	Performance Considerations	12
10.1	Visibility Performance	12
10.2	Mobile Optimization	13
11	Browser Support	13
11.1	Compatibility Table	13
12	Common Mistakes	13
12.1	Mistake 1: Using Hidden for Space Removal	13
12.2	Mistake 2: Animating Display	13
12.3	Mistake 3: Hidden Elements in Tab Order	14
12.4	Mistake 4: Forgetting Pointer-Events	14
12.5	Mistake 5: Visibility vs Opacity Confusion	15
13	Quick Reference	15
13.1	Common Visibility Patterns	15
13.2	Production Checklist	16
14	Summary	16

1 Introduction

The `visibility` property controls whether an element is visible or hidden on the page. Unlike `display: none` which removes an element from the document flow entirely, `visibility: hidden` hides an element while preserving its space in the layout. This distinction is crucial for creating animations, conditional displays, and interactive interfaces that respond intelligently to user actions without disrupting the page layout.

Understanding visibility is essential for modern web development because it enables sophisticated effects like reveal animations, hover states, and progressive disclosure patterns that enhance user experience while maintaining layout stability.

1.1 Why Visibility Matters

- **Space Preservation:** Hide elements while keeping layout intact
- **Animations:** Smooth fade-in/out effects without layout shifts
- **Conditional Display:** Show/hide elements based on state
- **Performance:** More efficient than reflow-causing changes
- **Accessibility:** Control element presence in visual rendering
- **Interactions:** Hover states, tooltips, progressive disclosure
- **Layout Stability:** Prevent content jumping

2 Understanding Visibility

The `visibility` property has three main values that control element visibility.

2.1 Basic Syntax

```
1 visibility: visible;    /* Fully visible (default) */
2 visibility: hidden;    /* Hidden but takes up space */
3 visibility: collapse;  /* Special for tables */
```

2.2 Visibility Values

Value	Visible	Space Taken
visible	Yes	Yes
hidden	No	Yes
collapse	No	No (table-specific)

3 Visibility vs. Display vs. Opacity

Understanding the differences between these three properties is essential for choosing the right tool.

3.1 Comparison Table

Property	Visible	Space	Animatable
visibility: visible	Yes	Yes	No
visibility: hidden	No	Yes	Yes (v2.1)
display: block	Yes	Yes	No
display: none	No	No	No
opacity: 1	Yes	Yes	Yes
opacity: 0	No	Yes	Yes

3.2 When to Use Each

```
1  /* Use visibility: hidden for space-preserving hide */
2  .placeholder {
3      visibility: hidden;
4  }
5
6  /* Use display: none for complete removal */
7  .removed {
8      display: none;
9  }
10
11 /* Use opacity: 0 for animated transparency */
12 .fade {
13     opacity: 0;
14     transition: opacity 0.3s;
15 }
16
17 /* Use visibility for hide with space preservation */
18 .reserved-space {
19     visibility: hidden;
20     transition: visibility 0.3s;
21 }
```

4 Visibility Values

4.1 Visible (Default)

```
1  /* Element is displayed normally */
2  visibility: visible;
3
4  /* Used to override hidden state */
5  .visible-override {
6      visibility: hidden;
7  }
8
9  .visible-override.show {
10     visibility: visible;
11 }
```

4.2 Hidden

```
1  /* Element is hidden but takes up space */
2  visibility: hidden;
3
4  /* Element remains in layout flow but is invisible */
5  .hidden {
6      visibility: hidden;
7  }
8
9  /* Children inherit hidden visibility */
10 .parent-hidden {
11     visibility: hidden;
12 }
13
14 .parent-hidden .child {
15     /* Still hidden */
16 }
17
18 .parent-hidden .child-visible {
19     visibility: visible; /* Can override for children */
20 }
```

4.3 Collapse

```
1  /* Special value for table rows and columns */
2  visibility: collapse;
3
4  /* Hide table row without leaving gap */
5  table tr.hidden {
6      visibility: collapse;
7  }
8
9  /* Hide table column */
10 table td.hidden {
11     visibility: collapse;
12 }
13
14 /* For non-table elements, behaves like hidden */
15 div { visibility: collapse; }
```

5 Visibility with Transitions

Smooth visibility changes enable sophisticated animations and effects.

5.1 Basic Transitions

```
1  /* Fade with visibility transition */
2  .element {
3      visibility: visible;
```

```
4     opacity: 1;
5     transition: visibility 0.3s, opacity 0.3s;
6 }
7
8 .element.hidden {
9     visibility: hidden;
10    opacity: 0;
11 }
12
13 /* Delay visibility change */
14 .element {
15     visibility: visible;
16     transition: visibility 0.3s, opacity 0.3s;
17 }
18
19 .element.hidden {
20     visibility: hidden;
21     opacity: 0;
22     transition-delay: 0.3s; /* Delay visibility change */
23 }
```

5.2 Advanced Transitions

```
1 /* Visibility with scale transform */
2 .popup {
3     visibility: visible;
4     opacity: 1;
5     transform: scale(1);
6     transition: visibility 0.3s, opacity 0.3s, transform 0.3s;
7 }
8
9 .popup.hidden {
10    visibility: hidden;
11    opacity: 0;
12    transform: scale(0.9);
13 }
14
15 /* Visibility with slide effect */
16 .drawer {
17     visibility: visible;
18     opacity: 1;
19     transform: translateX(0);
20     transition: visibility 0.3s, opacity 0.3s, transform 0.3s;
21 }
22
23 .drawer.hidden {
24     visibility: hidden;
25     opacity: 0;
26     transform: translateX(-100%);
27 }
```

6 Real-World Examples

6.1 Example 1: Toggle Visibility

```
1 <button id="toggleBtn">Toggle</button>
2 <div class="hidden-content">Hidden content here</div>
```

```
1 .hidden-content {
2     visibility: visible;
3     opacity: 1;
4     transition: visibility 0.3s, opacity 0.3s;
5 }
6
7 .hidden-content.hidden {
8     visibility: hidden;
9     opacity: 0;
10 }
```

```
1 const toggleBtn = document.getElementById('toggleBtn');
2 const content = document.querySelector('.hidden-content');
3
4 toggleBtn.addEventListener('click', () => {
5     content.classList.toggle('hidden');
6 });
```

6.2 Example 2: Tooltip

```
1 <button class="tooltip-trigger">Hover me</button>
2 <div class="tooltip">Helpful text here</div>
```

```
1 .tooltip {
2     visibility: hidden;
3     opacity: 0;
4     position: absolute;
5     background: #333;
6     color: white;
7     padding: 0.5rem 1rem;
8     border-radius: 4px;
9     white-space: nowrap;
10    transition: visibility 0.2s, opacity 0.2s;
11    margin-top: 0.5rem;
12 }
13
14 .tooltip-trigger:hover ~ .tooltip {
15     visibility: visible;
16     opacity: 1;
17 }
```

6.3 Example 3: Dropdown Menu

```
1 <div class="dropdown">
2   <button class="dropdown-trigger">Menu</button>
3   <ul class="dropdown-menu">
4     <li><a href="#item1">Item 1</a></li>
5     <li><a href="#item2">Item 2</a></li>
6     <li><a href="#item3">Item 3</a></li>
7   </ul>
8 </div>
```

```
1 .dropdown-menu {
2   visibility: hidden;
3   opacity: 0;
4   position: absolute;
5   background: white;
6   box-shadow: 0 2px 8px rgba(0, 0, 0, 0.1);
7   list-style: none;
8   padding: 0.5rem 0;
9   margin: 0;
10  transform: translateY(-10px);
11  transition: visibility 0.2s, opacity 0.2s, transform 0.2s;
12 }
13
14 .dropdown:hover .dropdown-menu {
15   visibility: visible;
16   opacity: 1;
17   transform: translateY(0);
18 }
19
20 .dropdown-menu li {
21   padding: 0.5rem 1.5rem;
22 }
23
24 .dropdown-menu a {
25   text-decoration: none;
26   color: #333;
27 }
```

6.4 Example 4: Modal Dialog

```
1 <button class="open-modal">Open Modal</button>
2
3 <div class="modal-backdrop hidden">
4   <div class="modal">
5     <h2>Modal Title</h2>
6     <p>Modal content</p>
7     <button class="close-modal">Close</button>
8   </div>
9 </div>
```

```
1 .modal-backdrop {
2   visibility: visible;
```



```
3     opacity: 1;
4     position: fixed;
5     top: 0;
6     left: 0;
7     width: 100%;
8     height: 100%;
9     background: rgba(0, 0, 0, 0.5);
10    transition: visibility 0.3s, opacity 0.3s;
11    display: flex;
12    align-items: center;
13    justify-content: center;
14  }
15
16  .modal-backdrop.hidden {
17    visibility: hidden;
18    opacity: 0;
19  }
20
21  .modal {
22    background: white;
23    border-radius: 8px;
24    padding: 2rem;
25    max-width: 500px;
26    width: 90%;
27  }
```

6.5 Example 5: Accordion

```
1  <div class="accordion">
2    <div class="accordion-item">
3      <button class="accordion-trigger">Section 1</button>
4      <div class="accordion-content">Content 1</div>
5    </div>
6    <div class="accordion-item">
7      <button class="accordion-trigger">Section 2</button>
8      <div class="accordion-content">Content 2</div>
9    </div>
10 </div>
```

```
1  .accordion-content {
2    visibility: hidden;
3    opacity: 0;
4    max-height: 0;
5    overflow: hidden;
6    transition: visibility 0.3s, opacity 0.3s, max-height 0.3s;
7  }
8
9  .accordion-item.active .accordion-content {
10    visibility: visible;
11    opacity: 1;
12    max-height: 500px;
13  }
```

```
14
15 .accordion-trigger {
16     width: 100%;
17     padding: 1rem;
18     background: #f5f5f5;
19     border: 1px solid #ddd;
20     text-align: left;
21     cursor: pointer;
22 }
```

6.6 Example 6: Loading State

```
1 <div class="content-area">
2     <button class="load-btn">Load Data</button>
3
4     <div class="loading hidden">
5         <div class="spinner"></div>
6         <p>Loading...</p>
7     </div>
8
9     <div class="result">
10         Data loaded successfully
11     </div>
12 </div>
```

```
1 .loading {
2     visibility: visible;
3     opacity: 1;
4     transition: visibility 0.3s, opacity 0.3s;
5 }
6
7 .loading.hidden {
8     visibility: hidden;
9     opacity: 0;
10 }
11
12 .spinner {
13     width: 40px;
14     height: 40px;
15     border: 4px solid #f3f3f3;
16     border-top: 4px solid #007bff;
17     border-radius: 50%;
18     animation: spin 1s linear infinite;
19 }
20
21 @keyframes spin {
22     0% { transform: rotate(0deg); }
23     100% { transform: rotate(360deg); }
24 }
```

7 Visibility and Inheritance

Understanding how visibility affects child elements is important.

7.1 Inheritance Behavior

```
1  /* Children inherit hidden from parent */
2  .parent {
3      visibility: hidden;
4  }
5
6  .parent .child {
7      /* Still hidden, inherits from parent */
8  }
9
10 /* Override in child */
11 .parent .child.visible {
12     visibility: visible;
13 }
14
15 /* Example */
16 .container {
17     visibility: hidden;
18 }
19
20 .container .important {
21     visibility: visible; /* Override to show */
22 }
```

7.2 Selective Child Visibility

```
1  /* Hide parent but show specific children */
2  .gallery {
3      visibility: hidden;
4  }
5
6  .gallery .featured {
7      visibility: visible;
8  }
9
10 /* Hide all children except important */
11 .section {
12     visibility: hidden;
13 }
14
15 .section .alert {
16     visibility: visible;
17 }
```

8 Visibility with Display

Combining visibility and display properties for different effects.

8.1 Combinations

```
1  /* Hidden with space preserved */
2  .reserved {
3      visibility: hidden;
4      display: block;
5  }
6
7  /* Completely removed */
8  .removed {
9      visibility: hidden;
10     display: none;
11 }
12
13 /* Flexible hidden */
14 .flexible-hidden {
15     visibility: hidden;
16     display: flex;
17 }
18
19 /* Grid hidden with space */
20 .grid-hidden {
21     visibility: hidden;
22     display: grid;
23 }
```

9 Accessibility Considerations

9.1 Screen Reader Impact

```
1  /* visibility: hidden hides from visual rendering */
2  .visually-hidden {
3      visibility: hidden;
4      /* Still accessible to screen readers */
5  }
6
7  /* Better for screen reader exclusion */
8  .sr-only {
9      position: absolute;
10     width: 1px;
11     height: 1px;
12     padding: 0;
13     margin: -1px;
14     overflow: hidden;
15     clip: rect(0, 0, 0, 0);
16     white-space: nowrap;
17     border-width: 0;
18 }
```

```
19
20 /* For decorative elements */
21 .decorative {
22     visibility: hidden;
23     aria-hidden: true;
24 }
```

9.2 Focus Management

```
1  /* Hidden elements shouldn't receive focus */
2  .modal.hidden {
3      visibility: hidden;
4  }
5
6  .modal.hidden button {
7      pointer-events: none;
8  }
9
10 /* Show on focus for keyboard users */
11 button {
12     visibility: hidden;
13 }
14
15 button:focus {
16     visibility: visible;
17 }
```

10 Performance Considerations

10.1 Visibility Performance

```
1  /* Preferred: visibility changes don't cause reflow */
2  .toggle {
3      visibility: hidden;
4      transition: visibility 0.3s;
5  }
6
7  /* Avoid: display changes cause reflow */
8  .avoid {
9      display: none;
10     transition: display 0.3s; /* Doesn't animate */
11 }
12
13 /* Optimize animations */
14 .element {
15     will-change: visibility;
16     visibility: visible;
17     transition: visibility 0.3s;
18 }
```

10.2 Mobile Optimization

```
1  /* Reduce motion on mobile */
2  @media (prefers-reduced-motion: reduce) {
3      .animated-visibility {
4          transition: none;
5          visibility: hidden;
6      }
7  }
8
9  /* Faster transitions on mobile */
10 @media (max-width: 768px) {
11     .element {
12         transition: visibility 0.15s, opacity 0.15s;
13     }
14 }
```

11 Browser Support

11.1 Compatibility Table

Feature	Chrome	Firefox	Safari	Edge
visibility: visible	All	All	All	All
visibility: hidden	All	All	All	All
visibility: collapse	All	All	All	All
Visibility transitions	All	All	All	All

12 Common Mistakes

12.1 Mistake 1: Using Hidden for Space Removal

Wrong (preserves unwanted space):

```
1  .removed {
2      visibility: hidden; /* Still takes up space */
3  }
```

Correct:

```
1  .removed {
2      display: none; /* Removes completely */
3  }
```

12.2 Mistake 2: Animating Display

Wrong (doesn't animate):

```
1  .element {
2      display: block;
3      transition: display 0.3s; /* Doesn't work */
4  }
5
```

```
6 .element.hidden {
7     display: none;
8 }
```

Correct:

```
1 .element {
2     visibility: visible;
3     opacity: 1;
4     transition: visibility 0.3s, opacity 0.3s;
5 }
6
7 .element.hidden {
8     visibility: hidden;
9     opacity: 0;
10 }
```

12.3 Mistake 3: Hidden Elements in Tab Order

Problem (hidden but focusable):

```
1 .hidden-input {
2     visibility: hidden;
3     /* Can still receive focus */
4 }
```

Solution:

```
1 .hidden-input {
2     visibility: hidden;
3     pointer-events: none; /* Prevent interaction */
4 }
5
6 /* Or for truly hidden */
7 .hidden-input {
8     display: none;
9 }
```

12.4 Mistake 4: Forgetting Pointer-Events

Problem (hidden but clickable):

```
1 .hidden-button {
2     visibility: hidden;
3     /* Still responds to clicks */
4 }
```

Solution:

```
1 .hidden-button {
2     visibility: hidden;
3     pointer-events: none; /* Prevent clicks */
4 }
```

12.5 Mistake 5: Visibility vs Opacity Confusion

Wrong approach (for animations):

```
1 .fade {  
2     visibility: hidden;  
3     /* Can't animate visibility smoothly */  
4 }
```

Better:

```
1 .fade {  
2     opacity: 0;  
3     transition: opacity 0.3s;  
4 }
```

13 Quick Reference

13.1 Common Visibility Patterns

```
1 /* Basic hide with space preservation */  
2 .hidden { visibility: hidden; }  
3  
4 /* Animated fade with visibility */  
5 .element {  
6     visibility: visible;  
7     opacity: 1;  
8     transition: visibility 0.3s, opacity 0.3s;  
9 }  
10 .element.hidden {  
11     visibility: hidden;  
12     opacity: 0;  
13 }  
14  
15 /* Toggle for interaction */  
16 .toggle:hover { visibility: visible; }  
17 .toggle { visibility: hidden; }  
18  
19 /* Accordion collapse */  
20 .collapsed {  
21     visibility: hidden;  
22     max-height: 0;  
23     transition: visibility 0.3s, max-height 0.3s;  
24 }  
25  
26 /* Modal hidden state */  
27 .modal.hidden {  
28     visibility: hidden;  
29     opacity: 0;  
30 }
```


13.2 Production Checklist

- Use `visibility: hidden` for space-preserving hide
- Use `display: none` for complete removal
- Use `opacity: 0` for smooth animations
- Add `pointer-events: none` to hidden interactive elements
- Test visibility on actual content
- Ensure hidden content is inaccessible to keyboard
- Use transitions for smooth reveal/hide
- Combine with appropriate display values
- Respect `prefers-reduced-motion`
- Test accessibility with screen readers

14 Summary

The `visibility` property controls element visibility while preserving layout space. Key takeaways:

1. `visibility: hidden` hides elements but preserves their space
2. `visibility: visible` shows elements (default)
3. `visibility: collapse` is for table-specific hiding
4. Use visibility for smooth animations with transitions
5. Combine with `opacity` for fade effects
6. Add `pointer-events: none` to prevent interaction
7. Use `display: none` when you want complete removal
8. Use `opacity: 0` for animatable transparency
9. Test keyboard navigation with hidden elements
10. Understand inheritance behavior for child elements

Master the visibility property to create smooth, responsive interactions that enhance user experience while maintaining layout stability and accessibility across all devices.