

# **CSS Transition Properties**

## Complete Guide: From Basics to Advanced

# Contents

|          |                                         |           |
|----------|-----------------------------------------|-----------|
| <b>1</b> | <b>Introduction</b>                     | <b>2</b>  |
| 1.1      | What are Transitions? . . . . .         | 2         |
| 1.2      | Transition vs. Animation . . . . .      | 2         |
| 1.3      | Why Use Transitions? . . . . .          | 2         |
| <b>2</b> | <b>Core Transition Properties</b>       | <b>3</b>  |
| 2.1      | transition-property . . . . .           | 3         |
| 2.1.1    | Syntax . . . . .                        | 3         |
| 2.1.2    | Common Values . . . . .                 | 3         |
| 2.1.3    | Examples . . . . .                      | 3         |
| 2.2      | transition-duration . . . . .           | 4         |
| 2.2.1    | Syntax . . . . .                        | 4         |
| 2.2.2    | Parameters . . . . .                    | 4         |
| 2.2.3    | Examples . . . . .                      | 5         |
| 2.3      | transition-delay . . . . .              | 5         |
| 2.3.1    | Syntax . . . . .                        | 5         |
| 2.3.2    | Parameters . . . . .                    | 6         |
| 2.3.3    | Examples . . . . .                      | 6         |
| <b>3</b> | <b>Transition Timing Functions</b>      | <b>7</b>  |
| 3.1      | transition-timing-function . . . . .    | 7         |
| 3.1.1    | Syntax . . . . .                        | 7         |
| 3.1.2    | Built-in Timing Functions . . . . .     | 7         |
| 3.2      | cubic-bezier() . . . . .                | 8         |
| 3.2.1    | Syntax . . . . .                        | 8         |
| 3.2.2    | Common Cubic Bezier Values . . . . .    | 9         |
| 3.2.3    | Examples . . . . .                      | 9         |
| 3.3      | steps() . . . . .                       | 9         |
| 3.3.1    | Syntax . . . . .                        | 9         |
| 3.3.2    | Examples . . . . .                      | 10        |
| <b>4</b> | <b>The Transition Shorthand</b>         | <b>11</b> |
| 4.1      | Using the transition Property . . . . . | 11        |
| 4.1.1    | Syntax . . . . .                        | 11        |
| 4.1.2    | Order Matters . . . . .                 | 11        |
| 4.1.3    | Examples . . . . .                      | 11        |

|          |                                                        |           |
|----------|--------------------------------------------------------|-----------|
| <b>5</b> | <b>Real-World Use Cases</b>                            | <b>13</b> |
| 5.1      | Button Hover Effects . . . . .                         | 13        |
| 5.2      | Smooth Color Change on Input . . . . .                 | 13        |
| 5.3      | Image Overlay Effect . . . . .                         | 14        |
| 5.4      | Dropdown Menu . . . . .                                | 15        |
| 5.5      | Page Navigation Slide-in . . . . .                     | 15        |
| 5.6      | Smooth Scroll to Section . . . . .                     | 16        |
| <b>6</b> | <b>Advanced Techniques</b>                             | <b>17</b> |
| 6.1      | Chaining Transitions with JavaScript . . . . .         | 17        |
| 6.2      | Transition End Events . . . . .                        | 17        |
| 6.3      | Accessibility: Respecting Motion Preferences . . . . . | 18        |
| 6.4      | GPU-Accelerated Properties . . . . .                   | 18        |
| <b>7</b> | <b>Browser Support &amp; Best Practices</b>            | <b>20</b> |
| 7.1      | Browser Support . . . . .                              | 20        |
| 7.2      | Performance Best Practices . . . . .                   | 20        |
| 7.3      | Common Mistakes . . . . .                              | 20        |
| 7.3.1    | Mistake 1: Wrong Duration . . . . .                    | 20        |
| 7.3.2    | Mistake 2: Transitioning Too Many Properties . . . . . | 21        |
| 7.3.3    | Mistake 3: Not Testing Focus States . . . . .          | 21        |
| 7.4      | Tips for Better Transitions . . . . .                  | 21        |
| 7.5      | Transition Duration Guidelines . . . . .               | 22        |
| <b>8</b> | <b>Quick Reference Guide</b>                           | <b>23</b> |
| 8.1      | Transition Properties Summary . . . . .                | 23        |
| 8.2      | Timing Functions Comparison . . . . .                  | 23        |
| 8.3      | Complete Example Collection . . . . .                  | 23        |
| 8.3.1    | Color Fade . . . . .                                   | 23        |
| 8.3.2    | Scale Zoom . . . . .                                   | 24        |
| 8.3.3    | Slide Left . . . . .                                   | 24        |
| 8.3.4    | Fade Out . . . . .                                     | 24        |
| 8.3.5    | Rotate . . . . .                                       | 24        |
| 8.4      | Do's and Don'ts . . . . .                              | 24        |

# Chapter 1

## Introduction

### 1.1 What are Transitions?

CSS transitions allow you to smoothly animate changes between two CSS states. Instead of a property changing instantly, a transition makes it change gradually over a specified time period.

Think of transitions like a slow-motion camera that captures the change from one style to another!

### 1.2 Transition vs. Animation

- **Transition:** Changes between two states smoothly (triggered by hover, focus, etc.)
- **Animation:** More complex, can have multiple keyframes, runs automatically
- **Transition use case:** Interactive effects, hover states, focus states
- **Animation use case:** Looping effects, complex sequences, auto-play

### 1.3 Why Use Transitions?

- **Better UX:** Makes interactions feel smooth and polished
- **Visual Feedback:** Users understand what's happening
- **Simple to implement:** Just a few CSS lines needed
- **Performance:** GPU-accelerated, smooth 60fps animations
- **Interactive:** Responds to user actions like hovering or clicking

## Chapter 2

# Core Transition Properties

### 2.1 transition-property

Specifies which CSS property will be transitioned.

#### 2.1.1 Syntax

```
transition-property: property-name;
```

#### 2.1.2 Common Values

- **all**: Transitions all properties that change (default)
- **color**: Transitions color changes
- **background-color**: Transitions background color
- **width**: Transitions width changes
- **height**: Transitions height changes
- **transform**: Transitions transform changes
- **opacity**: Transitions opacity changes
- Multiple properties: `color, background-color, width`

#### 2.1.3 Examples

##### Transition Specific Property

```
.button {  
  background-color: blue;  
  transition-property: background-color;  
}  
  
.button:hover {  
  background-color: red;  
}
```

Only the background-color transitions smoothly.

### Transition All Properties

```
.box {  
  width: 100px;  
  height: 100px;  
  background: blue;  
  transition-property: all;  
}  
  
.box:hover {  
  width: 200px;  
  height: 200px;  
  background: red;  
}
```

All properties (width, height, background) transition together.

### Transition Multiple Specific Properties

```
.card {  
  color: black;  
  background: white;  
  transform: scale(1);  
  transition-property: color, background, transform;  
}  
  
.card:hover {  
  color: white;  
  background: navy;  
  transform: scale(1.1);  
}
```

---

## 2.2 transition-duration

Specifies how long the transition takes.

### 2.2.1 Syntax

```
transition-duration: time;
```

### 2.2.2 Parameters

- Time in seconds (s): 0.5s, 1s, 2.5s
- Time in milliseconds (ms): 500ms, 1000ms

### 2.2.3 Examples

#### Fast Transition (0.3 seconds)

```
.button {  
  background: blue;  
  transition-property: background;  
  transition-duration: 0.3s;  
}  
  
.button:hover {  
  background: red;  
}
```

#### Slow Transition (2 seconds)

```
.box {  
  opacity: 1;  
  transition-property: opacity;  
  transition-duration: 2s;  
}  
  
.box.fade-out {  
  opacity: 0;  
}
```

#### Multiple Durations for Multiple Properties

```
.element {  
  color: black;  
  background: white;  
  transition-property: color, background;  
  transition-duration: 0.5s, 1s;  
}  
  
.element:hover {  
  color: white;  
  background: black;  
}
```

Color changes in 0.5s, background changes in 1s.

## 2.3 transition-delay

Specifies when the transition starts (delay before it begins).

### 2.3.1 Syntax

```
transition-delay: time;
```

### 2.3.2 Parameters

- Time in seconds or milliseconds
- Negative values allowed (starts transition partway through)

### 2.3.3 Examples

#### Simple Delay

```
.button {  
  background: blue;  
  transition-property: background;  
  transition-duration: 0.5s;  
  transition-delay: 0.2s;  
}  
  
.button:hover {  
  background: red;  
}
```

Waits 0.2 seconds before starting the color transition.

#### Staggered Animations (Different Delays)

```
.box:nth-child(1) {  
  transition-delay: 0s;  
}  
  
.box:nth-child(2) {  
  transition-delay: 0.2s;  
}  
  
.box:nth-child(3) {  
  transition-delay: 0.4s;  
}
```

Each box starts its transition at a different time.

#### Negative Delay

```
.element {  
  opacity: 0;  
  transition-property: opacity;  
  transition-duration: 1s;  
  transition-delay: -0.5s;  
}
```

Starts the animation partway through (useful for synchronized animations).

## Chapter 3

# Transition Timing Functions

### 3.1 transition-timing-function

Controls the speed curve of the transition (how it progresses over time).

#### 3.1.1 Syntax

```
transition-timing-function: function;
```

#### 3.1.2 Built-in Timing Functions

##### **ease (default)**

Starts slow, speeds up in the middle, slows at the end. Most natural feeling.

```
.button {  
  background: blue;  
  transition: background 0.5s ease;  
}  
  
.button:hover {  
  background: red;  
}
```

##### **linear**

Moves at constant speed throughout.

```
.progress-bar {  
  width: 0%;  
  transition: width 2s linear;  
}  
  
.progress-bar.complete {  
  width: 100%;  
}
```

### **ease-in**

Slow start, fast end.

```
.box {  
  transform: translateY(0);  
  transition: transform 1s ease-in;  
}  
  
.box.move {  
  transform: translateY(100px);  
}
```

### **ease-out**

Fast start, slow end.

```
.button {  
  opacity: 1;  
  transition: opacity 0.5s ease-out;  
}  
  
.button.disappear {  
  opacity: 0;  
}
```

### **ease-in-out**

Slow at both start and end, fast in the middle.

```
.modal {  
  transform: scale(0);  
  transition: transform 0.3s ease-in-out;  
}  
  
.modal.open {  
  transform: scale(1);  
}
```

---

## **3.2 cubic-bezier()**

Custom timing function for advanced control.

### **3.2.1 Syntax**

```
transition-timing-function: cubic-bezier(x1, y1, x2, y2);
```

### 3.2.2 Common Cubic Bezier Values

- **ease**: cubic-bezier(0.25, 0.1, 0.25, 1)
- **linear**: cubic-bezier(0, 0, 1, 1)
- **ease-in**: cubic-bezier(0.42, 0, 1, 1)
- **ease-out**: cubic-bezier(0, 0, 0.58, 1)
- **ease-in-out**: cubic-bezier(0.42, 0, 0.58, 1)

### 3.2.3 Examples

#### Custom Smooth Ease

```
.element {  
  background: blue;  
  transition: background 0.5s cubic-bezier(0.34, 1.56, 0.64, 1);  
}  
  
.element:hover {  
  background: red;  
}
```

#### Bouncy Effect

```
.bounce-box {  
  transform: scale(1);  
  transition: transform 0.5s cubic-bezier(0.68, -0.55, 0.265, 1.55);  
}  
  
.bounce-box:hover {  
  transform: scale(1.2);  
}
```

---

## 3.3 steps()

Creates discrete steps instead of smooth transitions.

### 3.3.1 Syntax

```
transition-timing-function: steps(number-of-steps);
```

### 3.3.2 Examples

#### Loading Animation (4 Steps)

```
.loader {  
  background-position: 0 0;  
  transition: background-position 0.8s steps(4);  
}  
  
.loader.loading {  
  background-position: -200px 0;  
}
```

#### Countdown Effect (10 Steps)

```
.countdown {  
  width: 100%;  
  transition: width 10s steps(10);  
}  
  
.countdown.active {  
  width: 0%;  
}
```

## Chapter 4

# The Transition Shorthand

### 4.1 Using the transition Property

You can combine all transition properties into one shorthand.

#### 4.1.1 Syntax

```
transition: property duration timing-function delay;
```

#### 4.1.2 Order Matters

1. Property (what to transition)
2. Duration (how long)
3. Timing function (speed curve)
4. Delay (wait time)

#### 4.1.3 Examples

##### Simple Transition

```
.button {  
  background: blue;  
  transition: background 0.3s ease;  
}  
  
.button:hover {  
  background: red;  
}
```

##### Transition with Delay

```
.box {
  opacity: 1;
  transition: opacity 0.5s ease 0.2s;
}

.box.hidden {
  opacity: 0;
}
```

## Multiple Properties

```
.card {
  background: white;
  transform: translateY(0);
  box-shadow: 0 2px 5px rgba(0,0,0,0.1);
  transition: background 0.3s ease,
              transform 0.3s ease,
              box-shadow 0.3s ease;
}

.card:hover {
  background: #f0f0f0;
  transform: translateY(-5px);
  box-shadow: 0 5px 15px rgba(0,0,0,0.2);
}
```

## Transition All

```
.element {
  transition: all 0.5s ease;
}

.element.active {
  /* Any CSS property change will be transitioned */
  background: blue;
  color: white;
  transform: scale(1.1);
  width: 200px;
}
```

## Chapter 5

# Real-World Use Cases

### 5.1 Button Hover Effects

```
<style>
  .button {
    background: #007bff;
    color: white;
    padding: 10px 20px;
    border: none;
    border-radius: 5px;
    cursor: pointer;
    transition: all 0.3s ease;
  }

  .button:hover {
    background: #0056b3;
    transform: scale(1.05);
    box-shadow: 0 4px 12px rgba(0, 86, 179, 0.3);
  }

  .button:active {
    transform: scale(0.98);
  }
</style>

<button class="button">Hover Me</button>
```

---

### 5.2 Smooth Color Change on Input

```
<style>
  input {
    padding: 10px;
    border: 2px solid #ccc;
    border-radius: 5px;
    transition: border-color 0.3s ease;
  }
```

```
input:focus {
  outline: none;
  border-color: #007bff;
}

input.error {
  border-color: #dc3545;
}
</style>

<input type="text" placeholder="Type here...">
```

### 5.3 Image Overlay Effect

```
<style>
.image-container {
  position: relative;
  width: 300px;
  overflow: hidden;
  border-radius: 8px;
}

.image-container img {
  width: 100%;
  display: block;
}

.overlay {
  position: absolute;
  top: 0;
  left: 0;
  width: 100%;
  height: 100%;
  background: rgba(0, 0, 0, 0);
  transition: background 0.3s ease;
}

.image-container:hover .overlay {
  background: rgba(0, 0, 0, 0.5);
}
</style>

<div class="image-container">
  
  <div class="overlay"></div>
</div>
```

## 5.4 Dropdown Menu

```
<style>
  .dropdown-menu {
    max-height: 0;
    overflow: hidden;
    transition: max-height 0.3s ease;
  }

  .dropdown-toggle:hover + .dropdown-menu {
    max-height: 200px;
  }

  .dropdown-menu li {
    padding: 10px;
    background: #f8f9fa;
  }
</style>

<button class="dropdown-toggle">Menu</button>
<ul class="dropdown-menu">
  <li>Option 1</li>
  <li>Option 2</li>
  <li>Option 3</li>
</ul>
```

## 5.5 Page Navigation Slide-in

```
<style>
  .sidebar {
    position: fixed;
    left: 0;
    top: 0;
    width: 250px;
    height: 100vh;
    background: #333;
    transform: translateX(-100%);
    transition: transform 0.3s ease;
  }

  .sidebar.open {
    transform: translateX(0);
  }

  .toggle-button {
    cursor: pointer;
    padding: 10px;
  }
</style>
```

```

<button class="toggle-button" onclick="toggleSidebar()">
  Menu
</button>
<div class="sidebar"></div>

<script>
  function toggleSidebar() {
    document.querySelector('.sidebar')
      .classList.toggle('open');
  }
</script>

```

## 5.6 Smooth Scroll to Section

```

<style>
  html {
    scroll-behavior: smooth;
  }

  .section {
    min-height: 100vh;
    display: flex;
    align-items: center;
    justify-content: center;
    transition: background 0.5s ease;
  }

  .section:nth-child(1) { background: #ff6b6b; }
  .section:nth-child(2) { background: #4ecdc4; }
  .section:nth-child(3) { background: #45b7d1; }
</style>

<nav>
  <a href="#section1">Section 1</a>
  <a href="#section2">Section 2</a>
  <a href="#section3">Section 3</a>
</nav>

<div id="section1" class="section"></div>
<div id="section2" class="section"></div>
<div id="section3" class="section"></div>

```

## Chapter 6

# Advanced Techniques

### 6.1 Chaining Transitions with JavaScript

```
<style>
  .box {
    width: 100px;
    height: 100px;
    background: blue;
    transition: width 0.5s ease, height 0.5s ease 0.5s;
  }

  .box.expand {
    width: 200px;
    height: 200px;
  }
</style>

<div class="box"></div>

<script>
  const box = document.querySelector('.box');

  box.addEventListener('click', () => {
    box.classList.toggle('expand');
  });
</script>
```

---

### 6.2 Transition End Events

```
<style>
  .element {
    opacity: 1;
    transition: opacity 1s ease;
  }

  .element.fade {
```

```

    opacity: 0;
  }
</style>

<div class="element">Transitioning element</div>

<script>
  const element = document.querySelector('.element');

  element.addEventListener('transitionend', function() {
    console.log('Transition finished!');
  });

  // Start transition
  element.classList.add('fade');
</script>

```

### 6.3 Accessibility: Respecting Motion Preferences

```

<style>
  .animated-button {
    background: blue;
    transition: background 0.5s ease;
  }

  .animated-button:hover {
    background: red;
  }

  /* Respect user's motion preferences */
  @media (prefers-reduced-motion: reduce) {
    .animated-button {
      transition: none;
    }
  }
</style>

<button class="animated-button">Hover Me</button>

```

### 6.4 GPU-Accelerated Properties

```

/* These properties are GPU-accelerated (smooth) */
.element {
  transition: transform 0.3s ease;    /* Good */
  transition: opacity 0.3s ease;     /* Good */
  transition: filter 0.3s ease;      /* Good */
}

```

```
/* Avoid transitioning these (CPU-intensive) */
.element {
  transition: width 0.3s ease;           /* CPU-intensive */
  transition: height 0.3s ease;         /* CPU-intensive */
  transition: left 0.3s ease;           /* CPU-intensive */
}

/* Better alternative */
.element {
  transition: transform 0.3s ease;       /* Use transform instead */
}
```

## Chapter 7

# Browser Support & Best Practices

### 7.1 Browser Support

CSS transitions are supported in all modern browsers:

- Chrome 26+
  - Firefox 16+
  - Safari 9+
  - Edge 12+
  - Mobile browsers (all modern versions)
- 

### 7.2 Performance Best Practices

1. **Use GPU-Accelerated Properties:** transform and opacity are smooth
  2. **Avoid Layout-Triggering Properties:** Don't transition width/height
  3. **Keep Duration Reasonable:** 0.2s to 1s usually works best
  4. **Test on Mobile:** Performance varies on different devices
  5. **Use will-change Sparingly:** Only for frequently animated elements
- 

### 7.3 Common Mistakes

#### 7.3.1 Mistake 1: Wrong Duration

```
/* Too fast - feels jerky */  
transition: all 0.05s ease;  
  
/* Too slow - feels sluggish */
```

```
transition: all 5s ease;

/* Just right */
transition: all 0.3s ease;
```

### 7.3.2 Mistake 2: Transitioning Too Many Properties

```
/* Avoid - heavy on performance */
.box {
  transition: all 0.5s ease;
}

/* Better - only transition what needs it */
.box {
  transition: background 0.5s ease,
             transform 0.5s ease;
}
```

### 7.3.3 Mistake 3: Not Testing Focus States

```
/* Remember to transition focus states too */
.button {
  transition: background 0.3s ease;
}

.button:hover,
.button:focus {
  background: red;
}
```

---

## 7.4 Tips for Better Transitions

- **Match Easing to Context:** ease for natural feel, linear for progress
  - **Use Delays for Sequences:** Stagger multiple elements
  - **Combine with Transform:** Use transform instead of position for smoothness
  - **Test Keyboard Navigation:** Transitions should work with keyboard focus
  - **Provide Feedback:** Always indicate what's happening
-

## 7.5 Transition Duration Guidelines

- **0.1s - 0.2s:** Quick feedback (button clicks)
- **0.2s - 0.5s:** Standard interaction (hover effects)
- **0.5s - 1s:** Important changes (page transitions)
- **1s+:** Big transformations (modal opens)

## Chapter 8

# Quick Reference Guide

### 8.1 Transition Properties Summary

- **transition-property:** Which CSS property to animate
  - **transition-duration:** How long the animation takes
  - **transition-delay:** Wait time before animation starts
  - **transition-timing-function:** Speed curve (ease, linear, etc.)
  - **transition:** Shorthand for all above
- 

### 8.2 Timing Functions Comparison

- **ease:** Smooth, natural (default)
  - **linear:** Constant speed
  - **ease-in:** Accelerating
  - **ease-out:** Decelerating
  - **ease-in-out:** Slow at both ends
  - **cubic-bezier():** Custom curves
  - **steps():** Discrete steps
- 

### 8.3 Complete Example Collection

#### 8.3.1 Color Fade

```
.element {  
  color: black;  
  transition: color 0.3s ease;  
}  
.element:hover { color: red; }
```

### 8.3.2 Scale Zoom

```
.element {  
  transform: scale(1);  
  transition: transform 0.3s ease;  
}  
.element:hover { transform: scale(1.1); }
```

### 8.3.3 Slide Left

```
.element {  
  transform: translateX(0);  
  transition: transform 0.3s ease;  
}  
.element:hover { transform: translateX(10px); }
```

### 8.3.4 Fade Out

```
.element {  
  opacity: 1;  
  transition: opacity 0.3s ease;  
}  
.element:hover { opacity: 0.5; }
```

### 8.3.5 Rotate

```
.element {  
  transform: rotate(0deg);  
  transition: transform 0.5s ease;  
}  
.element:hover { transform: rotate(180deg); }
```

## 8.4 Do's and Don'ts

| Do                         | Don't                     |
|----------------------------|---------------------------|
| Use transform and opacity  | Transition width/height   |
| Keep durations 0.2s-1s     | Make transitions too long |
| Respect motion preferences | Ignore accessibility      |
| Test on mobile             | Only test on desktop      |
| Use GPU properties         | Animate everything        |