

22. Styles aur Classes

Ek important rule

Element style karne ke 2 tarike: **CSS class** ya seedha **style**. **Hamesha CSS classes ko prefer karo.** **style** tab use karo jab classes se na ho sake (jaise runtime me calculate hue coordinates).

js

```
elem.style.left = left;    // e.g. '123px', runtime pe calculate hui
elem.style.top = top;
```

className aur **classList**

- **elem.className**: poori **class** string (assign karne par **saari classes replace** ho jaati hain).
- **elem.classList**: ek object jo individual classes ke liye methods deta hai:
 - **add("x")**, **remove("x")**
 - **toggle("x")**: hai to hata do, nahi hai to lagao
 - **contains("x")**: **true/false**
 - Ye iterable bhi hai (**for..of**).

js

```
document.body.classList.add('article');
```

elem.style

- **style** attribute jaisa object. Multi-word properties **camelCase** me:
 - **background-color** -> **style.backgroundColor**
 - **z-index** -> **style.zIndex**
 - **border-left-width** -> **style.borderLeftWidth**
 - **Prefixed: -webkit-border-radius** -> **style.WebkitBorderRadius**

Style reset karna

delete nahi, **empty string** assign karo:

js

```
elem.style.display = "none";    // hide
elem.style.display = "";        // wapas normal (CSS classes lag jaati hain)
// ya
elem.style.removeProperty('background');
```

style.cssText

Poora style ek string me set karna (`!important` bhi de sakte ho). Par ye **purane sab inline styles ko replace** kar deta hai, isliye kam use hota hai.

```
js
div.style.cssText = `color: red !important; width: 100px;`;
```

(`div.style = "..."`) **nahi** chalta, (`style`) read-only object hai.)

Units mat bhulo!

```
js
document.body.style.margin = 20;    // kaam nahi karta (ignore)
document.body.style.margin = '20px'; // sahi
```

Browser (`margin`) ko todkar (`marginTop`), (`marginLeft`) etc. bhi nikal deta hai.

getComputedStyle (style padhne ke liye)

(`elem.style`) sirf (`style`) attribute ko dekhta hai, **CSS classes/cascade nahi**. Isliye:

```
js
let cs = getComputedStyle(document.body);
cs.marginTop;    // "5px"
cs.color;        // "rgb(255, 0, 0)"
```

Syntax: (`getComputedStyle(element, [pseudo])`) (jaise (`'::before'`)).

Kuch notes:

- Aajkal ye **resolved value** deta hai (relative units jaise (`1em`) ka fixed (`px`) version).
- **Poora property naam** do (`paddingLeft`), shorthand (`padding`) ka result guaranteed nahi.
- (`:visited`) link ke styles **chhupe** rahte hain (privacy ke liye).

Summary

- Classes: `className` (poora set), `classList` (individual).
- Styles likhna: `style.property`, `style.cssText`.
- Styles padhna (final): `getComputedStyle(elem)`, read-only.