

29. Browser Default Actions

Kai events ke saath browser **apne aap kuch karta hai** (default action):

- Link par click -> us URL par jaana
- Submit button par click -> form submit
- Mouse dabakar ghumana -> text select
- Right click (`contextmenu`) -> browser ka context menu

Agar hum event khud handle kar rahe hain, to hum default action **rokna** chah sakte hain.

Default action rokne ke 2 tarike

1. `event.preventDefault()` (main tarika)
2. Handler `on<event>` se laga ho to `return false` bhi wahi karta hai.

html

```
<a href="/" onclick="return false">Click here</a>
<a href="/" onclick="event.preventDefault()">here</a>
```

Handler ki return value aam taur par ignore hoti hai, sirf `on<event>` me `return false` exception hai. `addEventListener` me `return false` ka koi asar nahi.

Example: JS menu

Menu items (`<a>`) hi rakho (right click, search engines, accessibility ke liye), par click JS se handle karo:

js

```
menu.onclick = function(event) {
  if (event.target.nodeName !== 'A') return;
  let href = event.target.getAttribute('href');
  alert(href);
  return false; // URL par jaane se roko
};
```

Follow-up events

Kuch events ek ke baad ek aate hain. Pehla roka to doosra nahi aata. Jaise `mousedown` roko to `<input>` par **focus** nahi hota (Tab key se ho jaata hai).

`passive: true` option

js

```
elem.addEventListener('touchmove', handler, { passive: true });
```

Browser ko batata hai ki handler `preventDefault()` **nahi** karega. Isse mobile scrolling jhatke ke bina smooth hoti hai (browser handlers ke khatam hone ka wait nahi karta). Firefox/Chrome me `touchstart`/`touchmove` par ye default `true` hai.

`event.defaultPrevented`

`true` agar default action roka gaya, warna `false`.

Use case: `stopPropagation()` ke bajay ye signal dena ki event "handle ho chuka":

```
js

elem.oncontextmenu = function(event) {
  event.preventDefault();
  alert("Button context menu");
};

document.oncontextmenu = function(event) {
  if (event.defaultPrevented) return; // pehle hi handle ho gaya
  event.preventDefault();
  alert("Document context menu");
};
```

`stopPropagation()` se bahar ka code (jaise analytics) ko right click ki info nahi milti, isliye ye behtar hai.

`stopPropagation()` aur `preventDefault()` **alag cheezein** hain, ek doosre se related nahi.

Semantic raho, abuse mat karo

Technically kisi bhi element ka behavior badal sakte ho (link ko button jaisa), par HTML elements ka meaning banaye rakho: `<a>` navigation ke liye, `<button>` action ke liye. Isse accessibility better rehti hai aur "new tab me kholo" jaisi browser features kaam karti hain.

Kuch aur default actions

`mousedown` (selection shuru), checkbox par `click` (check/uncheck), `submit`, `keydown` (character likhna), `contextmenu`.

Tasks (short)

- `return false` kyun nahi chala? `onclick="handler()"` me browser function banata hai jo `handler()` ko call karke uski value **return nahi karta**. Fix: `onclick="return handler()"` ya `handler(event)` me `event.preventDefault()`.
- Links ke liye confirm:** container par delegation, `link.getAttribute('href')` use karo.

- **Image gallery:** container par click, `<a>` par `preventDefault()`, main image ka `src` = thumbnail ka `href`.