

# Big Data with High Performance Computing (HPC)

Tarek El-Ghazawi, Krunal Puri, and Armin Mehrabian

George Washington University

**Abstract** Abstract goes here


**Keywords:** ...

## 1 Introduction

With the recent emergence of Big Data over the past few years, one of the questions that arises is, how Big Data is different from High Performance Computing (HPC) at various levels such as application, technology, investment, etc. Another critical question to be asked is if Big Data is widely different from HPC, which of the technologies may we want to adopt or, do we really have to choose one from the two to apply to our problems? Another scenario is that the gap between Big Data and HPC may form a spectrum of choices rather than two independent worlds. To answer these questions in this chapter we will first bring an introduction and look at Big Data and HPC from a high level abstraction view. Then, we explain the state of the art efforts to take advantage of the best of two worlds. Finally, we will address future challenges and future directions.

In order to answer the above questions we first may need to identify the workloads and computational requirements of workflows for our applications. It is also important to not focus only current trends, and take into account the future data and computation demands. Figure 1 shows the matrix of data size versus computation size for some applications. It also shows that the current big data technologies, formed around Apache Big Data Stack (ABDS), is data-intensive but focused less on computational performance. On the other hand the High Performance Computing (HPC), which mostly applied to solving scientific problems, has been mostly concentrated on computation-savvy, data limited application such and iterative simulations.

Over the past decade, the rate of data generation has dramatically increased. As a result, we saw the emergence of data-intensive applications to solve a range of problems from data distribution and management to data processing. The open-source Apache Big Data Stack with its Hadoop Data File System (HDFS) kernel and many higher abstraction level frameworks for data analytics and machine learning has provided a coherent ecosystem, which has dominated the



**Figure 1.** Matrix of data and computation applications.


industry.

In contrast, HPC with roots in computational intensive scientific computing, has mainly been applied and fine-tuned for particular problems, which resulted in significantly more limited implementations compared to ABDS. Figure 2 depicts the HPC and Big Data ecosystems from many abstraction level view. The lowest layers are the resources, resource management, and communication layers. The higher layers comprise of processing and analytical components. In remaining parts of this section we compare current typical HPC and Big Data architectures and their respective ecosystems.

### 1.1 HPC Architecture

A typical HPC architecture consists of processing units such a multi-core structures, possibly accelerated by GPUs, FPGAs, or even CPUs such as intel Xeon Phi. These processing units are supported by local storage units with Lustre [4] or General Parallel File System (GPFS) [12] file system or a remote storage connected through a fast network such as Infiniband.

Lustre and GPFS are parallel file systems designed mainly for clusters. Lustre, which combines the words Linux and Cluster is generally accepted as the file system with scalability for large scale cluster computing. Due to its high performance it has been continuously used by top supercomputers. On the other hand GPFS introduced by IBM and adopted by many of the biggest companies all around the world. GPFS have its roots in academic grounds and its scalability is a matter of question. Storage resources in HPC are managed by storage management unit such as integrated Rule-Oriented Data-management System



**Figure 2.** Apache Big Data Stack (ABDS) ecosystem vs. High Performance Computing (HPC) ecosystem [17].

(iRODS), Storage Resource Manager interface (SRM) [27] [25], Global Federated File System (GFFS) [15].

While storage resources are usually shared in applications, computational resources are local. Such local compute resources are managed by their own management units such as Slurm [31], Torque [29], and Sun Grid Engine (SGE) [13].

In HPC applications, data need to fly around across network using a low latency communication. These fast interconnect networks along with features such as non-blocking and one-sided communications allow for more data-intensive HPC within HPC environment. As a matter of fact, data-intensive applications are not totally unfamiliar to HPC community. There has been many approaches to implement MapReduce compatible with HPC environment such as MapReduce-MPI [21], Pilot-MapReduce [20], and Twister for machine learning applications [10]. In a parallel effort, there has been many implementations of data intensive loosely coupled tasks at run-time level [19][24][8].

## 1.2 ABDS Architectures

The Apache Big Data Stack is formed around the Hadoop Distributed File System (HDFS), which originated at Yahoo but is an open source implementation of Google's file system [28] [14]. As we know now, the idea behind ABDS was to bring the computation to data, which is usually stored at cheap commodity hardware. Hadoop 1.0 also took advantage of Google's MapReduce programming model for data processing. MapReduce imposes it's own limitations since all processes is forced to be implemented in the form of a mapper followed by a

reducer. MapReduce’s inherent limitations along with tight coupling of Hadoop and MapReduce proved to be inflexible when used in applications such as iterative computations, which is an indispensable piece of all Machine Learning algorithms.

As a result of such deficits in Hadoop 1.0, Apache YARN was introduced with Hadoop 2.0 as a much more lenient resource manager, enabling many applications and frameworks with higher level abstractions [30]. YARN’s key feature was introduction multi-level scheduling, which would allow higher level applications to schedule their own processes. As a results we saw the emerge of many high level applications such as, HBase, a column based distributed database, Spark, Giraph, which are iterative and graph processing applications[3][32].

## 2 State of the art projects

In this section we will review some of the state of the art researches and projects within HPC-Big Data domains. We categorized these project under four class of research topics, namely,


1. Integration of HPC and ABDS stack
2. Machine Learning (ML) using HPC
3. Parallel databases
4. Parallel I/O

### 2.1 Integration of HPC and Big Data stack

Big Data and HPC used to be used interchangeably for many years. But, with HPC targeting scientific problems with huge number of iterations, and Big Data aiming for relatively simple model on huge datasets, it seems they diverged for a while. As the rate of data generation increase, deployment of HPC tools and techniques seem more and more inevitable. Following projects are some of the state of the arts in combining HPC and Big Data stack.

**High Performance Big Data System (HPBDS) project [23]** : The HPBDS project aims for integrating some of the components of the HPC such as scientific libraries, fast communication and resource management features with commercial Big Data ecosystem namely, ABDS.

The primary proposed execution of HPBDS is built around Apache Hadoop and therefore named High Performance Computing Big Data Stack (HPC-ABDS). The HPC-ABDS comprise two sub-project,



**Figure 3.** MIDAS and SPIDAL within HPC-ABDS stack[23]

1. Middleware for Data Intensive Analytics and Science (MIDAS)
2. Scalable Parallel Interoperable Data Analytics Library (SPIDAL)

Figure 3 depicts the structure of the MIDAS-SPIDAL with respect to the overall HPC-ABDS stack. MIDAS is proposed to provide a lower level infrastructure based on which higher level components such as libraries operates. On the other hand SPIDAL goal is to take advantage of useful tool within HPC such as MPI, PETSc, and SCALAPACK and modify them for data intensive applications.

The HPC-ABDS project is inspired by the NIST Big Data initiative in Fall 2013, when NIST provided a collection of use cases. These use cases were analyzed against the identifiers proposed as big data Ogres [11]. The result is tabulated in Table 1. Based on the data in

**Table 1.** Armin

Abbreviation	Count	Description
PP	26	Pleasingly Parallel or Map Only
MR	18	Classic MapReduce MR (add MRStat below for full count)
MRStats	7	Simple version of MR where key computations are simple reduction as found in statistical averages such as histograms and averages
MRIter	23	Iterative MapReduce or MPI
Graph	9	Complex graph data structure needed in analysis
Fusion	11	Integrate diverse data to aid discovery/decision making; could involve sophisticated algorithms or could just be a portal
Streaming	41	Some data comes in incrementally and is processed this way
Classify	30	Classification: divide data into categories
S/Q	12	Index, Search and Query
CF	4	Collaborative Filtering for recommender engines
LML	36	Local Machine Learning (Independent for each parallel entity)
GML	26	Global Machine Learning: Deep Learning, Clustering, LDA, PLSI, MDS, Large Scale Optimizations as in Variational Bayes, MCMC, Lifted Belief Propagation, Stochastic Gradient Descent, L-BFGS, Levenberg-Marquardt. Can call EGO or Exascale Global Optimization with scalable parallel algorithm
	51	Workflow: Universal so no label
GIS	16	Geotagged data and often displayed in ESRI, Microsoft Virtual Earth, Google Earth, GeoServer etc.
HPC	5	Classic large-scale simulation of cosmos, materials, etc. generating (visualization) data
Agent	2	Simulations of models of data-defined macroscopic entities represented as agents

## 2.2 Machine Learning and HPC

Traditionally the words Machine Learning and HPC would imply two separate worlds with distinct border. But, over the past decade areas of AI such as machine learning and training neural networks of deep learning have found their ways through HPC world.

Iterative AI tools such as machine learning and deep learning initially introduced to HPC by adopting GPU accelerators and FPGAs. Such tools adopted to perform a wide range of AI task from image classification, audio recognition, data analytics. Machine learning is not a novel concept and has been around for a relatively long time. But, along with more computational power introduced by accelerators, two major factors played an undeniable role in re-emergence of machine learning and deep learning. First, data generation at the very fast rates fuels up machine learning training algorithms. In a series of reports by Domo, [1] the amount of data created at the some of the biggest Internet giants, is presented. Table show some of these numbers in only one minute time of Internet. Secondly, introduction of new training algorithms such as those adopted to train deep belief nets and resulted to the birth of the term Deep Learning [16]. Only even twenty years ago it would take very long time, if possible, to train a neural network with only ten hidden layers.

**Table 2.** One minute of Internet usage [1].

Company	Count
Facebook	Users like <b>4,166,667</b> posts.
Twitter	Users send <b>347,222</b> tweets.
Youtube	Users upload <b>300</b> hours of video.
Instagram	Users like <b>1,736,111</b> photos.
Pinterest	Users pin <b>9,722</b> images.
Apple	Users download <b>51,000</b> apps.
Netflix	Subscribers stream <b>77.160</b> hours of video.
Reddit	Users cast <b>18,327</b> votes.
Amazon	Receives <b>4,310</b> unique visitors.
Vine	Users play <b>1,041,666</b> videos.
Tinder	Users swipe <b>590,276</b> times.
Snapchat	Users share <b>284,722</b> snaps.
Buzzfeed	Users view <b>34,150</b> videos.
Skype	Users make <b>110,040</b> calls.
Uber	Passengers take <b>694</b> rides.


Deep Learning, which itself is a sub-category of machine learning. The major distinguishing difference between most of machine learning techniques and deep learning is in feature selection stage. In conventional machine learning techniques labeled/unlabeled data is fed into a set of hand crafted feature detectors to extract

features. A classifier takes the features as inputs to perform some statistical analysis and decide on the class of each input. Since the engineering of a good set of such hand crafted features is extremely costly and require a lot of expertise and domain knowledge, deep learning is introduced to find and tune such features automatically using machine and data to be used for a particular task.

There is a general consensus that scaling up each of the the training data size and model size will increase the accuracy of prediction in deep learning. Therefore, as the size of training data or the model increases, we require to parallelize the process on many machines and processing cores to enable the scaling. Consequently, two parallelization schemes is offered namely, data parallelization and model parallelization.

In data parallelization scheme, the training set is sharded into smaller data fragments. Each of these fragments is assigned to a different processing node. Each node replicates the global model so that each model will have a fragment of data with a copy of full model. During the training process the model is updated. Since different copies of the model are updated separately using different data, we need to synchronize all copies of the model into a global model, which is representative of all the data. The issue with such synchronizations is that the model are usually relatively big (up to Gigabytes) that we cannot easily synchronize them frequently. In addition, it is also so hard to fit large models in GPUs' memory.

In a similar manner, in model parallelization scheme, models are cut into smaller




**Figure 4.** Data parallelism architecture performing Stochastic Gradient Descent (SGC). Model replicas at each node calculate gradients  $\Delta w$  on a piece of data. Gradients are later transmitted asynchronously to Parameter Server to calculate updated weights.

pieces, which allows for scaling of the model. A drawback of model parallelization is that you have to synchronize all your copies of the model even more frequently



than data parallelization. Synchronization should take place for each model at every layer of it, which for nowadays deep networks can be tens of layers. Thus, networking plays an very important role when it comes to model parallelization. For instance, a typical neural network architecture with 1 billion nodes may require tens of seconds is using a typical Ethernet networking for synchronization. As a results, HPC known tools such a Infiniband and PCI Express would greatly enhance the networking bottleneck for Inter-node and Intra-node communications respectively.



**Figure 5.** An example of model parallelism scheme in DistBelief framework for deep distributed neural networks by Google [7]. Model is distributed accross four machines. Only nodes, which have edges crossing from one machine to another need to report their state.

There are many primary questions to be addressed when thinking about integration of machine learning and HPC. Questions such as, aside from accelerating machine learning applications with GPUs and FPGAs, is traditional HPC ready to be the drive force behind data savvy machine learning applications? Are current top 500 supercomputers capable of powering new AI era of machine learning and deep learning? From software point of view, does conventional HPC require extensive modification to deal with mostly correlated data variables in machine learning application? In the remaining of this section we will briefly introduce some of the ongoing researches and projects concentrated empowering machine learning with HPC medium.

#### **Project Adam: Building an Efficient and Scalable Deep Learning Training System [6]**

In 2012 Google announced that they have trained an unsupervised image recognition neural network with 1 billion connections using 10 million training images,

which can recognize cats from Youtube videos. Their training system consisted of a cluster of 1,000 computers with an aggregate of 16,000 cores [18].

Project Adam by Microsoft could be thought as the successor of Google's project. The goal of the project Adam is to train a photograph classifier using 14 million images of Imagenet [9] into 22,000 image categories. The trained system by project Adam is claimed to be 50 times faster than the state of the art system. Speed is not the only concern of Microsoft researchers, it is also claimed that the system will be as twice accurate with 30 times less number of machines.

**Dadiannao: A machine-learning supercomputer [5]**

### 3 Conclusion and Outlook

#### Acknowledgments ...

In the bibliography, use `\textsuperscript` for “st”, “nd”, ...: E.g., “The 2<sup>nd</sup> conference on examples”.

#### References

1. Data Never Sleeps, <https://www.domo.com/blog/2015/08/data-never-sleeps-3-0/>
2. NIST Big Data Working Group (NBD-WG), <http://bigdatawg.nist.gov/usecases.php>
3. Borthakur, D., Gray, J., Sarma, J.S., Muthukkaruppan, K., Spiegelberg, N., Kuang, H., Ranganathan, K., Molkov, D., Menon, A., Rash, S., et al.: Apache hadoop goes realtime at facebook. In: Proceedings of the 2011 ACM SIGMOD International Conference on Management of data. pp. 1071–1080. ACM (2011)
4. Braam, P.J., et al.: The lustre storage architecture (2004)
5. Chen, Y., Luo, T., Liu, S., Zhang, S., He, L., Wang, J., Li, L., Chen, T., Xu, Z., Sun, N., et al.: Dadiannao: A machine-learning supercomputer. In: Microarchitecture (MICRO), 2014 47th Annual IEEE/ACM International Symposium on. pp. 609–622. IEEE (2014)
6. Chilimbi, T., Suzue, Y., Apacible, J., Kalyanaraman, K.: Project adam: Building an efficient and scalable deep learning training system. In: 11th USENIX Symposium on Operating Systems Design and Implementation (OSDI 14). pp. 571–582 (2014)
7. Dean, J., Corrado, G., Monga, R., Chen, K., Devin, M., Mao, M., Senior, A., Tucker, P., Yang, K., Le, Q.V., et al.: Large scale distributed deep networks. In: Advances in Neural Information Processing Systems. pp. 1223–1231 (2012)
8. Deelman, E., Gannon, D., Shields, M., Taylor, I.: Workflows and e-science: An overview of workflow system features and capabilities. *Future Generation Computer Systems* 25(5), 528–540 (2009)
9. Deng, J., Dong, W., Socher, R., Li, L.J., Li, K., Fei-Fei, L.: Imagenet: A large-scale hierarchical image database. In: Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on. pp. 248–255. IEEE (2009)
10. Ekanayake, J., Li, H., Zhang, B., Gunarathne, T., Bae, S.H., Qiu, J., Fox, G.: Twister: a runtime for iterative mapreduce. In: Proceedings of the 19th ACM International Symposium on High Performance Distributed Computing. pp. 810–818. ACM (2010)
11. Fox, G.C., Jha, S., Qiu, J., Luckow, A.: Towards an understanding of facets and exemplars of big data applications. In: In proceedings of Workshop: Twenty Years of Beowulf (2014)
12. Frank Schmuck, R.H.: GPFS: A Shared-Disk File System for Large Computing Clusters <http://citeseer.ist.psu.edu/viewdoc/summary?doi=10.1.1.19.7147>
13. Gentzsch, W.: Sun grid engine: Towards creating a compute power grid. In: Cluster Computing and the Grid, 2001. Proceedings. First IEEE/ACM International Symposium on. pp. 35–36. IEEE (2001)
14. Ghemawat, S., Gobioff, H., Leung, S.T.: The google file system. In: ACM SIGOPS operating systems review. vol. 37, pp. 29–43. ACM (2003)
15. Grimshaw, A., Morgan, M., Kalyanaraman, A.: Gfs’s the xsede global federated file system. *Parallel Processing Letters* 23(02), 1340005 (2013)

16. Hinton, G.E., Osindero, S., Teh, Y.W.: A fast learning algorithm for deep belief nets. *Neural computation* 18(7), 1527–1554 (2006)
17. Jha, S., Qiu, J., Luckow, A., Mantha, P., Fox, G.C.: A Tale of Two Data-Intensive Paradigms: Applications, Abstractions, and Architectures. In: 2014 IEEE International Congress on Big Data. pp. 645–652. IEEE (jun 2014), <http://ieeexplore.ieee.org/articleDetails.jsp?arnumber=6906840>
18. Le, Q.V.: Building high-level features using large scale unsupervised learning. In: Acoustics, Speech and Signal Processing (ICASSP), 2013 IEEE International Conference on. pp. 8595–8598. IEEE (2013)
19. Luckow, A., Santcroos, M., Merzky, A., Weidner, O., Mantha, P., Jha, S.: PáLŰ: a model of pilot-abstractions. In: E-Science (e-Science), 2012 IEEE 8th International Conference on. pp. 1–10. IEEE (2012)
20. Mantha, P.K., Luckow, A., Jha, S.: Pilot-mapreduce: an extensible and flexible mapreduce implementation for distributed data. In: Proceedings of third international workshop on MapReduce and its Applications Date. pp. 17–24. ACM (2012)
21. Plimpton, S.J., Devine, K.D.: Mapreduce in mpi for large-scale graph algorithms. *Parallel Computing* 37(9), 610–632 (2011)
22. Qiu, J.: Towards HPC-ABDS : An Initial High-Performance Big Data Stack 1(1), 1–22 (2014)
23. Qiu, J., Jha, S., Luckow, A., Fox, G.C.: Towards hpc-abds: An initial high-performance big data stack. Building Robust Big Data Ecosystem ISO/IEC JTC 1 Study Group on Big Data pp. 18–21 (2014)
24. Raicu, I., Foster, I.T., Zhao, Y.: Many-task computing for grids and supercomputers. In: Many-Task Computing on Grids and Supercomputers, 2008. MTAGS 2008. Workshop on. pp. 1–11. IEEE (2008)
25. Rajasekar, A., Moore, R., Hou, C.y., Lee, C.A., Marciano, R., de Torcy, A., Wan, M., Schroeder, W., Chen, S.Y., Gilbert, L., et al.: irods primer: integrated rule-oriented data system. *Synthesis Lectures on Information Concepts, Retrieval, and Services* 2(1), 1–143 (2010)
26. Reed, D.a., Dongarra, J.: Exascale computing and big data. *Communications of the ACM* 58(7), 56–68 (2015), [http://dl.acm.org/ft\\_gateway.cfm?id=2699414&type=html](http://dl.acm.org/ft_gateway.cfm?id=2699414&type=html)
27. Shaun De Witt, R.: The storage resource manager interface specification (2007)
28. Shvachko, K., Kuang, H., Radia, S., Chansler, R.: The hadoop distributed file system. In: Mass Storage Systems and Technologies (MSST), 2010 IEEE 26th Symposium on. pp. 1–10. IEEE (2010)
29. Staples, G.: Torque resource manager. In: Proceedings of the 2006 ACM/IEEE conference on Supercomputing. p. 8. ACM (2006)
30. Vavilapalli, V.K., Murthy, A.C., Douglas, C., Agarwal, S., Konar, M., Evans, R., Graves, T., Lowe, J., Shah, H., Seth, S., et al.: Apache hadoop yarn: Yet another resource negotiator. In: Proceedings of the 4th annual Symposium on Cloud Computing. p. 5. ACM (2013)
31. Yoo, A.B., Jette, M.A., Grondona, M.: Slurm: Simple linux utility for resource management. In: Job Scheduling Strategies for Parallel Processing. pp. 44–60. Springer (2003)
32. Zaharia, M., Chowdhury, M., Das, T., Dave, A., Ma, J., McCauley, M., Franklin, M.J., Shenker, S., Stoica, I.: Resilient distributed datasets: A fault-tolerant abstraction for in-memory cluster computing. In: Proceedings of the 9th USENIX conference on Networked Systems Design and Implementation. pp. 2–2. USENIX Association (2012)

All links were last followed on October 5, 2014.