Aim: To create a Lambda function which will log "An Image has been added" once you add an object to a specific bucket in S3

Theory:

AWS Lambda and S3 Integration:

AWS Lambda allows you to execute code in response to various events, including those triggered by Amazon S3. When an object is added to an S3 bucket, it can trigger a Lambda function to execute, allowing for event-driven processing without managing servers.

Workflow:

1. Create an S3 Bucket:

 First, create an S3 bucket that will store the objects. This bucket will act as the trigger source for the Lambda function.

2024-2025

2. Create the Lambda Function:

- o Set up a new Lambda function using AWS Lambda's console. You can choose a runtime environment like Python, Node.js, or Java.
- Write code that logs a message like "An Image has been added" when triggered.

3. Set Up Permissions:

o Ensure that the Lambda function has the necessary permissions to access S3. You can do this by attaching an IAM role with policies that allow reading from the bucket and writing logs to CloudWatch.

4. Configure S3 Trigger:


 Link the S3 bucket to the Lambda function by setting up a trigger. Specify that the function should be triggered when an object is created in the bucket (e.g., when an image is uploaded).

5. Test the Setup:


o Upload an object (e.g., an image) to the S3 bucket to test the trigger. The Lambda function should execute and log the message "An Image has been added" in AWS CloudWatch Logs.


Steps To create the lambda function:


Step 1: Login to your AWS Academy account. Now open S3 from services and click on create S3 bucket.



Step 2: Now Give a name to the Bucket, select general purpose project and deselect the Block public access and keep other this to default.








Step 3: Open lambda console and click on create function button.


2024-2025




Step 4: Now Give a name to your Lambda function, Select the language to use to write your function. Note that the console code editor supports only Node.js, Python, and Ruby. So will select Python 3.12 , Architecture as x86, and Exceution role to Create a new role with basic Lambda permissions.

Start with a simple Hello World example.	Use a blueprint Build at Lambda application from sample code and configuration presets for common use cases. Container image Select a container image to deploy for your furction.
Basic information	
Function name Enter a name that describes the purpose	of your function.
Rushi	
Use only letters, numbers, hyphens, or u	nderscores with no spaces.
Runtime Info	r function. Note that the console code editor supports only Node.js, Python, and Ruby.
Python 3.12 Architecture Info Choose the instruction set architecture v x86_64 arm64 Permissions Info	▼ 0
Python 3.12 Architecture Info Choose the instruction set architecture y x86_64 arm64 Permissions Info	▼ 0
Python 3.12 Architecture Info choose the instruction set architecture y x86_64 arm64 Permissions Info 8y default, Lambda will create an execur	▼ C
Pythen 3.12 Architecture Info Choice the instruction set architecture; 0 m86,64 amm64 Permissions Info Info Info Info Info Info Info Info	vo want for your function code. To role with permissions to upload logs to Amazon ClaudWatch Logs. You can customize this
Python 3.12 Architecture Info Architecture Info Choose the instruction set architecture y 0 x86,64 arm64 Permissions info By default, Lambda will create an execution Gefault relate when adding triggers. ** Change default execution role Execution role Execution role Execution role	▼ © ou want for your function code. ion role with permissions to upload logs to Amazon CloudWath Logs. You can customize this ons of your function. To create a custom role, go to the IAM cornole Logs.
Python 3.12 Mochitecture infe choses the inducation set architecture y g 165,6-4 arm64 arm64 by default, Lamida will create an executed and the control of the control	▼ © ou want for your function code. ion role with permissions to upload logs to Amazon CloudWath Logs. You can customize this ons of your function. To create a custom role, go to the IAM cornole Logs.
Python 3.12 Architecture Info Choose the Instruction set architecture; 0 M8,64 amm64 Permissions Info Permissions Info Variable Instruction and Experimental Info Variable Info Vari	v C ou want for your function code. ion role with permissions to uplace logs to Amazon Coudflotch Logs. You can customize this ms of your function. To create a custom role, go to the IAM console mbda permissions
Python 3.12 Architecture Line Character Line Section 12 (1997) Se	v C ou want for your function code. ion role with permissions to uplace logs to Amazon Coudflotch Logs. You can customize this ms of your function. To create a custom role, go to the IAM console mbda permissions
Python 3.12 Architecture: Inde Owner de instruction set architecture y N85, 64 arm64 Permissions inde Permissions inde Permissions inde Permissions inde Permissions inde Permissions inde Owner and execution role Execution role Execution role Create a new role with basic La O Use an existing out O Use an existing role Execution role	to want for your function code. Ion role with permissions to upload logs to Amazon CloudWatch Logs. You can customize this one of your function, To create a custom role, go to the IAM censole Combine Commissions.


2024-2025






So See or Edit the basic settings go to configuration then click on edit general setting. Here, you can enter a description and change Memory and Timeout. I've changed the Timeout period to 1 sec since that is sufficient for now.

Step 5: Now Click on the Test tab then select Create a new event, give a name to the event and select Event Sharing to private, and select s3 put template.





Step 6: Now In Code section select the created event from the dropdown .




Step 7: Now In the Lambda function click on add tigger.

Now select the source as S3 then select the bucket name from the dropdown, keep other things to default and also you can add prefix to image.







Step 8: Now Write code that logs a message like "An Image has been added" when triggered. Save the file and click on deploy.




Step 9: Now upload any image to the bucket.



Step 10: Now to click on test in lambda to check whether it is giving log when image is added to S3.



Step 11: Now Lets see the log on Cloud watch. To see it go to monitor section and then click on view cloudwatch logs.



Conclusion: In this experiment, we successfully created an AWS Lambda function that logs a message when an image is uploaded to an S3 bucket. It is important to note that we have to select S3-put template in event other wise code will give an error. The function was successfully triggered by S3 object uploads, validating the functionality of Lambda's event-driven architecture. This experiment demonstrated how Lambda can efficiently respond to S3 events and how to troubleshoot common issues with event structure.