

Jiangxi University of Finance and Economics

Zachman Framework and Relational Data Model Report

Luckin Coffee Inc.

A Technology-Driven New Retail Coffee Enterprise

IK2015: Enterprise Architecture and Database Programming

Seminar 5

Group 4

Zhe-Kai Yang (Krust), Shi-Hang Chen (Sean), Wei-Yu Cai (Nosta),
Huan-Wen Chen (Evan), Yuan-Yong Liao (Foreve)

June 12, 2026

1 Report Basic Information

Table 1: Basic information of the Seminar 5 report.

Item	Information
Selected enterprise / business	Luckin Coffee Inc.; mobile-first coffee retail, pickup, delivery, partnership-store operation, and packaged coffee business.
Course and seminar	IK2015 Enterprise Architecture and Database Programming; Seminar 5.
Group number	Group 4.
Group members	Zhe-Kai Yang (Krust), Shi-Hang Chen (Sean), Wei-Yu Cai (Nosta), Huan-Wen Chen (Evan), Yuan-Yong Liao (Foreve).
Main deliverable	A Row 1 Scope description of the Zachman Framework for Luckin Coffee and a relational data model transformed from the Seminar 4 conceptual model.

This report follows the Seminar 5 instruction sheet. It first fills in the first row of the Zachman Framework for the selected case-study business, and then transforms the conceptual model developed in Seminar 4 into a relational data model. The transformation identifies relations, primary keys, foreign keys, bridge tables, and integrity rules that make the conceptual model implementable in a database.

2 Zachman Framework: Row 1 Scope

The Zachman Framework is a classification scheme for enterprise architecture. It organizes architectural descriptions by two dimensions: stakeholder perspectives and basic interrogatives. In this report, only Row 1 is required. Row 1 is the **Scope** or **Contextual** perspective of the planner. It does not describe detailed system implementation; instead, it lists the high-level business things, processes, locations, organizations, events, and goals that define the enterprise boundary.

For Luckin Coffee, the Row 1 view is useful because the company combines digital ordering, physical store fulfilment, standardized recipes, supply resources, and performance feedback. The following table describes this scope across the six Zachman columns.

Table 2: Zachman Framework Row 1 Scope for Luckin Coffee Inc.

	DATA (What?)	FUNCTION (How?)	NETWORK (Where?)	PEOPLE (Who?)	TIME (When?)	MOTIVATION (Why?)
SCOPE (Contextual) Planner	- Customers and members - Digital channels - Orders and order items - Products and recipes - Stores and staff - Raw materials and suppliers - Delivery partners - Operational KPIs	- Attract and register customers - Publish campaigns and coupons - Accept mobile orders and payments - Prepare pickup and delivery tasks - Manage recipes and products - Replenish store materials - Monitor service and financial results	- Mobile app and mini-program - Cloud ordering platform - Headquarters planning units - Self-operated and partner stores - City retail locations - Supplier origins and warehouses - Delivery service areas	- Digital-native customers - Members and coupon users - Store managers and baristas - Product and recipe teams - Corporate planners - Franchise or partner-store operators - Material suppliers and delivery riders	- App sessions and campaign periods - Order date and order time - Real-time queue and preparation status - Daily store operating hours - Morning and lunch peak demand - Weekly replenishment cycles - Recipe-version effective dates	- Mobile-first new retail strategy - Fast and standardized fulfilment - Affordable premium positioning - Customer lifetime value growth - Product innovation and margin control - Supply reliability - Data-driven operating decisions

This Row 1 scope clarifies what must remain connected when the architecture becomes more detailed. For example, the data column identifies the objects that later become database tables, while the function and time columns explain why order status, campaign validity, recipe versions, and replenishment timing must be represented explicitly.

3 Conceptual Model Used as the Source

The relational data model below is transformed from the Seminar 4 conceptual model for Luckin Coffee. The conceptual model described Luckin as an integrated retail platform with demand-side, fulfilment-side, product-side, and resource-side objects. Its main business objects were Customer, Membership Account, Digital Channel, Promotion Campaign, Digital Order, Order Item, Product, Recipe Standard, Raw Material, Supplier, Store, Store Staff, Fulfilment Task, Delivery Partner, and Performance Result.

The conceptual relationships used for transformation are summarized as follows:

- **Demand relationships:** customers use digital channels, customers own membership accounts, members place digital orders, and promotions are distributed to members and applied to orders.
- **Fulfilment relationships:** digital orders contain order items and create fulfilment tasks; fulfilment tasks are executed by stores and may involve delivery partners.
- **Product and resource relationships:** order items refer to products; products have recipe standards; recipes consume raw materials; suppliers provide materials; stores hold materials as inventory.
- **Analytical feedback:** performance results are derived from operational tables such as orders, fulfilment tasks, stores, campaigns, and delivery partners. Because these are calculated KPIs, they are implemented as reporting queries or views rather than as one base transaction table in the core schema.

4 Relational Data Model Design

The relational model applies standard mapping rules. Each major conceptual object becomes a relation. One-to-many relationships are represented by placing the primary key of the parent relation as a foreign key in the child relation. Many-to-many relationships are resolved using bridge relations with composite primary keys. The model also includes basic domain constraints, such as non-negative monetary values, valid status values, campaign date ranges, and recipe effective dates.

4.1 Relations, Primary Keys, and Foreign Keys

In the following table, underlined attributes are primary-key attributes. Attributes marked with FK reference another relation. Composite keys are shown by underlining more than one attribute in the same relation.

Table 3: Relational data model transformed from the conceptual model.

Relation	Attributes
Customers	<u>CustomerId</u> , Segment, City, AgeBand
MembershipAccounts	<u>MemberId</u> , CustomerId ^{FK} (Unique), PointsBalance, CouponValue, MemberTier, ActivityStatus
DigitalChannels	<u>ChannelId</u> , ChannelType, AccessDevice, AppVersion
PromotionCampaigns	<u>CampaignId</u> , CampaignType, TargetSegment, StartDate, EndDate, SubsidyAmount
MemberCampaigns	<u>MemberId</u> ^{PK, FK} , <u>CampaignId</u> ^{PK, FK} , ReceivedDate, UsedStatus
DigitalOrders	<u>OrderId</u> , MemberId ^{FK} , ChannelId ^{FK} , PaymentMethod, QueueStatus, GrossOrderAmount, CampaignDiscountAmount, ItemDiscountAmount, ActualDeliveryFee, NetPayableAmount, OrderDate, OrderTime
OrderCampaigns	<u>OrderId</u> ^{PK, FK} , <u>MemberId</u> ^{FK} , <u>CampaignId</u> ^{PK, FK} , AppliedAmount
Products	<u>ProductId</u> , ProductName, Category, Season, GrossMargin, CurrentStandardCost
OrderItems	<u>OrderId</u> ^{PK, FK} , <u>ItemNr</u> , ProductId ^{FK} , Quantity, Customization, LineDiscountAmount, UnitItemPrice
DeliveryPartners	<u>PartnerId</u> , PartnerName, PartnerType, ServiceArea, StandardDeliveryFee, ComplaintRate
Stores	<u>StoreId</u> , StoreName, OwnershipType, CityTier, LocationType, Revenue, LaborCost
FulfilmentTasks	<u>TaskId</u> , OrderId ^{FK} , StoreId ^{FK} , PartnerId ^{FK nullable} , TaskType, PrepTime, WaitingTime, CompletionRate, Status
StoreStaff	<u>StaffId</u> , StoreId ^{FK} , StaffName, StaffRole, TrainingStatus, WorkingHours, LaborCost, Productivity
Suppliers	<u>SupplierId</u> , SupplierName, SupplierType, LeadTime
RawMaterials	<u>MaterialId</u> , SupplierId ^{FK} , MaterialName, MaterialType, Origin, BatchStatus, InventoryValue
StoreMaterials	<u>StoreId</u> ^{PK, FK} , <u>MaterialId</u> ^{PK, FK} , StockLevel, StockoutRate
RecipeStandards	<u>RecipeId</u> , ProductId ^{FK} , RecipeVersion, SopStatus, RecipeStandardCost, DefectRate, EffectiveFrom, EffectiveTo
RecipeMaterials	<u>RecipeId</u> ^{PK, FK} , <u>MaterialId</u> ^{PK, FK} , DosageAmount, DosageUnit

4.2 Foreign-Key Structure

Table 4: Main foreign-key dependencies in the relational data model.

Foreign key in relation	References	Meaning
MembershipAccounts CustomerId	Customers CustomerId	One customer owns one membership account; the unique constraint prevents duplicate membership accounts for the same customer.
DigitalOrders MemberId	MembershipAccounts MemberId	A member can place many digital orders.
DigitalOrders ChannelId	DigitalChannels ChannelId	Each order is placed through one recorded digital channel.
MemberCampaigns MemberId	MembershipAccounts MemberId	A member can receive many campaigns.
MemberCampaigns CampaignId	PromotionCampaigns CampaignId	A campaign can be distributed to many members.
OrderCampaigns OrderId, MemberId	DigitalOrders OrderId, MemberId	A campaign usage is attached to a specific order and the member who placed it.
OrderCampaigns MemberId, CampaignId	MemberCampaigns MemberId, CampaignId	An order can only apply a campaign that was issued to that member.
OrderItems OrderId	DigitalOrders OrderId	One order can contain multiple product lines.
OrderItems ProductId	Products ProductId	Each order line sells one product.
FulfilmentTasks OrderId	DigitalOrders OrderId	One order may create preparation, pickup, delivery, or exception tasks.
FulfilmentTasks StoreId	Stores StoreId	Each fulfilment task is handled by one store.
FulfilmentTasks PartnerId	DeliveryPartners PartnerId	Delivery tasks may involve a delivery partner; pickup tasks may leave this value null.
StoreStaff StoreId	Stores StoreId	One store employs many staff members.
RawMaterials SupplierId	Suppliers SupplierId	One supplier can provide many materials.
StoreMaterials StoreId, MaterialId	Stores StoreId; RawMaterials MaterialId	Store inventory is represented as a bridge between stores and materials.
RecipeStandards ProductId	Products ProductId	A product can have multiple recipe versions.
RecipeMaterials RecipeId, MaterialId	RecipeStandards RecipeId; RawMaterials MaterialId	Recipe ingredients are represented as a bridge between recipes and materials.

4.3 Mapping Logic from Conceptual Model to Relations

Table 5: Conceptual-to-relational mapping decisions.

Conceptual element	Relational result	Reasoning
Customer and Membership Account	Customers; MembershipAccounts	These objects are separated because demographic segmentation and membership benefits have different attributes. The CustomerId foreign key in MembershipAccounts is unique, representing a one-to-one relationship.
Digital Channel and Digital Order	DigitalChannels; DigitalOrders	Channel information is stored once and referenced by orders. This avoids repeating app, mini-program, device, and version data in every order record.
Promotion Campaign issued to members	MemberCampaigns	The member-campaign relationship is many-to-many, so a bridge relation records which member received which campaign and whether it was used.
Promotion Campaign applied to orders	OrderCampaigns	A second bridge relation records actual campaign use on orders and the discount amount applied. Including MemberId keeps campaign use consistent with member campaign distribution.
Order and Order Item	DigitalOrders; OrderItems	Order-level fields such as payment method, queue status, and net amount are separated from product-line fields such as quantity, customization, discount, and unit price.
Product and Recipe Standard	Products; RecipeStandards	Product catalogue information is separated from recipe versions, SOP status, standard cost, and effective dates. This supports controlled product changes over time.
Recipe Standard and Raw Material	RecipeMaterials	Recipes and materials are many-to-many. The bridge relation records dosage amount and dosage unit for each ingredient.
Store and Raw Material	StoreMaterials	Stores hold many materials, and the same material can be stocked by many stores. The bridge relation records local stock level and stockout rate.
Order fulfilment and delivery	FulfilmentTasks; DeliveryPartners	Fulfilment work is separated from the purchase event, making preparation time, waiting time, completion rate, and delivery complaints measurable.
Performance Result	Reporting views or queries	KPIs such as average order value, campaign redemption rate, store utilization, and stock-out rate are derived from operational relations rather than stored as a separate base transaction table.

The model also uses integrity constraints beyond simple key definitions. For example, order amounts must be non-negative, net payable amount equals gross amount minus campaign and item discounts plus actual delivery fee, campaign start date cannot be later than campaign end date, stock level cannot be negative, and recipe effective dates must be ordered correctly. The SQL implementation also uses triggers to ensure that a campaign applied to an order is valid for that order date and does not exceed the campaign subsidy amount.

5 Relational Data Model Diagrams

The relational data model is shown in two diagrams to keep the schema readable on A4 paper. The first diagram focuses on customer demand, digital orders, campaign use, and fulfilment. The second diagram focuses on products, recipes, materials, store inventory, and suppliers. Together, the two diagrams represent the same complete relational model listed in the relation table above.

Luckin Coffee Relational Data Model: Customer, Order and Fulfilment





Figure 1: Relational data model diagram for customer, order, campaign, and fulfilment relations. Underlined attributes are primary-key attributes; FK marks foreign-key references.

Luckin Coffee Relational Data Model: Product, Recipe and Supply



Underlined attributes are primary keys. FK marks foreign-key references.

Figure 2: Relational data model diagram for product, recipe, material, inventory, and supplier relations. Underlined attributes are primary-key attributes; FK marks foreign-key references.

The diagrams are organized around the same business flow as the conceptual model: customer and membership data feed digital orders; orders connect to items, fulfilment tasks, stores, campaigns, and delivery partners; products connect to recipes; recipes and stores connect to raw materials and suppliers.

6 Implementation Notes for the Database Schema

The relational model is implemented in the accompanying SQL schema file. The SQL version uses explicit primary-key, foreign-key, unique, check, and trigger rules so that the database structure preserves the business logic of the conceptual model.

Table 6: Examples of integrity rules implemented by the schema.

Rule type	Example in the Luckin Coffee schema
Entity integrity	Every base relation has a primary key, such as CustomerId, OrderId, ProductId, StoreId, or MaterialId.
Referential integrity	DigitalOrders.MemberId must match an existing MembershipAccounts.MemberId; OrderItems.ProductId must match an existing Products.ProductId.
One-to-one control	MembershipAccounts.CustomerId is unique, so one customer cannot have multiple membership account rows in this schema.
Bridge-table control	MemberCampaigns, OrderCampaigns, StoreMaterials, and RecipeMaterials use composite primary keys to represent many-to-many relationships.
Domain validity	Status and type fields are restricted to allowed values, such as queue status, activity status, task type, ownership type, and batch status.
Business arithmetic	NetPayableAmount is constrained to equal GrossOrderAmount minus discounts plus ActualDeliveryFee.
Time validity	PromotionCampaigns require StartDate to be earlier than or equal to EndDate; RecipeStandards require a valid effective-date range.
Cross-table rule	OrderCampaigns triggers check that a campaign is valid for the order date and that the applied amount does not exceed allowed campaign or order values.

7 Business Scenarios Supported by the Relational Model

7.1 Scenario 1: Mobile Order and Pickup Fulfilment

When a customer logs in, receives a coupon, submits a coffee order, and picks it up at a store, the database can trace the full chain:

- **Relations joined:** Customers → MembershipAccounts → MemberCampaigns → PromotionCampaigns → DigitalOrders → OrderCampaigns → OrderItems → Products → FulfilmentTasks → Stores.

- **Business value:** The chain shows who bought the drink, which digital channel was used, which coupon was distributed and applied, which product lines were ordered, how long fulfilment took, and which store completed the task.

7.2 Scenario 2: Product Launch and Margin Auditing

When Luckin launches a new beverage, analysts can evaluate recipe cost, selling price, discounts, and margin performance:

- **Relations joined:** Products → RecipeStandards → RecipeMaterials → RawMaterials → Suppliers; Products → OrderItems → DigitalOrders for actual sales and discounts.
- **Business value:** The chain compares recipe standard cost and ingredient dosage against item revenue and discount behavior, supporting product profitability analysis.

7.3 Scenario 3: Store Inventory Replenishment

When a store's stock of coffee beans, milk, syrup, or packaging falls below a safety level, the schema supports replenishment decisions:

- **Relations joined:** Stores → StoreMaterials → RawMaterials → Suppliers.
- **Business value:** The system can identify low stock levels by store and material, group replenishment needs by supplier, and connect stockout patterns to store performance.

7.4 Scenario 4: Delivery Reliability Monitoring

When delivery complaints or waiting time increases, managers can inspect the responsible operational links:

- **Relations joined:** DigitalOrders → FulfilmentTasks → Stores and DeliveryPartners.
- **Business value:** The schema separates store preparation performance from partner delivery performance, helping managers decide whether the bottleneck is queue preparation, store capacity, or external logistics.

8 Conclusion

This report completed the two main Seminar 5 tasks for the Luckin Coffee case study. First, the Zachman Framework Row 1 Scope view described the business at a planner level by listing the main data, functions, locations, people, timing concerns, and motivations. This clarified the enterprise boundary before technical design.

Second, the report transformed the Seminar 4 conceptual model into a relational data model. The model contains relations for customers, membership, channels, campaigns, orders, order items, products, recipes, stores, staff, materials, suppliers, fulfilment tasks, and delivery partners. Primary keys, foreign keys, unique constraints, bridge relations, check constraints, and triggers preserve the business relationships identified in the conceptual model. As a result, the schema supports mobile ordering, coupon use, product and recipe management, store fulfilment, inventory replenishment, delivery monitoring, and management reporting.

References

- [1] Zachman, J. A. (1987). *A Framework for Information Systems Architecture*. IBM Systems Journal, 26(3), 276–292.
- [2] Ylimäki, T., & Halttunen, V. (2005). *Method engineering in practice: A case of applying the Zachman framework in the context of small enterprise architecture oriented projects*. Information Knowledge Systems Management, 5(3), 189–209.
- [3] Sundgren, B. (2013). *Methodological and technical perspectives on e-governance*.
- [4] Elmasri, R., & Navathe, S. B. (2015). *Fundamentals of Database Systems* (7th ed.). Pearson.