

```
In [1]: import pandas as pd
```

```
In [7]: df=pd.read_csv('C:/Users/vinay/Downloads/customer_shopping_behavior.csv')
```

```
In [8]: df.head()
```

Out[8]:

	Customer ID	Age	Gender	Item Purchased	Category	Purchase Amount (USD)	Location	Size	Color
0	1	55	Male	Blouse	Clothing	53	Kentucky	L	Gray
1	2	19	Male	Sweater	Clothing	64	Maine	L	Maroon
2	3	50	Male	Jeans	Clothing	73	Massachusetts	S	Maroon
3	4	21	Male	Sandals	Footwear	90	Rhode Island	M	Maroon
4	5	45	Male	Blouse	Clothing	49	Oregon	M	Turquoise

```
In [9]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 3900 entries, 0 to 3899
Data columns (total 18 columns):
 #   Column                                Non-Null Count  Dtype  
---  -
 0   Customer ID                          3900 non-null  int64  
 1   Age                                  3900 non-null  int64  
 2   Gender                               3900 non-null  object  
 3   Item Purchased                       3900 non-null  object  
 4   Category                             3900 non-null  object  
 5   Purchase Amount (USD)                3900 non-null  int64  
 6   Location                             3900 non-null  object  
 7   Size                                 3900 non-null  object  
 8   Color                                3900 non-null  object  
 9   Season                               3900 non-null  object  
10  Review Rating                        3863 non-null  float64 
11  Subscription Status                  3900 non-null  object  
12  Shipping Type                        3900 non-null  object  
13  Discount Applied                     3900 non-null  object  
14  Promo Code Used                      3900 non-null  object  
15  Previous Purchases                   3900 non-null  int64  
16  Payment Method                       3900 non-null  object  
17  Frequency of Purchases               3900 non-null  object  
dtypes: float64(1), int64(4), object(13)
memory usage: 548.6+ KB
```

```
In [10]: df.describe(include="all")
```

Out[10]:

	Customer ID	Age	Gender	Item Purchased	Category	Purchase Amount (USD)	Location	Size
count	3900.000000	3900.000000	3900	3900	3900	3900.000000	3900	3900
unique	NaN	NaN	2	25	4	NaN	50	NaN
top	NaN	NaN	Male	Blouse	Clothing	NaN	Montana	NaN
freq	NaN	NaN	2652	171	1737	NaN	96	17
mean	1950.500000	44.068462	NaN	NaN	NaN	59.764359	NaN	NaN
std	1125.977353	15.207589	NaN	NaN	NaN	23.685392	NaN	NaN
min	1.000000	18.000000	NaN	NaN	NaN	20.000000	NaN	NaN
25%	975.750000	31.000000	NaN	NaN	NaN	39.000000	NaN	NaN
50%	1950.500000	44.000000	NaN	NaN	NaN	60.000000	NaN	NaN
75%	2925.250000	57.000000	NaN	NaN	NaN	81.000000	NaN	NaN
max	3900.000000	70.000000	NaN	NaN	NaN	100.000000	NaN	NaN

```
In [11]: df.isnull().sum()
```

```
Out[11]: Customer ID      0
Age      0
Gender    0
Item Purchased  0
Category  0
Purchase Amount (USD)  0
Location  0
Size      0
Color     0
Season    0
Review Rating    37
Subscription Status  0
Shipping Type    0
Discount Applied  0
Promo Code Used  0
Previous Purchases  0
Payment Method   0
Frequency of Purchases  0
dtype: int64
```

```
In [12]: #choosing median since median is robust to outliers
df['Review Rating'] = df.groupby('Category')['Review Rating'].transform(lambda x: x.median())
```

```
In [13]: ▶ df.isnull().sum()
```

```
Out[13]: Customer ID          0
Age          0
Gender       0
Item Purchased  0
Category     0
Purchase Amount (USD)  0
Location     0
Size         0
Color        0
Season       0
Review Rating  0
Subscription Status  0
Shipping Type  0
Discount Applied  0
Promo Code Used  0
Previous Purchases  0
Payment Method  0
Frequency of Purchases  0
dtype: int64
```

```
In [14]: ▶ df.columns = df.columns.str.lower()
df.columns = df.columns.str.replace(' ', '_')
df = df.rename(columns={'purchase_amount_(usd)': 'purchase_amount'})
```

```
In [15]: ▶ df.columns
```

```
Out[15]: Index(['customer_id', 'age', 'gender', 'item_purchased', 'category',
               'purchase_amount', 'location', 'size', 'color', 'season',
               'review_rating', 'subscription_status', 'shipping_type',
               'discount_applied', 'promo_code_used', 'previous_purchases',
               'payment_method', 'frequency_of_purchases'],
              dtype='object')
```

```
In [16]: ▶ #create a column age_group
labels = ['Young Adult', 'Adult', 'Middle-aged', 'Senior']
df['age_group'] = pd.qcut(df['age'], q=4, labels=labels)
```

```
In [17]: df[['age', 'age_group']].head(10)
```

```
Out[17]:
```

	age	age_group
0	55	Middle-aged
1	19	Young Adult
2	50	Middle-aged
3	21	Young Adult
4	45	Middle-aged
5	46	Middle-aged
6	63	Senior
7	27	Young Adult
8	26	Young Adult
9	57	Middle-aged

```
In [18]: # create column purchase_frequency_days

frequency_mapping = {
    'Fortnightly': 14,
    'Weekly': 7,
    'Monthly': 30,
    'Quarterly': 90,
    'Bi-Weekly': 14,
    'Annually': 365,
    'Every 3 Months': 90
}

df['purchase_frequency_days'] = df['frequency_of_purchases'].map(frequency
```

```
In [19]: df[['purchase_frequency_days', 'frequency_of_purchases']].head(10)
```

```
Out[19]:
```

	purchase_frequency_days	frequency_of_purchases
0	14.0	Fortnightly
1	14.0	Fortnightly
2	7.0	Weekly
3	7.0	Weekly
4	365.0	Annually
5	7.0	Weekly
6	NaN	Quarterly
7	7.0	Weekly
8	365.0	Annually
9	NaN	Quarterly

```
In [20]: ▶ df[['discount_applied', 'promo_code_used']].head(10)
```

```
Out[20]:
```

	discount_applied	promo_code_used
0	Yes	Yes
1	Yes	Yes
2	Yes	Yes
3	Yes	Yes
4	Yes	Yes
5	Yes	Yes
6	Yes	Yes
7	Yes	Yes
8	Yes	Yes
9	Yes	Yes

```
In [21]: ▶ (df['discount_applied'] == df['promo_code_used']).all()
```

```
Out[21]: True
```

```
In [22]: ▶ df = df.drop('promo_code_used', axis=1)
```

```
In [23]: ▶ df.columns
```

```
Out[23]: Index(['customer_id', 'age', 'gender', 'item_purchased', 'category',  
               'purchase_amount', 'location', 'size', 'color', 'season',  
               'review_rating', 'subscription_status', 'shipping_type',  
               'discount_applied', 'previous_purchases', 'payment_method',  
               'frequency_of_purchases', 'age_group', 'purchase_frequency_days'],  
              dtype='object')
```

```
In [25]: ▶ pip install psycpg2-binary sqlalchemy
```

```
Requirement already satisfied: psycpg2-binary in c:\users\vinay\anaconda3\lib\site-packages (2.9.12)  
Requirement already satisfied: sqlalchemy in c:\users\vinay\anaconda3\lib\site-packages (1.4.32)  
Requirement already satisfied: greenlet!=0.4.17 in c:\users\vinay\anaconda3\lib\site-packages (from sqlalchemy) (1.1.1)  
Note: you may need to restart the kernel to use updated packages.
```

In [29]:  `from sqlalchemy import create_engine`

```
#Step 1
#connect to PostgreSQL
#replace placeholders with actual details
username = "postgres"
password = "kruthi123"
host = "localhost"
port = "5432"
database = "customer_behaviour"

engine= create_engine(f"postgresql+psycopg2://{username}:{password}@{host}")

#Step 2:Load Dataframe into PostgreSQL
table_name = "customer"
df.to_sql(table_name, engine, if_exists="replace", index=False)

print(f"Data successfully loaded into table '{table_name}' in database '{d
```

Data successfully loaded into table 'customer' in database 'customer_behaviour',

In []: 