Assignment 7: Sample Data Insertion

Database: MySQL | Project: Airline Reservation System

1. Objective

Insert realistic records into all tables while respecting keys, relationships and constraints.

2. Insert sample data

Execute the inserts in the order shown so parent rows exist before dependent rows.

```
INSERT INTO Passengers VALUES
(101,'Arjun Sharma','arjun@example.com','9876543210','P10001'),
(102,'Priya Nair','priya@example.com','9876543211','P10002'),
(103,'Rahul Kumar','rahul@example.com','9876543212','P10003'),
(104,'Sneha Rao','sneha@example.com','9876543213','P10004'),
(105,'Vikram Singh','vikram@example.com','9876543214','P10005'),
(106,'Ananya Iyer','ananya@example.com','9876543215','P10006');

INSERT INTO Aircraft VALUES
(201,'Airbus A320',180,'IndiGo'),
(202,'Boeing 737-800',189,'Air India Express'),
(203,'Airbus A321',220,'Air India');

INSERT INTO Flights VALUES
(301,'6E101','Bengaluru','Delhi','2026-11-01 06:30:00','2026-11-01 09:15:00',201),
(302,'AI202','Delhi','Mumbai','2026-11-01 10:00:00','2026-11-01 12:10:00',203),
(303,'IX303','Mumbai','Bengaluru','2026-11-01 14:00:00','2026-11-01 15:45:00',202),
(304,'6E404','Bengaluru','Kolkata','2026-11-02 08:00:00','2026-11-02 10:45:00',201);
```

```
INSERT INTO Bookings VALUES
(401,'2026-10-20','12A','Economy',101,301),
(402,'2026-10-20','14B','Economy',102,301),
(403,'2026-10-21','03C','Business',103,302),
(404,'2026-10-21','18A','Economy',104,303),
(405,'2026-10-22','02A','First',105,304),
(406,'2026-10-22','15C','Economy',101,304),
(407,'2026-10-22','16D','Economy',106,304),
(408,'2026-10-22','20B','Economy',102,303);

INSERT INTO Payments VALUES
(501,'2026-10-20',5500,'UPI','Paid',401),
(502,'2026-10-20',5200,'Card','Paid',402),
(503,'2026-10-21',12500,'Net Banking','Paid',403),
(504,'2026-10-21',4800,'UPI','Paid',404),
(505,'2026-10-22',18000,'Card','Paid',405),
(506,'2026-10-22',5000,'UPI','Pending',406),
(507,'2026-10-22',5100,'Card','Paid',407),
(508,'2026-10-22',4900,'UPI','Paid',408);
```

3. Verify record counts

```
SELECT COUNT(*) AS total_passengers FROM Passengers;
SELECT COUNT(*) AS total_aircraft FROM Aircraft;
SELECT COUNT(*) AS total_flights FROM Flights;
SELECT COUNT(*) AS total_bookings FROM Bookings;
SELECT COUNT(*) AS total_payments FROM Payments;
```

Table	Expected records
Passengers	6
Aircraft	3
Flights	4
Bookings	8
Payments	8

4. Sample booking report

```
SELECT p.full_name, f.flight_number,
       b.seat_number, b.travel_class,
       b.booking_date
FROM Bookings b
JOIN Passengers p ON b.passenger_id=p.passenger_id
JOIN Flights f ON b.flight_id=f.flight_id
ORDER BY p.passenger_id, f.flight_id;
```

This query combines Passengers, Flights and Bookings to show reservation details. It should return 8 rows.

5. Conclusion

The sample dataset provides six passengers, three aircraft, four flights, eight bookings and eight payment records for the remaining SQL assignments.