A Smart Initiation Kit for Engineers in Agriculture

Prof. Ramya Sri
Department of Computer Science & Engineering,
The Oxford College of Engineering

Keerthana C N
Department of Computer Science & Engineering,
The Oxford College of Engineering

Harshitha V M
Department of Computer Science & Engineering,
The Oxford College of Engineering

Nandhitha B S
Department of Computer Science & Engineering,
The Oxford College of Engineering

M Kruthika
Department of Computer Science & Engineering,
The Oxford College of Engineering

Abstract - Through a practical, technologically advanced learning environment, the Smart Initiation Kit for Engineers in Agriculture aims to assist novices in comprehending contemporary farming methods. To assist students see how many factors affect crop growth, the kit incorporates automated irrigation control, real-time environmental monitoring, and important agricultural metrics. The system offers a simplified example of how smart agriculture solutions function in actual farms by fusing automated water management with microcontroller-based data collecting. This method encourages effective resource use, greater crop health, and enhanced decision-making in agricultural applications in addition to supporting engineering students' experiential learning. The kit allows students to investigate precision agriculture in an approachable and useful way by acting as an educational link between conventional farming knowledge and new digital agricultural technologies.

Keywords **:** Smart Agriculture, Automated Irrigation, Precision Farming, IoT-based Agriculture, Agricultural Monitoring, Microcontroller Systems, Sustainable Farming, Educational Agriculture Kit, Environmental Monitoring, Decision Support System.

I. INTRODUCTION

Even though agriculture is still one of the most important economic sectors in India, it still faces difficulties with soil degradation, water scarcity, climate variability, and rising productivity demands. Modern farming methods are moving towards data-driven and automated systems as a result of the quick development of technology. It is challenging for many engineering students and novices to comprehend how digital tools can be incorporated into agricultural processes, though, because they have not had much hands-on experience with these technology. An introduction platform that makes these ideas simple and gives students practical experience is becoming more and more necessary. To close this gap, the Smart Initiation Kit for Engineers in Agriculture was created, offering an approachable learning framework that illustrates the core ideas of smart farming.

The kit focusses on automated irrigation management, real-time agricultural parameter monitoring, and fundamental data interpretation. Learners can comprehend how technology improves productivity, minimises manual involvement, and promotes sustainable farming practices by seeing how environmental factors affect crop performance. The kit serves as a link between theoretical understanding and real-world application.

Additionally, this system teaches students how to apply digital agriculture tools, intelligent decision-making models, and automation based on microcontrollers. The kit promotes experimentation in areas including crop care, water management, and environmental monitoring through interactive elements and streamlined workflows.

II. METHODOLOGY

The approach used in this study focusses on creating a straightforward yet powerful framework that illustrates how smart farming technologies function in actual agricultural environments. Real-time data collection is the first step in the system's sequential process, which is followed by data processing, decision-making, and automated actuation. Every phase of the process is intended to make it simple and useful for engineering students to comprehend the precision agriculture workflow.

A. Method of Data Acquisition

Through a series of agricultural monitoring devices linked to an ESP32 microcontroller, the system gathers key field data. While environmental factors like air temperature and humidity are tracked to determine their impact on crop water requirements, soil-related indicators like moisture, fertility levels, and soil temperature are regularly recorded. At predetermined intervals, the microcontroller samples these values and temporarily stores them for examination.

With this data collection technique, students may see in real time how changes in the environment affect crop conditions.

B. Framework for Data Processing and Decision Making

An embedded rule-based framework built on the ESP32 is used to process the gathered sensor data. When the

crop needs irrigation, threshold-based reasoning is applied. The current soil moisture reading is compared by the system to predetermined moisture thresholds that indicate "dry," "optimal," and "wet" conditions. To maintain stability and stop the pump from turning on and off repeatedly, a hysteresis model is used. While temperature and humidity readings are utilised to comprehend evapotranspiration trends, soil fertility values from the EC readings aid in fundamental nutrition assessments.

This rule-based decision model is purposefully maintained straightforward to allow for future incorporation of machine learning-based decision systems while also keeping the rationale easy for students to understand.

C. Mechanism for Automation and Control

The ESP32 triggers a relay module that manages a 12V water pump or solenoid valve when the decision framework concludes that irrigation is necessary. As a safety precaution, a float sensor makes sure that irrigation only happens when there is enough water in the tank.

This automation technique creates a closed-loop system in which the pump is stopped once the ideal moisture level is reached, irrigation is only started when necessary, and soil moisture is continuously monitored. This cycle enables students to see how automated irrigation functions in actual farming and comprehend the significance of water and energy conservation in sustainable agriculture.

D. Model of Algorithms

The study used a straightforward threshold-based irrigation algorithm that consists of:

- Sensor Read Stage: continually gather environmental and soil data.
- Assess whether soil moisture is below the lower threshold during the Condition Check Stage.
- Decision Stage: If irrigation regulations are met and water is available, turn on the pump.
- Stabilisation and Hysteresis: only halt irrigation when an upper moisture threshold is reached.
- Maximum pump runtime restrictions and float switch validation are examples of safety regulations.

This algorithm offers a simple learning paradigm for novices and mimics the logical flow found in many real-world smart agriculture systems.

E. Framework for Dataset and Expansion

The kit is appropriate for practical experimentation because the system largely uses self-generated, real-time field data rather than pre-existing datasets. Nonetheless, the architecture is intended to facilitate the incorporation additional datasets in the future, such as machine learning models for irrigation prediction, crop water need records, and soil categorisation data.

By adding LSTM, Random Forest, or regression models later on, the system's modular design enables students to transform it into a sophisticated precision farming tool.

III. IMPLEMENTATION

In order to automate irrigation and show real-time agricultural parameters, the suggested Smart Initiation Kit was constructed using both hardware and software components.

The ESP32 microcontroller, which was chosen for its Wi-Fi functionality, low power consumption, and appropriateness for educational IoT applications, served as the system's central component. A capacitive soil moisture sensor, a DS18B20 soil temperature sensor, a SHT31/DHT22 atmospheric sensor, and an EC probe for nutrient estimate were among the field sensors with which the ESP32 was interfaced.

To provide precise data sampling, the sensors were linked by analogue, 1-Wire, and I2C communication lines with a shared ground reference. An automatic water supply from a storage tank was made possible by connecting a 12V DC water pump to a relay driver module. As a safety measure, a float switch was added to stop the pump from operating when the tank level was too low.

Periodically, embedded firmware developed in Arduino C/C++ was used to read and process sensor data. To stop pump toggling in near-boundary moisture circumstances, a threshold-based method with hysteresis control was used. The ESP32 triggered the pump via the relay if the soil moisture level fell below the lower threshold. When the moisture content hit the upper limit, irrigation automatically stopped.

Additionally, the I²C module was used to continuously show temperature, humidity, and moisture readings on a 16x2 LCD display, enabling users to see sensor behaviour and system operation in real time. Repeated sensor sampling was employed to validate the LCD readings in order to reduce noise-related variations.

The execution prioritised instructional clarity, making sure that each kit component could be independently tested and altered by students. Because of the design's modularity, students were able to add more features to the system, including fertiliser control units, cloud data logging, mobile app dashboards, and machine learning algorithms.

By connecting theory and practical technology, this modular and useful implementation shows how inexperienced engineering students can build a functional smart agriculture prototype.




Fig 1 : System Architecture

IV. RESULTS AND DISCUSSION

The Smart Initiation Kit's ability to monitor soil characteristics and automate irrigation was evaluated in controlled agricultural environments. Throughout the experiment, the system consistently displayed readings and effectively gathered real-time data from all linked components. Sample readings from the test are displayed in Table 1. The sensor output demonstrated the dependability of the data collecting technique by clearly reflecting variations in temperature, humidity, and moisture.
The Smart Initiation Kit's ability to monitor soil characteristics and automate irrigation was evaluated in controlled agricultural environments. Throughout the experiment, the system consistently displayed readings and effectively gathered real-time data from all linked components. Sample readings from the test are displayed in Fig 2. The sensor output demonstrated the dependability of the data collecting technique by clearly reflecting variations in temperature, humidity, and moisture.

When the tank level was low, the float sensor consistently stopped the water pump during testing. In order to prevent pump dry-run situations, this safety feature was crucial. The microcontroller's effective processing was demonstrated by the system response time, which was continuously less than one second from the time low moisture was detected to pump activation. Students were better able to comprehend the connection between weather and irrigation requirements thanks to environmental factors like temperature and humidity.
The results' discussion emphasises the kit's usefulness as a teaching tool. Students studying engineering might easily see how sensor data affects agricultural decision-making. The autonomous watering cycle gave customers a hands-on example of precision farming and helped them see the advantages of water conservation. Because the system is modular, it may be expanded with cloud-based dashboards or machine-learning algorithms. Overall, the results show that the Smart Initiation Kit provides a straightforward but efficient platform for experimentation, training, and the uptake of smart agriculture technology.

The system was evaluated for stability, response time, and user interpretation. During testing, the **sensor-to-actuator response time averaged below 1 second**, indicating efficient real-time communication between the microcontroller and connected components. This rapid response ensured that irrigation decisions were executed without delay, especially when moisture values crossed the control threshold. The hysteresis-based algorithm effectively prevented frequent relay switching, which is an essential requirement in practical irrigation systems to avoid pump damage and electrical surges.

Furthermore, the modular design made it extensible beyond a simple classroom kit by enabling optional interfaces like cloud dashboards, soil fertility correlation, and crop-specific moisture statistics. These findings confirm that the Smart Initiation Kit connects engineering education with real-world agricultural innovation by effectively automating irrigation and acting as a flexible learning and research platform.




Fig 2 : Connections in Circuit Diagram



Fig 3 : Readings drawn at Room Temperature



Fig 4: Automated Technology using Relay Module



Fig 5: Readings drawn when connected to Relay module




Fig 6: Live Data fetched from Sensors using ML



Fig 7: Prediction of Crops




Fig 8: Soli Moisture and Enviromental Data




Fig 9: Soli Moisture Trends over Time

Soil Moisture Variation Graph

The soil moisture graph represents how moisture levels in the soil fluctuate over time. The curve shows a gradual decline in moisture values, which is consistent with natural soil drying due to evaporation, root absorption, and environmental temperature changes. As time progresses, the decreasing trend indicates when the soil becomes too dry and irrigation becomes necessary. This helps identify the irrigation cycle required for optimal crop growth.

In agricultural monitoring, such a pattern is extremely important because soil moisture is one of the most critical parameters for plant development. A steep drop indicates faster water loss, often due to high temperature or windy conditions. A more stable line suggests moisture retention, typically seen after irrigation or during cooler weather. By analyzing this graph, the system can determine the right irrigation schedule and prevent both overwatering and underwatering. Overall, the soil moisture graph helps farmers or automated systems understand water usage patterns in the soil and optimize irrigation timing. This contributes to water conservation and improves crop health.

Temperature Variation Graph

The temperature variation graph demonstrates how temperature changes across different time intervals. The curve generally shows a rising trend, which typically corresponds to temperature increase from early hours to mid-day. This pattern is consistent with natural climatic behavior, where temperature rises due to solar radiation and begins to stabilize or decline afterward. Such monitoring is crucial in agriculture, as temperature directly affects plant metabolism and growth rate. Elevated temperatures may indicate potential stress conditions for crops, especially if the values exceed ideal thresholds.

A stable or moderate curve represents favorable conditions for plant growth. By observing the temperature line, the system can detect patterns such as heatwaves or sudden cooling, which may affect irrigation requirements and disease susceptibility

Humidity Variation Graph

The humidity graph displays the changes in atmospheric moisture over time. Humidity tends to fluctuate based on temperature, irrigation events, and plant transpiration. In this graph, humidity generally follows a rising pattern, which may correspond to increasing temperature or environmental factors that promote moisture in the air. Higher humidity indicates favorable conditions for certain crops but may also increase the risk of fungal diseases.

Monitoring humidity is vital because it affects transpiration rates, pest activity, and crop health. A low humidity value means the air is dry, leading to faster moisture loss from soil and plants. Conversely, high humidity may slow down evaporation and create a microclimate that needs close supervision. By analyzing this curve, the user can understand whether the field environment is moving toward dry or humid conditions. In intelligent agriculture systems, humidity data contributes to predicting water needs, disease risks, and crop suitability. The trend in this graph supports better decision-making for greenhouse or open-field farming environments.

Water Level Variation Graph

The water level graph illustrates how the water availability in the tank or field changes over time. In many irrigation systems, water level may gradually increase due to pumping cycles or remain steady depending on the control mechanism. The graph typically shows moderate fluctuations, representing the balance between water usage and replenishment. This is especially important for automated irrigation systems where water level directly controls the relay or pump.

V. CONCLUSION

The Smart Initiation Kit for Engineers in Agriculture effectively illustrates how technology may be incorporated into agriculture to facilitate automation and intelligent decision-making. The system offers a useful and instructive platform for comprehending the principles of smart agriculture by fusing real-time monitoring of soil and environmental data with a microcontroller-based control mechanism. By ensuring that water is only delivered when needed, the automated irrigation feature helps preserve resources and enhances crop health without requiring continuous human supervision.

The study's findings emphasise the value of sensor-based learning and show how engineering students can practically investigate the fundamentals of precision farming. The kit's modular design enables further expansion through cutting-edge technologies like machine learning, cloud analytics, and mobile-based data visualisation. All things considered, the system serves as a gateway for learners to develop creative solutions in the agri-tech domain, encouraging wider adoption of sustainable and intelligent agricultural practices in the future.

REFERENCES

1. **Upendra Roy B.P, Khalid Nazim Abdul Sattar & Ahmed A. Elngar**, *"A Smart Irrigation System Using the IoT and Advanced Machine Learning Model"*, Journal of Smart Internet of Things, 2024/2025.
2. **Marco Del-Coco, Pierluigi Carcagnì**, *"Machine Learning for Smart Irrigation in Agriculture: How Far along Are We?"*, *Information* (MDPI), 2024.
3. **A Morchid et al.**, *"IoT-enabled smart agriculture for improving water use efficiency"*, *Sustainable Computing: Informatics and Systems*, 2025.
4. **G. Routis**, *"Low Power IoT Electronics in Precision Irrigation"*, *Journal of Embedded Systems and IoT* (or similar), 2023.
5. **Vineet K. Sharma, Wilson Jeberson, Rajendra K. Isaac**, *"Internet-of-Things (IoT)-Based Smart Agriculture and Precision Irrigation for Agriculture — an Intelligent Water Management"*, YUJOR (or Journal of Agritech), 2025.
6. **I. Lephondo**, *"The Outcomes of Smart Irrigation System using Machine Learning"*, *Procedia / 4IR-enabled Systems*, 2024.
7. **Mirco Tincani, Khaled Kerouch, Umberto Garlando, Alessandro Sanginario, Giacomo Indiveri, Chiara De Luca**, *"A neuromorphic continuous soil monitoring system for precision irrigation"*, arXiv, 2025.
8. **Yunus Emre Kunt**, *"Development of a Smart Autonomous Irrigation System Using IoT and AI"*, arXiv, 2025.
9. **Nasser Ghadiri, Bahman Javadi, Oliver Obst, Sebastian Pfautsch**, *"Data Optimisation of Machine Learning Models for Smart Irrigation in Urban Parks"*, arXiv, 2024.
10. **Yeonju Lee, Rui Qi Chen, Joseph Oboamah, et al.**, *"SPADE: A Large Language Model Framework for Soil Moisture Pattern Recognition and Anomaly Detection in Precision Agriculture"*, arXiv, 2025.