

# SMART SIGNAGE

Clear Vision Into Your Business

MAKE AN IMPACTFUL SHOPPING

**PROFESSIONAL  
DISPLAY SOLUTION**

**S** **SERIES**

# PROFESSIONAL DISPLAY SOLUTION

|                                                                                    |                                                                                                                        |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|
|    | <b>32" FHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, Slim Depth with SOLUM CMS solution |
|    | <b>43" UHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, Slim Depth with SOLUM CMS solution |
|    | <b>50" UHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, Slim Depth with SOLUM CMS solution |
|    | <b>55" UHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, Slim Depth with SOLUM CMS solution |
|   | <b>65" UHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, Slim Depth with SOLUM CMS solution |
|  | <b>75" UHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, with large size solution           |
|  | <b>86" UHD display</b><br>Digital Signage, Network & HDMI Support,<br>Sound 10 Wx2, with large size solution           |



DIGITAL SIGNAGE 32” FHD (S32A) SPECIFICATIONS



DISPLAY

|                     |                                   |
|---------------------|-----------------------------------|
| Size                | 32"                               |
| Resolution          | 1,920 x 1,080 (FHD)               |
| W*H Ratio           | 1.77 (16:9)                       |
| Luminance (Typ.)    | 500 cd/m²                         |
| Orientation         | Landscape/Portrait                |
| Contrast Ratio      | 4,000:1                           |
| Viewing Angle (H/V) | 178° / 178°                       |
| Response Time       | 8 ms                              |
| Active Area (HxV)   | 698.4 x 392.9 mm / 27.5 x 15.5 in |
| Color Gamut         | 85%                               |
| Backlight type      | E-LED                             |
| Life Time (LED)     | 50,000 Hrs                        |

MECHANICAL

|                          |                       |
|--------------------------|-----------------------|
| SET Dimensions           | 724.6 x 419.8 x 40 mm |
|                          | 28.5 x 16.5 x 1.6 in  |
| VESA Mount               | 150 x 200 mm          |
| SET Weight               | 5.4 kg / 11.9 lbs.    |
| Packing Dimensions       | 795 x 520 x 115 mm    |
|                          | 31.3 x 20.5 x 4.5 in  |
| Packing Weight           | 7.3 kg / 16.1 lbs.    |
| Bezel Width (U/L/R/B mm) | 11.6 (even)           |

SYSTEM

|               |                             |
|---------------|-----------------------------|
| OS            | Android 9.0                 |
| CPU           | Quad-core ARM Cortex-A35    |
| GPU           | ARM Mali-G31 MP2            |
| RAM           | 2 GB DDR4                   |
| Storage (ROM) | 16GB eMMC                   |
| Network       | Ethernet (RJ45)             |
|               | Wi-Fi (2.4 G / 5 G)         |
| Connectivity  | USB 2.0 Type A 2EA , RS232C |
| HDMI / DP     | HDMI (3)                    |
| Speaker       | 10 W + 10 W                 |

POWER REQUIREMENTS

|                   |                          |
|-------------------|--------------------------|
| Power Consumption | 70 W (Max)               |
| Standby Power     | ≤ 0.5 W                  |
| Power Source      | AC 110-240 V @50 / 60 Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 20-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

DIGITAL SIGNAGE 43” UHD (S43A) SPECIFICATIONS



DISPLAY

|                     |                                   |
|---------------------|-----------------------------------|
| Size                | 43"                               |
| Resolution          | 3,840 x 2,160 (UHD)               |
| W*H Ratio           | 1.77 (16:9)                       |
| Luminance (Typ.)    | 500 cd/m²                         |
| Orientation         | Landscape/Portrait                |
| Contrast Ratio      | 4,000:1                           |
| Viewing Angle (H/V) | 178° / 178°                       |
| Response Time       | 6.5 ms                            |
| Active Area (HxV)   | 941.2 x 529.4 mm / 37.1 x 20.8 in |
| Color Gamut         | 85%                               |
| Backlight type      | E-LED                             |
| Life Time (LED)     | 50,000 Hrs                        |

MECHANICAL

|                          |                       |
|--------------------------|-----------------------|
| SET Dimensions           | 967.4 x 555.9 x 40 mm |
|                          | 38.1 x 21.9 x 1.6 in  |
| VESA Mount               | 400 x 300 mm          |
| SET Weight               | 9.1 kg / 20.1 lbs.    |
| Packing Dimensions       | 1,075 x 652 x 144 mm  |
|                          | 42.3 x 25.7 x 5.7 in  |
| Packing Weight           | 12.7 kg / 28.0 lbs.   |
| Bezel Width (U/L/R/B mm) | 11.5 (even)           |

SYSTEM

|               |                             |
|---------------|-----------------------------|
| OS            | Android 9.0                 |
| CPU           | Quad-core ARM Cortex-A35    |
| GPU           | ARM Mali-G31 MP2            |
| RAM           | 2 GB DDR4                   |
| Storage (ROM) | 16GB eMMC                   |
| Network       | Ethernet (RJ45)             |
|               | Wi-Fi (2.4 G / 5 G)         |
| Connectivity  | USB 2.0 Type A 2EA , RS232C |
| HDMI / DP     | HDMI (3)                    |
| Speaker       | 10 W + 10 W                 |

POWER REQUIREMENTS

|                   |                          |
|-------------------|--------------------------|
| Power Consumption | 120 W (Max)              |
| Standby Power     | ≤ 0.5 W                  |
| Power Source      | AC 110-240 V @50 / 60 Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 20-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

DIGITAL SIGNAGE 50” UHD (S50A) SPECIFICATIONS



DISPLAY

|                     |                                     |
|---------------------|-------------------------------------|
| Size                | 50"                                 |
| Resolution          | 3,840 x 2,160 (UHD)                 |
| W*H Ratio           | 1.77 (16:9)                         |
| Luminance (Typ.)    | 500 cd/m²                           |
| Orientation         | Support                             |
| Contrast Ratio      | 1,200:1                             |
| Viewing Angle (H/V) | 178° / 178°                         |
| Response Time       | 8 ms                                |
| Active Area (HxV)   | 1,095.9 x 616.4 mm / 43.1 x 24.3 in |
| Color Gamut         | 85%                                 |
| Backlight type      | E-LED                               |
| Life Time (LED)     | 50,000 Hrs                          |

MECHANICAL

|                          |                        |
|--------------------------|------------------------|
| SET Dimensions           | 1,125.8 x 646.8 x 41mm |
|                          | 44.3 x 25.4 x 1.6 in   |
| VESA Mount               | 400 x 300 mm           |
| SET Weight               | 12.6 kg / 27.8 lbs     |
| Packing Dimensions       | 1,250 x 760 x 128 mm   |
|                          | 49.2 x 29.9 x 5.0 in   |
| Packing Weight           | 15.9 kg / 35 lbs       |
| Bezel Width (U/L/R/B mm) | 10.6 (even)            |

SYSTEM

|               |                          |
|---------------|--------------------------|
| OS            | Android 9.0              |
| CPU           | Quad-core ARM Cortex-A35 |
| GPU           | ARM Mali-G31 MP2         |
| RAM           | 2GB DDR4                 |
| Storage (ROM) | 16GB eMMC                |
| Network       | Ethernet (RJ45) /        |
|               | Wi-Fi (2.4 G / 5 G)      |
| Connectivity  | USB 2.0 (2), RS232C      |
| HDMI / DP     | HDMI (3)                 |
| Speaker       | 10 W + 10 W              |

POWER REQUIREMENTS

|                   |                      |
|-------------------|----------------------|
| Power Consumption | 130 W (Max)          |
| Standby Power     | ≤ 0.5W               |
| Power Source      | AC 110~240V @50/60Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 20-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

DIGITAL SIGNAGE 55” UHD (S55A) SPECIFICATIONS



DISPLAY

|                     |                                             |
|---------------------|---------------------------------------------|
| Size                | 55"                                         |
| Resolution          | 3,840 x 2,160 (UHD)                         |
| W*H Ratio           | 1.77 (16:9)                                 |
| Luminance (Typ.)    | 500 cd/m²                                   |
| Orientation         | Landscape/Portrait                          |
| Contrast Ratio      | 5,000:1                                     |
| Viewing Angle (H/V) | 178° / 178°                                 |
| Response Time       | 6.5 ms                                      |
| Active Area (HxV)   | 1,209.6 (H) x 680.4 (V) mm / 47.6 x 26.8 in |
| Color Gamut         | 85%                                         |
| Backlight type      | E-LED                                       |
| Life Time (LED)     | 50,000 Hrs                                  |

MECHANICAL

|                          |                           |
|--------------------------|---------------------------|
| SET Dimensions           | 1,239.7 x 712.5 x 38.6 mm |
|                          | 48.8 x 28.1 x 1.5 in      |
| VESA Mount               | 300 x 400 mm              |
| SET Weight               | 17.6 kg / 38.8 lbs.       |
| Packing Dimensions       | 1,390 x 850 x 136 mm      |
|                          | 54.7 x 33.5 x 5.4 in      |
| Packing Weight           | 22.9 kg / 50.5 lbs.       |
| Bezel Width (U/L/R/B mm) | 13.3 / 13.3 / 13.3 / 15.3 |

SYSTEM

|               |                          |
|---------------|--------------------------|
| OS            | Android 9.0              |
| CPU           | Quad-core ARM Cortex-A35 |
| GPU           | ARM Mali-G31 MP2         |
| RAM           | 2 GB DDR4                |
| Storage (ROM) | 16GB eMMC                |
| Network       | Ethernet (RJ45)          |
|               | Wi-Fi (2.4 G / 5 G)      |
| Connectivity  | USB 2.0 (2), RS232C      |
| HDMI / DP     | HDMI (3)                 |
| Speaker       | 10 W + 10 W              |

POWER REQUIREMENTS

|                   |                          |
|-------------------|--------------------------|
| Power Consumption | 140 W (Max)              |
| Standby Power     | ≤ 0.5 W                  |
| Power Source      | AC 110-240 V @50 / 60 Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 20-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

DIGITAL SIGNAGE 65” UHD (S65A) SPECIFICATIONS



DISPLAY

|                     |                                               |
|---------------------|-----------------------------------------------|
| Size                | 65"                                           |
| Resolution          | 3,840 x 2,160 (UHD)                           |
| W*H Ratio           | 1.77 (16:9)                                   |
| Luminance (Typ.)    | 500 cd/m²                                     |
| Orientation         | Landscape/Portrait                            |
| Contrast Ratio      | 5,000:1                                       |
| Viewing Angle (H/V) | 178° / 178°                                   |
| Response Time       | 8 ms                                          |
| Active Area (HxV)   | 1,428.48 (H) x 803.52 (V) mm / 56.2 x 31.6 in |
| Color Gamut         | 85%                                           |
| Backlight type      | E-LED                                         |
| Life Time (LED)     | 50,000 Hrs                                    |

MECHANICAL

|                          |                           |
|--------------------------|---------------------------|
| SET Dimensions           | 1,459.2 x 837.1 x 38.9 mm |
|                          | 57.4 x 33.0 x 1.5 in      |
| VESA Mount               | 400 x 400 mm              |
| SET Weight               | 25.3 kg / 55.8 lbs.       |
| Packing Dimensions       | 1,640 x 990 x 164 mm      |
|                          | 64.6 x 39.0 x 6.5 in      |
| Packing Weight           | 34.6 kg / 76.3 lbs.       |
| Bezel Width (U/L/R/B mm) | 14.0 / 14.0 / 14.0 / 16.0 |

SYSTEM

|               |                          |
|---------------|--------------------------|
| OS            | Android 9.0              |
| CPU           | Quad-core ARM Cortex-A35 |
| GPU           | ARM Mali-G31 MP2         |
| RAM           | 2 GB DDR4                |
| Storage (ROM) | 16GB eMMC                |
| Network       | Ethernet (RJ45)          |
|               | Wi-Fi (2.4 G / 5G)       |
| Connectivity  | USB 2.0 (2), RS232C      |
| HDMI / DP     | HDMI (3)                 |
| Speaker       | 10W + 10W                |

POWER REQUIREMENTS

|                   |                          |
|-------------------|--------------------------|
| Power Consumption | 150 W (Max)              |
| Standby Power     | ≤ 0.5 W                  |
| Power Source      | AC 110-240 V @50 / 60 Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 20-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

DIGITAL SIGNAGE 75” UHD (S75A) SPECIFICATIONS



DISPLAY

|                     |                                     |
|---------------------|-------------------------------------|
| Size                | 75"                                 |
| Resolution          | 3,840 x 2,160 (UHD)                 |
| W*H Ratio           | 1.77 (16:9)                         |
| Luminance (Typ.)    | 800 cd/m²                           |
| Orientation         | Landscape/Portrait                  |
| Contrast Ratio      | 900:1                               |
| Viewing Angle (H/V) | 178° / 178°                         |
| Response Time       | 8 ms                                |
| Active Area (HxV)   | 1,649.7 × 927.9 mm / 64.9 x 36.5 in |
| Color Gamut         | NTSC 72%                            |
| Backlight type      | D-LED                               |
| Life Time (LED)     | 50,000 Hrs                          |

MECHANICAL

|                          |                           |
|--------------------------|---------------------------|
| SET Dimensions           | 1,681.66 x 959.94 x 55 mm |
|                          | 66.2 x 37.8 x 2.2 in      |
| VESA Mount               | 600 x 400 mm              |
| SET Weight               | 29 kg / 63.9 lbs.         |
| Packing Dimensions       | 1,883 x 1,140 x 186 mm    |
|                          | 74.1 x 44.9 x 7.3 in      |
| Packing Weight           | 40.5 kg / 89.3 lbs.       |
| Bezel Width (U/L/R/B mm) | 13.0 (even)               |

SYSTEM

|               |                                                 |
|---------------|-------------------------------------------------|
| OS            | Android 11                                      |
| CPU           | Quad core ARM Cortex-A73 + Quad core Cortex-A53 |
| GPU           | ARM Mali-G52 MP8                                |
| RAM           | 4 GB DDR4                                       |
| Storage (ROM) | 32 GB eMMC                                      |
| Network       | Ethernet (RJ45)                                 |
|               | Wi-Fi (2.4 G / 5G)                              |
| Connectivity  | USB 2.0 (2), RS232C                             |
| HDMI / DP     | HDMI (2) / DP (1)                               |
| Speaker       | 10 W + 10 W                                     |

POWER REQUIREMENTS

|                   |                          |
|-------------------|--------------------------|
| Power Consumption | 305 W (Typ)              |
| Standby Power     | ≤ 0.5 W                  |
| Power Source      | AC 100-240 V @50 / 60 Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 10-90%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

DIGITAL SIGNAGE 86” UHD (S86A) SPECIFICATIONS



DISPLAY

|                     |                                       |
|---------------------|---------------------------------------|
| Size                | 86"                                   |
| Resolution          | 3,840 x 2,160 (UHD)                   |
| W*H Ratio           | 1.77 (16:9)                           |
| Luminance (Typ.)    | 800 cd/m²                             |
| Orientation         | Landscape/Portrait                    |
| Contrast Ratio      | 1,000:1                               |
| Viewing Angle (H/V) | 178° / 178°                           |
| Response Time       | 8 ms                                  |
| Active Area (HxV)   | 1,895.0 × 1,066.0 mm / 74.6 x 42.0 in |
| Color Gamut         | NTSC 72%                              |
| Backlight type      | D-LED                                 |
| Life Time (LED)     | 50,000 Hrs                            |

MECHANICAL

|                          |                             |
|--------------------------|-----------------------------|
| SET Dimensions           | 1,928.04 x 1,098.96 x 57 mm |
|                          | 75.9 x 43.3 x 2.2 in        |
| VESA Mount               | 600 x 400 mm                |
| SET Weight               | 49 kg / 108.0 lbs.          |
| Packing Dimensions       | 2,123 x 1,247 x 225 mm      |
|                          | 83.6 x 49.1 x 8.9 in        |
| Packing Weight           | 64 kg / 141.1 lbs.          |
| Bezel Width (U/L/R/B mm) | 13.0 (even)                 |

SYSTEM

|               |                                                 |
|---------------|-------------------------------------------------|
| OS            | Android 11                                      |
| CPU           | Quad core ARM Cortex-A73 + Quad core Cortex-A53 |
| GPU           | ARM Mali-G52 MP8                                |
| RAM           | 4 GB DDR4                                       |
| Storage (ROM) | 32 GB eMMC                                      |
| Network       | Ethernet (RJ45)                                 |
|               | Wi-Fi (2.4 G / 5G)                              |
| Connectivity  | USB 2.0 (2), RS232C                             |
| HDMI / DP     | HDMI (2) / DP (1)                               |
| Speaker       | 10 W + 10 W                                     |

POWER REQUIREMENTS

|                   |                          |
|-------------------|--------------------------|
| Power Consumption | 395 W (Typ)              |
| Standby Power     | ≤ 0.5 W                  |
| Power Source      | AC 100-240 V @50 / 60 Hz |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 10-90%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

MEET

NEW ADVERTISEMENT PLATFORM

**BAR  
DISPLAY SOLUTION**

**B** SERIES



# *naturaleza* SPARKLING WATER

Make Your Life Better

Help for dyspepsia and constipation. Rich in health promoting minerals.





BAR DISPLAY SOLUTION

23" B Series FHD

23" FHD Bar display

Newton Touch, specialized ESL interlocking function with slim depth design

24" B Series FHD

24" Bar display

620 mm Bar Display product specialized for the retail market and customized signage with high performance

25" B Series FHD

25" Bar display

606 mm Bar Display product specialized for elevator signage with high-performance

29" B Series FHD

29" FHD Bar display

Newton Touch, specialized ESL interlocking function with slim depth design

35" B Series UHD

35" UHD Bar display

890mm Bar Display product specialized for retail shelves

37" B Series FHD

37" FHD Bar display

940 mm Bar Display product specialized for video multi-decoding with high performance

47.1" B Series UHD

47.1" UHD Bar display

1,200 mm Bar Display product specialized for video multi-decoding with high performance



33" B Series FHD

33" Bar display (Square)

Square Display product specialized for customized signage with high performance

NEWTON SIGNAGE 23” (B23A) SPECIFICATIONS



DISPLAY

|                     |                                 |
|---------------------|---------------------------------|
| Size                | 23.1"                           |
| Resolution          | 1,920 x 158 (FHD)               |
| W*H Ratio           | 12.15                           |
| Luminance (Typ.)    | 700 cd/m²                       |
| Orientation         | Landscape/Portrait              |
| Contrast Ratio      | 1,000:1                         |
| Viewing Angle (H/V) | 178° / 178°                     |
| Response Time       | 9 ms                            |
| Active Area (HxV)   | 585.6 x 48.2 mm / 23.1 x 1.9 in |
| Color Gamut         | 72%                             |
| Backlight type      | E-LED                           |
| Life Time (LED)     | 50,000 Hrs                      |

MECHANICAL

|                          |                        |
|--------------------------|------------------------|
| SET Dimensions           | 593.8 x 63.4 x 20.0 mm |
|                          | 23.4 x 2.5 x 0.8 in    |
| VESA Mount               | X                      |
| SET Weight               | 0.8 Kg / 1.8 lbs.      |
| Packing Dimensions       | 905 x 153 x 73 mm      |
|                          | 35.6 x 6.0 x 2.9 in    |
| Packing Weight           | 1.4 Kg / 3.1 lbs.      |
| Bezel Width (U/L/R/B mm) | 5.6 / 4.1 / 4.1 / 9.6  |

SYSTEM

|              |                                            |
|--------------|--------------------------------------------|
| OS           | Android 8.1                                |
| CPU          | Quad-core ARM Cortex-A35, 1.35 GHz         |
| GPU          | ARM Mali-G31 MP2 :<br>2D/3D Graphic Engine |
| RAM          | 1 GB DDR3                                  |
| Storage(ROM) | 8 GB eMMC                                  |
| Network      | 802.11 b/g/n (2.4 GHz)                     |
| Connectivity | Micro USB 2.0 (OTG 1 ea)                   |
| Touch        | O                                          |
| Speaker      | X                                          |

POWER REQUIREMENTS

|                   |                         |
|-------------------|-------------------------|
| Power Consumption | 11.8 W (Typ)            |
| Standby Power     | X                       |
| Power Source      | USB Type C (Power Only) |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-45°C    |
|                       | 32-113 °F |
| Operating Humidity    | 10-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

LCD SIGNAGE 25” QHD (B25B) SPECIFICATIONS



DISPLAY

|                    |                                        |
|--------------------|----------------------------------------|
| Size               | 25" Slim bezel                         |
| Resolution         | 2,560 x 1,080 (QHD)                    |
| W*H Ratio          | 2.37                                   |
| Luminance (Typ.)   | 350 cd/m²                              |
| Orientation        | Landscape/Portrait                     |
| Contrast Ratio     | 1,000:1                                |
| Viewing Angle(H/V) | 178° / 178°                            |
| Response Time      | 16 ms                                  |
| Active Area (HxV)  | 585.2(H) × 246.9(V) mm / 23.0 x 9.7 in |
| Color Gamut        | 76%                                    |
| Back Light type    | E-LED                                  |
| Life Time(LED)     | 30,000 Hrs                             |

MECHANICAL

|                          |                         |
|--------------------------|-------------------------|
| SET Dimension            | 285 x 606.2 x 29.8 mm   |
|                          | 11.2 x 23.9 x 1.17 in   |
| VESA Mount               | X (exclusive Bracket)   |
| SET Weight               | 4.4 Kg / 9.7 lbs.       |
| Packing Dimension        | 390 x 685 x 80 mm       |
|                          | 15.4 x 27.0 x 3.1 in    |
| Packing Weight           | 7.2 Kg / 15.9 lbs.      |
| Bezel Width (U/L/R/B mm) | 18.5 / 9.6 / 9.6 / 18.5 |

SYSTEM

|              |                                                            |
|--------------|------------------------------------------------------------|
| OS           | Android 7.1                                                |
| CPU          | RK3288 , Quad-Core Cortex - A17,<br>up to 1.8 GHz          |
| GPU          | ARM Mali-T764 MP                                           |
| RAM          | 2 GB DDR3                                                  |
| Storage(ROM) | 8 GB eMMC                                                  |
| Network      | Ethernet 1Gbps (RJ45) , Wi-Fi Option                       |
| Connectivity | USB 2.0 Type A 2EA, Micro USB 2.0<br>(OTG 1ea /Only Debug) |
| Touch        | X                                                          |
| Speaker      | Mono 3 W                                                   |

POWER REQUIREMENTS

|                   |                                |
|-------------------|--------------------------------|
| Power Consumption | 19.1 W (Typ)                   |
| Standby Power     | X                              |
| Power Source      | DC Jack (19 V / 3.17 A / 59 W) |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operating Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operating Humidity    | 10-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

NEWTON SIGNAGE 29" (B29A) SPECIFICATIONS



DISPLAY

|                     |                                  |
|---------------------|----------------------------------|
| Size                | 29"                              |
| Resolution          | 1,920 x 540 (FHD)                |
| W*H Ratio           | 3.56                             |
| Luminance (Typ.)    | 500 cd/m²                        |
| Orientation         | Landscape/Portrait               |
| Contrast Ratio      | 1,000:1                          |
| Viewing Angle (H/V) | 178° / 178°                      |
| Response Time       | 9 ms                             |
| Active Area (HxV)   | 698.4 x 196.4 mm / 27.5 x 7.7 in |
| Color Gamut         | 72%                              |
| Backlight type      | E-LED                            |
| Life Time (LED)     | 50,000 Hrs                       |

MECHANICAL

|                          |                         |
|--------------------------|-------------------------|
| SET Dimensions           | 712.8 x 213.7 x 16.0 mm |
|                          | 28.1 x 8.4 x 0.6 in     |
| VESA Mount               | X                       |
| SET Weight               | 2.45 Kg / 5.4 lbs.      |
| Packing Dimensions       | 905 x 273 x 73 mm (1pc) |
|                          | 35.6 x 10.7 x 2.9 in    |
| Packing Weight           | 3.25 Kg / 7.2 lbs.      |
| Bezel Width (U/L/R/B mm) | 7.7 / 7.2 / 7.2 / 9.6   |

SYSTEM

|               |                                            |
|---------------|--------------------------------------------|
| OS            | Android 8.1                                |
| CPU           | Quad-core ARM Cortex-A35, 1.35 GHz         |
| GPU           | ARM Mali-G31 MP2 :<br>2D/3D Graphic Engine |
| RAM           | 1 GB DDR3                                  |
| Storage (ROM) | 8 GB eMMC                                  |
| Network       | 802.11 b/g/n (2.4 GHz)                     |
| Connectivity  | Micro USB 2.0 (OTG 1 ea)                   |
| Touch         | O                                          |
| Speaker       | X                                          |

POWER REQUIREMENTS

|                   |                         |
|-------------------|-------------------------|
| Power Consumption | 22 W (Typ)              |
| Standby Power     | X                       |
| Power Source      | USB Type C (Power Only) |

ENVIRONMENTAL

|                       |          |
|-----------------------|----------|
| Operating Temperature | 0-45°C   |
|                       | 32-113°F |
| Operating Humidity    | 10-80%   |
| Storage Temperature   | -20-60°C |
|                       | -4-140°F |

NEWTON SIGNAGE 35" FHD (B35A) SPECIFICATIONS



DISPLAY

|                     |                                 |
|---------------------|---------------------------------|
| Size                | 35"                             |
| Resolution          | 3,840 x 200 (FHD)               |
| W*H Ratio           | 19.1                            |
| Luminance (Typ.)    | 500 cd/m²                       |
| Orientation         | Only Landscape                  |
| Contrast Ratio      | 1,000:1                         |
| Viewing Angle (H/V) | 178° / 178°                     |
| Response Time       | 8 ms                            |
| Active Area (HxV)   | 877.8 x 45.7 mm / 34.6 x 1.8 in |
| Color Gamut         | 68%                             |
| Backlight type      | E-LED                           |
| Life Time (LED)     | 30,000 Hrs                      |

MECHANICAL

|                          |                        |
|--------------------------|------------------------|
| SET Dimensions           | 891.6 x 60.4 x 26.3 mm |
|                          | 35.1 x 2.4 x 1.0 in    |
| VESA Mount               | X                      |
| SET Weight               | 2.0 Kg / 4.4 lbs.      |
| Packing Dimensions       | 1,125 x 80 x 123 mm    |
|                          | 44.3 x 3.1 x 4.8 in    |
| Packing Weight           | 2.5 Kg / 5.5 lbs.      |
| Bezel Width (U/L/R/B mm) | 7.8 / 5.7 / 5.7 / 4.5  |

SYSTEM

|               |                                                   |
|---------------|---------------------------------------------------|
| OS            | Android 9.0                                       |
| CPU           | Quad-core ARM Cortex-A55, 1.9 GHz                 |
| GPU           | ARM Mali-G31 MP2                                  |
| RAM           | 2 GB DDR3                                         |
| Storage (ROM) | 16GB eMMC                                         |
| Network       | Wi-Fi 2.4 GHz (1T1R)                              |
| Connectivity  | USB 2.0 (1), Micro USB (OTG 1 ea),<br>TF Card (1) |
| Touch         | X                                                 |
| Speaker       | X                                                 |

POWER REQUIREMENTS

|                   |                                     |
|-------------------|-------------------------------------|
| Power Consumption | 21.5 W (Typ)                        |
| Standby Power     | X                                   |
| Power Resource    | USB Type C Jack (12 V / 3 A / 36 W) |

ENVIRONMENTAL

|                       |          |
|-----------------------|----------|
| Operation Temperature | 0-50°C   |
|                       | 32-122°F |
| Operation Humidity    | 20-80%   |
| Storage Temperature   | -10-60°C |
|                       | 14-140°F |

NEWTON SIGNAGE 37” FHD (B37A) SPECIFICATIONS



DISPLAY

|                     |                                   |
|---------------------|-----------------------------------|
| Size                | 37"                               |
| Resolution          | 1,920 x 540 (FHD)                 |
| W*H Ratio           | 3.56                              |
| Luminance (Typ.)    | 700 cd/m²                         |
| Orientation         | Landscape/Portrait                |
| Contrast Ratio      | 1,000:1                           |
| Viewing Angle (H/V) | 178° / 178°                       |
| Response Time       | 14 ms                             |
| Active Area (HxV)   | 899.7 x 253.0 mm / 35.4 x 10.0 in |
| Color Gamut         | 72%                               |
| Backlight type      | E-LED                             |
| Life Time (LED)     | 50,000 Hrs                        |

MECHANICAL

|                          |                         |
|--------------------------|-------------------------|
| SET Dimensions           | 914.9 x 280.9 x 27 mm   |
|                          | 36.0 x 11.1 x 1.1 in    |
| VESA Mount               | X                       |
| SET Weight               | 6.45 Kg / 14.2 lbs.     |
| Packing Dimensions       | 1,097 x 85 x 388 mm     |
|                          | 43.2 x 3.3 x 15.3 in    |
| Packing Weight           | 8.1 Kg / 17.8 lbs.      |
| Bezel Width (U/L/R/B mm) | 11.9 / 5.6 / 5.6 / 11.9 |

SYSTEM

|              |                                                   |
|--------------|---------------------------------------------------|
| OS           | Android 12                                        |
| CPU          | Quad-core ARM Cortex-A55, 1.5 GHz                 |
| GPU          | ARM Mali-G52 MP8                                  |
| RAM          | 2 GB LPDDR4                                       |
| Storage(ROM) | 16 GB eMMC                                        |
| Network      | Ethernet (RJ45) / Wi-Fi (802.11 a/b/g/n/ac, 2T2R) |
| Connectivity | USB 2.0 (1), Micro USB (OTG 1 ea), USB 3.0 (1)    |
| Touch        | X                                                 |
| Speaker      | Mono 3 W                                          |

POWER REQUIREMENTS

|                   |                                |
|-------------------|--------------------------------|
| Power Consumption | 41 W (Typ)                     |
| Standby Power     | X                              |
| Power Resource    | DC Jack (19 V / 3.17 A / 59 W) |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operation Temperature | 0-40°C    |
|                       | 32-104 °F |
| Operation Humidity    | 10-80%    |
| Storage Temperature   | -20-60°C  |
|                       | -4-140 °F |

NEWTON SIGNAGE 47.1” UHD (B47A) SPECIFICATIONS



DISPLAY

|                     |                                   |
|---------------------|-----------------------------------|
| Size                | 47.1"                             |
| Resolution          | 3,840 x 160 (UHD)                 |
| W*H Ratio           | 24.0                              |
| Luminance (Typ.)    | 500 cd/m²                         |
| Orientation         | Only Landscape                    |
| Contrast Ratio      | 1,000:1                           |
| Viewing Angle (H/V) | 178° / 178°                       |
| Response Time       | 8 ms                              |
| Active Area (HxV)   | 1,196.2 x 45.7 mm / 47.1 x 1.8 in |
| Color Gamut         | 70%                               |
| Backlight type      | E-LED                             |
| Life Time (LED)     | 30,000 Hrs                        |

MECHANICAL

|                          |                          |
|--------------------------|--------------------------|
| SET Dimensions           | 1,211.6 x 67.5 x 24.3 mm |
|                          | 47.7 x 2.7 x 1.0 in      |
| VESA Mount               | X                        |
| SET Weight               | 3.33 Kg / 7.3 lbs.       |
| Packing Dimensions       | 1,445 x 85 x 123 mm      |
|                          | 56.9 x 3.3 x 4.8 in      |
| Packing Weight           | 3.9 kg / 8.6 lbs.        |
| Bezel Width (U/L/R/B mm) | 8.4 / 7.0 / 7.0 / 8.4    |

SYSTEM

|               |                                               |
|---------------|-----------------------------------------------|
| OS            | Android 9.0                                   |
| CPU           | Quad-core ARM Cortex-A55, 1.9 GHz             |
| GPU           | ARM Mali-G31 MP2                              |
| RAM           | 2 GB LPDDR4                                   |
| Storage (ROM) | 16GB eMMC                                     |
| Network       | Wi-Fi 2.4 GHz (1T1R)                          |
| Connectivity  | USB 2.0 (1), Micro USB (OTG 1ea), TF Card (1) |
| Touch         | X                                             |
| Speaker       | X                                             |

POWER REQUIREMENTS

|                   |                                     |
|-------------------|-------------------------------------|
| Power Consumption | 20.1 W (Typ)                        |
| Standby Power     | X                                   |
| Power Source      | USB Type C Jack (12 V / 3 A / 36 W) |

ENVIRONMENTAL

|                       |           |
|-----------------------|-----------|
| Operation Temperature | 0-50°C    |
|                       | 32-122 °F |
| Operation Humidity    | 20-80%    |
| Storage Temperature   | -10-60°C  |
|                       | 14-140 °F |

TAKE LIFE - SHOPPING  
EXPERIENCE

**SPECIAL  
DISPLAY SOLUTION**







## SPECIAL DISPLAY SOLUTION



10.1"

Tablet product or Retail LCD Tag product  
for retail promotion display



49/55" Dual display

Dual display solution,  
two displays integrated into one body



55" Video wall

Planning products can be applied to each site





10.1” TABLET SPECIFICATIONS



DISPLAY

|                     |                                      |
|---------------------|--------------------------------------|
| Size                | 10.1"                                |
| Resolution          | 800(H) x 1,280(V)                    |
| W*H Ratio           | 1.6                                  |
| Luminance           | 300 cd/m²                            |
| Portrait Mode       | Support                              |
| Contrast Ratio      | 1,000:1                              |
| Viewing Angle (H/V) | 160° / 160°                          |
| Response Time       | 30 ms                                |
| Active Area         | 135.36 X 216.576 mm / 5.33 x 8.52 in |
| Color Gamut         | 60%                                  |
| Backligh type       | E-LED                                |
| Life Time (LED)     | 25,000 hrs                           |

ADDITIONAL FUNCTIONS

|         |                 |
|---------|-----------------|
| Speaker | 2 speaker × 2 W |
| Touch   | YES             |

ENVIRONMENTAL

|                       |                               |
|-----------------------|-------------------------------|
| Operating Temperature | 0-45°C, 32-113°F              |
| Operating Humidity    | 10-80%                        |
| Storage Temperature   | -20-60°C, -4-140°F            |
| Warranty              | As per the regional agreement |

SYSTEM

|                |                                     |
|----------------|-------------------------------------|
| OS             | Android 12                          |
| CPU            | MT8185                              |
| GPU            | ARM G76-3EE                         |
| RAM            | 3 GB                                |
| Storage (ROM)  | 32 GB                               |
| Network        | WiFi 2.4 GHz / 5 GHz (2T2R)         |
| Connectivity   | USB-C Port 2ea support (With Cable) |
| Remote Control | No                                  |
| HDMI / DP      | No                                  |

MECHANICAL

|                          |                                              |
|--------------------------|----------------------------------------------|
| SET Dimensions           | 241.8 x 160.6 x 15 mm / 9.52 x 6.32 x 0.6 in |
| VESA                     | No                                           |
| SET Weight               | 465 g / 1.0 lbs.                             |
| Packing Dimensions       | 312 × 50 × 210 mm / 12.3 x 1.97 x 8.27 in    |
| Packing Weight           | 655 g / 1.4 lbs.                             |
| Bezel Width (U/L/R/D mm) | -                                            |

POWER REQUIREMENTS

|                   |                              |
|-------------------|------------------------------|
| Power Consumption | ≤15 W                        |
| Standby Power     | ≤ 0.5 W                      |
| Power Source      | DC Input 5 V /3 A ( Adapter) |

49” DUAL (D49A) SPECIFICATIONS



DISPLAY

|                     |                                 |
|---------------------|---------------------------------|
| Size                | 49" (Dual)                      |
| Resolution          | 1,920 x 1,080 (FHD)             |
| W*H Ratio           | 1.77 (16:9)                     |
| Luminance           | A : 400 cd/m² / B : 800 cd/m²   |
| Portrait Mode       | Portrait Only (Landscape X)     |
| Contrast Ratio      | 1,000:1                         |
| Viewing Angle (H/V) | 178° / 178°                     |
| Response Time       | 8 ms                            |
| Active Area         | 1,074 x 604 mm / 42.3 x 23.8 in |
| Color Gamut         | 72%                             |
| Backligh type       | E-LED                           |
| Life Time (LED)     | 50,000 Hrs                      |

ADDITIONAL FUNCTIONS

|         |             |
|---------|-------------|
| Speaker | 10 W + 10 W |
| Touch   | No          |

ENVIRONMENTAL

|                       |                    |
|-----------------------|--------------------|
| Operating Temperature | 0-40°C, 32-104°F   |
| Operating Humidity    | 10-80%             |
| Storage Temperature   | -20-60°C, -4-140°F |
| Warranty              | 3 Years (US/EU/JA) |

SYSTEM

|                |                          |
|----------------|--------------------------|
| OS             | Android 11               |
| CPU            | Arm Cortex-A17 Quad core |
| GPU            | ARM G52 2EE              |
| RAM            | 2 GB DDR3                |
| Storage (ROM)  | 16 GB eMMC               |
| Network        | WiFi 2.4 GHz (1T1R)      |
| Connectivity   | USB 2.0 x 2 ea           |
| Remote Control | No                       |
| HDMI / DP      | HDMI out                 |

MECHANICAL

|                          |                                            |
|--------------------------|--------------------------------------------|
| SET Dimensions           | 659.1 x 1,340 x 25.4 mm / 26 x 52.7 x 1 in |
| VESA                     | No                                         |
| SET Weight               | 24 kg / 52.9 lbs                           |
| Packing Dimensions       | 1,525 x 835 x 210 mm / 60 x 32.9 x 8.3 in  |
| Packing Weight           | 33 kg / 72.7 lbs.                          |
| Bezel Width (U/L/R/D mm) | 12.5 / 12.5 / 12.5 / 12.5                  |

POWER REQUIREMENTS

|                   |                    |
|-------------------|--------------------|
| Power Consumption | 210 W (Max)        |
| Standby Power     | ≤ 2 W              |
| Power Source      | 100-240 Vac / SMPS |

55"DUAL (D55A) SPECIFICATIONS



| DISPLAY             |                                   |
|---------------------|-----------------------------------|
| Size                | 55" Dual                          |
| Resolution          | 1,920 x 1,080 (FHD)               |
| W*H Ratio           | 1.77 (16:9)                       |
| Luminance           | A : 400 cd/m² / B : 800 cd/m²     |
| Portrait Mode       | Portrait Only (Landscape X)       |
| Contrast Ratio      | 1,000:1                           |
| Viewing Angle (H/V) | 178° / 178°                       |
| Response Time       | 8 ms                              |
| Active Area         | 1,209 x 680.4 mm / 47.6 x 26.8 in |
| Color Gamut         | 72%                               |
| Backlight type      | E-LED                             |
| Life Time (LED)     | 50,000 Hrs                        |

| ADDITIONAL FUNCTIONS |             |
|----------------------|-------------|
| Speaker              | 10 W + 10 W |
| Touch                | No          |

| ENVIRONMENTAL         |                    |
|-----------------------|--------------------|
| Operating Temperature | 0-40°C, 32-104°F   |
| Operating Humidity    | 10-80%             |
| Storage Temperature   | -20-60°C, -4-140°F |
| Warranty              | 3 Years (US/EU/JA) |

| SYSTEM         |                          |
|----------------|--------------------------|
| OS             | Android 11               |
| CPU            | Arm Cortex-A17 Quad core |
| GPU            | ARM G52 2EE              |
| RAM            | 2 GB DDR3                |
| Storage (ROM)  | 16 GB eMMC               |
| Network        | WiFi 2.4 GHz (1T1R)      |
| Connectivity   | USB 2.0 x 2 ea           |
| Remote Control | No                       |
| HDMI / DP      | HDMI out                 |

| MECHANICAL               |                                             |
|--------------------------|---------------------------------------------|
| SET Dimensions           | 737.5 x 1,475.5 x 25.7 mm / 29 x 58 x 1 in  |
| VESA                     | No                                          |
| SET Weight               | 29 kg / 63.9 lbs                            |
| Packing Dimensions       | 1,655 x 905 x 210 mm / 65.2 x 35.6 x 8.3 in |
| Packing Weight           | 40 kg / 88 lbs.                             |
| Bezel Width (U/L/R/D mm) | 12.5 / 12.5 / 12.5 / 12.5                   |

| POWER REQUIREMENTS |                    |
|--------------------|--------------------|
| Power Consumption  | 230 W (Max)        |
| Standby Power      | ≤ 2 W              |
| Power Source       | 100-240 Vac / SMPS |

55" VIDEO WALL (V55A) SPECIFICATION



| DISPLAY             |                                     |
|---------------------|-------------------------------------|
| Size                | 55"                                 |
| Resolution          | 1,920 x 1,080 (UHD)                 |
| W*H Ratio           | 1.77 (16:9)                         |
| Luminance           | 500 cd/m²                           |
| Portrait Mode       | Support                             |
| Contrast Ratio      | 1200:1                              |
| Viewing Angle (H/V) | 178° / 178°                         |
| Response Time       | 8 ms                                |
| Active Area         | 1,209.6 x 680.4 mm / 47.6 x 26.8 in |
| Color Gamut         | 70% NTSC                            |
| Backlight type      | D-LED                               |
| Life Time (LED)     | 50,000 Hrs                          |

| ADDITIONAL FUNCTION |    |
|---------------------|----|
| Speaker             | No |
| Touch               | No |

| ENVIRONMENTAL         |                    |
|-----------------------|--------------------|
| Operating Temperature | 0-50°C, 32-122°F   |
| Operating Humidity    | 10%-80%            |
| Storage Temperature   | -20-60°C, -4-140°F |
| Warranty              | 3 Years (US/EU/JA) |

| SYSTEM         |                                               |
|----------------|-----------------------------------------------|
| OS             | Non OS                                        |
| CPU            | 8051                                          |
| GPU            | -                                             |
| RAM            | 1GB DDR3                                      |
| Storage (ROM)  | 1 MB                                          |
| Network        | IR-IN, RS232C IN/OUT                          |
| Connectivity   | DVI IN×1, HDMI IN× 2, DP IN/OUT× 1, VGA IN× 1 |
| Remote Control | Yes                                           |
| HDMI / DP      | HDMI-IN, DP IN/OUT                            |

| MECHANICAL                 |                                               |
|----------------------------|-----------------------------------------------|
| SET Outline Dimensions     | 1,213.5 x 125 x 684.3 mm / 47.8 x 4.9 x 27 in |
| VESA                       | 700 x 400 mm                                  |
| SET Weight                 | 25 kg / 55 lbs.                               |
| Packing Outline Dimensions | T.B.D                                         |
| Packing Weight             | 60 kg / 132 lbs.                              |
| Bezel Width (U/L/R/D mm)   | 2.62 / 1.48 / 2.62 / 1.48                     |

| POWER REQUIREMENTS |                            |
|--------------------|----------------------------|
| Power Consumption  | 180 W (Typ)                |
| Standby Power      | -                          |
| Power Source       | AC 100 V ~ 240 V, 50/60 Hz |

THANK YOU