

CloudSync API Documentation

Version 3.2.1

Last updated: June 2026

Contact: api-support@cloudsync.io

1. Authentication

1.1 API Keys

All API requests require authentication via API key. Include your key in the Authorization header:

```
Authorization: Bearer your-api-key-here
```

API keys are scoped to your organization and can be revoked at any time from the dashboard.

1.2 OAuth 2.0

For server-to-server authentication, we recommend OAuth 2.0 with client credentials flow.

```
Token endpoint: https://auth.cloudsync.io/oauth/token
```

Rate limit: 1000 requests per minute per client ID

2. REST API Endpoints

2.1 Files

GET	/api/v3/files	- List all files
POST	/api/v3/files	- Upload a file
GET	/api/v3/files/{id}	- Get file metadata
DELETE	/api/v3/files/{id}	- Delete a file
GET	/api/v3/files/{id}/content	- Download file content

2.2 Folders

GET	/api/v3/folders	- List all folders
POST	/api/v3/folders	- Create a folder
GET	/api/v3/folders/{id}	- Get folder contents
PUT	/api/v3/folders/{id}	- Update folder
DELETE	/api/v3/folders/{id}	- Delete folder

2.3 Sharing

POST	/api/v3/shares	- Create a share link
GET	/api/v3/shares/{id}	- Get share details
DELETE	/api/v3/shares/{id}	- Revoke share link

3. WebSocket API

3.1 Connection

Connect to: `wss://ws.cloudsync.io/v3/events`

Connection timeout: 30 seconds

Idle timeout: 5 minutes (sends ping every 60s)

Max message size: 1MB

3.2 Authentication

Send auth message immediately after connection:

```
{"type": "auth", "token": "your-api-key"}
```

Server responds with `{"type": "auth_ok"}` on success.

3.3 Events

- `file.created` - New file uploaded
- `file.updated` - File content modified
- `file.deleted` - File removed
- `folder.created` - New folder created
- `share.created` - Share link created
- `share.revoked` - Share link revoked

4. Rate Limiting

4.1 Limits by Plan

Free tier: 100 requests/minute
Pro tier: 1,000 requests/minute
Enterprise tier: 10,000 requests/minute
Premium tier: 50,000 requests/minute

4.2 Rate Limit Headers

X-RateLimit-Limit: Maximum requests per window
X-RateLimit-Remaining: Requests remaining
X-RateLimit-Reset: Unix timestamp when window resets

4.3 Exceeded Limits

Returns HTTP 429 Too Many Requests with Retry-After header.
Backoff exponentially: 1s, 2s, 4s, 8s, 16s, max 60s.

5. Error Codes

400	Bad Request	- Invalid request parameters
401	Unauthorized	- Missing or invalid API key
403	Forbidden	- Insufficient permissions
404	Not Found	- Resource does not exist
409	Conflict	- Resource already exists
413	Payload Too Large	- File exceeds 100MB limit
429	Too Many Requests	- Rate limit exceeded
500	Internal Server Error	- Server-side error
503	Service Unavailable	- Maintenance or overload

6. SDK Reference

6.1 Official SDKs

Python: `pip install cloudsync-python (v3.2.0)`
Node.js: `npm install @cloudsync/sdk (v3.2.1)`
Java: `com.cloudsync:sdk:3.2.0`
Go: `go get github.com/cloudsync/sdk-go/v3`
Ruby: `gem install cloudsync (v3.2.0)`
C#: `Install-Package CloudSync.SDK (v3.2.1)`
PHP: `composer require cloudsync/sdk (v3.2.0)`
Swift: `.package(url: "https://github.com/cloudsync/sdk-swift")`

6.2 Quick Start (Python)

```
from cloudsync import CloudSync
client = CloudSync(api_key="your-key")
files = client.files.list(folder_id="root")
for file in files:
    print(f"{file.name} ({file.size} bytes)")
```

7. Webhooks

7.1 Configuration

Webhooks deliver real-time notifications to your server via HTTP POST.

Endpoint must respond with 2xx within 5 seconds.

Failed deliveries retry 3 times with exponential backoff.

7.2 Payload Format

```
{"event": "file.created", "timestamp": "...",  
  "data": {"id": "...", "name": "..."}}
```

7.3 Signature Verification

X-CloudSync-Signature: HMAC-SHA256 of payload with your webhook secret

Always verify signatures to prevent spoofed requests.

8. Pagination

All list endpoints support cursor-based pagination.

Query parameters:

- limit - Items per page (default: 20, max: 100)
- cursor - Pagination cursor from previous response
- sort - Sort field (name, created_at, size)
- order - Sort order (asc, desc)

Response includes:

- data[] - Array of items
- next_cursor - Cursor for next page (null if no more)
- has_more - Boolean indicating more pages

Appendix A: Changelog

v3.2.1 (June 2026)

- Fixed WebSocket reconnection bug
- Added webhook signature verification
- Improved rate limit headers

v3.2.0 (May 2026)

- Added WebSocket API for real-time events
- New sharing endpoints with expiration
- SDK support for Go and Swift

v3.1.0 (March 2026)

- Added folder management endpoints
- Improved error messages
- Added pagination support