03-60-340-30

2017 Winter, Tues. Feb. 7, 2017 in TC 204 University of Windsor, School of Computer Science

Midterm 1 Examination

Mr. Paul Preney

Student ID:	
FIRST Name:	
LAST Name:	
"I have neither given nor received unauthorized help with this examination. Any suspicion of cheating will automatically void my mark on this examination."	
	Signature Unsigned examination booklets will not be graded. Signature implies agreement with the above statement in quotes.

INSTRUCTIONS

- 1. You have **1 hour** maximum to complete this examination. Pace yourself accordingly.
- 2. Write your answers in the space provided. No additional space will be provided.
- 3. Do **not** remove any papers from this booklet or add new ones.
- 4. You may **not** use any reference material(s) **except** what has been provided within this examination booklet and the course text books *The C++ Programming Language*, 4th *Edition* and/or *The C++ Standard Library: A Tutorial and Reference*.
- **5.** You may not use the C Standard Library unless given explicit permission to do so. C++ coding techniques and the C++ Standard Library without the C Standard Library subset must always be used.
- 6. **Document your code where appropriate.** Unclear answers may not receive partial marks. Ensure any written English uses proper spelling, grammar, and can be understood. Answers must be neat and legible to receive marks.
- 7. **Be sure** that you have printed your name and student number on all pages of this examination.
- 8. Ensure that you have all **10 pages** of this examination (including this page) before starting to write this exam. If you don't, bring this to the attention of the instructor immediately.
- 9. Ensure the proper case, spelling, syntax, grammar, and punctuation marks are correctly used in all answers involving code.

EXAMINATION MARK:	
MAXIMUM MARK:	73

Part I: Multiple Choice and Short Answer Questions (45 marks)

For each question in this section, neatly and plainly **circle or underline** the **single** response which most correctly completes/answers the statement/question given for multiple choice or True/False questions, otherwise, write in the appropriate answer(s) in the space provided. Read carefully! Unintelligible or ambiguous responses will receive a mark of zero (0) for that question, so ensure that your answer is clear.

Q1) True/False: Strictly speaking and unlike ISO C, ISO C++ only supports pass-by-value when calling functions. [1 mark]	•
(a) True (b) False	
Q2) The first official ISO C++ standard is associated with the year	
Answer:	1 mark]
Q3) To compile C++14 code using GCC's g++, the compiler option one must use is:	
Answer:[1 mark]
Q4) True/False: In C++, one can declare a variable whose type is a reference to a reference. [1 mark]	
(a) True (b) False	
Q5) The creator of C++ originally created the language while working at (Provide company name	1e.)
Answer:	1 mark]
Q6) All C++ types that have as their rightmost decoration one or two ampersands are known as types.	ypes.
Answer:	1 mark]
Q7) If a C++ compiler chose to implement a variable of type char const*& as a pointer, what would the variable's (exact equivalent) type be?	e pointer
Answer: [2 marks]
Q8) If a C++ compiler chose to implement a variable of type Foo& as a pointer, what would the pointer variable's (exact equivalent) type be?	r
Answer: [:	2 marks]
Q9) If a C++ compiler chose to implement a variable of type Bar*&& as a pointer, what would the point variable's (exact equivalent) type be?	nter
Answer:[2 marks]
Q10) Given the declaration, int i;, what does i++; return? [1 mark]	
(a) an l-value (b) an r-value (c) neither of these	

STUDENT NAME:Copyright © 20	STUDENT I.D. # D16 Paul Preney. All Rights Reserved. No part of this document may be duplicated without permission.	
	ession that declares a reference to a temporary int object who's value is 5.	
Answer:		[1 mark]
Q12) A variable can be	easily determined to be an l-value when it	
Answer:		[1 mark]
Q13) A variable can be	easily determined to be an r-value when it	
Answer:		[1 mark]
Q14) True/False: ISO C	++'s evolution is driven by theoretical problems not by real ones. [1 mark]	
(a) True	(b) False	
Q15) True/False: C++ p	permits implicit violations of the static type system. [1 mark]	
(a) True	(b) False	
Q16) Match the appropr	riate term with the best definition. The possible terms to choose from are:	

imperative, modular, object-based, object-oriented, generic, functional [6 marks]

Definition	Write Term Associated With Definition In Row
Computation is defined in terms of patterns with placeholders that act on common aspects of those placeholder's interfaces.	
Computation is defined in terms of state that determines the expression of the next operation to be performed.	
Computation is defined in terms of programming statements that describe changes in state.	
Computation is defined in terms of hierarchically organized state that determines the expression of the next operation to be performed.	
Computation is defined in terms of operations that have no side effects.	
Computation is defined in terms of programming statements that describe changes in state with the additional ability to expose/hide functions and/or variables as seen from other translation units or namespaces.	

STUDENT NAME:Copyrig	STUDENT I.D. #
	rules, to use C's <ctype.h> header in a C++ program, explain what one has to do to #include</ctype.h>
the neader in C++.	Be sure to also write the final C++ #include code for <ctype.h> in your answer. [3 marks]</ctype.h>
Q18) All C Standa	rd Library functions are contained in the cstd namespace. [1 mark]
(a) True	(b) False
Q19) All C++ Stan	dard Library functions are contained in the cxxstd namespace. [1 mark]
(a) True	(b) False
Q20) Briefly, what	is the difference between cout and cerr? [2 marks]
•	Library uses the bit shift operator to write formatted data out to an ostream.
	[1 mark]
- ,	Library uses the bit shift operator to read in formatted data from an istream.
Answer:	[1 mark]
	C++, the auto keyword prefixed in front of a variable declaration in a function meant that the red and placed on a function's
Answer: _	[1 mark]
Q24) In the current in C++? [1 mark]	t C++ standard, using the auto keyword to declare a variable allows a programmer to do what

STUDENT NAME:	STUDENT I.D. #
Copyright © 2016 Paul Pier	iey. All Rights Reserved. No part of this document may be duplicated without permission.
Q25) Using the current C++ stand why it will not compile. [2 marks	lard, will writing auto i; in main() compile? Answer yes or no. If no, explain
	e foo(int i) { return 3.14; } to use the new C++ function suffix declarator know you need to use -> .) [2 marks]
Q27) Rewrite the function double complicate this!) [2 marks]	e foo(int c) { return 3; } so that it is a C++ lambda function. (Don't over-
Q28) If a C++ I/O Stream type is	cast to a bool , what do the true and false results mean? [3 marks]
Q29) True/False: The ISO C++ sta Standard Library. [1 mark]	andards dictate complexity requirements for nearly everything in the C++
(a) True (b) False	

STUDENT NAME: Copyright © 2016 Paul Preney. All Rights Reserved. No part of thi	STUDENT I.D. #s document may be duplicated without permission.
Part II: General Questions (28 Marks) Answer all parts of each question in the space provided below each question is indicated at the end of each question. You sentences and proper grammar. If the answer is program code question unless you are explicitly asked to write a full-and-order to the control of t	v each question. The number of marks assigned to are expected to answer questions using complete, simply write the code fragment that answers the
Q30) Write the code fragment to declare a variable called valu std::string instances. [2 marks]	es whose type is a std::vector containing
std::string instances. [2 marks]	
Q31) Write the code fragment to read in all std::string words:	from etdin (ucing a cingle while loop) into the
variable values whose declaration you wrote in Q30. (An EOF of the words to be read in.) Remember to declare your std::str	or any occurrence of an error constitutes the end
of the words to be read in.) remember to declare your stansar	ing variable. [4 marks]
Q32) Use the C++ range-based for-loop to output all words in std::cout . [3 marks]	the values variable (from Q30 and Q31) to

STUDENT NAME:	STUDENT I.D. #

Copyright © 2016 Paul Preney. All Rights Reserved. No part of this document may be duplicated without permission.

Q33) Call **<algorithm>'s std::for_each** function passing the arguments required to output all words in the **values** variable (from Q30 and Q31) to **std::cout** within a <u>single</u> C++ statement. Recall the prototype for for_each is:

template <typename Iter, typename UnaryPredicate>
UnaryPredicate for_each(Iter first, Iter last, UnaryPredicate pred);

[4 marks]

STUDENT NAME: STUDENT I.D. #

Copyright © 2016 Paul Preney. All Rights Reserved. No part of this document may be duplicated without permission.

Q34) Given the **values** variable (from Q30 and Q31) write the complete code fragment that performs the following:

- Starting at the beginning of **values**, search for the word "**the**" using **<algorithm>'s std::find**. Store the result in a variable called "**the_pos**".
 - NOTE: This must be done using a single C++ statement.
- Starting at "**the_pos**", search for the first word whose string length (i.e., string_var.size()) is greater than 10 using algorithms's **std::find if.** Store the result in a variable called "**big_pos**".
 - NOTE: This must be done using a single C++ statement.
- As you did in Assignment 1, declare a **std::map** capable of representing a frequency histogram of words. Call this variable "**hist**".
 - NOTE: This must be done using a single C++ statement.
- Using <algorithm>'s std::for_each, add everything in the range [the_pos, big_pos) to the histogram hist variable.
 - NOTE: This must be done using a single C++ statement.
 - Hint 1: Recall how the histogram was constructed in Assignment 1 which included using [].
 - Hint 2: Use a lambda function to add the data to the histogram.
 - Hint 3: Remember to capture something!

The prototypes for **std::find**, **std::find_if** are as follows:

```
template <typename Iter, typename T>
Iter find(Iter first, Iter last, T const& value);
template <typename Iter, typename UnaryPredicate>
Iter find_if(Iter first, Iter last, UnaryPredicate pred);
```

[15 marks]

Copyright © 2016 Paul Preney. All Rights Reserved. No part of this document may be duplicated without permission.

This page was intentionally left blank. You may write answers on it.

Copyright © 2016 Paul Preney. All Rights Reserved. No part of this document may be duplicated without permission.

This page was intentionally left blank. You may write answers on it.