



LOCKOUT-TAGOUT PROCEDURE

Developed By:

Cardinal Compliance Consultants
5353 Secor Rd.
Toledo, OH 43623
P: 419-882-9224

Description:

Procedure #:

Facility:

Location:

Rev:

Date:

Origin:

Machine to be Locked Out









**Isolation Points to be
Locked and Tagged**

Notes:

SHUTDOWN SEQUENCE

1. Notify affected personnel. 2. Properly shut down machine. 3. Isolate all energy sources. 4. Apply LOTO devices. 5. Verify total de-energization of all sources.

Energy Source	Device	Isolation Point	Isolation Method	Verification Method	Verification Device
Electric 240 V	Lower component to full down position Tag: #1234 Description Description Description		Isolation Method	Verification Method	
Chemical Boron 1500 PSI	Lower component to full down position Tag: #1234 Description Description Description		Isolation Method	Verification Method	
_____	_____ Tag: #_____ _____		_____	_____	



LOCKOUT-TAGOUT PROCEDURE

Developed By:

Cardinal Compliance Consultants
5353 Secor Rd.
Toledo, OH 43623
P: 419-882-9224

Description:

Procedure #:

Facility:

Location:

Rev:

Date:

Origin:

RESTART SEQUENCE

1. Ensure all tools and items have been removed. 2. Confirm that all employees are safely located. 3. Verify that controls are in neutral. 4. Remove LOTO devices and re-energize machine. 5. Notify affected employees that servicing is complete. 1. Ensure all tools and items have been removed. 2. Confirm that all employees are safely located. 3. Verify that controls are in neutral. 4. Remove LOTO devices and re-energize machine. 5. Notify affected employees that servicing is complete.