Assignment 2: MaRTy and the Many Grades of Shade

Load packages

Import Data

Step 1: Air Temperature vs. MRT

Start by exploring the difference between air temperature and MRT. Choose several observations from the dataset and compare AirT_C_detrended and MRT_C_detrended.

• Are air temperature and MRT usually similar?


• When are the differences largest?

• Why can two locations with similar air temperatures have very different MRT?

Use examples from the dataset in your explanation.

Differences

```
hist_diff <- hist(marty$diff, right = FALSE, col = "firebrick", las = 1)
```



The histogram shows us that broadly, air temperature and MRT are fairly similar. The largest columns are all clustered around 0, meaning there are a lot of results with only a small difference between the two variables. However, there is also a small but noticeable cluster of results with a larger difference (around 20-40), showing that there are plenty of exceptions where the two values diverge.

Linear Regression

To answer the question of why two locations with similar air temperatures can have different MRT, a multiple linear regression model was created to measure the influence of different variables on the difference between air temperature and MRT. The independent variables selected for this model were Time_of_Day, Surface_Type, Shade_Category2, RH, and WindSpeed_ms because they are each representative of a unique measurement, avoiding the problem of multicollinearity.

```
# dependent variable: diff
# independent variables: Time_of_Day, Surface_Type, Shade_Category2, RH, WindSpeed_ms

# build model
reg_diff <- lm(diff ~ Time_of_Day + Surface_Type + Shade_Category2 + RH + WindSpeed_ms, data

summary(reg_diff)
```

```
Call:
lm(formula = diff ~ Time_of_Day + Surface_Type + Shade_Category2 +
    RH + WindSpeed_ms, data = marty)

Residuals:
    Min      1Q  Median      3Q     Max
-15.492  -3.955   1.092   4.894  13.915

Coefficients:
                                Estimate Std. Error t value Pr(>|t|)
(Intercept)                      1.70161    2.76766   0.615   0.5398
Time_of_Day3:30 PM               0.07057    1.55420   0.045   0.9639
Time_of_Day8:30 PM             -15.06639    1.52085  -9.907  < 2e-16 ***
Surface_Typegravel               2.75927    2.23682   1.234   0.2198
Surface_Typeimpervious           2.88574    1.80529   1.598   0.1126
Shade_Category2Engineered shade  4.88870    1.95633   2.499   0.0138 *
Shade_Category2Sun-exposed      15.38850    1.76921   8.698 2.22e-14 ***
Shade_Category2Tree shade        2.05451    1.91307   1.074   0.2850
RH                               0.05832    0.08882   0.657   0.5127
WindSpeed_ms                     1.07224    0.87521   1.225   0.2229
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 6.531 on 119 degrees of freedom
Multiple R-squared:  0.7022,    Adjusted R-squared:  0.6797
F-statistic: 31.18 on 9 and 119 DF,  p-value: < 2.2e-16
```

The two most influential variables were 'Time_of_Day8:30 PM' and 'Shade_Category2Sun-exposed'. They both have p-values of the highest significance rating (confidence interval of 100%) and the highest coefficients in the model. 'Time_of_Day8:30 PM' has a coefficient of -15.46, meaning it causes the difference between air temperature and MRT to go in a negative direction, while 'Shade_Category2Sun-exposed' has a coefficient of 15.46, causing the difference to increase. The variable 'Shade_Category2Engineered shade' also had a statistically significant influence, with a coefficient of 4.99 and a confidence interval of 99%, meaning it has a moderate effect of increasing the difference between air temperature and MRT. Overall, this model has an adjusted R-squared of 0.68, meaning it explains about 68% of variation in the difference between air temperature and MRT.

```
vif_reg_diff <- car::vif(reg_diff)
kable(vif_reg_diff)
```

	GVIF	Df	GVIF^(1/(2*Df))
Time_of_Day	1.682624	2	1.138929
Surface_Type	1.527595	2	1.111737
Shade_Category2	1.705605	3	1.093066
RH	1.620202	1	1.272872
WindSpeed_ms	1.194580	1	1.092968

The VIF analysis shows that none of the variables have a VIF of greater than 2.0, much lower than the typical threshold of 5.0, confirming that multicollinearity is not an issue with this model.

```
anova_reg_diff <- anova(reg_diff)
kable(anova_reg_diff)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
Time_of_Day	2	6687.40942	3343.70471	78.4013320	0.0000000
Surface_Type	2	254.17746	127.08873	2.9799061	0.0546019
Shade_Category2	3	4941.17763	1647.05921	38.6193301	0.0000000
RH	1	21.54406	21.54406	0.5051531	0.4786353
WindSpeed_ms	1	64.01199	64.01199	1.5009177	0.2229496
Residuals	119	5075.17985	42.64857	NA	NA


This ANOVA analysis confirms that there is a large variance in the Time_of_Day and Shade_Category2 categorical variables, as shown by their high F values and low p-values. Surface_Type also shows up as the next most impactful category, but with a much smaller F value and a confidence interval of around 94.5%, just under the usual threshold for statistical significance.

Step 2: How Much Does Shade Matter?

Compare MRT across the three main shade categories: Sun-exposed, Tree shade, and Engineered/Built shade.

Create one figure that clearly communicates the comparison. Choose a visualization that helps answer the question and briefly explain what the figure shows. Your figure might illustrate average MRT by shade category, individual observations, MRT at different times of day, or another useful comparison.

```r
bars_MRT <- ggplot(marty, aes(Shade_Category2, MRT_C_detrended, fill = Shade_Category2)) +
    geom_bar(position='dodge', stat='summary', fun='mean', width = 0.7) +
    scale_fill_manual(values = c(
        "Built shade" = "firebrick",
        "Engineered shade" = "steelblue",
        "Sun-exposed" = "goldenrod",
        "Tree shade" = "forestgreen"
    )) +
    labs(
        title = "Mean MRT by Shade Category",
        x = "Shade Category",
        y = "Mean MRT"
    ) +
    scale_y_continuous(breaks = seq(0, 60, by = 10))
bars_MRT + theme_classic()
```



This bar chart shows how average MRT compares across each shade category. From this, we can see that built shade has the lowest average MRT, followed closely by tree shade, with engineered shade having the highest average MRT among types of shade, but still much lower than the average MRT in sun-exposed areas.

Step 3: Does Time of Day Matter?

Compare the three measurement times, considering sun-exposed and shaded locations.


• When are the largest differences between sun and shade?

• What happens by 8:30 PM?

• Why might shade have a very different effect during the day than after sunset?


Include either a second figure or a small summary table.

```
line_TOD <- ggplot(tod_summary, aes(x = time, y = MRT_mean, color = shade, group = shade)) +
    geom_line(linewidth = 1.2) +
    geom_point(size = 3) +
    scale_color_manual(
        name = "Shade Type",
        values = c("goldenrod", "steelblue")) +
    labs(
        title = "Average MRT over Time",
        x = "Time (24-hour)",
        y = "Average MRT"
    )
line_TOD + theme_classic()
```



This line chart shows the difference in the average MRT of shaded versus exposed areas over time - measurements were taken at 12:30 PM (1230), 3:30 PM (1530), and 8:30 PM (2030). From this graphic, we can see that between 12:30 and 3:30, the MRT of sun-exposed areas sharply rises while in shaded areas it stays flat. However, by 8:30, we see that the average temperature of sun-exposed areas actually falls below that of shaded areas. Naturally, shade has a much greater impact on MRT during the day when it can block the sun's radiation than at night when all areas are 'shaded'. However, this alone does not explain why shaded areas would have a higher MRT than exposed areas at night.

```
line_shade <- ggplot(shade_summary, aes(x = time, y = MRT_mean, color = Shade_Category2, grou
    geom_line(linewidth = 1.2) +
    geom_point(size = 3) +
    scale_color_manual(
        name = "Shade Type",
        values = c("goldenrod", "steelblue", "firebrick", "forestgreen")) +
    labs(
        title = "Average MRT over Time",
        x = "Time (24-hour)",
        y = "Average MRT"
    )
line_shade + theme_classic()
```



Differences in shade category do not account for this unexpected result, as all types of shade individually have a higher average MRT than sun-exposed locations, so this was not the result of say, built and engineered shade being higher outweighing tree shade being lower. [cut section?]

Step 4: Become a Radiation Detective

Choose two locations with noticeably different MRT values, for example:

• sun vs. tree shade;

• sun vs. engineered shade;

• tree shade vs. engineered shade; or

• two different kinds of shade.

Use the available site information to explain why their MRT values differ. Consider direct sunlight, type of shade, surrounding surfaces and materials, vegetation, time of day, air temperature, wind speed, and/or other characteristics you think matter. You do not need to use every variable. Focus on the factors that provide the best explanation.

```
examples <- marty[c(72, 13), ]
examples <- subset(examples, select = -c(Shade_Category2, Shade_Type_No, Surface_Cover_No, ti
kable(examples)
```

Location_ID	Shade_Category	Surface_Cover	Surface_Type	Time_of_Day	RH	Wind-Speed_ms	AirT_C_detrended	MRT_C_detrended	diff
3150	Tree shade	gravel	gravel	8:30 PM	7.93	0.40	37.61	35.08	-2.53
3750	Sun-exposed	concrete rough	impervious	12:30 PM	10.79	0.45	35.30	59.94	24.64

These two sites have very similar air temperatures (37.61C and 35.30C) and very different MRTs (35.08C and 59.94C). One is a tree-shaded gravel site from 8:30PM, and the other is a sun-exposed concrete site at 12:30PM. They both have fairly low relative humidity (7.93 and 10.79) and similar wind speeds (0.40 and 0.45). Gravel and concrete are both impervious surfaces, so the biggest differences between the sites are shade type and time of day. This is consistent with the regression model built earlier which found 'Time_of_Day8:30 PM' and 'Shade_Category2Sun-exposed' to be the most influential variables in determining the difference between air temperature and MRT.

Step 5: What Does This Mean for Urban Design?

Imagine that a city has limited resources to improve pedestrian thermal environments. Based on your analysis, write a short recommendation answering: What should planners or designers consider when providing shade for pedestrians? Do not simply conclude that "shade is good." Use evidence from the dataset to discuss whether the type, timing, and surrounding environment of shade matter.

Based on this data from MaRTy, it is evident that the biggest factor planners and designers have control over in improving thermal comfort for pedestrians is simply the presence of shade. This is demonstrated by the significance of sun exposure in the regression analysis as well as the site comparison which exemplified how the presence of shade can make a big difference regardless of surrounding environmental factors such as surface type, humidity, or wind speed. The best strategy for increasing shade will be different for different cities. For example, a desert city like Phoenix may have relatively high barriers to implementing a tree canopy-based shade plan due to water scarcity and extreme heat damaging growing trees, while a rural town in Vermont may find planting trees to be a more cost-efficient strategy than building engineered shade structures. While city-specific factors like this will play a dominant role in guiding urban design choices for increasing shade, the MaRTy data does tell us that shade from built structures has the lowest MRT of all shade types. This is great news for cities because built structures deliver numerous other benefits besides shade - they are housing, businesses, transportation infrastructure - all things that are desirable to have. However, buildings are not typically designed in a way that deliberately maximizes shade for pedestrians. This is where more intentional work by planners and designers is required. Planners should update zoning codes with features like increasing densities in residential areas and decreasing minimum setback requirements so that buildings become taller and closer to the sidewalk, producing more shade for pedestrians. These changes would also work to solve other problems such as improving housing affordability and decreasing environmentally harmful sprawling development patterns. Designers should take into account more nuanced details when designing spaces for pedestrians such as decreasing impervious surfaces which retain and reflect more heat than natural surfaces, or ensuring that shade-providing structures do not block the cooling effects of wind. Even if these variables have a smaller impact statistically, all together they can add up to make a meaningful difference.

Your Submission

Submit a short report of approximately 700–1,000 words, plus your figures and/or tables. You do not need to write a formal scientific paper. Your report should contain:

1. Brief introduction

a. What question are you investigating, and what did you expect to find?

2. Methods

a. Briefly describe the provided dataset and state what tool or tools you used for the analysis. If you used AI, identify the AI tool.

3. Results

a. Include your air temperature vs. MRT comparison, at least two clear figures or tables, and your comparison among shade categories and times of day.

4. Radiation Detective

a. Explain the difference between two contrasting locations using evidence from the dataset.

5. Discussion and Urban Design Recommendation

a. What do the measurements tell us about shade and pedestrian heat exposure? What should urban designers take away from your analysis?