

ECEN 4638: Lab X

Rane Brown
Kate Schneider

January 14, 2016

Purpose

Lab X is designed to review the basics of feedback control. This will be accomplished through a series of procedures that analyze a cruise control system. The end goal of this project is to gain enough knowledge and background information to create a feasible control solution for use with the torsion disk system.

Background

Feedback is important in nature and technology. Without feedback life as we know it would not exist and the technological marvels that exist today would not be possible. There are numerous examples of existing feedback systems but a few of the most important are listed below.

E1

1. Airplane: The autopilot can be set to maintain a level orientation at a given altitude. Disturbances in the air may cause the wings to dip and this movement is read by a gyroscope. The information from the gyroscope is read by the control system and adjustments are made to the ailerons to bring the plane back to a level orientation.
2. Thermostat: The user can select a desired temperature and the thermostat will compare this value to the measured temperature. If hot air from outside the house raises the temperature above the set value the ac will be activated.
3. Climate change: Greenhouse gases increase the Earth's temperature and this rise in temperature increases water vapor in the air. The increase in water vapor further increases the Earth's temperature. In addition, there is ice albedo feedback where the reduction of ice due to melting reduces the amount of reflected radiation and therefore the surface temperature rises which leads to further ice melting.
4. Metabolism: The metabolism of an animal is adjusted depending on food intake. As the food intake decreases the metabolism slows and vice versa.

Procedure

A simple example of a feedback system that has wide spread real world application is cruise control. The most common example of this appears in vehicles. The driver can set the desired speed and the feedback system will maintain that speed in the presence of disturbances such as wind and hills.

As seen in Figure 1 there are two input signals to the cruise control feedback system: the reference $R(s)$ and the disturbance $D(s)$. There is one output signal $Y(s)$ for this system but there are many other points of interest as labeled in Figure 1. With these signals many useful transfer functions can be derived that will help in the selection of an appropriate controller $C(s)$. The selection for $C(s)$ is dependent on many factors including desired rise time, settle time, overshoot, and steady state error.




Figure 1: Cruise Control Feedback System

Signal or Transfer Function	Description
$Y(s) = V(s)$	vehicle velocity
$R(s)$	reference velocity
$E(s) = R(s) - Y(s)$	velocity error
$U(s)$	controller output
$A(s)$	vehicle acceleration
$D(s)$	disturbance acceleration
$P(s) = \frac{k}{s+b}$	plant transfer function
$C(s)$	controller transfer function
$H_{yr}(s) = \frac{Y(s)}{R(s)}$	closed loop transfer function from $R(s)$ to $Y(s)$
$H_{yd}(s) = \frac{Y(s)}{D(s)}$	closed loop transfer function from $D(s)$ to $Y(s)$
$H_{ur}(s) = \frac{U(s)}{R(s)}$	closed loop transfer function from $R(s)$ to $U(s)$
$H_{ud}(s) = \frac{U(s)}{D(s)}$	closed-loop transfer function from $D(s)$ to $U(s)$

Table 1: Signals and Transfer Functions

Table 1 provides definitions for the signals and transfer functions that will be used for the remainder of Lab X. Common notation will be to exclude the (s) when writing equations i.e. $R(s)$ will be represented as R .

E2

E3

E4

E5

E6

E7

E8

E9

E10

E11

E12

E13

E14

E15

E16

E17