



Industrie Service

EU-TYPE EXAMINATION CERTIFICATE

According to Annex IV, Part A of 2014/33/EU Directive

Certificate No.: EU-UCM 1035

Notified Body: TÜV SÜD Industrie Service GmbH
Westendstr. 199
80686 Munich - Germany
Identification No. 0036

Certificate Holder: Blain Hydraulics GmbH
Pfaffenstr. 1
74078 Heilbronn - Germany

Manufacturer of the Test Sample: Blain Hydraulics GmbH
Pfaffenstr. 1
74078 Heilbronn - Germany

Product: Hydraulic valve for a brake element as part of a protection against unintended downward car movement

Type: iL10-S

Directive: 2014/33/EU

Reference Standards: EN 81-20:2020
EN 81-50:2020

Test Report: EU-UCM 1035-1036 of 2024-09-25

Outcome: The product conforms to the essential health and safety requirements of the mentioned Directive if the requirements of the annex to this EU-type examination certificate are kept.

Date of Issue: 2024-10-12


Achim Janocha
Notified Body LCC



Annex to the EU-type examination certificate
No. EU-UCM 1035 of 2024-10-12



1 Scope of application

Hydraulic valve for a brake element as part of a protection against unintended downward car movement, type iL10-S

1.1 Scope of application for UCM-valve, type iL10-S:

UCM-valve, type iL10-S, size $\frac{3}{4}$ "

Maximum braking distance after triggering up to	800	mm
Maximum permissible distance: level position - triggering up to	200	mm
Permissible nominal speed up to	1.00	m/s
Permissible release speed up to	1.30	m/s
Permissible nominal flow	≤ 125	l/min
Nominal pressure range	10 - 95	bar
Viscosity range	20 - 300	cSt

UCM-valve, type iL10-S, size 1", 1 $\frac{1}{2}$ " and 2"

Maximum braking distance after triggering up to	800	mm
Maximum permissible distance: level position - triggering up to	200	mm
Permissible nominal speed up to	1.00	m/s
Permissible release speed up to	1.30	m/s
Permissible nominal flow	≤ 800	l/min
Nominal pressure range	8 - 75	bar
Viscosity range	20 - 300	cSt

UCM-valve, type iL10-S, size 2 $\frac{1}{2}$ "

Maximum braking distance after triggering up to	800	mm
Maximum permissible distance: level position - triggering up to	200	mm
Permissible nominal speed up to	1.00	m/s
Permissible release speed up to	1.30	m/s
Permissible nominal flow	≤ 1530	l/min
Nominal pressure range	8 - 75	bar
Viscosity range	20 - 300	cSt

**Annex to the EU-type examination certificate
No. EU-UCM 1035 of 2024-10-12**

2 Terms and Conditions

- 2.1 For identification and information about the principal design and operation and for demarcation of the examined and approved sample the corresponding approval drawing
- No. iL10-S-0.75a dated 2024-03-22
 - No. iL10-S-1.5-2a dated 2024-05-15
 - No. iL10-S-2.5a dated 2024-05-15
- each with certification stamp of 2024-09-25 has to be enclosed to the EU-type examination certificate and its annex.
- 2.2 The above-mentioned safety component represents only one part of the protective equipment against movements of the car in downward direction. Only in combination with a detection and triggering component (also two different components are possible), which must be subjected to an own EU-type examination according to the test procedure specified in EN 81-50:2020, section 5.8, the created system can fulfil the requirements for a protection means in accordance with EN 81-20:2020, section 5.6.7.
- 2.3 The installer must prepare test instructions in order to meet the overall concept of the elevator system, enclose these test instructions in the elevator documents and if necessary provide important tools or measuring devices which allow easy tests (e.g., when landing doors are closed).
- 2.4 Provided that the voltage drop on the coil has occurred within the distance of 200 mm as indicated in the scope of application it can be assumed that the requirements for braking distance and acceleration according to EN 81-20:2020, point 5.6.7.5 and 5.6.7.6 are met.
- 2.5 The Blain UCM-valve is an electrically operated check valve which can only be used in connection with a Blain control valve as an additional safety valve for the prevention of unintended downward travel while a landing door is open according to EN 81-20:2020, section 5.6.7. The detection of emergency cases, the function of the brake in an upwards direction and the triggering of both brakes is the task of the control unit.
- 2.6 In order for it to function properly, the coil of the Blain UCM valve must be de-energized in accordance with the requirements of EN 81-20:2020, Section 5.6.6.5 at the latest when the car has moved a maximum of 200 mm from the flush position with the door open. Dead times of the electronic system must be considered.
- 2.7 The control valve must be adjusted in accordance with the operating instructions - iL10-S-L_EN (sheets 1-4) of 09/2024 with certification stamp of 2024-09-25.
- 2.8 The installer must be provided with written confirmation of the compliance of the component with the type tested part as well as of the guaranteed braking distances and accelerations.
- 2.9 The EU-type examination certificate may only be used in combination with the corresponding annex and enclosure (List of authorized manufacturer of the serial production). The enclosure will be updated immediately after any change by the certification holder.

3 Remarks

- 3.1 This EU-type examination certificate was issued according to the following standards:
- EN 81-20:2020 (D), part 5.6.7
 - EN 81-50:2020 (D), part 5.8
- A revision of this EU-type examination certificate is inevitable in case of changes or additions of the above-mentioned standards or of changes of state of the art.
- 3.2 In case that there is a risk of unintended car movement in the upward direction, appropriate measures must be taken by the installer.
- 3.3 The Certification Body LCC of the TÜV SÜD Industrie Service GmbH is a Certification Body accredited by DAkkS according to DIN EN ISO 17065. The accreditation is only valid for the scope of accreditation listed in the Annex of the certificate D-ZE-14153-03-00.