



PHP

FLOW CONTROL / FUNCTIONS **2025**

Silvio Priem Mendes, PhD

PHP Flow Control

- Flow Control in PHP
- Functions
- SuperGlobal vectors
- Include/Require Files

PHP Flow Control

- PHP Conditional Statements (if)

```
if (condition) {  
    code to be executed if condition is true;  
}
```

```
<?php  
    $t = date("H");  
  
    if ($t < "20") {  
        echo 'Have a good day!';  
    }  
?>
```

PHP Flow Control

- PHP Conditional Statements (if-else)

```
if (condition) {  
    code to be executed if condition is true;  
} else {  
    code to be executed if condition is false;  
}
```

```
<?php  
    $t = date("H");  
  
    if ($t < "20") {  
        echo 'Have a good day!';  
    } else {  
        echo 'Have a good night!';  
    }  
?>
```

PHP Flow Control

- PHP Conditional Statements (if-elseif-if)

```
if (condition) {  
    code to be executed if this condition is true;  
} elseif (condition) {  
    code to be executed if this condition is true;  
} else {  
    code to be executed if all conditions are false;  
}
```

```
<?php  
    $t = date("H");  
  
    if ($t < "10") {  
        echo 'Have a good morning!';  
    } elseif ($t < "20") {  
        echo 'Have a good day!';  
    } else {  
        echo 'Have a good night!';  
    }  
?>
```

PHP Flow Control

- PHP switch Statement

```
switch (n) {  
    case label1:  
        code to be executed if n=label1;  
        break;  
    case label2:  
        code to be executed if n=label2;  
        break;  
    case label3:  
        code to be executed if n=label3;  
        break;  
    ...  
    default:  
        code to be executed if n is different from all  
labels;  
}
```

PHP Flow Control

- PHP switch Statement

```
<?php
    $favcolor = "red";

    switch ($favcolor) {
        case 'red':
            echo 'Your favorite color is red!';
            break;
        case 'blue':
            echo 'Your favorite color is blue!';
            break;
        case 'green':
            echo 'Your favorite color is green!';
            break;
        default:
            echo 'Your favorite color is neither red, blue, nor green!';
    }
?>
```

PHP Flow Control

- PHP Loops (while)

```
while (condition is true) {  
    code to be executed;  
}
```

```
<?php  
    $x = 1;  
  
    while($x <= 5) {  
        echo 'The number is: ' . $x . '<br>';  
        $x++;  
    }  
?>
```


PHP Flow Control

- PHP Loops (do-while)

```
do {  
    code to be executed;  
} while (condition is true);
```

```
<?php  
    $x = 1;  
  
    do {  
        echo 'The number is: ' . $x . '<br>';  
        $x++;  
    } while ($x <= 5);  
?>
```

PHP Flow Control

- PHP Loops (for)

```
for (init counter; test counter; increment counter) {  
    code to be executed;  
}
```

```
<?php  
    for ($x = 0; $x <= 10; $x++) {  
        echo 'The number is: ' . $x . '<br>';  
    }  
?>
```

PHP Flow Control

- PHP Loops (foreach)

```
foreach ($array as $value) {  
    code to be executed;  
}
```

```
<?php  
$colors = array('red', 'green', 'blue', 'yellow');  
  
foreach ($colors as $value) {  
    echo $value . '<br>';  
}  
?>
```

```
<?php  
$age = array('Peter'=>'35', 'Ben'=>'37', 'Joe'=>'43');  
  
foreach($age as $x => $x_value) {  
    echo 'Key=' . $x . ', Value=' . $x_value;  
    echo '<br>';  
}  
?>
```

PHP Structural

- PHP Functions

```
function functionName(params) {  
    code to be executed;  
}
```

```
<?php  
    function writeMsg() {  
        echo 'Hello world!';  
    }  
  
    writeMsg(); // call the function  
?>
```

PHP Structural

- PHP Function Arguments

```
<?php

function familyName($fname) {
    echo "$fname Refsnes.<br>";
}

familyName("Jani");
familyName("Hege");
familyName("Stale");
familyName("Kai Jim");
familyName("Borge");

?>
```

PHP Structural

- PHP Default Argument Value

```
<?php

function setHeight($minheight = 50) {
    echo "The height is : $minheight <br>";
}

setHeight(350);
setHeight(); // will use the default value of 50
setHeight(135);
setHeight(80);
?>
```

PHP Structural

• PHP Superglobals

- `$GLOBALS`
- `$_SERVER`
- `$_REQUEST`
- `$_POST`
- `$_GET`
- `$_FILES`
- `$_ENV`
- `$_COOKIE`
- `$_SESSION`

PHP Structural

- PHP Superglobals `$_SERVER`

```
<?php
    echo $_SERVER['SERVER_NAME'];
    echo '<br>';
    echo $_SERVER['HTTP_HOST'];
    echo '<br>';
    echo $_SERVER['HTTP_REFERER'];
    echo '<br>';
    echo $_SERVER['HTTP_USER_AGENT'];
    echo '<br>';
    echo $_SERVER['SCRIPT_NAME'];
?>
```


PHP Structural

- PHP Superglobals \$_GET

```
<html>
  <body>

    <a href="test_get.php?subject=PHP">Test $GET</a>

  </body>
</html>
```

```
<html>
  <body>

    <?php
      echo 'Study ' . $_GET['subject'];
    ?>

  </body>
</html>
```

PHP Structural

- PHP Superglobals \$_POST

```
<html>
  <body>

    <form method="post" action="<?php echo $_SERVER['PHP_SELF'];?>">
      Name: <input type="text" name="fname">
      <input type="submit">
    </form>

    <?php
      if ($_SERVER["REQUEST_METHOD"] == "POST") {
        // collect value of input field
        $name = $_POST['fname'];
        if (empty($name)) {
          echo "Name is empty";
        } else {
          echo $name;
        }
      }
    ?>

  </body>
</html>
```

PHP Structural

- PHP Include Files

```
<?php
    //FILENAME: footer.php

    echo "<p>Copyright &copy; 1999-" . date("Y") . " ESTG</p>";
?>
```

```
<html>
  <body>

    <h1>Welcome to my home page!</h1>
    <p>Some text.</p>
    <p>Some more text.</p>
    <?php include_once 'footer.php';?>

  </body>
</html>
```

PHP Structural

- PHP Require Files

```
<?php
    //FILENAME: menu.php
    echo '<a href="/default.asp">Home</a> -
    <a href="/html/default.asp">HTML Tutorial</a> -
    <a href="/css/default.asp">CSS Tutorial</a> -
    <a href="/js/default.asp">JavaScript Tutorial</a> -
    <a href="default.asp">PHP Tutorial</a>';
?>

<html>
    <body>

        <div class="menu">
            <?php require_once 'menu.php';?>
        </div>

        <h1>Welcome to my home page!</h1>
        <p>Some text.</p>
        <p>Some more text.</p>

    </body>
</html>
```

PHP Structural

- PHP Require Files

require: if the file cannot be included, it will generate a fatal error, halting the script execution.

require_once is similar to **require** but with an additional check to ensure that the file is not included more than once. If the file has already been included elsewhere in the script, **require_once** will not include it again. Like **require**, if the file cannot be included, it generates a fatal error and halts script execution.

PHP Structural

- **PHP Include Files**

include: is used to include a file in PHP. If the file cannot be included (e.g., if the file is missing or there's an error in the file), it will generate a warning. However, the script will continue to execute despite the warning.

include_once include_once is similar to include but with an additional check to ensure that the file is not included more than once. If the file has already been included elsewhere in the script, include_once will not include it again. Like include, if the file cannot be included, it generates a warning, but script execution continues.



BIBLIOGRAPHY