VARIA CONNECT · RISK ASSESSMENT

HIRARC — Hazard Identification, Risk Assessment and Risk Control

Pengenalpastian Hazard, Penaksiran Risiko dan Kawalan Risiko

Form **RA-HIRARC**
Company logo

When to use: Formal risk assessment for each work activity, following the DOSH Guidelines for HIRARC (2008). Score risk = Likelihood × Severity using the matrix.
Validity / frequency: Review when the method changes, after an incident, or at least yearly

ASSESSMENT DETAILS

Project / site	
Activity / process	
Location	
Assessment no.	
Date	
Assessed by	
Review date	

RISK MATRIX

Likelihood ↓ / Severity →	1 Negligible	2 Minor	3 Serious	4 Fatal	5 Catastrophic
5 Most likely	5	10	15	20	25
4 Possible	4	8	12	16	20
3 Conceivable	3	6	9	12	15
2 Remote	2	4	6	8	10
1 Inconceivable	1	2	3	4	5

Risk = Likelihood × Severity. 15–25 HIGH: stop, act immediately. 5–12 MEDIUM: plan controls, then proceed with care. 1–4 LOW: acceptable, keep monitoring.

HAZARD REGISTER

No.	Work step	Hazard	Effect / who is harmed	Existing controls	L	S	Risk (L×S)	Additional controls	Residual risk	PIC & due date

No.	Work step	Hazard	Effect / who is harmed	Existing controls	L	S	Risk (L×S)	Additional controls	Residual risk	PIC & due date

HIERARCHY OF CONTROLS

Apply controls in this order: 1. Eliminate the hazard. 2. Substitute with something less hazardous. 3. Engineering controls (guards, guardrails, ventilation). 4. Administrative controls (permits, procedures, training, signage). 5. PPE as the last line of defence.

APPROVAL

Role	Name	Signature	Date & time
Prepared by (supervisor / engineer)			
Reviewed by (SHO)			
Approved by (project manager)			

Keep the original at the site office for the duration of the project. Display permits at the work area while work is in progress.