```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn import linear_model
from sklearn.tree import DecisionTreeClassifier
df= pd.read_csv('adult.csv')
```

```
df= pd.read_csv('adult.csv')
df.head()
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	rela
0	90	?	77053	HS-grad	9	Widowed	?	No
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	No
2	66	?	186061	Some-college	10	Widowed	?	
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	
4	41	Private	264663	Some-college	10	Separated	Prof-specialty	

```
df.shape
```

```
(32561, 15)
```

```
df.describe()
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.p
count	32561.000000	3.256100e+04	32561.000000	32561.000000	32561.000000	32561
mean	38.581647	1.897784e+05	10.080679	1077.648844	87.303830	40
std	13.640433	1.055500e+05	2.572720	7385.292085	402.960219	12
min	17.000000	1.228500e+04	1.000000	0.000000	0.000000	1
25%	28.000000	1.178270e+05	9.000000	0.000000	0.000000	40
50%	37.000000	1.783560e+05	10.000000	0.000000	0.000000	40
75%	48.000000	2.370510e+05	12.000000	0.000000	0.000000	45
max	90.000000	1.484705e+06	16.000000	99999.000000	4356.000000	99

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 32561 entries, 0 to 32560
Data columns (total 15 columns):
 #   Column          Non-Null Count  Dtype 
---  ------          --------------  ----- 
 0   age             32561 non-null  int64 
 1   workclass       32561 non-null  object
 2   fnlwgt          32561 non-null  int64 
 3   education       32561 non-null  object
 4   education.num   32561 non-null  int64 
 5   marital.status  32561 non-null  object
 6   occupation      32561 non-null  object
 7   relationship    32561 non-null  object
 8   race            32561 non-null  object
 9   sex             32561 non-null  object
 10  capital.gain    32561 non-null  int64 
 11  capital.loss    32561 non-null  int64 
 12  hours.per.week  32561 non-null  int64 
 13  native.country  32561 non-null  object
 14  income          32561 non-null  object
dtypes: int64(6), object(9)
memory usage: 3.7+ MB
```

```
df['income'].value_counts()
```

```
<=50K    24720
>50K      7841
Name: income, dtype: int64
```

```
df['sex'].value_counts()
```

```
Male      21790
Female    10771
Name: sex, dtype: int64
```

```
df['native.country'].value_counts()
```

```
United-States                 29170
Mexico                          643
?                               583
Philippines                     198
Germany                         137
Canada                          121
Puerto-Rico                     114
El-Salvador                     106
India                           100
Cuba                             95
England                          90
Jamaica                          81
South                            80
China                            75
Italy                            73
Dominican-Republic               70
Vietnam                          67
Guatemala                        64
Japan                            62
Poland                           60
Columbia                         59
Taiwan                           51
Haiti                            44
Iran                             43
Portugal                         37
Nicaragua                        34
Peru                             31
Greece                           29
France                           29
Ecuador                          28
Ireland                          24
Hong                             20
Cambodia                         19
Trinadad&Tobago                  19
Laos                             18
Thailand                         18
Yugoslavia                       16
Outlying-US(Guam-USVI-etc)       14
Hungary                          13
Honduras                         13
Scotland                         12
Holand-Netherlands                1
Name: native.country, dtype: int64
```

```
df['workclass'].value_counts()
```

```
Private             22696
Self-emp-not-inc     2541
Local-gov            2093
?                    1836
State-gov            1298
Self-emp-inc         1116
Federal-gov           960
Without-pay            14
Never-worked            7
Name: workclass, dtype: int64
```

```
df['occupation'].value_counts()
```

```
Prof-specialty       4140
Craft-repair         4099
Exec-managerial      4066
Adm-clerical         3770
Sales                3650
Other-service        3295
Machine-op-inspct    2002
?                    1843
Transport-moving     1597
Handlers-cleaners    1370
Farming-fishing       994
Tech-support          928
Protective-serv       649
Priv-house-serv       149
Armed-Forces            9
Name: occupation, dtype: int64
```

```
df.replace('?', np.NaN,inplace = True)
df.head()
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	rela
0	90	NaN	77053	HS-grad	9	Widowed	NaN	No
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	No
2	66	NaN	186061	Some-college	10	Widowed	NaN	
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	
4	41	Private	264663	Some-college	10	Separated	Prof-specialty	

```
#fills missing values (NaNs) with the most recent non-missing value
df.fillna(method = 'ffill', inplace = True)
```

```
from sklearn.preprocessing import LabelEncoder

le = LabelEncoder()
df['workclass'] = le.fit_transform(df['workclass'])
df['education'] = le.fit_transform(df['education'])
df['marital.status'] = le.fit_transform(df['marital.status'])
df['occupation'] = le.fit_transform(df['occupation'])
df['relationship'] = le.fit_transform(df['relationship'])
df['race'] = le.fit_transform(df['race'])
df['sex'] = le.fit_transform(df['sex'])
df['native.country'] = le.fit_transform(df['native.country'])
df['income'] = le.fit_transform(df['income'])

df.head()
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	rela
0	90	8	77053	11	9	6	14	
1	82	3	132870	11	9	6	3	
2	66	3	186061	15	10	6	3	
3	54	3	140359	5	4	0	6	
4	41	3	264663	15	10	5	9	

```
df.describe()
```

	age	workclass	fnlwgt	education	education.num	marital.
count	32561.000000	32561.000000	3.256100e+04	32561.000000	32561.000000	32561.
mean	38.581647	3.102761	1.897784e+05	10.298210	10.080679	2
std	13.640433	1.136995	1.055500e+05	3.870264	2.572720	1.
min	17.000000	0.000000	1.228500e+04	0.000000	1.000000	0.
25%	28.000000	3.000000	1.178270e+05	9.000000	9.000000	2.
50%	37.000000	3.000000	1.783560e+05	11.000000	10.000000	2.
75%	48.000000	3.000000	2.370510e+05	12.000000	12.000000	4.
max	90.000000	8.000000	1.484705e+06	15.000000	16.000000	6.

```
#Splitting the data set into features and outcome
X = df.drop(['income'], axis=1)
Y = df['income']
```

```
df.isnull().sum()
```

```
age              0
workclass        0
fnlwgt           0
education        0
education.num    0
marital.status   0
```

```
occupation        0
relationship      0
race              0
sex               0
capital.gain      0
capital.loss      0
hours.per.week    0
native.country    0
income            0
dtype: int64
```

```
df.duplicated().sum()
```

```
24
```

```
df=df.dropna()
```

```
#Splitting the data into test data and training data

from sklearn.model_selection import train_test_split

X_train, X_test, Y_train, Y_test = train_test_split(X, Y, test_size = 0.2, random_state = 42)
```

```
X_train.head()
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation
5514	26	3	256263	11	9	4	2
19777	24	3	170277	11	9	4	7
10781	36	3	75826	9	13	0	0
32240	22	6	24395	15	10	2	0
9876	31	1	356689	9	13	2	9

```
Y_train = Y_train.replace((np.inf, -np.inf, np.nan), 0).reset_index(drop=True)
```

```
Y_train.head()
```

```
0    0
1    0
2    0
3    0
4    0
Name: income, dtype: int64
```

```
Y_test = Y_test.replace((np.inf, -np.inf, np.nan), 0).reset_index(drop=True)
```

```
from sklearn.tree import DecisionTreeClassifier
dec_tree = DecisionTreeClassifier(random_state=42)
dec_tree.fit(X_train, Y_train)
Y_pred_dec_tree = dec_tree.predict(X_test)
```

```
import matplotlib.pyplot as plt
from sklearn.tree import DecisionTreeClassifier, plot_tree
plot_tree(dec_tree)
plt.show()
```

```
from sklearn.metrics import accuracy_score
from sklearn.metrics import f1_score
from sklearn.metrics import precision_score
from sklearn.metrics import recall_score
```

```
print('Decision Tree Classifier:')
print('Accuracy score:',accuracy_score(Y_test, Y_pred_dec_tree) * 100)
print('Precision :',precision_score(Y_test,Y_pred_dec_tree) *100)
print('Recall: ',recall_score(Y_test,Y_pred_dec_tree)* 100)
print('F1 score: ',f1_score(Y_test,Y_pred_dec_tree) *100)
```

```
Decision Tree Classifier:
Accuracy score: 81.1761093198219
Precision : 59.749216300940446
Recall:  62.0039037085231
F1 score:  60.85568326947638
```