

```

import os
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline
sns.set(style='white', context='notebook', palette='deep')
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier
from sklearn.model_selection import GridSearchCV, cross_val_score, StratifiedKFold, learning_curve, train_test_split, KFold
from sklearn.metrics import classification_report
from sklearn.metrics import confusion_matrix
from sklearn.metrics import accuracy_score

```

```

import warnings
warnings.filterwarnings('ignore')
adult_dataset_path = "/content/adult.csv"
def load_adult_data(adult_path=adult_dataset_path):
    csv_path = os.path.join(adult_path)
    return pd.read_csv(csv_path)

```

```

df = load_adult_data()
df.head()

```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	relationship
0	90	?	77053	HS-grad	9	Widowed	?	Never-married
1	82	Private	132870	HS-grad	9	Widowed	Exec-managerial	Never-married
2	66	?	186061	Some-college	10	Widowed	?	Never-married
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	Married
4	41	Private	264663	Some-college	10	Separated	Prof-specialty	Married

```

print ("Rows : ",df.shape[0])
print ("Columns : ",df.shape[1])
print ("\nFeatures : \n",df.columns.tolist())
print ("\nMissing values : ", df.isnull().sum().values.sum())
print ("\nUnique values : \n",df.nunique())

```

```

Rows : 32561
Columns : 15

```

```

Features :
['age', 'workclass', 'fnlwgt', 'education', 'education.num', 'marital.status', 'occupation', 'relationship', 'race', 'sex', 'capital.gain', 'capital.loss', 'hours.per.week', 'native.country', 'income']

```

```

Missing values : 0

```

```

Unique values :
age                73
workclass           9
fnlwgt            21648
education           16
education.num       16
marital.status       7
occupation          15
relationship         6
race                 5
sex                  2
capital.gain        119
capital.loss         92
hours.per.week       94
native.country       42
income               2
dtype: int64

```

```

df.info()

```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 32561 entries, 0 to 32560
Data columns (total 15 columns):

```

```
#      Column      Non-Null Count  Dtype
---  -
0     age          32561 non-null    int64
1     workclass     32561 non-null    object
2     fnlwgt        32561 non-null    int64
3     education     32561 non-null    object
4     education.num  32561 non-null    int64
5     marital.status 32561 non-null    object
6     occupation     32561 non-null    object
7     relationship   32561 non-null    object
8     race           32561 non-null    object
9     sex            32561 non-null    object
10    capital.gain    32561 non-null    int64
11    capital.loss    32561 non-null    int64
12    hours.per.week  32561 non-null    int64
13    native.country  32561 non-null    object
14    income          32561 non-null    object
dtypes: int64(6), object(9)
memory usage: 3.7+ MB
```

```
df.describe()
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.p
count	32561.000000	3.256100e+04	32561.000000	32561.000000	32561.000000	32561
mean	38.581647	1.897784e+05	10.080679	1077.648844	87.303830	40.620815
std	13.640433	1.055500e+05	2.572720	7385.292085	402.960219	12.139945
min	17.000000	1.228500e+04	1.000000	0.000000	0.000000	1
25%	28.000000	1.178270e+05	9.000000	0.000000	0.000000	40
50%	37.000000	1.783560e+05	10.000000	0.000000	0.000000	40
75%	48.000000	2.370510e+05	12.000000	0.000000	0.000000	45
max	90.000000	1.484705e+06	16.000000	99999.000000	4356.000000	99

```
df_missing = (df=='?').sum()
df_missing
```

```
age          0
workclass    1836
fnlwgt       0
education    0
education.num 0
marital.status 0
occupation   1843
relationship 0
race         0
sex          0
capital.gain 0
capital.loss 0
hours.per.week 0
native.country 583
income       0
dtype: int64
```

```
percent_missing = (df=='?').sum() * 100/len(df)
percent_missing
```

```
age          0.000000
workclass    5.638647
fnlwgt       0.000000
education    0.000000
education.num 0.000000
marital.status 0.000000
occupation   5.660146
relationship 0.000000
race         0.000000
sex          0.000000
capital.gain 0.000000
capital.loss 0.000000
hours.per.week 0.000000
native.country 1.790486
income       0.000000
dtype: float64
```

```
df.apply(lambda x: x != '?',axis=1).sum()
```

```
age          32561
workclass    30725
fnlwgt       32561
education    32561
education.num 32561
```

```
marital.status    32561
occupation        30718
relationship      32561
race              32561
sex               32561
capital.gain      32561
capital.loss      32561
hours.per.week    32561
native.country    31978
income            32561
dtype: int64
```

```
# dropping the rows having missing values in workclass
df = df[df['workclass'] != '?']
df.head()
```

	age	workclass	fnlwgt	education	education.num	marital.status	occupation	rela
1	82	Private	132870	HS-grad	9	Widowed	Exec-manage	Not-in-family
3	54	Private	140359	7th-8th	4	Divorced	Machine-op-inspct	Unmarried
4	41	Private	264663	Some-college	10	Separated	Prof-specialty	Own-child
5	34	Private	216864	HS-grad	9	Divorced	Other-service	Unmarried
6	38	Private	150601	10th	6	Separated	Adm-clerical	Own-child

```
df_categorical = df.select_dtypes(include=['object'])
df_categorical.apply(lambda x: x=='?',axis=1).sum()
```

```
workclass      0
education       0
marital.status  0
occupation      7
relationship    0
race            0
sex            0
native.country 556
income          0
dtype: int64
```

```
from sklearn import preprocessing
df_categorical = df.select_dtypes(include=['object'])
df_categorical.head()
```

	workclass	education	marital.status	occupation	relationship	race	sex	nat
1	Private	HS-grad	Widowed	Exec-manage	Not-in-family	White	Female	
3	Private	7th-8th	Divorced	Machine-op-inspct	Unmarried	White	Female	
4	Private	Some-college	Separated	Prof-specialty	Own-child	White	Female	

```
# apply label encoder to df_categorical
le = preprocessing.LabelEncoder()
df_categorical = df_categorical.apply(le.fit_transform)
df_categorical.head()
```

	workclass	education	marital.status	occupation	relationship	race	sex	native.
1	3	11	6	4	1	4	0	
3	3	5	0	7	4	4	0	
4	3	15	5	10	3	4	0	
5	3	11	0	8	4	4	0	
6	3	0	5	1	4	4	1	

```
# Next, Concatenate df_categorical dataframe with original df (dataframe)
# first, Drop earlier duplicate columns which had categorical values
df = df.drop(df_categorical.columns,axis=1)
df = pd.concat([df,df_categorical],axis=1)
df.head()
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	workclass
1	82	132870	9	0	4356	18	3
3	54	140359	4	0	3900	40	3
4	41	264663	10	0	3900	40	3
5	34	216864	9	0	3770	45	3
6	38	150601	6	0	3770	40	3

```
# look at column type
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
Int64Index: 30725 entries, 1 to 32560
Data columns (total 15 columns):
#   Column                Non-Null Count  Dtype
---  -
0   age                   30725 non-null  int64
1   fnlwgt                30725 non-null  int64
2   education.num         30725 non-null  int64
3   capital.gain          30725 non-null  int64
4   capital.loss          30725 non-null  int64
5   hours.per.week        30725 non-null  int64
6   workclass             30725 non-null  int64
7   education             30725 non-null  int64
8   marital.status        30725 non-null  int64
9   occupation            30725 non-null  int64
10  relationship          30725 non-null  int64
11  race                  30725 non-null  int64
12  sex                   30725 non-null  int64
13  native.country        30725 non-null  int64
14  income                30725 non-null  int64
dtypes: int64(15)
memory usage: 3.8 MB
```

```
plt.figure(figsize=(14,10))
sns.heatmap(df.corr(),annot=True,fmt='.2f')
plt.show()
```



```
# convert target variable income to categorical
df['income'] = df['income'].astype('category')
# check df info again whether everything is in right format or not
df.info()

<class 'pandas.core.frame.DataFrame'>
Int64Index: 30725 entries, 1 to 32560
Data columns (total 15 columns):
#   Column                Non-Null Count  Dtype
---  -
0   age                    30725 non-null  int64
1   fnlwgt                 30725 non-null  int64
2   education.num          30725 non-null  int64
3   capital.gain           30725 non-null  int64
4   capital.loss           30725 non-null  int64
5   hours.per.week         30725 non-null  int64
6   workclass              30725 non-null  int64
7   education              30725 non-null  int64
8   marital.status         30725 non-null  int64
9   occupation             30725 non-null  int64
10  relationship           30725 non-null  int64
11  race                   30725 non-null  int64
12  sex                    30725 non-null  int64
13  native.country         30725 non-null  int64
14  income                 30725 non-null  category
dtypes: category(1), int64(14)
memory usage: 3.5 MB
```

```
# Importing train_test_split
from sklearn.model_selection import train_test_split
# Putting independent variables/features to X
X = df.drop('income',axis=1)
# Putting response/dependent variable/feature to y
y = df['income']
X.head(3)
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	workclass
1	82	132870	9	0	4356	18	3
3	54	140359	4	0	3900	40	3
4	41	264663	10	0	3900	40	3

```
y.head(3)

1    0
3    0
4    0
Name: income, dtype: category
Categories (2, int64): [0, 1]
```

```
# Splitting the data into train and test
X_train,X_test,y_train,y_test = train_test_split(X,y)
X_train.head()
```

	age	fnlwgt	education.num	capital.gain	capital.loss	hours.per.week	workc:
23791	67	286372	13	0	0	40	
17414	34	318886	9	0	0	40	
13106	38	200153	12	0	0	40	
12421	62	211035	13	0	0	30	
13576	42	31621	12	0	0	40	

```
test_size = 0.20
seed = 7
num_folds = 10
scoring = 'accuracy'
# Params for Random Forest
num_trees = 100
max_features = 3

random_forest = RandomForestClassifier(n_estimators=250,max_features=5)
random_forest.fit(X_train, y_train)
predictions = random_forest.predict(X_test)
print("Accuracy: %s%" % (100*accuracy_score(y_test, predictions)))
print(confusion_matrix(y_test, predictions))
print(classification_report(y_test, predictions))
```

```
Accuracy: 85.78495183545951%
[[5358  406]
 [ 686 1232]]
      precision    recall  f1-score   support

      0       0.89       0.93       0.91       5764
      1       0.75       0.64       0.69       1918

 accuracy          0.86          7682
  macro avg       0.82       0.79       0.80       7682
 weighted avg     0.85       0.86       0.85       7682
```